INCH-POUND

A-A-50096B
February 21, 1990
SUPERSEDING
A-A-50096A
March 4, 1988

COMMERCIAL ITEM DESCRIPTION

HAMMER, ROCK AND ICE

The General Services Administration has authorized the use of the commercial item description in preference to MIL-H-1431.

1. SALIENT CHARACTERISTICS

1.1 Design and construction. The rock and ice hammer shall have a 12-inch fiberglass core handle with a polyethylene outer sheath to dampen vibrations. The head shall be stainless steel in construction with three steel socket head cap screws to hold a removable serrated ice climbing pick. The head shall be attached to the handle with epoxy. The ice climbing stainless steel pick shall have a hole for the attachment of a wrist loop. Each hammer shall have a replaceable nylon lanyard. Each hammer shall be provided with an "allen wrench" with which to remove the serrated pick. Maximum weight of the hammer including the lanyard, "allen wrench", pick and socket head cap screws shall be 672 grams. Handle and lanyard color shall be black. Head and pick color shall be natural. The manufacturer's identification symbol shall be stamped on each hammer. The hammer shall be U.I.A.A. (Union Internationale des Associations d'Alpinsme) approved.

2. QUALITY ASSURANCE

2.1 Certification. The contractor shall certify, and maintain substantiating evidence, that the product offered meets the salient characteristics and requirements of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: Commander, U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014.

AMSC N/A FSC 5120

DISTRIBUTION STATEMENT. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

2.2 Visual examination. Each lot of hammers shall be inspected in accordance with MIL-STD-105. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0. The lot size shall be expressed in units of hammers. The sample unit shall be one hammer. The hammers shall be examined for the defects listed below:

Finish not smooth and adherent; not free of burrs, rough spots, sharp edges, slivers, flat areas or projections; any component missing or not specified type; any component fractured, split, dented, bowed, malformed, damaged or loose; markings in wrong location, incomplete, illegible, incomplete, or not as specified.

2.3 Dimensional examination. The hammers shall be examined without damaging or disassembling the hammers. Any dimension not within the specified tolerances shall be classified as a defect. The lot size shall be expressed in units of hammers. The sample unit shall be one hammer. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

3. PACKAGING

3.1 Packaging. Each hammer shall be unit packed in a snug-fitting fiberboard box fabricated from 200-pound test corrugated fiberboard.

3.2 Packing. Twelve hammers, unit packed as specified, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, class domestic, grade 275 of PPP-B-636. The shipping container shall be completely filled with no voids and be of a size that can be palletized in accordance with MIL-STD-147. Each shipping container shall be closed in accordance with the appendix of PPP-B-636.

3.3 Palletization. When specified (see 4.2), hammers packed as specified, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means C and D, or film bonding means F or G, in accordance with MIL-STD-147.

3.4 Marking. In addition to any special markings required by the contractor or purchase order, unit packs, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129.

4. NOTES

4.1 Intended use. The rock and ice hammer is for hammering pitons into cracks in rocks and to provide direct aid on ice climbs with the use of the ice climbing pick.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

4.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When palletization is required (see 3.3).

4.3 Sources of documents.

4.3.1 Source of government documents. Copies of military and Federal documents are available from:

Standardization Documents Order Desk
Bldg. 4D, 700 Robbins Avenue
Philadelphia, PA 19111-5094

MILITARY INTERESTS:

Custodians

Army - GL
Navy - NU
Air Force - 99

Review Activities

Air Force - 82, 84
DLA - CT

User Activity

Navy - MC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

(Project 5120-C094)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.