METRIC

A-A-50096C
March 19, 1993
SUPERSEDING
A-A-50096B
February 21, 1990

COMMERCIAL ITEM DESCRIPTION

HAMMER, ROCK

The General Services Administration has authorized the use of this commercial item description in preference to MIL-H-1431.

Abstract. This commercial item description covers a rock climbing hammer to be used for hammering pitons into cracks in rock faces, testing the rock density prior to piton placement, testing the security of the piton once hammered into place, and removing pitons and chocks from rock cracks.

1. SALIENT CHARACTERISTICS

1.1 Description. The rock climbing hammer shall have an oiled hickory handle not less than 26 centimeters (10.25 inches) and not more than 31 centimeters (12.20 inches) in length. The hammer head shall be stainless steel, weigh not less than 510 grams (1.1 pounds) and not more than 567 grams (1.3 pounds), and have both a striking face for driving pitons and a drooped pick with a carabineer hole for removing chocks and pitons. The hammer head shall be permanently attached to the hickory handle. Each hammer shall have a replaceable tubular nylon webbing leash, approximately 54 centimeters (21.26 inches) in length, attached into the base of the hammer handle for easy insertion and removal from a climbing holster.

1.2 Finish. The surface roughness of striking face shall be 317.5 microcentimeters (125 microinches) to 635.0 microcentimeters (250 microinches).

Beneficial comments, (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development and Engineering Center, Natick, MA 01760-5019, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5120

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

1.3 Hardness of hammer head. The hammer head shall be made of stainless steel and shall be hardened to 30 to 50 HRC (Rockwell Hardness Test). Case hardened heads shall not be acceptable.

1.4 Handles. The handles shall be grade "A" Hickory only.

1.5 Weight. The total weight of the hammer shall be not less than 672 grams (1.5 pounds) (weight will vary with the density of the hickory handle).

1.6 Crack detection. All hammerheads shall be 100 percent in-process inspected after heat treating, prior to finishing and assembly, and subjected a bidirectional wet magnetic particle inspection test in accordance with ASTM E 709. All surfaces shall be examined. If a hammerhead is found to have indications of a crack, the manufacturer may grind or buff to eliminate this condition but must maintain the overall weight and dimensional requirements.

1.7 Color. The handle shall be flat finish natural wood, the head shall be flat metal grey and the nylon webbing leash be Camouflage Green 483 (CG 483), brown or black.

2. QUALITY ASSURANCE

2.1 Certification. The contractor shall certify, and maintain substantiating evidence, that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of of the contract.

2.2 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practical.

2.3 Metric product. Products manufactured using metric units will be considered on an equal basis with those manufactured using inch-pound units, provided that the product measurements fall within specified tolerances using conversion tables contained in the latest revision of FED-STD-376 and that all other requirements of this CID are met.

2.4 Visual examination. Each lot of hammers shall be inspected in accordance with MIL-STD-105. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.4. The lot size shall be expressed in units of hammers. The sample unit shall be one hammer. The hammers shall be examined for the defects listed below:

Finish not smooth and adherent; not free of burrs, rough spots, sharp edges, slivers, flat areas or projections; any component missing or not

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:38Z
Check the source to verify that this is the current version before use.

specified type; any component fractured, split, dented, bowed, malformed, damaged, loose, knots, heavy stain, or slight failure; markings in wrong location, incomplete, illegible, incomplete, or not as specified.

2.5 Dimensional examination. The hammers shall be examined without damaging or disassembling the hammers. Any dimension not within the specified tolerances shall be classified as a defect. The lot size shall be expressed in units of hammers. The sample unit shall be one hammer. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 1.7.

3. PACKAGING

3.1 Packaging. Each hammer shall be unit packed in a snug-fitting fiberboard box fabricated from 200-pound test corrugated fiberboard.

3.2 Packing. Twelve hammers, unit packed as specified, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, class domestic, grade 275 of PPP-B-636. The shipping container shall be completely filled with no voids and be of a size that can be palletized in accordance with MIL-STD-147. Each shipping container shall be closed in accordance with the appendix of PPP-B-636.

3.3 Palletization. When specified (see 4.1), hammers packed as specified, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means C and D, or film bonding means F or G, in accordance with MIL-STD-147.

3.4 Marking. In addition to any special markings required by the contractor or purchase order, unit packs, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129.

4. NOTES

4.1 Ordering data.

a. Title, number, and date of this document.
b. When palletization is required (see 3.3).

4.2 Sources of documents.

4.2.1 Source of government documents. Copies of Military and Federal documents are available from:

Standardization Documents Order Desk
Building 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:38Z
Check the source to verify that this is the current version before use.

4.2.2 Source of non-government documents. Copies of non-governmental documents are available from:

American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103-1187

MILITARY INTERESTS:

Custodians

Army - GL
Air Force - 99

Review Activities

Air Force - 82, 84
DLA - CT

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project 5120-D024

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	A-A-50096C	1993 March 19

3. DOCUMENT TITLE
HAMMER, ROCK

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON/DSN
U.S. Army Natick RD&E Center	508-651-4532	256-4532
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: SATNC-IRS Natick, MA 01760-5019	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 NATICK OPI: JUL 91 Previous editions are obsolete.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the most current version before use.