INCH-POUND

A-A-50097A
February 21, 1990
SUPERSEDING
A-A-50097
March 23, 1987

COMMERCIAL ITEM DESCRIPTION

PULLEY, MOUNTAIN RESCUE

The General Services Administration has authorized the use of this commercial item description.

1. SALIENT CHARACTERISTICS

1.1 Design and construction. The mountain rescue pulley shall have spilt halves that enable the user to put the rope in the pulley without having to thread the rope through the pulley. The pulley sides and wheel shall be fabricated from alumuinum. The center bolt shall have a 3/8 inch diameter shaft fabricated from steel. The shaft nut shall have a self-locking nylon insert. The pulley wheel shall have roller bearings and be large enough, to accommodate a 1/2 inch diameter rope . The snap link hole shall be large enough to accommodate two snap links. Minimum breaking strength shall be 5000 pounds. Maximum weight shall be 0.5 pounds. Finish shall be black anodized. The manufacturer's identification symbol shall be stamped on each pulley assembly.

2. QUALITY ASSURANCE

2.1 Certification, The contractor shall certify, and maintain substantiating evidence, that the product offered meets the salient characteristics and requirements of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract,

2.2 Visual examination. Each lot of pulleys shall be inspected in accordance with MIL-STD-105. The inspection level shall be II and the accept-able quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0. The lot size shall be expressed in units of pulleys. The sample unit shall be one pulley. The pulleys shall be examined for the defects listed below:

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: Commander, U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014.

AMSC N/A FSC 3020

DISTRIBUTION STATEMENT. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

Finish not smooth and adherent; not free of burrs, rough spots, sharp edges. slivers, flat areas or projections; any component missing or not specified type; any component fractured, spilt, dented, bowed, malformed, damaged or loose; shaft nut turns freely on the bolt; all other parts do not rotate freely through 360 degrees rotation; markings in wrong location, Incomplete, illegible, Incomplete, or not as specified.

2.3 Dimensional examination, The pulleys shall be examined without damaging or disassembling the pulleys. Any dimension not within the specified tolerances shall be classified as a defect. The lot size shall be expressed in units of pulleys, The sample unit shall be one pulley. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

3. PACKAGING

3 1 Packaging. Each pulley shall be completely wrapped in kraft paper. Eight wrapped pulleys shall then be packed in a snug-fitting intermediate fiberboard box fabricated from 200-pound test corrugated fiberboard.

3.2 Packing. Eighty pulleys, packaged as specified. shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, class domestic, grade 275 of PPP-B-636. The shipping container shall be completely filled with no voids and be of a size that can be palletized in accordance with MIL-STD-147. Each shipping container shall be closed in accordance with the appendix of PPP-B-636.

3.3 Palletization. When specified (see 4.2), pulleys packed as specified, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means C and D, or film bonding means F or G, in accordance with MIL-STD-147.

3.4 Marking. In addition to any special markings required by the contractor or purchase order, unit packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-125.

4. NOTES

4.1 Intended use. The mountain pulley is used for hauling equipment and emergency personnel rescue.

4.2 Ordering data. Acquisition documents should specify the following:

a. Title. number, and date of this document.
b, When palletization is required (see 3.3).

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:38Z
Check the source to verify that this is the current version before use.

4.3 Sources of documents.

4.3.1 Source of government documents. Copies of military and Federal documents are **available** from:

Standardization Documents Order Desk
Bldg. 4D, 700 Robbins Avenue
Philadelphia, PA 19111-5094

MILITARY INTERESTS:

Custodians

Army - GL
Air Force - 99

Review Activities

Air Force - 82
DLA - CT

User Activity

Navy - MC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

(project 3020-0121)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.