A-A-50107
March 31, 1987

COMMERCIAL ITEM DESCRIPTION

DOLLY, FOOD HANDLING EQUIPMENT (DISHWASHING RACKS)

The General Services Administration has authorized the use of this commercial item description in preference to MIL-D-43442.

1. SALIENT CHARACTERISTICS

1.1 Material, design, and construction. The dolly shall be fabricated from either stainless steel or aluminum alloy. The dolly shall be designed for transporting nominal 20-inch by 20-inch dishwashing racks. The dolly shall be capable of transporting a load of 250 pounds without any visible deformation. The dolly base shall have a minimum 3/4-inch lip on all four sides to prevent racks from sliding off. The inside dimensions shall be no less than 20-1/4 inches and no more than 20-3/4 inches. The overall height, excluding handle, shall not exceed 12 inches.

1.1.1 Casters. The dolly shall be provided with four 5-inch diameter swivel casters suitable for the load specified.

1.1.2 Bumpers. The dolly shall be equipped with bumpers to protect walls from damage by any side or corner of the dolly. There shall be no evidence of deformation, separation, or failure of the bumpers and dolly when the dolly is propelled against a vertical rigid wall at a speed of 30 feet in 10 seconds.

1.1.3 Handle. The dolly shall be equipped with a removable tubular handle. The handle shall be fabricated of material having a minimum 1-inch outside diameter, with a minimum wall thickness of .062 inch. The overall height, including handle shall be no less than 33 inches and no more than 40 inches.

1.2 Standards compliance. Dollies shall comply with the sanitation requirements of the National Sanitation Foundation Standard No. 2.

1.3 Data name plate (Government unique requirement see 4.4).

The dolly shall be furnished with a data name plate in accordance with the applicable requirements of MIL-STD-130 except the requirement for: (a) Methods of applying, (b) Identification tags, (c) Information not required and (d) Optional marking information shall not apply. The data name plate shall be made of minimum 20-gauge corrosion-resisting metal and attached to the dolly by rivets, by screws, or by welding in such a manner as to meet the applicable NSF sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved, or applied by photosensitive means:

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:39Z
Check the source to verify that this is the current version before use.

National Stock Number
Procurement Instrument Identification Number
Specification Data
Manufacturer's Name, Address, and Telephone Number
Supplier's Name, Address, and Telephone Number (List only if different from Manufacturer)
Manufacturer's Model Number
Government Approved Manual Number (see 4.2)

Each plate shall be placed so that it is readily visible to the operator during normal operating use and so as to not adversely affect the life and utility of the dolly.

1.4 Workmanship. The finished dolly shall be complete, clean, and free of burrs, scratches, breaks, sharp edges, sharp corners, and slivers. Rivets, shall be tight and properly peened, and in full contact with the metal surfaces. Welding shall be continuous and sound and free of slag, pits, buildup, and undercuts. All flux shall be removed and welds shall be ground smooth. Threaded fasteners shall be drawn tight and shall be free of crossed or stripped threads. There shall be no missing nuts, bolts, or lock-washers.

2. QUALITY ASSURANCE

2.1 Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, conforms to the producer's own drawings, specifications, standards, and quality assurance practices, complies with the referenced industry standards, and is the same as the product offered for sale in the commercial marketplace, except for those additional requirements/characteristics specified herein. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under provisions of the contract.

3. PACKAGING

3.1 Packaging and packing. Packaging and packing shall be commercial or export as specified (see 4.2).

3.2 Commercial. Each dolly shall be cleaned, preserved, packaged, packed, and unitized in accordance with ASTM D 3951.

3.3 Export packaging. Each dolly shall be cleaned, preserved, and cushioned to protect against corrosion, deterioration, and physical damage during shipment and storage. Each dolly shall be packaged in a fiberboard box conforming to type CF or SF, class domestic, style optional of PPP-B-636.

3.3.1 Export packing. Four dollies shall be packed in a nailed and lock-corner wood box conforming to class 1, style optional, type 2 load of PPP-B-621, or a cleated-plywood wood box conforming to domestic type, style optional, type 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:39Z
Check the source to verify that this is the current version before use.

load of PPP-B-601. Each box shall be closed and strapped in accordance with the appendix of PPP-B-621 or PPP-B-601, as applicable.

3.3.2 Palletization. When specified, shipping containers shall be palletized in accordance with MIL-STD-147 (see 4.2).

3.4 Marking (commercial and export). Marking of unit packs, shipping containers and unit loads shall be in accordance with MIL-STD-129, or ASTM D 3951, as applicable.

4. NOTES

4.1 Intended use. The dolly is intended for use in transporting bowls, cups, and glasses in dishwashing racks.

4.2 Ordering data.

a. Title, number, and date of this document.
b. Government approved manual number to be included on data name plate (see 1.3).
c. Selection of applicable packaging and packing required (see 3.1).
d. When palletization is required (see 3.3.2).

4.3 Sources of documents.

4.3.1 Sources for nongovernment association documents.

NSF Standard No. 2 - Food Service Equipment, is available from:

National Sanitation Foundation (NSF)
3475 Plymouth Road
P.O. Box 1468
Ann Arbor, MI 48106

ASTM D 3951 - Standard Practice for Commercial Packaging, is available from:

The American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103.

4.3.2 Sources of governmental documents.

Military documents are available from:

Naval Publications and Forms Center
5801 Tabor Avenue
Philadelphia, PA 19120

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:39Z
Check the source to verify that this is the current version before use.

4.4 Government unique requirements. Whenever "(Government unique requirements)" is included in the title of a paragraph under "salient characteristics" it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

MILITARY INTERESTS:

Custodians

Army - GL
Navy - YD
Air Force - 99

Review activities

Army - MD, TS
Air Force - 84
DLA - GS

User activity

Navy - MC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project No. 7320-0799

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:39Z
Check the source to verify that this is the current version before use.