MILITARY SPECIFICATION

BODY ASSEMBLY FOR MINE, ANTI-PERSONNEL: HE, M74

This specification is approved for use by the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements and quality assurance provisions for the fabrication of parts, assembly and packing of one type of Body Assembly for Mine, Anti-Personnel: HE, M74.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner

MILITARY

MIL-B-117 - Bags, Sleeves and Tubing - Interior Packaging

FSC 1345

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn: DRSMC-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

MIL-P-14232 - Parts, Equipment and Tools for Army Materiel, Packaging of
MIL-S-45743 - Soldering, Manual Type, High Reliability, Electrical and Electronic Equipment
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for
MIL-B-48761 - Battery, Single Cell
MIL-E-63300 - Electronic Assembly for Mine, AP: HE, M74

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-202 - Test Methods for Electronic and Electrical Component Parts
MIL-STD-275 - Printed Wiring for Electronic Equipment
MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests For

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer).

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS (See 6.7)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER (ARDC)

PRODUCT AND PACKAGING DRAWING

9292680 - Body Assembly
9292960 - Electronic Assembly Timing Operations, Oscillator Periods and Low Voltage Detection Levels (U)

INSPECTION EQUIPMENT DRAWINGS

9293021 - Power Supply Transmitter
9293046 - Transmitter, Assembly

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CODE OF FEDERAL REGULATIONS

TITLE 49 - Transportation, Parts 100-199

(The Code of Federal Regulations is available from the Superintendent of Documents, US Government Printing Office, Washington, DC 20402. Orders should specify, "49 CFR 100-199 (latest revision)").

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM E 18 - Standard Method of Test for Rockwell Hardness

(Application for copies should be addressed to: American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 191.03).

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts. The parts shall comply with all requirements specified on Drawing (Dwg.) 9292680, all associated drawings, and with all requirements specified in applicable specifications and standards.

3.3 Environmental conditioning.

3.3.1 Transportation vibration. The Body Assemblies shall be safe to handle and transport and shall show no evidence of internal or external damage that will affect the intended functions following transportation vibration Test No. 119, Procedure 2 of MIL-STD-331 (See 3.7).

3.3.2 Temperature conditioning of Body Assemblies. The Body Assemblies shall function as specified in 3.4 after temperature conditioning as follows:

a. Cold - minus 35° - 5°F for 4 hours minimum (min).
b. Ambient - for four hours min.
c. Hot - 145° + 5°F for 4 hours min.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

3.4 Functioning. After being conditioned as specified in 3.3.1 and 3.3.2, the Body Assembly shall be capable of arming and functioning high order in any of the following modes:

a. Anti-disturbance (AD) mode.
b. Trip-line (TL) mode.
c. Normal or extended self-destruct (SD) mode.

3.5 Ultrasonic welded assemblies.

3.5.1 Seal leakage testing of ultrasonic welded assemblies. Dwg's 9292616, 9292631. The ultrasonic welded assemblies listed above, when subjected to an internal test pressure of 75 ± 3 psig of dry nitrogen gas, shall not exhibit a pressure drop greater than ten (10) psig in 5 seconds min.

3.5.2 Torque test of selector switch weldment. Dwg. 9292679. The selector switch weldment to the upper housing assembly shall withstand a torque of 35 inch pounds (in-lbs) min. without cracking or failure of selector switch/upper housing assembly ultrasonic weldment.

3.6 Verification of safe condition of S&A Assemblies prior to assembly to Body Assemblies. Prior to assembly in the Body Assembly, positive verification of the following safety features shall be made for each S&A Assembly:

a. Presence and safe position of both spring loaded centrifugal locks.

b. Safe position of slider release pin and shear pin.

c. Safe position of spring loaded slider assembly: distance from end of S&A to slider assembly, maximum (max.) .

d. Presence of shorting eyelet.

3.7 Verification checks on Body Assembly.

3.7.1 Verification of safe condition of Body Assemblies. Positive verification of each completely assembled Body Assembly shall be made: 1) that both battery cells are inactivated, 2) that the firing capacitor is shorted by the shorting bar, and 3) that the distance of the S&A slider assembly from the end of the S&A is within the max. allowed. Battery cell voltage and firing capacitor resistance requirements are listed in Table II.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:26Z
Check the source to verify that this is the current version before use.

3.7.2 Verification of Body Assembly circuit resistance. Circuit resistance checks of completely assembled Body Assembly shall be made for all triplines, the magnetic coupling system (MCS) circuit, pressure cartridge, S&A piston actuator and S&A detonator. Resistance requirements are listed in Table II.

3.8 Process control. The contractor shall submit to the Government for approval with the first article sample, process control documents for the processes listed in the following subparagraphs. These processes shall be those used in the fabrication of the first article sample and shall not be changed after approval of the first article sample without prior approval of the Government. At unscheduled intervals during the operation of the approved processes, the Government inspector shall observe the processes to ascertain that production to the approved process control documents is being maintained. No deviation shall be allowed without approval from the procuring activity. In the event that the contractor desires a change in an approved process control document, a new first article sample may, at the discretion of the Government be required. (Ref Sec 6.5, DI-P-1604 (MOD) with Attachment 1).

3.8.1 Process control of molded plastic parts. A process control document shall be prepared for each of the molded plastic parts. These documents shall briefly describe the entire process and shall fully document the controls to be utilized for maintaining the process. They shall specify the time, temperature, pressure ranges and cure process which shall be maintained during production of the molded parts as well as how the glass content of the raw material will be controlled.

3.8.2 Process control of ultrasonic weldments. A process control document shall be prepared for each of the following weldments. These documents shall fully describe the entire assembly process and the controls to be utilized for maintaining the process. They shall specify the preparation of all material and components and the assembly operations that are needed prior to welding to meet the requirements of the applicable drawing as well as the welding pressure, weld time and hold time for the welding operation, cure temperature and time after welding.

a. Selector Switch Assembly, Dwg. 9292609.
b. Housing, Power Supply (Weldment), Dwg. 9292617.
c. Housing, Upper (Weldment), Dwg. 9292633.
d. Selector Switch Assembly to Upper Housing Assembly, Dwg 9292679.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

e. Body Assy - Power Supply Housing Assy to Electronic and Housing Assy, Dwg. 9292680.
f. Body Assy - Cover, Power Supply to Power Supply Housing Assy, Dwg. 9292680.

3.8.3 Process control of potting. A process control document shall be prepared each of the following potting operations. These documents shall fully describe the entire process and the controls for maintaining the process. They shall specify the preparation of all materials, pot life, and subsequent cure temperature and time.

a. Potting of sensors in Power Supply Housing Assy, Dwg. 9292616.
b. Potting of sensors in Upper Housing Assy, Dwg. 9292631.
c. Body Assy - Potting of Pressure Cartridge, Dwg. 9292680.
d. Body Assy - Potting of Receiver Coil Assy, Dwg. 9292680.

3.9 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.10 Soldering workmanship. All soldered electrical connections shall comply with MIL-S-45743, the Appendix herein, and the requirements of all applicable drawings.

3.11 Workmanship. All parts and assemblies shall be fabricated and assembled in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, grease, rust, and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. Exterior surface coatings shall be continuous; however, a few light scratches not exposing base material may be permitted. All required marking and stamping shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following type of inspection shall be conducted on this item.

a. First Article Inspection
b. Quality Conformance Inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawings	Quantity
Body Assembly	9292680	80
Electronic and Housing Assembly	9292679	15
Power Supply Housing Assembly	9292616	15
Shorting Bar and Connector Assembly	9292158	15
Receiver Coil Assembly	9292652	15
Battery and Lead Assembly	9292678	15
Upper Housing Assembly	9292631	15

A sample of 10 for all other components listed in Table I.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 5		DRAWING NUMBER
	Body Assembly and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Selector Switch Assembly (Dwg 9292609) Examination for defects	10		3.2	4.4.2.1
	Housing, Upper Selector Switch (Dwg 9292620) Examination for defects	10		3.2	4.4.2.2
	Housing, Lower, Selector Switch (Dwg 9292621) Examination for defects	10		3.2	4.4.2.3
	Insert (Dwg 9292629) Examination for Defects	10		3.2	4.4.2.4
	Disc, Polyester, Double Coated (Dwg 9292637) Examination for defects	10		3.2	4.4.2.5
	Gasket (Dwg 9292651) Examination for defects	10		3.2	4.4.2.6
	Terminal (Dwg 9292628) Examination for defects	10		3.2	4.4.2.7

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-B-63299A(AR)

PARAGRAPH	TITLE: Body Assembly and Components		SHEET 2 OF 5		DRAWING NUMBER: See Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE / INSPECTION METHOD
	Post, Weld (Dwg 9292622)				
	Examination for defects	10		3.2	4.4.2.8
	Spring, Take-Up (Dwg 9292676)				
	Examination for defects	10		3.2	4.4.2.9
	Hardness test	10		3.2	4.4.2.9
	Cover, Power Supply (Dwg 9292614)				
	Examination for defects	10		3.2	4.4.2.10
	O-Ring (Dwg 9292657)				
	Examination for defects	10		3.2	4.4.2.11
	Holder, Lead (Dwg 9292611)				
	Examination for defects	10		3.2	4.4.2.12
	Battery and Lead Assembly (Dwg 9292678)				
	Examination for defects	15		3.2	4.4.2.13
	Pull test	15		3.2	4.5.2
	Circuit Board (Dwg 9292654)				
	Examination for defects	10		3.2	4.4.2.14

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 3 OF 5		DRAWING NUMBER
	Body Assembly and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Receiver Coil Assembly (Dwg 9292652)				
	Examination for defects	15		3.2	4.4.2.15
	Electrical tests	15		3.2	4.4.2.15
	Coil (Dwg 9292653)				
	Examination for defects	10		3.2	4.4.2.16
	Retainer, Coil (Dwg 9292660) when used				
	Examination for defects	10		3.2	4.4.2.17
	Housing, Power Supply (Weldment) (Dwg 9292617)				
	Examination for defects	10		3.2	4.4.2.18
	Housing, Power Supply (Dwg 9292618)				
	Examination for defects	10		3.2	4.4.2.19
	Plate, Power Supply (Dwg 9292619)				
	Examination for defects	10		3.2	4.4.2.20
	Power Supply Housing Assembly (Dwg 9292616)				
	Examination for defects	15		3.2	4.4.2.21
	Leak test	15		3.5	4.5.3

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 4 OF 5		DRAWING NUMBER
	Body Assembly and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Pin, Retaining, Test Point (Dwg 9292675)				
	Examination for defects	10		3.2	4.4.2.22
	Housing, Upper (Weldment) (Dwg 9292633)				
	Examination for defects	10		3.2	4.4.2.23
	Housing, Upper (Dwg 9292635)				
	Examination for defects	10		3.2	4.4.2.24
	Plate, Upper (Dwg 9292634)				
	Examination for defects	10		3.2	4.4.2.25
	Shorting Bar, Ceramic (Dwg 9292157)				
	Examination for defects	10		3.2	4.4.2.26
	Shorting Bar and Connector Assy (Dwg 9292158)				
	Examination for defects	15		3.2	4.4.2.27
	Shorting Bar (Dwg 9292682)				
	Examination for defects	10		3.2	4.4.2.28

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-B-63299A(AR)

PARAGRAPH	TITLE: Body Assembly and Components		SHEET 5 OF 5		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Upper Housing Assembly (Dwg 9292631)				
	Examination for defects	15		3.2	4.4.2.29
	Leak test	15		3.5	4.5.3
	Cushion (Dwg 9292636)				
	Examination for defects	10		3.2	4.4.2.30
	Electronic and Housing Assembly (Dwg 9292679)				
	Examination for defects	15		3.2	4.4.2.31
	Torque test	15		3.5.2	4.5.3.2
	Body Assembly (Dwg 9292680)				
	Examination for defects	80		3.2	4.4.2.32-38
	Transportation vibration	80		3.3.1, 3.7.1	4.5.5
	Performance Tests:				
	a. Cold (-35° - 5°F)	27		3.3,3.4	4.5.6, 4.4.2.40
	b. Hot (+145° + 5°F)	27		3.3,3.4	4.5.6, 4.4.2.40
	c. Ambient	26		3.3,3.4	4.5.6, 4.4.2.40

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

4.4 Quality Conformance Inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, each inspection lot shall contain the following.

a. Subassemblies of one interfix lot number from one manufacturer.
b. S&A assembly of one interfix lot number from one manufacturer.
c. Pressure cartridges of one interfix lot number from one manufacturer.
d. Electronic assemblies of one interfix lot number from one manufacturer.
e. Sensor assemblies of one interfix lot number from one manufacturer.
f. Receiver coil assemblies of one interfix lot number from one manufacturer.
g. Battery, Single Cell Primary Reserve of one interfix lot number from one manufacturer.
h. Primer, Battery, Electric of one interfix lot number from one manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Tests Forms, sampling plans for major and minor defects shall be in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Selector Switch Assembly				9292609
					NEXT HIGHER ASSEMBLY 9292679
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Height		0.40%	3.2	Gage
102	Binding or sticking of ball after welding		0.40%	3.2	Manual-Auditory
Minor					
201	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.2	Housing, Upper, Selector Switch		9292620
			NEXT HIGHER ASSEMBLY 9292609

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined	*			
Major					
101	True position of O-Ring groove diameter with Datum A		0.40%	3.2	Gage
102	O-Ring groove diameter		0.40%	3.2	Gage
103	Width of retaining flange for O-Ring		0.40%	3.2	Gage
104	Height from O-Ring groove to ret. flange		0.40%	3.2	Gage
105	Largest outside diameter of boss		0.40%	3.2	Gage
106	Inside diameter for switch ball		0.40%	3.2	Gage
107	Angular seating requirement for switch ball		0.40%	3.2	Gage
108	Depth of switch ball hole		0.40%	3.2	Gage
109	Radius of pressure cartridge cavity		0.40%	3.2	Gage
110	Length of pressure cartridge cavity from groove		0.40%	3.2	Gage
111	Total height of boss - interface with power supply hsg		0.40%	3.2	Gage
112	Height from face to and including weld tongue (View C-C)		0.40%	3.2	Gage
113	Diameter of smallest hole		0.40%	3.2	Gage
114	Height to boss		0.40%	3.2	Gage

NOTES:
*See 4.5.1 for qualification and production control of the mold cavities.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.2	Housing, Upper, Selector Switch				9292620
					NEXT HIGHER ASSEMBLY 9292609
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
115	Length from smallest hole to epoxy groove		0.40%	3.2	Gage
116	Depth of pressure cartridge cavity		0.40%	3.2	Gage
Minor					
201	Ejection pin marks, max (Note 7)		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Housing, Lower, Selector Switch		9292621
			NEXT HIGHER ASSEMBLY 9292609

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined	*			
Major					
101	Inside diameter - For switch ball		0.40%	3.2	Gage
102	Angular seating requirement for switch ball		0.40%	3.2	Gage
103	Height to boss		0.40%	3.2	Gage
104	Height from largest cavity to boss		0.40%	3.2	Gage
105	Largest outside diameter of boss		0.40%	3.2	Gage
106	Depth of pressure cartridge cavity		0.40%	3.2	Gage
107	Width of pressure cartridge cavity		0.40%	3.2	Gage
108	Smallest outside diameter of boss		0.40%	3.2	Gage
109	Depth of switch ball hole		0.40%	3.2	Gage
110	Diameter of smallest hole		0.40%	3.2	Gage
111	Length from smallest hole to groove		0.40%	3.2	Gage
112	Length of pressure cartridge cavity from groove		0.40%	3.2	Gage
113	Total height of boss		0.40%	3.2	Gage
Minor					
201	Ejection pin marks, max (Note 7)		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES: *See 4.5.1 for qualification and production control of the mold cavities.

DRSMC-DA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Insert		9292629
			NEXT HIGHER ASSEMBLY 9292680

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined	See 4.5.1 *			
Major					
101	Diameter		0.40%	3.2	Gage
102	Length		0.40%	3.2	Gage
Minor					
201	Chamfer missing, 2 places		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

*See 4.5.1 for qualification and production control of mold cavities.

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Disc, Polyester, Double Coated				9292637
					NEXT HIGHER ASSEMBLY 9292680
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Profile		0.65%	3.2	Gage
202	Thickness, max		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DPSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Gasket				9292651
					NEXT HIGHER ASSEMBLY 9292680
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Profile		0.40%	3.2	Gage
102	Thickness		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DPSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	*Terminal				9292628
					NEXT HIGHER ASSEMBLY 9292680
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Solderability (*)	1/	0-1	3.2	MIL-STD-202,Method 208
102	Length		0.40%	3.2	Gage
103	Knurl diameter (*)		0.40%	3.2	Gage
104	Total length from flange to knurled end (*)		0.40%	3.2	Gage
105	Diameter of flange (*)		0.40%	3.2	Gage
106	Width, 2 places		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

*Reference part source 9292646

1/ Sample size for MIL-STD-105, Inspection Level S-4.

DPSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Post, Weld				9292622
					NEXT HIGHER ASSEMBLY 9292680
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined	See 4.5.1			
Major					
101	Total length		0.40%	3.2	Gage
102	Total height		0.40%	3.2	Gage
103	Total width, 2 places		0.40%	3.2	Gage
104	Height of step relief, 4 places		0.40%	3.2	Gage
105	Width of step relief, 4 places		0.40%	3.2	Gage
106	Length of pads, 2 places		0.40%	3.2	Gage
Minor					
201	Ejection pin marks, max (Note 4)		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9292676
4.4.2.9	Spring, Take-Up				NEXT HIGHER ASSEMBLY 9292680
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Total length - Datum A		0.40%	3.2	Gage
102	Width		0.40%	3.2	Gage
103	Height		0.40%	3.2	Gage
104	Largest radius		0.40%	3.2	Gage
105	Thickness		0.40%	3.2	Gage
106	Hardness test	5	0-1	3.2	Test*
Minor					
201	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES: *Samples selected shall be tested in accordance with ASTM E 18, Accept 0, Reject 1.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.10	Cover, Power Supply				9292614
					NEXT HIGHER ASSEMBLY 9292680
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined	*			
Major					
101	Profile		0.40%	3.2	Gage
102	Largest thickness		0.40%	3.2	Gage
103	Hole diameter, 2 places		0.40%	3.2	Gage
104	Location of terminal hole, 2 places		0.40%	3.2	Gage
105	Diameter of center recess		0.40%	3.2	Gage
106	Thickness of center recess		0.40%	3.2	Gage
107	Thickness of triangular recess, 3 places		0.40%	3.2	Gage
108	Height of angular section (View B)		0.40%	3.2	Gage
Minor					
201	Ejection pin marks, max (Note 4)		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES: *See 4.5.1 for qualification and production control of mold cavities.

DESC-R-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.11	O-Ring	1	1	9292657
				NEXT HIGHER ASSEMBLY: 9292680

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter		0.40%	3.2	Gage
102	Thickness		0.40%	3.2	Gage
Minor					
201	Excess flash - cut or scored finish		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DRSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.12	Holder, Lead				9292611
					NEXT HIGHER ASSEMBLY 9292680
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined	See 4.5.1			
Major					
101	Inside diameter		0.40%	3.2	Gage
102	Height of pad above boss		0.40%	3.2	Gage
103	Width (datum -A-)		0.40%	3.2	Gage
104	Length (datum -B-)		0.40%	3.2	Gage
105	Height to shoulder of boss		0.40%	3.2	Gage
106	Length of clearance recess		0.40%	3.2	Gage
107	True position of pad diameter*		0.40%	3.2	Gage
108	Diameter of pad above boss*		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES: *Banking pad or boss for P.W. Board.

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.13	Battery and Lead Assembly				9292678
					NEXT HIGHER ASSEMBLY 9292680
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Height of side lead		0.40%	3.2	Gage
102	Height of center lead		0.40%	3.2	Gage
103	Length of center lead, max		0.40%	3.2	Gage
104	Length of side lead from top of case		0.40%	3.2	Gage
105	Distance of side lead from top of case, max		0.40%	3.2	Gage
106	Solderability, 2 places	(a)	0-1	3.2	MIL-S-45743
107	Pull test, 2 places	(b)	0-1	3.2	4.5.2
Minor					
201	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:
- (a) Sample size per MIL-STD-105, Inspection Level S-3.
- (b) Sample size per MIL-STD-105, Inspection Level S-4.

DRSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.14	Circuit Board				9292654
					NEXT HIGHER ASSEMBLY 9292652
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Largest outside diameter		0.40%	3.2	Gage
102	Total thickness, max		0.40%	3.2	Gage
103	Diameter of second smallest hole, 2 places (View B)		0.40%	3.2	Gage
104	Location of second smallest hole, 2 places (Note 4)		0.40%	3.2	Gage
105	Diameter of largest solder resist area, max (View A) (Note 2B)		0.40%	3.2	Gage
106	Smallest solder resist area radius (View B) (Note 2B)		0.40%	3.2	Gage
107	Outside corner radius, 3 places		0.40%	3.2	Gage
108	Minimum angular ring (Note 6)		0.40%	3.2	Gage
Minor					
201	Plating of pad incorrect 9 places (Note 5)		0.65%	3.2	MIL-STD-275
202	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.15	Receiver Coil Assembly	1 OF 1	9292652
			NEXT HIGHER ASSEMBLY: 9292680

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Spacing of coil's 1st turn to edge of ckt board, min - 3 places		0.40%	3.2	Gage
102	Incorrect soldering, 2 places		0.40%	3.10	Visual
103	Thickness, max		0.40%	3.2	Gage
104	Spacing of coil to solder pad, min - 4 places		0.40%	3.2	Gage
105	Resistance		0.40%	3.2	Milliohmmeter
106	Inductance		0.40%	3.2	Impedance Bridge
Minor					
201	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DRSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9292653
4.4.2.16	Coil				NEXT HIGHER ASSEMBLY 9292652
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter, max		0.40%	3.2	Gage
102	Inside first coil diameter, min		0.40%	3.2	Gage
103	Thickness, max		0.40%	3.2	Gage
104	Resistance	(a)	0-1	3.2	Milliohmmeter
105	Inductance	(a)	0-1	3.2	Impedance Bridge
Minor					
201	Length of flat, 2 places		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:
(a) Samples as per MIL-STD-105, Inspection Level S-3.

DRSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.17	Retainer, Coil (when used)				9292660
					NEXT HIGHER ASSEMBLY 9292652
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Thickness		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DRSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.18	Housing, Power Supply (Weldment)				9292617
					NEXT HIGHER ASSEMBLY 9292616
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Insulation sleeving around sensor nozzle missing or improper *		0.40%	3.2	Visual
102	Height after welding, max		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES: *Inspection performed prior to inserting sensors.

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.19	Housing, Power Supply		9292618
			NEXT HIGHER ASSEMBLY 9292617

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined	*			
Major					
101	Diameter of O-Ring groove		0.40%	3.2	Gage
102	Width of O-Ring groove		0.40%	3.2	Gage
103	Length to and including groove		0.40%	3.2	Gage
104	Total height		0.40%	3.2	Gage
105	Flatness		0.40%	3.2	Gage
106	Largest outside diameter, 2 places		0.40%	3.2	Gage
107	Width of smallest slot - body orientation , 2 places		0.40%	3.2	Gage
108	Diameter of blind holes, indexing, 4 places		0.40%	3.2	Gage
109	Location of holes in #108		0.40%	3.2	Gage
110	Diameter of hole for Battery Primer		0.40%	3.2	Gage
111	Depth of S&A cavity		0.40%	3.2	Gage
112	Smallest diameter of angular hole, 4 places		0.40%	3.2	Gage
113	Location of holes in #112		0.40%	3.2	Gage
114	Depth of ultrasonic weld grooves 8 places		0.40%	3.2	Gage
115	True position of O-Ring groove diameter		0.40%	3.2	Gage

NOTES: *See 4.5.1 for qualification and production control of mold cavities.

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.19	Housing, Power Supply	2 OF 2	9292618
			NEXT HIGHER ASSEMBLY: 9292617

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
116	Diameter of S&A cavity		0.40%	3.2	Gage
117	Width of Datum C		0.40%	3.2	Gage
118	Diameter of Terminal Hole, 2 places		0.40%	3.2	Gage
119	Location of Terminal Hole, 2 places		0.40%	3.2	Gage
Minor					
201	Width of tapered slots - 3 for weld posts		0.65%	3.2	Gage
202	Location of slots of #201		0.65%	3.2	Gage
203	Depth of slots of #201		0.65%	3.2	Gage
204	Ejection pin marks above flush (Note 8)		0.65%	3.2	Gage
205	Width of ultrasonic weld groove 8 places		0.65%	3.2	Gage
206	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DRSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.20	Plate, Power Supply				9292619
					NEXT HIGHER ASSEMBLY 9292617
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined	*			
Major					
101	Largest outside diameter		0.40%	3.2	Gage
102	Diameter of center hole (S&A)		0.40%	3.2	Gage
103	Length to flat in center hole (S&A)		0.40%	3.2	Gage
104	Length to flats around central cavity (4 places)		0.40%	3.2	Gage
105	Height of weld tongue from datum D		0.40%	3.2	Gage
106	Height of weld tongue		0.40%	3.2	Gage
107	Thickness to datum D		0.40%	3.2	Gage
108	Location of largest outside diameter		0.40%	3.2	Gage
109	Location of lead holder slots, 4 places		0.40%	3.2	Gage
110	Width of lead holder slots, 4 places		0.40%	3.2	Gage
111	Diameter of selector switch hole		0.40%	3.2	Gage
112	Location of selector switch hole		0.40%	3.2	Gage
113	Depth of selector switch hole		0.40%	3.2	Gage
114	Width of Datum B		0.40%	3.2	Gage

NOTES:

*See 4.5.1 for qualification and production control of mold cavities.

DPSMC-0A (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.20	Plate, Power Supply				9292619
					NEXT HIGHER ASSEMBLY 9292617
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Largest width of weld tongue		0.65%	3.2	Gage
202	Depth of smallest radius between weld tongue		0.65%	3.2	Gage
203	Width of cutout on outside diameter, 2 places		0.65%	3.2	Gage
204	Height between protrusion in central area, 4 places		0.65%	3.2	Gage
205	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DPSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.21	Power Supply Housing Assembly				9292616
					NEXT HIGHER ASSEMBLY 9292680
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Sensor leak are crossed, or touch sensor case, 4 places		0.40%	3.2	Visual
102	Potting above flush, 4 places (Note 2)		0.40%	3.2	Gage
103	Leak test		100%	3.5	4.5.3
Minor					
201	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.22	Pin, Retaining, Test Point	1 OF 1	9292675
			NEXT HIGHER ASSEMBLY: 9292679

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Height of pin above flange bottom		0.40%	3.2	Gage
102	Diameter of hole		0.40%	3.2	Gage
103	Knurl diameter		0.40%	3.2	Gage
104	Length of pin below flange bottom including knurl		0.40%	3.2	Gage
105	Diameter of pin above flange		0.40%	3.2	Gage
106	True position of hole		0.40%	3.2	Gage
Minor					
201	Flange diameter		0.65%	3.2	Gage
202	Incorrect finish		0.65%	3.2	Certificate of Conformance
203	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DRSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.23	Housing, Upper (Weldment)				9292633
					NEXT HIGHER ASSEMBLY 9292631
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Insulation sleeving around sensor nozzle missing or improper*		0.40%	3.2	Visual
102	Height after welding, max.		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

*Inspection performed prior to inserting sensors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 3		DRAWING NUMBER
4.4.2.24	Housing, Upper				9292635
					NEXT HIGHER ASSEMBLY 9292633
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined	*			
Major					
101	Diameter of O-Ring groove		0.40%	3.2	Gage
102	Width of O-Ring groove		0.40%	3.2	Gage
103	Length to and including groove		0.40%	3.2	Gage
104	Total height		0.40%	3.2	Gage
105	Flatness		0.40%	3.2	Gage
106	Diameter of holes in flat on O.D., 2 places 5A/4		0.40%	3.2	Gage
107	Location of holes in flat on O.D., 2 places 5A/4		0.40%	3.2	Gage
108	Largest outside diameter, 2 places		0.40%	3.2	Gage
109	Diameter of second largest blind hole, 4 places		0.40%	3.2	Gage
110	Location of second largest blind hole, 4 places		0.40%	3.2	Gage
111	Smallest diameter of angular hole, 4 places		0.40%	3.2	Gage
112	Location of holes in CD #111		0.40%	3.2	Gage
113	Depth of ultrasonic weld groove, 5 places		0.40%	3.2	Gage
114	Depth of second largest central cavity S&A		0.40%	3.2	Gage

NOTES: *See 4.5.1 for qualification and production control of mold cavities.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 2 OF 3		DRAWING NUMBER
4.4.2.24	Housing, Upper				9292635
					NEXT HIGHER ASSEMBLY
					9292633
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
115	Depth of ring cutout between weld grooves, 4 places		0.40%	3.2	Gage
116	Diameter of largest hole 5D/3		0.40%	3.2	Gage
117	Diameter of smallest hole, 5D/3		0.40%	3.2	Gage
118	Diameter of holes in flat on O.D., 2 places, 4D/4		0.40%	3.2	Gage
119	Location of holes in flat on O.D., 2 places, 4D/4		0.40%	3.2	Gage
120	True position of O-Ring groove diameter		0.40%	3.2	Gage
121	Diameter of second largest central cavity - S&A		0.40%	3.2	Gage
Minor					
201	Width of ultrasonic weld groove, 8 places		0.65%	3.2	Gage
202	Width of tapered slot in outside diameter, 3 places - for weld posts		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 3 OF 3		DRAWING NUMBER
4.4.2.24	Housing, Upper				9292635
					NEXT HIGHER ASSEMBLY 9292633
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
203	Location of tapered slot in outside diameter, 3 places		0.65%	3.2	Gage
204	Depth of tapered slot in outside diameter, 3 places		0.65%	3.2	Gage
205	Ejection pin marks above flush		0.65%	3.2	Visual
206	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DRSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.25	Plate, Upper				9292634
					NEXT HIGHER ASSEMBLY 9292633
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Largest outside diameter		0.40%	3.2	Gage
102	Smallest inside diameter		0.40%	3.2	Gage
103	Height of weld tongue		0.40%	3.2	Gage
104	Height of weld point		0.40%	3.2	Gage
105	Diameter of central cavity		0.40%	3.2	Gage
106	Thickness to Datum D		0.40%	3.2	Gage
107	Location of largest outside diameter		0.40%	3.2	Gage
108	Diameter of selector switch hole		0.40%	3.2	Gage
109	Depth of selector switch hole		0.40%	3.2	Gage
110	Location of selector switch hole		0.40%	3.2	GAge
111	Width of Datum B		0.40%	3.2	Gage
Minor					
201	Largest width of weld tongue		0.65%	3.2	Gage
202	Depth of smallest radius between weld and tongue		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES: *See 4.5.1 for qualification and production control of the mold cavities.

DRSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9292157
4.4.2.26	Shorting Bar, Ceramic				NEXT HIGHER ASSEMBLY 9292158
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness (substrate)		0.40%	3.2	Gage
102	Solderability	10	1/	3.2	2/
Minor					
201	Total height		0.65%	3.2	Gage
202	Total length		0.65%	3.2	Gage
203	Dielectric glaze missing or incomplete		0.65%	3.2	Visual
204	Solder coating outside area "A" incorrect		0.65%	3.2	Visual
205	Thickness of solder pad (2 places)		0.65%	3.2	Gage
206	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:
1/ Reject for one (1) or more defective.
2/ Per MIL-S-45743.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.27	Shorting Bar and Connector Assembly				9292158
					NEXT HIGHER ASSEMBLY 9292682
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Solder workmanship incorrect		0.40%	3.10	Visual (10x)
102	Evidence of cracks or chips		0.40%	3.2	Visual
Minor					
201	Edge of connector extends beyond ceramic, 2 places		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.28	Shorting Bar				9292682
					NEXT HIGHER ASSEMBLY 9292680
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Epoxy adhesive missing or applied incorrectly		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DRSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.29	Upper Housing Assembly				9292631
					NEXT HIGHER ASSEMBLY 9292679
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Lead location after potting, 4 places		0.40%	3.2	Visual
102	Potting above flush, 4 places		0.40%	3.2	Gage
103	Leak test		100%	3.5	4.5.3
Minor					
201	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.30	Cushion				9292636
					NEXT HIGHER ASSEMBLY
					9292679
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of smallest holes, 4 places		0.40%	3.2	Gage
102	True position of smallest holes with datums -A- and -B-		0.40%	3.2	Gage
Minor					
201	Inside diameter		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.31	Electronic and Housing Assembly				9292679
					NEXT HIGHER ASSEMBLY 9292680
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Height to selector switch		0.40%	3.2	Gage
102	Clearance of pressure cartridge end of selector switch from O.D. of upper plate incorrect		0.40%	3.2	Gage
103	Test point retainer missing or not secured (Note 4) 4 places		0.40%	3.2	Visual
104	Location of sensor wires (Note 5), 4 places		0.40%	3.2	Visual
105	Soldering of sensor wires incorrect, (Note 5) 8 places		0.40%	3.10	Visual
106	Folding of flexible wiring incorrect, 2 places		0.40%	3.2	Visual
107	Solder joints not coated (Note 6), 8 places		0.40%	3.2	Visual
108	Sensor lead insulation protrudes beyond outside diameter of electronic assy while latter is held against cushion, 8 places		0.40%	3.2	Visual-Manual

NOTES:

DPSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9292679
4.4.2.31	Electronic and Housing Assembly				NEXT HIGHER ASSEMBLY 9292680
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
109	Torque test of selector switch	(a)	0-1	3.5.2	4.5.3.2
110	Selector ball binds, is stuck or is missing		0.40%	3.2	Visual-Auditory
Minor 201	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES: (a) Test parts without sensors or potting may be used, provided the torque test is performed every four (4) hours, including the beginning and end of shift.

NRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.32	Body Assembly (Assembly of Battery Primer and Insert)				9292680
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Staking of insert improper, Note 4		0.40%	3.2	Visual
102	Insert or electrical battery primer loose after staking, Note 4		0.40%	3.2	Visual/Manual
Minor					
201	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DPSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.33	Body Assembly (Prior to Bonding of Battery Cells)				9292680
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Number of layers and position of insulation tape on end of battery cell incorrect (Note 5), 2 places		0.40%	3.2	Visual
102	Insulator disc missing or improperly applied to terminal end of battery cell, 2 places		0.40%	3.2	Visual
103	Soldering of battery cell leads missing or incorrect, 4 places (Note 2)		0.40%	3.10	Visual
104	Coating of battery cell leads missing or incorrect, 4 places (Note 3)		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
4.4.2.34	Body Assembly (Prior to Welding the Power Supply Housing Assy and the Electronic/Housing Assy together)		1 OF 2	9292680
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	1/				
1	Presence and safe position of spring loaded centrifugal locks, 2 places		100%	3.6	Visual
2	Safe position of slider release pin and shear pin		100%	3.6	Visual
3	Distance from end of S&A to slider assy, max.		100%	3.6	Gage
4	Shorting eyelet missing		100%	3.6	Visual
Major					
101	Soldering of sensor leads missing or incorrect, 8 places (Note 2)		0.40%	3.10	Visual
102	Soldering of S&A cables missing or incorrect, 3 places (Note 2)		0.40%	3.10	Visual
103	Coating of solder joints missing or incorrect, 11 places (Note 3)		0.40%	3.2	Visual
104	Bonding of lead holders incorrect, 4 places, (Notes 6, 25)		0.40%	3.2	Visual
105	Take-up spring missing or inverted		0.40%	3.2	Visual

NOTES: 1/ Safety inspection of S&A assy prior to assembly in Body Assembly.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.34	Body Assembly (Prior to Welding the Power Supply Housing Assy and the Electronic/Housing Assy together)	2 OF 2	9292680
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
106	S&A orientation incorrect		0.40%	3.2	Visual
107	Shorting portion of S&A cable not removed		0.40%	3.2	Visual
108	O-Ring missing or not lubricated, (Note 8)		0.40%	3.2	Visual
109	Tape on sensor leads missing or incorrect, 4 places (Note 24)		0.40%	3.2	Visual
110	Any component missing or incorrect		0.40%	3.2	visual
Minor					
201	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DPSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.35	Body Assembly (Prior to Assembly of Gasket and Epoxy Putty)				9292680
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Ultrasonic welding at both ends of weld post incorrect, 3 places (Note 10)		0.40%	3.2	Visual
102	Bonding of battery cells or location of side terminal incorrect, 2 places (Note 5)		0.40%	3.2	Visual
103	Assembly orientation of shorting bars incorrect, 2 places - prior to soldering		0.40%	3.2	Visual
104	Seating of terminals prior to soldering incorrect, 2 places		0.40%	3.2	Visual
105	Soldering of shorting bar and battery primer leads missing or incorrect, 6 places (Note 2)		0.40%	3.10	Visual
106	Height of shorting bar and battery primer solder joints, max (6 places)		0.40%	3.2	Gage
107	Coating of shorting bar and battery primer solder joints missing or incorrect, 6 places (Note 3)		0.40%	3.2	Visual

NOTES:

DPSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
4.4.2.35	Body Assembly (Prior to Assembly of Gasket and Epoxy Putty)		2 OF 2	9292680
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
108	Soldering of flexible circuit to terminals missing or incorrect, 2 places (Note 2)		0.40%	3.10	Visual
109	Height of flexible circuit to terminal solder joints, max. (2 places)		0.40%	3.2	Visual
Minor 201	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DPSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.36	Body Assembly (Prior to Assembly Power Supply Cover)				9292680
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Gasket missing or improperly assembled		0.40%	3.2	Visual
102	Epoxy missing from cover (Note 14)		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DRSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.37	Body Assembly (Prior to Applying Sealing Compound Over Receiver Coil)				9292680
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Welding of power supply cover incorrect (before assembly of coil)		0.40%	3.2	Visual
102	Bonding of receiver coil incorrect		0.40%	3.2	Visual
103	Soldering of receiver coil to terminals missing or incorrect, 2 places (Note 2)		0.40%	3.10	Visual
104	Distance from end of body assembly to end of terminals and terminal solder joints, min (2 places)		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DPSMC-0A (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.38	Body Assembly (Final)				9292680
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Resistance across shorted firing capacitor		100%	3.7.1	4.5.4
2	Distance from end of S&A to slider assy, max		100%	3.7.1	Gage
Major					
101	Soldering of pressure cartridge to electronic assembly incorrect, 2 places		0.40%	3.10	Visual
102	Potting of pressure cartridge missing or incorrect		0.40%	3.2	Visual
103	Coating of pressure cartridge solder joints incorrect, 2 places (Note 3)		0.40%	3.2	Visual
104	Sealant over coil is over flush (Note 19)		0.40%	3.2	Visual
105	Solder joints and receiver coil not covered by potting (Note 19)		0.40%	3.2	Visual
106	Outside diameter, max		0.40%	3.2	Gage
107	Overall height		0.40%	3.2	Gage
108	Tripline circuit resistance, max (4 places)		100%	3.7.2	4.5.4

NOTES:

DRSMC-DA (R) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.38	Body Assembly (Final)				9292680
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
109	Resistance of receiver coil circuit		100%	3.7.2	4.5.4
110	Resistance of pressure cartridge ckt		100%	3.7.2	4.5.4
111	Resistance of piston actuator ckt		100%	3.7.2	4.5.4
112	Resistance of detonator ckt		100%	3.7.2	4.5.4
113	Unactivated cell voltage, max. 2 places		100%	3.7.1	4.5.4
Minor 201	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.39	Body Assembly (Packaging, Packing)				9292680
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Conductive foam material missing from terminal pads, 2 places		0.40%	5.1	Visual
102	Barrier bag missing or improperly sealed		0.40%	5.1	Visual
103	Separators and cushioning between barrier bag and outer box improper or missing		0.40%	5.2	Visual
104	Marking missing, incorrect or illegible		0.40%	5.3	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

DPSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.40	Body Assembly				9292680
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	LOT ACCEPTANCE TESTS	(a)			
Critical					
1	Unsafe after transportation-Vibration		0-1	3.3.1	4.5.5
2	Premature arming		0-1	3.4	4.5.6.4 (See Note c)
3	Premature detonation		0-1	3.4	4.5.6.4
4	Hazardous dud	(b)	0-1	3.4	4.5.6.4
Major					
	RESISTANCE OF EED's AFTER T-V	(a)		3.7.2	4.5.4
101	M100 Detonator				
102	Micro Piston Actuator				
103	Pressure Cartridge				
104	Receiver Coil Circuit Resistance				
	PERFORMANCE TEST: LAUNCH/FUNCTION	(b)		3.4	4.5.6
105	Tripline (TL)/Breakwire (BW) mode				
106	Self Destruct (SD): normal/extended				
107	Antidisturbance (AD) mode				
108	Dud				
109	Early SD				

NOTES:
(a) Sample as per MIL-STD-105 gen insp level I, single sampling, normal insp.
(b) (See Sheet 2).
(c) Acoustic sensor shall be used for monitoring

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9292680
4.4.2.40	Body Assembly (cont.)				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD

LOT ACCEPTANCE: TEMPERATURE CONDITIONING-LAUNCH-FUNCTION — ACCEPT-REJECT 1/

BODY INS.	ASSY LOT	SAMPLE SIZE	-35° -5°F TL/BW	-35° -5°F SD (N)	-35° -5°F * SD (E)	-35° -5°F AD	Ambient TL BW	Ambient SD (N)	Ambient * SD (E)	Ambient AD	+145° +5°F TL/BW	+145° +5°F SD (N)	+145° +5°F * SD (E)	+145° +5°F AD	FAILURE DUD L.O. DET **	FAILURE DUD EARLY SD	HAZARD-OUS DUD	PREMATURE ARM-ING	PREMATURE DETON-ATION
501	1200	32	5	3	1	2	4	3	1	2	5	3	1	2	1-2	1-2	0-1	0-1	0-1
1201	3200	50	7	5	2	3	6	5	2	3	7	5	2	3	2-3	2-3	0-1	0-1	0-1
3201	10000	80	11	7	4	5	10	7	4	5	11	7	4	5	3-4	2-3	0-1	0-1	0-1
10001	35K	125	17	11	6	8	16	11	6	8	17	11	6	8	4-5	3-4	0-1	0-1	0-1

*For information only with test data supplied to DRSMC-QAT-M(D).
**Include TL/BW, SD_N & AD failures.

1/ See 4.5.6.4 for definitions of defects listed above under accept-reject.
2/ See 4.5.6.6 for data to be recorded.
3/ For any sample size listed above, no premature or hazardous duds are allowed.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Forms.

4.4.4 Inspection Equipment. The inspection equipment required to perform the examinations and tests prescribed is listed or described in the Paragraph Reference/Inspection Method column in the forms starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.4.5 Test Mine Case Assembly. A reusable or expendable test mine case assembly will have the equivalent testing features of a regular mine case assembly for a Body Assembly but will contain an inert filler, removable cover (s) and no explosive boosters. The test case enclosure for Body Assembly will be used as fixtures for subjecting lot acceptance sample to environmental conditioning, launching of mine and subsequent functioning in various modes. The Test Mine Case Assembly or Test Fixture shall be reusable if it is found safely feasible to remove the Body Assemblies from these test fixtures immediately after they are returned to the conditioning or functioning chamber but prior to the actuation of the micropiston actuator.

4.4.6 Launcher for test mines. The launcher for launch arming the lot acceptance test sample of Body Assemblies in test mine case assemblies noted in 4.4.5 shall be a device simulating the M128 Launcher with the following features:

a. Impart a back spin to the mine assemblies so that they exit launcher with a back spin of 3075 min. RPM.

b. Impart an ejection velocity of 65.0 - 6.0 feet per second and orient the mines so that the mine spin axis will have an elevation of 43.0 degrees to the horizontal and a tilt of 20.0 degrees with the vertical.

c. The launch trajectory height from ground shall be 28 to 38 feet and trajectory distance of 100 to 140 feet.

d. Initiate the electric battery primer and set the self-destruct time by inducing either of two preselected voltage levels in the mine receiver coil circuit at the launcher exit using the following: Power Supply, Transmitter, Dwg. 9293021; Transmitter Assembly, Dwg. 9293046; and a 28.0 ± 0.3 VDC supply voltage which is stable under all loading conditions .

1. The air gap between the Transmitter Assembly and the mine as it passes the Transmitter Assembly shall be 0.086 inch max. and the axial offset (misalignment) shall be 0.1 inch max.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

2. Assure proper system operation by monitoring the self-checking circuit outputs of the Transmitter Power supply.

4.4.7 Impact medium. The impact or target material will simulate an asphalt surface and will consist of three (3) 1.5 inch thick particle boards (Clipboard), with a density of approximately 31 pounds per cubic foot.

4.5 Methods of inspection.

4.5.1 Dimensional control of molded or plastic parts. In place of the normal sampling and inspections associated with the Classification of Defects, and after a curing time for the parts has been approved (See Note 1), a sample of three (3) parts (as molded) from each cavity shall be fully inspected dimensionally (all dimensions on drawing) to qualify a new or reworked cavity for use in production. The molded parts shall carry the individual cavity identification. As a control of each cavity during production, the above quantity of parts from each cavity shall be inspected for at least the defects listed in the pertaining paragraphs 4.4.2.1 through 4.4.2.30, after continuous production of each 5,000 parts or at the end of each week, whichever occurs first. Of the three (3) samples, one (1) sample shall be the last part produced. If any defective parts are found during qualification of the cavity, the cavity producing the defective part(s) will not be used in production. If any defective parts are found when inspection is performed for the control of the cavity, the cavity producing the defective part(s) shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for inspection for each separate type of defect according to MIL-STD-105, using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. All cavities removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request. Contractor designs of gages and test equipment required to perform the inspections listed herein shall be forwarded to Commander, ARDC, Dover, New Jersey 07801, ATTN: DRSMC-QAT-I(D) for approval prior to manufacture of equipment. The noted sub-paragraphs identify those items and minimum inspections subject to the requirements of this paragraph.

NOTE 1: In establishing a curing time, dimensionally check ten (10) parts from each cavity at periodic intervals (e.g. every 30, 60 etc minutes) until dimensional stability is attained. The curing time will be from the time the part comes out of the mold until

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

dimensional stability is attained. The inspection data used in determining the curing time shall be sent to ARDC, Dover, New Jersey 07801, ATTN: DRSMC-QAT-M (D). If there is a change in material, or in the cycle time, or if a cavity is reworked, or a new cavity is used, a new curing time shall be established and approved (see 6.5).

NOTE 2: Those features of a part which are subsequently machined or otherwise worked upon to meet its drawing requirements shall be inspected in accordance with the classification of defects.

4.5.2 Pull test of Battery and Lead Assembly leads. Dwg. 9292678 - The assembly shall be placed in approved test fixture and the pull load specified on the drawing shall be applied. Observation shall be made for compliance with the applicable drawing requirement. (Non-Destructive test.)

4.5.3 Ultrasonic welded assemblies.

4.5.3.1 Seal Leak Test of the Power supply Housing Assembly; Upper Housing Assembly. The integrity of the seal or quality of the weldment and applicable subsequent potting shall be verified by subjecting the assemblies to an internal pressure of 75 ± 3 psig and measuring the pressure drop in a 5 second minimum time interval. A leak rate in excess of that specified in 3.5 shall indicate excessive leakage and reject the assembly. Dry nitrogen shall be used to apply the required pressure and the assembly under test shall be held in a fixture such that the fixture will not aid the sealing being tested. The test fixture shall incorporate a means for sealing the outside parts of the four sensors. (Non-Destructive Test).

4.5.3.2 Torque test of selector switch assy. The required torque shall be applied between the selector switch assy and the upper housing assy of the Electronic and Housing Assembly, Dwg. 9292679. The resistive force shall act on the upper housing assy. Observation shall be made for conformance to the requirement of 3.5.2. (Non-Destructive Test).

4.5.4 Electrical circuit checks of Body Assemblies. Dwg . 9292680 - The circuits checks as listed in Table II shall be performed on the complete Body Assemblies. Body assemblies failing the requirements listed shall be rejected. (Non-Destructive Test).

4.5.5 Transportation-Vibration of Body Assemblies. The lot acceptance test samples of Body Assemblies shall be serialized and secured in fixtures, then assembled to the table of the vibrator and tested in accordance with Test 119, Procedure 2, of MIL-STD-331. Observation shall be made for compliance with the requirement of 3.3.1. Samples shall be used in subsequent testing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

NOTE: The Body Assemblies may be tested in standard shipping (service item) package in lieu of rigid mounting in a fixture.

4.5.6 Performance tests of Body Assemblies. After completion of the transportation vibration, the sample Body Assemblies in the test mine case assemblies or fixtures shall be divided in groups for temperature conditioning required. Each group shall be subjected to only one temperature for a minimum period of 4 hours as specified in 3.3.2. The Body Assemblies shall be taken from the conditioning chamber and tested as follows:

Within five (5) minutes after being removed from the conditioning chamber, the Body Assemblies shall be launched to enable the S&A's, activate the battery cells and set the self destruct feature at normal or extended (see 4.4.5, 4.4.6 and 4.4.7). After launch, the test mine case assemblies containing sample Body Assemblies shall be returned to the temperature conditioning/functioning chamber (controlled area) as required. The Body Assemblies shall be placed with one half of each sample oriented receiver coil up; the remaining sample, receiver coil down. After enable time has occurred, the test samples shall be functioned in the three following modes: 1. AD mode; 2. Tripline mode; 3. Self destruct mode either normal or extended (Destructive Tests). Enable time is defined as the maximum Group C Electronic Arm Time specified on Dwg. 9292960, plus five (5) minutes, minimum.

4.5.6.1 Antidisturbance (AD) Mode functioning. Following launch (see 4.5.6) and before micropiston actuator actuation, the test samples shall be secured in a tilt fixture. After enable time has occurred, the test sample shall then be subjected to the following:

a. The item shall have its central axis tilted slowly through 900 from the horizontal ; then slowly returned to its original position.

b. Failing functioning, (a) shall be repeated in the opposite direction.

c. If failure is obtained from (a) and (b), rocking or jarring mine should be attempted.

d. Allow one minute intervals between attempts.

e. If no detonation is detected, attempt to function by triplines (see 4.5.6.2).

f. Failing (e), item shall be monitored until expiration of extended SD.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

g. Observe and record the number and length of triplines deployed per mine (length applies to ambient temperature only).

h. Observation shall be made for compliance with the requirements of 3.4 and Dwg. 9292960.

i. Subsequent to the test and observing necessary safety precautions, the tested assemblies shall be dismantled and failure analyzed. For duds, allow a min of 24 hours after extended SD runout (see 4.5. 6.3.a). Failure analysis shall include cause of tripline nondeployment. (Destructive Test)

4.5.6.2 Tripline (TL) Mode functioning. Following launch (see 4.5.6), the test samples selected for TL function shall be secured so as to preclude functioning by AD Mode. First article samples slated for TL function at ambient temperature shall, after TL deployment, have their sensor cavities filled with salt water (3.5 percent by weight of sea salt in distilled water). After enable time has occured, all test samples shall be functioned as follows:

a. Attempts shall be made to function the item by applying a gradual increasing pull force, in turn, to each tripline available until detonation occurs.

b. Observe and record the number and length of triplines deployed per mine; the number and types of failures prior to the successful attempt and the pull force when detonation occurred. (Length applies to ambient temperature only).

c. If detonation does not occur in (a), attempt shall be made to function Body Assy in AD mode per 4.5.6.1(c).

d. If unsuccessful in (a), and (b), the assy shall be monitored until expiration of extended SD.

e. Observation shall be made for compliance with the requirement of 3.4 and Dwg 9292960.

f. Subsequent to the test and observing necessary safety precautions, the Tested Assemblies shall be dismantled and failure analyzed. For duds, allow a min of 24 hrs after extended SD runout (see 4.5. 6.3.a). Failure analysis shall include cause of tripline nondeployment. (Destructive Test)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

TABLE II

MINE, AP: HE, M74
BODY ASSEMBLY ELECTRICAL CHECKS
PRIOR TO PACKAGING

	ELECTRICAL CHECK	TEST POINTS	REQUIREMENT
1.	SHORT ACROSS FIRING CAPACITOR	13 to 8	1.25 OHMS MAX
2.	UNACTIVATED BATTERY CELL #1 VOLTAGE	18 to 8	0.005 VDC MAX (Note 2)
3.	UNACTIVATED BATTERY CELL #2 VOLTAGE	18 to 10	0.005 VDC MAX (Note 2)
4.	TRIPLINE Resistance (#1 & 7)	3 to 8	6.0 OHMS MAX
5.	TRIPLINE Resistance (#2 & 6)	4 to 8	6.0 OHMS MAX
6.	TRIPLINE Resistance (#3 & 8)	1 to 8	6.0 OHMS MAX
7.	TRIPLINE Resistance (#4 & 5)	2 to 8	6.0 OHMS MAX
8.	Receiver Coil Circuit Resistance	5 to 8	0.8 - 1.7 OHMS
9.	PRESSURE CARTRIDGE Resistance	19 to 8	2.0 - 6.1 OHMS
10.	PISTON ACTUATOR Resistance	20 to 8	4.0 - 11.0 OHMS
11.	DETONATOR Resistance	17 to 8	3.0 - 12.5 OHMS

NOTES :

1. Applies to Body Assembly Dwg No 9292680. See Dwg 9292965 for test point locations.

2. For voltage checks, use a voltmeter with 3 10 Megohm input impedance.

3. For resistance checks, use a milliohmmeter having a short circuit current of 1 ma or less e.g. Valhalla Igniter circuit checker .

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

4.5.6.3 Self Destruct (SD) Mode. The Body Assemblies selected for SD Mode (See Note), set for normal or extended at launch, shall be subjected to the following:

a. The conditioning temperature shall be maintained until the programmed SD time has elapsed. CAUTION SHALL BE OBSERVED DURING AND AFTER RETURN OF DUDS TO AMBIENT TEMPERATURE FOR POSSIBLE HEALING OR REMISSION OF FAULT(S) FOLLOWED BY LATE OR LOW VOLTAGE DETECTION (LVD) FUNCTIONING.

b. Assy set for normal SD and failing to function at the end of the programmed interval shall be monitored until extended SD. Attempts shall then be made to function unit in Tripline mode (see 4.5.6.2). Failing both modes the unit shall be set aside for 24 hours for later dismantling and analysis with precautions taken as noted in (a) above.

c. Observe and record the number of triplines deployed per mine.

d. Observation shall be made for compliance with requirements of 3.4 (b, c) and Dwg 9292960.

e. Subsequent to the test and observing necessary safety precautions, the Tested Assemblies shall be dismantled and failure analyzed. For duds, allow a min of 24 hours after extended SD runout (see 4.5.6.3.a). Failure analysis shall include cause of tripline nondeployment. (Destructive Test)

NOTE: Ground lead of AD Switch, P/N 9298512-1, located on Electronic Assembly P/N 9292965 shall be cut just prior to performing the destructive test specified in paragraph 4.4.2.40, Category 106.

4.5.6.4 Premature Arming; Premature Detonation; Early Self Destruct; Low Order; Detonation; Hazardous Dud; Non-Hazardous Dud; Tripline Failures.

a. Premature Arming is defined as arming of the S&A Assy (actuation of micropistion actuator) prior to minimum arming time specified on Dwg 9292960.

b. Premature Detonation is defined as detonation of an armed S&A Assy prior to the minimum electronic arm time specified on Dwg 9292960.

c. Early Self Destruct is defined as detonation of an armed S&A occurring at or after the minimum electronic arm time specified on Dwg 9292960 but prior to the set SD time period, or prior to being functioned by AD or TL Mode.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

d. Low Order Detonation for the Body Assembly Dwg 9292680 is defined as detonation of an armed S&A where only two main charge leads detonate properly.

e. Hazardous Dud is any armed mine or body assy which detonates after the programmed SD time has elapsed by any of the following:

1. Actuation by prime fuze.
2. Being disturbed.
3. Power source run-down.

f. A Non-Hazardous Dud is defined as a mine/body assy which will not detonate by conditions 1, 2, or 3 listed under Hazardous Dud.

g. Tripline failures are any of the following:

1. Less than 28 meters of total effective length of deployed TL.
2. Failure of two (2) breakwires to function mine.

4.5.6.5 Disposition of Duds. Procedural plans or methods for disposing of duds by either safely dismantling and failure analysis, or by safely destroying shall be furnished to ARDC for approval see 6.4. Caution: When depleted, battery cells become unstable and generate high internal pressures.

4.5.6.6 Recording of performance data, The following performance data shall be recorded with serial numbers:

a. Orientation of body assemblies.
b. Time to arm (launch to actuation of micropiston actuator).
c. The time for Triplines to deploy after launch.
d. The number of broken triplines per mine.
e. The number of main charge leads that functioned.
f. The number of triplines deployed per mine.
g. The pull force at which each tripline broke and/assembly functioned in TL Mode.
h. The number and type of tries before detonation.
i. The order of detonation.
j. Time from launch to normal SD function.
k. Time from launch to extended SD function.
l. The number of duds.
m. For TL and AD modes (ambient only), length of deployed triplines.
n. The number of hazardous dud (see 4.5.6.4).
o. After failure analysis record cause of malfunctions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging and marking. The body assembly shall be packaged in accordance with level B of Spec MIL-P-14232 with the following mandatory requirements: The two terminal pads shall be wrapped with conductive foam material and each body assembly shall be wrapped to preclude foreign matter settling inside body assembly; the items shall be packaged in a fiberboard box and separated by loose partitions and separators as required. Cushioning as needed shall be used; the fiberboard box shall be sealed in a barrier bag conforming to Type I, Class F, Style 1, Spec MIL-B-117.

5.2 Packing. The body assemblies in box and barrier bag shall be packed in accordance with level B of Spec MIL-P-14232 and Code of Federal Regulations, Title 49 with the following mandatory requirements: The outer packing box shall be wood conforming to Class 1, Style 4, Spec PPP-B-621 or fiberboard conforming to Spec 12H, 23F, or 23H of code of Federal Regulation, Title 49; Sufficient cushioning and separators must be used between the barrier bag and outer box to prevent damage to the items or tearing of the barrier bag.

5.3 Marking. The marking of the outer box shall be in accordance with MIL-STD-129 and DOT marking per Code of Federal Regulation, Title 49. Marking indicating the components are fragile electronics shall be employed.

5.4 Shipping. When Body Assemblies from more than one lot are shipped as a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use. The Body Assemblies covered by this specification are intended for use in Mine, Antipersonnel: HE, M74.

6.2 Ordering data. See MIL-A-48078. In addition the acquisition documents shall specify, as required, the following:

a. Provisions for first article as specified in Sections 3 and 4 of the following documents:

MIL-B-48761 - Battery, Single Cell
MIL-E-63300 - Electronics Assembly
MIL-B-63299 - Body Assembly for Mine, Antipersonnel: HE, M74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to Commander, ATT N: DRSMC-QAT-I(D), ARDC, Dover, NJ 07801.

6.4 Submission of plans for approval. The plans required in Section 4.5.6.5 shall be submitted for approval to: Commander, ARDC, Dover, NJ 07801, ATTN: DRSMC-QAT-M(D).

6.5 Submission of process control documents. Process control documents as specified in 3.8 shall be submitted in accordance with DI-P-1604 (Mod) with Attachment 1 listed on DD Form 1423 incorporated in the contract.

6.6 Submission of ammunition data cards and performance data. In addition to the normal distribution of records, one (1) copy of all performance data and ammunition data cards shall be forwarded to Commander, ARDC, Dover, NJ 07801, ATTN: DRSMC-QAT-M(D).

6.7 Data requirements. Deliverable data required by this specification is cited in the following paragraph.

Paragraph	Data requirements	Applicable DID
6.3	Quality Engineering Acceptante Inspection Equipment Descriptive Documentation	DI-R-1714 (Tailored)
3.8, 6.5	Manufacturing Method Report	DI-P-1604 (MOD) ATTACHMENT 1
4.5.6.5, 6.4	Disposition of Duds	*DI-T-5372 (Tailored)

*Delete a, b, c, d of previous paragraph 1 block 10, DD Form 1664 and substitute contractor designated parameters and limits.

6.6	Ammunition Data Card	DI-L-1410
4.4.2.34	Quality Inspection Defect	DI-R-1721
4.4.2.38	Report (Critical Defects Only)	
4.4.2.40		

6.8 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Center (ARDC) may also include drawings prepared by and identified as Edgewood Arsenal, U.S. Army Armament Research and Development Command (ARRADCOM), Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDC.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

6.9 Change from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A302)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

APPENDIX

EXCEPTIONS AND CLARIFICATIONS TO SOLDERING SPECIFICATION

NOTES:

10 SCOPE: This appendix details clarifications and exceptions to MIL-S-45743 for hand soldering.

20 APPLICABLE DOCUMENT

MIL-S-45743 - Soldering, Manual Type, High Reliability, Electrical and Electronic Equipment.

30 REQUIREMENTS: The following exceptions/clarifications to reference MIL-S-45743 paragraphs shall apply.

Paragraph 3.3.1.2 Control of airborne contaminants. Delete the sentence, "Positive pressure shall . . . between them".

Paragraph 3.3. 2.4.5 Soldering irons and resistance soldering irons. Delete the sentence, "The soldering iron shall . . . or standby condition.", and substitute the sentence, "The soldering iron shall be a soldering iron approved by the technical agency or a soldering iron that attains a temperature not greater than 10°F (5.6°C) above the control temperature when in an idling or standby condition."

Paragraph 3.4.5.7 Printed board termination. Subparagraph d - Change to read, "When leads cannot be clinched per above, they shall extend through the printed board, be visible and properly soldered."

Paragraph 3.4.5.8 Ribbon lead geometry. Add new sentence, "Ribbon lead terminations from battery and lead assembly shall comply with paragraph 3.4.5.7b."

Paragraph 3.6.1 Cleaning the soldered connection. Delete the sentence, "After the solder . . . contaminants," and substitute the sentence, "After the solder is completely solidified, all residual flux and soils shall be removed (within 1 hour) using solvents which will remove residual flux, activators and other contaminants.

Paragraph 3.6.3 Resistivity of solvent extract. Delete requirement .

Paragraph 4.2.1 One hundred percent inspection. - Delete and substitute the following: "4.2.1 Level of Inspection. - Inspection for soldered connections and associated wiring and leads shall be performed to the level specified in the product classification of defects and the product specification."

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:26Z
Check the source to verify that this is the current version before use.

Paragraph 4.2.2 Sampling inspection. Delete requirement.

Paragraph 4.3.1 Visual inspection. Change third sentence to read, "A clear incandescent or fluorescent light should be used for detection of uncovered copper."

Paragraph 4.3.2 Cleanliness test. Delete requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARMAMENT RESEARCH & DEVELOPMENT CENTER
ATTN: DRSMC-QA
DOVER, NJ 07801

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:26Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-B-63299A	BODY ASSEMBLY FOR MINE, ANTI-PERSONNEL: HE M74

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:26Z
Check the source to verify that this is the current version before use.