INCH-POUND

MIL-C-63261 (AR)
AMENDMENT 2
03 November 1993
SUPERSEDING
AMENDMENT 1
20 January 1990

MILITARY SPECIFICATION

CARTRIDGE, 105MM, TNT, HE, M760
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-C-63261 (AR) dated 9 October 1980 and is approved for use by the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1 Standards Military

* Add: "MIL-STD-129 - Marking for Storage and Shipment"

Add: "MIL-STD-410 - Nondestructive Testing Personnel Qualification and Certification"

Add: "MIL-STD-414 - Sampling Procedures and Tables for Inspection by Variables for Percent Defective"

Delete: "MIL-STD-1235 - Single and Multi-level Continuous Sampling Procedures and Tables for Inspection by Attributes"

PAGE 2

2.1 Drawings:

9211610-2 and 9278812-2 Delete in their entirety.

AMSC N/A

FSC 1315

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

2.1 Drawings: 9289185, delete title:

"Cartridge, 105MM, HE, M760, with M200 Propelling Charge Assembly for Howitzer, M204, Loading" and substitute the following:

"Cartridge, 105MM, HE, M760, for Howitzer M119 Loading Assembly"

2.1 Drawings: Add the following:

"12551889 - Projectile, 105MM, HE, M760 Loading Assembly"

* 2.1 Product and Package Drawings:

Delete the following in their entirety:

"9275180" and "9275181".

(Note packaging drawings "7549072" and "7549073" which were deleted in amendment 1, have been reinstated in amendment 2.)

In the title of drawing numbers 7549072 and 7549073:

Change "Fiber container M105A2" to "Fiber Container M105A3"

* Delete Packaging drawing 9271850 in its entirety and substitute the following:

"12934901 - Packing and Marking for Container Ammo Metal, PA117, for 105MM, Howitzer ctg. Packed in PA55 or M105A3

19-48-4231/
45-20PM1006 - Unitization Procedures for Ammunitions Components Packed in a Cylindrical Metal or Plastic Container on 4-Way Entry Metal Pallets"

* 2.1.1 Add the following paragraph:

"2.1.1 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

PAGE 3

3.3.1 Add the following sentence to the end of Table I:

"An Annular rating is defined as cavitation that takes the form of a ring or portion thereof around the periphery of the cast."

PAGE 4

3.3.2, Last line, delete: "9211610-2 or dwg. 9278812-2" and substitute "12551889".

Add 3.3.6 and 3.3.7 as follows:

"3.3.6 Metal parts defects. There shall be no cracks, pipes or thin wall sections in the projectile.

3.3.7 Foreign material. There shall be no foreign material in the explosive charge."

3.4.3.2.1, Title, delete the following "(applicable to M572 Fuze only)"

PAGE 5

3.4.3.3, Line 2 and 3 delete:

"shall not be more than 2195 feet per second nor less than 2145 feet per second" and substitute the following:

"shall not be more than 2102 feet per second nor less than 2052 feet per second".

3.4.3.4 Delete in its entirety and substitute the following:

"3.4.3.4 Pressure. The pressure of the cartridge, fired at +145 degrees Fahrenheit, shall not produce a PIMP (Permissible Individual Maximum Pressure) greater than 57,000 psi when fired in a M119 Howitzer."

3.5 Lines 3, 4, 5 and 6: Delete: "US Army Armament. . . projectile. A substitute item. . . Dover, New Jersey 07801." and substitute the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

"U.S. Army Armament Research, Development and Engineering Center, for use in radiographing this projectile. A substitute item shall not be used before prior testing and approval by the U.S. Army Armament Research, Development and Engineering Center, ATTN: SMCAR-QA, Picatinny Arsenal, New Jersey, 07806-5000."

PAGE 6

* Add paragraphs 3.7, 3.8 and 3.9:

"3.7 Moisture content. The maximum moisture content of the packing material shall not exceed the limit as specified on dwg. 12934901, 7549073 and 9258026.

3.8 Air pressure test. The packed and sealed metal container assemblies shall withstand an air pressure test as specified on drawing 12934901.

3.9 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be specified in the contract."

4.2 Delete and substitute:

"4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection"

Add 4.2.1, 4.2.1.1, 4.2.1.2 and 4.2.1.3:

"4.2.1 First article inspection.

4.2.1.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.2.1.2. The first article sample shall consist of:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

	Part Description	Drawing	Quantity
	Cartridge, 105MM, HE, M760, LAP	9289185	52
	Projectile, 105MM, HE, M760, LAP	12551889	10
*	Packing and Marking for Container, Ammo Fiber, M105A3 for 105MM Howitzer	7549073	10
*	Packing and Marking for Container, Fiber, PA55 for 105MM Howitzer Ammo Without Fuze	9258026	10
*	Packing and Marking for Container, Ammo Metal, PA117 for 105MM Howitzer cartridge Packed in PA55 or M105A3	12934901	10

(Amendment 2 adds three new packaging and marking first article inspections as per above newly added packaging)

4.2.1.2 Inspection to be performed. See MIL-A-48078 and Table II specified herein.

4.2.1.3 Rejection. See MIL-A-48078."

* Add Table II First article as included pages 6a and 6b.

(Table II First article is expanded to two pages per Amendment 2. Sheet "1 of 1" is changed to Sheet "1 of 2". Drawing number "9289185 or 12551889 as applicable" is changed to "See Below".)

PAGE 8

4.3.2.1 Block, Drawing Number: delete: "9211610-2 or 9278812-2 as applicable" and substitute "12551889".

PAGE 9

4.3.2.2 Block, Drawing Number: delete: "9211610-2 or 9278812-2 as applicable" and substitute "12551889".

PAGE 10

4.3.2.3 Block, Drawing Number: delete: "9211610-2" and substitute "12551889".

PAGE 11

4.3.2.4 Block, Drawing Number: delete "9211610-2" and substitute "12551889".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

TABLE II. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
	Cartridge, 105MM, HE, M760 Loading, Assembling and Packing				See below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cartridge, 105MM, HE, M760 Loading, Assembling and Packing (Dwg. 9289185)				
	Examination for defects	52(a)	100%	3.2	4.3.2.10
	Proving Ground Test (Muzzle Velocity-Functioning)	30(a)	100%	3.4	4.3.3.5.4, 4.4.2
	Proving Ground Test (Safety)	20(a)	100%	3.4	4.3.3.5.2, 4.4.2
	Examination for defects	b(a)	100%	3.2	4.3.2.6 thru 4.3.2.9
	Projectile, 105MM, HE, M760 Loading Assembly (Dwg. 12551889)				
	Examination for defects	10	100%	3.2	4.3.2.3 thru 4.3.2.4
	Radiographic inspection	10	100%	3.3	4.4.1

NOTES:
(a) Use same samples for these tests and examinations.
(b) Two cartridges shall be disassembled to allow checking of the examination from para. 4.3.2.6 thru 4.3.2.9.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:26Z
Check the source to verify that this is the current version before use.

TABLE II. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE Cartridge, 105MM, HE, M760 Loading, Assembling and Packing		SHEET 2 OF 2		DRAWING NUMBER See below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Packing and Marking for Container Fiber PA55 for 105MM Howitzer Ammunition Without Fuze (Dwg. 9258026) Examination for defects	10	100%	3.1	4.3.2.11/4.3.2.12
	Packing and Marking for Container Ammo Metal PA117, for 105MM, Howitzer Ctg. Packed in PA55 or M105A3 (Dwg. 12934901)	10	100%	3.1	4.3.2.14/4.3.2.15
	Packing and Marking for Container, Ammo Fiber M105A3 for 105MM Howitzer (Dwg. 7549073)	10	100%	3.1	4.3.2.11/4.3.2.12

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T04:26Z
Check the source to verify that this is the current version before use.

PAGE 12 and 13

4.3.2.5 Delete in its entirety.

PAGE 19

* 4.3.2.11 Delete table in its entirety and substitute new table (See included table).

PAGE 20

* 4.3.2.12 Delete table in its entirety and substitute new table (See included table).

* 4.3.2.14 Add new table entitled, "Metal Container (unsealed)": (See included table).

* 4.3.2.15 Add new table entitled, "Sealed Metal Container": (See included table).

* 4.3.2.16 Add new table entitled, "Unitization Procedure for Cylindrical Metal or Plastic Containers in 4-Way Entry Pallets" (See included table).

PAGE 21

* 4.3.2.13 Title: After Sealed wood packing box, add: "(alternate)".

* Drawing Number Block: delete in its entirety and substitute "7549072 or 9258027 (as applicable)".

* Major 103 Delete "DOT symbol missing or incorrect", " 5.2" and substitute "Marking missing, misleading, illegible or incorrect", "5.3".

* Minor 204 Delete "Marking (other than DOT) misleading, missing or unidentifiable"; "5.3" and substitute "Evidence of poor workmanship"; "3.6".

PAGE 22

4.3.3.2 Delete the last para in its entirety: "The sample plan . . . equipment needed for this test is CD." and substitute the following:

"This test shall be performed on all loaded projectile assemblies (100 percent inspection). The radiographic test shall be performed as specified in 4.4.1, using equipment in accordance with 4.3.4. Any assembly which has any one of the above critical defects shall be classed defective and removed from the lot."

Source: https://assist.dla.mil -- Downloaded: 20261O-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.3.2.11	Packing and Marking for Container Fiber (Unsealed)		7549073 or 9258026
			NEXT HIGHER ASSEMBLY: 7549072 or 12934901

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Packing components missing, damaged or improperly assembled		0.40%	3.1	Visual
102	Cartridge cannot be inserted or removed easily by hand		0.40%	3.1	Manual
103	Container covers cannot be removed easily by hand		0.40%	3.1	Manual
104	Insufficient fillers for tight pack (slight gap between body and corners)		0.40%	3.1	Visual
105	Moisture content of packing material		0.40%	3.1	4.4.4
Minor					
201	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

(61) 6

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2.12	Sealed Fiber Container				7549073 or 9258026
					NEXT HIGHER ASSEMBLY
					7549072 or 12934901
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Tape incomplete, wrinkled or incorrect material		0.40%	3.1	Visual
102	Contents loose		0.40%	3.1	Manual
103	Marking missing, misleading illegible or incorrect		0.40	3.1	Visual
104	Any component missing or damaged		0.40	3.1	Visual
Minor					
201	Tear tab length, minimum		0.65%	3.1	Gage
202	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.3.2.14	Metal Container (unsealed)		12934901
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Tape damaged during inserting/ extraction from metal container		0.40%	3.1	Visual
102	Cloth strap incorrect width or length		0.40%	3.1	Visual
103	Cloth strap assembled incorrectly or missing		0.40%	3.1	Visual
104	Moisture content of packing material		0.40%	3.7	4.4.4
Minor					
201	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63261 (AR)
AMENDMENT 2

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.3.2.15	Sealed Metal Container		12934901
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Container damaged, exposing contents		0.40%	3.1	Visual
102	Metallic seal missing or improperly secured		0.40%	3.1	Visual
103	UN Marking missing or incorrect		0.40%	3.1	Visual
104	Air leak test		100%	3.8	4.4.3
105	Screw not properly replaced and torqued after test		0.40%	3.1	Visual
106	Contents loose in metal container		0.40%	3.1	Manual
107	Marking incorrect, missing or unidentifiable		0.40%	3.1	Visual
Minor					
201	Evidence or poor workmanship		1.00%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.3.2.16	Unitization Procedure for Cylindrical Metal or Plastic Containers on 4-Way Entry Pallets	1 OF 1	19-48-4231/45-20PM1006
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Missing or loose strapping		0.40%	3.1	Visual/Manual
102	Incorrect number of containers on pallet (except for light load)		0.40%	3.1	Visual
103	Containers not all positioned in the same direction and properly interlocked		0.40%	3.1	Visual
104	Marking missing, incorrect or illegible		0.40%	3.1	Visual
Minor					
201	Evidence or poor workmanship		1.00%	3.6	Visual

NOTES:

Source: https://assist.dla.mil Downloaded: 2024-10-25T05:36Z
Check the source to verify that this is the current version before use.

Add paragraphs 4.3.3.2.1 and 4.3.3.2.2 as follows:

"4.3.3.2.1 Metal parts defects. (Critical defect). All radiographs of projectile section loading assemblies shall be examined for evidence of cracks, pipes and thin wall sections in the warhead. The presence of any such indication shall cause that assembly to be classed defective and removed from the lot. (See section 6.18).

4.3.3.2.2 Foreign material. (Critical defect). All radiographs of projectile section loading assemblies shall be examined for foreign material in the explosive charge. The presence of any foreign material shall cause that assembly to be classed defective and removed from the lot."

4.3.3.3 Paragraph title, delete: "9211610 or 9278812 as applicable," and substitute "12551889".

PAGE 23

4.3.3.5.2.1; 4.3.3.5.2.2; 4.3.3.5.3 and 4.3.3.5.4 delete:

"M572 Fuze" wherever it appears (5 places) and substitute "M739 Fuze".

PAGE 24

4.3.3.5.5 and 4.3.3.5.5.1 delete in their entirety and substitute the following:

"4.3.3.5.5 Pressure test, with fuze, M739 (see 3.4.3.4) - Major defect. For the first three lots manufactured, the cartridges used in 4.3.3.5.2.1 (conditioned to +145 degrees Fahrenheit) shall be used for this test. If any individual pressure exceeds requirement specified in 3.4.3.4 when tested as specified in 4.4.2.2.1, the lot shall be rejected.

4.3.3.5.5.1 Pressure test, with fuze, M739 (see 3.4.3.4) - Major defect. After three (3) consecutive lots have complied with the criteria of 4.3.3.5.5, the cartridges used in 4.3.3.5.2.2 (conditioned to +145 degrees Fahrenheit) shall be used for this test. If any individual pressure exceeds requirement specified in 3.4.3.4, when tested as specified in 4.4.2.2.1, the lot shall be rejected."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

4.3.4 Delete in its entirety and substitute the following:

"4.3.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.3.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See section 6 of MIL-A-48078 and 6 herein."

PAGE 26

Add paragraph 4.4.1.3 as follows:

"4.4.1.3 Operator qualifications. For operation of radiograph equipment, personnel shall be qualified and certified in accordance with MIL-STD-410, Level I. For set-up and calibration of radiographic equipment, personnel shall be qualified and certified in accordance with MIL-STD-410, Level II."

4.4.2, Line 4, delete: "M204 howitzer" and substitute "M119 howitzer".

4.4.2.1, Paragraph title: delete "M572 Fuze" and substitute "M739 Fuze".

4.4.2.1, Change "informational control projectiles/rounds/ samples" to "M760 master calibration cartridges" wherever it appears (4 places).

4.4.2.1, Delete "1146 Mils" and "381 Mils" wherever they appear (2 places) and substitute "750 Mils $\pm$ 50 Mils" and "380 Mils $\pm$ 50 Mils" respectively.

PAGE 28

4.4.2.2, Line 2, Add the following sentence after the first sentence:

"Each group shall be temperature conditioned for 16 hours minimum."

4.4.2.2, Line 10, delete: "1146 Mils" and substitute "750 Mils $\pm$ 50 Mils".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

4.4.2.2, Line 11, delete the last sentence and substitute the following:

"Pressure data for group 2 shall be recorded for information only."

Add paragraph 4.4.2.2.1:

"4.4.2.2.1 PIMP pressure (+145 degrees Fahrenheit). The projectile samples and test conditions for this test shall be group I of paragraph 4.4.2.2. The pressure data for each round shall be recorded."

4.4.2.3 Delete "and pressure" from paragraph title.

4.4.2.3, Line 5, delete: "1146 Mils" and substitute "750 Mils ± 50 Mils".

* Add two new paragraphs 4.4.3 and 4.4.4:

"4.4.3 Air pressure test. The packed and sealed metal container assemblies shall be subjected to the external air pressure test as specified on drawing 12934901. Observation shall be made for a pressure drop exceeding the requirement for the specified time. The cartridge packed in a defective metal container may be removed from that container and packed in a different container to be tested.

4.4.4 Maximum moisture content of packing material. Testing for the maximum percentile of moisture content of the packaging material may be accomplished using commercially available test equipment."

* 5., 5.1, 5.1.1, 5.1.1.1, 5.2, 5.2.1, 5.2.1.1, 5.3 and 5.3.1 delete in their entirety and substitute the following:

"5. PACKING

5.1 Preservation and packaging.

* 5.1.1 Level A. Each cartridge shall be packaged in accordance with drawing 7549073 or 9258026.

5.2 Packing.

* 5.2.1 Level A. Each packaged fiber container (dwg. 7549073 or 9258026) shall be packed in a PA117 metal container and cushion assembly in accordance with dwg. 12934901.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

* 5.2.2 Alternate packing - Level A. Only with the specific approval of the contracting officer, the cartridge in fiber container shall be packed and marked in a wooden box in accordance with dwgs. 7549072 or 9258027.

5.3 Marking.

* 5.3.1 Level A (Fiber container). The fiber container shall be marked in accordance with dwgs. 7549073 or 9258026.

* 5.3.2 Level A (Metal container). The metal container outer pack shall be marked in accordance with dwg. 12934901 and MIL-STD-129.

* 5.3.3 Level A (Alternate wood box). The wood box shall be marked in accordance with dwg. 7549072 or 9258027.

* 5.4 Unitization.

* 5.4.1 Level A. The packed metal container shall be unitized in accordance with dwg. 19-48-4231/45-20PM1006."

PAGE 29

6.1, Line 2, delete: "Howitzer, M204" and substitute "Howitzer, M119".

6.2.1 Add new paragraph:

"6.2.1 Data card. Data cards are required and shall be prepared. See MIL-A-48078 (AR)."

6.3 Delete in its entirety and substitute the following:

"6.3 Drawings. Drawings listed in section 2 of this specification under the headings U.S. Army Armament Research and Development Center (ARDC) may also include drawings prepared by and identified as, U.S. Army Armament Research and Development Commander (ARRADCOM), Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

Delete 6.7, 6.7.1, 6.7.2 and 6.7.3 in their entirety and substitute the following:

* "6.7 Submission of contractor inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs, as required, to: Commander, U.S. Army Armament, Munition and Chemical Command, ATTN: SMCAR-QAR-I, Picatinny Arsenal, New Jersey 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract."

PAGE 31

6.8, Lines 3 and 4: delete the following:

"Army Armament Research and Development Command, Dover, New Jersey 07801, ATTN: DRDAR-QAR-Q" and substitute the following:

"Army Armament Research, Development and Engineering Center, Picatinny Arsenal, New Jersey 07806-5000, ATTN: SMCAR-QAR-Q".

6.10, Lines 5, 6, 7 and 8: delete the following:

"Commander
U.S. Army Armament Research and Development Command
ATTN: DRDAR-QAR-Q and DRDAR-LCA-G
Dover, New Jersey 07801" and substitute the following:

"Commander
U.S. Army Armament Research, Development and Engineering Center
Picatinny Arsenal, New Jersey 07806-5000
ATTN: SMCAR-QAR-Q and SMCAR-FSA-MS"

PAGE 32

6.15, Lines 4 and 5: delete the following:

"Army Armament Research and Development Command, ATTN: DRDAR-QAR-Q, Dover, New Jersey 07801" and substitute the following:

"Army Armament Research, Development and Engineering Center, ATTN: SMCAR-QAR-Q, Picatinny Arsenal, New Jersey 07806-5000".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

6.16, delete: "M752 Fuze" wherever it appears (4 places) and substitute "M739 Fuze".

6.16, delete: "1146 Mils" wherever it appears (6 places) and substitute "750 Mils ± 50 Mils".

6.16 Test 1. Change title from "Safety" to "Safety and Pressure".

Test 3. Change title from "Informational Control Rounds" to "M760 Master Calibration Cartridges".

Test 5. Change title from "Muzzle Velocity and Pressure" to "Muzzle Velocity".

6.16 delete: "381 Mils" wherever it appears (2 places) and substitute "380 Mils ± 50 Mils".

Add paragraph 6.18 as follows:

"6.18 Rejected projectile metal parts. The procuring activity will be notified of any projectile rejected for metal parts defects found upon inspection of the radiographs. The rejected projectile will be held pending disposition by the procuring activity."

The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirement of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-AD58)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.