MILITARY SPECIFICATION

DELAY MODULE, IMPACT, METAL PARTS ASSEMBLY, AND PACKING

This specification is approved for use by the U.S. Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not covered by the drawings and provides quality assurance provisions for the fabrication of metal parts, assembly and packing for the Delay Module, Impact.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-I-45607 - Inspection Equipment, Acquisition, Maintenance and Disposition of

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests for

MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition components

FSC: 1390

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

DRAWINGS

U S Army Armament Research and Development Command (ARRADCOM)

9258606	Fuze Body Assembly for M739
9258607	Booster Cup
9258611	Closing Screw
9282958	S & A Module and Retainer Assy (inert)
11836270	Delay Module, Impact

(Copies of specifications standards drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

3. REQUIREMENTS

3 1 Materials Materials shall be in accordance with applicable drawings and specifications.

3 2 Parts The parts shall comply with all requirements specified on drawings listed in 2 1 and associated drawings and with all requirements specified in applicable specifications and standards.

3 3 Drop test. The Module (Dwg 11836270) shall function satisfactorily as evidenced by the complete firing of the assembly.

3 4 Jolt and jumble. The Module (Dwg. 11836270) shall comply with the requirements of MIL-STD-331, Tests 101.2 and 102.1.

3.5 Transportation vibration. The Module (Dwg. 11836270) shall comply with the requirements of MIL-STD-331, Test 119.

3.6 Die castings. The die castings shall be of uniform quality, free of cold shuts, and blowholes.

3.6.1 Surface porosity.

3 6.1.1 Plunger. No voids will be permitted on inside surface of spin detent holes and slider ball grooves.

3.6.1.2 Holder, firing pin. No voids will be permitted on the slider mating diameter and firing pin sliding surface.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

3.7 Workmansnip. All parts shall be fabricated and finisned in a thorough, workmanlike manner and all manufacturing, processing and assembly operations shall be correctly performed. The parts shall be clean and free of burrs, sharp edges, unblended radii, surface defects, cracks, cnips, dirt, grease and oil (except where specifically required), rust and other foreign matter. The cleaning method used snall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat, legible and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspection. The following types of inspection shall be conducted on this item:

a. First article inspection.
b. Quality conformance inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with provisions of 4.3.2.

4.3.2. Inspection to be performed. See MIL-A-48078 and Table I specified herein. In addition (5) five of each component part and sub-assembly shall be inspected in accordance with 4.4.2.

4.3.3 Rejection. See MIL-STD-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with lot formation provisions of MIL-A-48078.

4.4.2. Examination. See MIL-A-48078.

Sampling plans. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

TABLE I First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63406 (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
	Delay Module, Impact	1	1	11836270
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None Defined.				
MAJOR					
101	Height of protrusion max.	80			
102	Outside diameter, max.	80			
103	Height from bottom of housing to top of housing cover, max.	80			
104	Non-arming test	80	(a)	3.2	4.5.3
105	Arming test	80	(a)	3.2	4.5.2
106	Drop test	80	(a) (b)	3.3	4.5.1
107	Jolt and Jumble	18		3.4	4.5.4
108	Transportation/Vibration	15		3.5	4.5.5
109	Cover fails to withstand pushout force	5		3.2	4.5.6
MINOR					
201	Evidence of poor workmanship	80	3.7	Visual	

NOTES:
(a) Testing must follow the sequence shown.
(b) Use accepted, armed units from arming test Major 105.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63406 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Cover, Housing	1 OF 1	11836288
			NEXT HIGHER ASSEMBLY 11836270

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Diameter of center hole, min.	(a)		3.2	Gage
102	True position of center hole	(a)		3.2	Gage
103	Outside diameter, max.	(a)		3.2	Gage
MINOR					
201	Evidence of poor workmanship	(a)		3.7	Visual

NOTES:
(a) Five (5) pieces per punch per day (see 4.5.8).

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63406 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Spring, Plunger	1 OF 1	11836287
			NEXT HIGHER ASSEMBLY: 11836270

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined.				
MAJOR					
101	Load P_1 or P_2 does not comply with drawing requirements		0.40%	3.2	Gage
102	Does not work freely in a dia. bore at an installed height		0.40%	3.2	Gage
103	Does not work freely over a dia. rod at an installed height		0.40%	3.2	Gage
MINOR					
201	Evidence of poor workmanship		0.65%	3.7	Visual
202	Solid height, max.		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63406 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Housing				11836286
					NEXT HIGHER ASSEMBLY
					11836270
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined.				
MAJOR					
101	Diameter of center hole, min.	(a)		3.2	Gage
102	Location of center hole	(a)		3.2	Gage
103	Inside diameter, min.	(a)		3.2	Gage
104	Outside diameter, max.	(a)		3.2	Gage
105	Inside length	(a)		3.2	Gage
MINOR					
201	Evidence of poor workmanship	(a)		3.7	Visual

NOTES:

(a) Five (5) pieces per punch per day (see 4.5.8).

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63406 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Retainer, Slider Spring	1 OF 1	11836285
			NEXT HIGHER ASSEMBLY: 11836278

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined.				
MAJOR	None defined.				
MINOR					
201	Evidence of poor workmanship		0.65%	3.7	Visual
202	Presence of slots		0.65%	3.2	Visual
203	Outside diameter		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63406 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Spring, Slider	1 OF 1	11836284
			NEXT HIGHER ASSEMBLY 11836278

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined.				
MAJOR					
101	Load P_1 or P_2 does not comply with drawing requirements		0.40%	3.2	Gage
102	Does not work freely in a dia. bore at an installed height		0.40%	3.2	Gage
103	Does not work freely over a dia. rod at an installed height		0.40%	3.2	Gage
MINOR					
201	Evidence of poor workmanship		0.65%	3.7	Visual
202	Solid height, max.		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:37Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63406 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Spring, Firing Pin	1 OF 1	11836283
			NEXT HIGHER ASSEMBLY 11836278

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None Defined.				
MAJOR					
101	Load P_1 or P_2 does not comply with drawing requirements		0.40%	3.2	Gage
102	Does not work freely in a dia. bore at an installed height		0.40%	3.2	Gage
MINOR					
201	Evidence of poor workmanship		0.65%	3.7	Visual
202	Solid height, max.		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63406 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Slider	1 OF 1	11836282
			NEXT HIGHER ASSEMBLY 11836278

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None Defined.				
MAJOR					
101	Outside diameter of spring mating surface, max.		0.40%	3.2	Gage
102	Inside diameter, min.		0.40%	3.2	Gage
103	Inside diameter (ball locking), min.		0.40%	3.2	Gage
104	Length of undercut, min.	12 (a)		3.2	Gage
105	Distance from locking surface to the top, min.	12 (a)		3.2	Gage
MINOR					
201	Outside diameter, max.		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

(a) Destructive testing. Reject the lot if one or more defects in the sample.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63406 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.8	Pin, Firing		11836281
			NEXT HIGHER ASSEMBLY 11836278

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Width of tip, max.		0.40%	3.2	Gage
102	Depth of cavity, min.		0.40%	3.2	Gage
103	Location of notch		0.40%	3.2	Gage
104	Diameter of notch, max.		0.40%	3.2	Gage
105	Outside diameter, max.		0.40%	3.2	Gage
106	Diameter of cavity, min.		0.40%	3.2	Gage
MINOR					
201	Evidence of poor workmanship		0.65%	3.7	Visual
201	Profile of point		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63406 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Holder, Firing Pin	1 OF 1	11836279
			NEXT HIGHER ASSEMBLY 11836278

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Inside diameter, min.	(a)		3.2	Gage
102	Outside diameter, max.	(a)		3.2	Gage
103	True position of outside diameter	(a)		3.2	Gage
104	Small inside diameter, min.	(a)		3.2	Gage
105	Diameter for ball seating area, min.	(a)		3.2	Gage
106	True position of ball seating diameter	(a)		3.2	Gage
107	Small outside diameter of forward end	(a)		3.2	Gage
108	Length from bottom of forward housing seat to rear surface of the flange	(a)		3.2	Gage
109	Large outside diameter of forward end	(a)		3.2	Gage
110	Surface porosity	(a)		3.6.1.2	Visual
MINOR					
201	Evidence of poor workmanship	(a)		3.7	Visual

NOTES:

(a) Five (5) samples per cavity (see 4.5.7 and 4.5.9).

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.10	Firing Pin Holder Assembly	1	1	11836278
				NEXT HIGHER ASSEMBLY 11836270

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Push off force does not withstand 5 lbs.	5		3.2	4.5.6
102	Missing firing pin		0.40%	3.2	Visual
103	Either ball missing		0.40%	3.2	Visual
MINOR					
201	Improper assembly		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63406 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.11	Pin, Pivot	1 OF 1	11836277
			NEXT HIGHER ASSEMBLY: 11836271

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Outside diameter, max.		0.40%	3.2	Gage
MINOR					
201	Evidence of poor workmanship		0.65%	3.7	Visual
202	Overall length, max.		0.65%	3.2	Gage

NOTES:

DRSAR-QA Form 760 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63406 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.12	Lock, Detent	1 OF 1	11836276
			NEXT HIGHER ASSEMBLY 11836271

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined.				
MAJOR					
101	Pin hole diameter, min.		0.40%	3.2	Gage
102	True position of pin hole dia.		0.40%	3.2	Gage
103	Distance between tabs, max.		0.40%	3.2	Gage
MINOR					
201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63406 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.13	Retainer, Detent		11836275
			NEXT HIGHER ASSEMBLY 11836271

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Thickness max.		0.40%	3.2	Gage
MINOR					
201	Evidence of poor workmanship		0.65%	3.7	Visual
202	Outside diameter, max.		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 2020-10-20T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63406 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.14	Spring, Detent	1 OF 1	11836274
			NEXT HIGHER ASSEMBLY 11836271

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Load P_1 or P_2 does not comply with drawing requirements		0.40%	3.2	Gage
102	Does not work freely in dia. bore at an installed height		0.40%	3.2	Gage
103	Does not work freely over a dia. rod at an installed height		0.40%	3.2	Gage
MINOR					
201	Evidence of poor workmanship		0.65%	3.7	Visual
202	Solid height, max.		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63406 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.15	Detent, Spin	1 OF 1	11836273
			NEXT HIGHER ASSEMBLY 11836271

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined.				
MAJOR					
101	Diameter of spring cavity, min.		0.40%	3.2	Gage
102	Overall length		0.40%	3.2	Gage
103	Diameter of mating surface for firing pin holder		0.40%	3.2	Gage
104	Height max. from inside of spring cavity		0.40%	3.2	Gage
105	Large outside diameter, max.		0.40%	3.2	Gage
MINOR					
201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assistdla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.16	Plunger	1	1	11836272
				NEXT HIGHER ASSEMBLY 11836271

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Outside diameter, max.	(a)		3.2	Gage
102	Distance between tabs, min.	(a)		3.2	Gage
103	Inside diameter, min.	(a)		3.2	Gage
104	Spin detent hole diameter, min.	(a)		3.2	Gage
105	Spin detent hole center distance, max.	(a)		3.2	Gage
106	Ball slot width, min.	(a)		3.2	Gage
107	Surface porosity	(a)		3.6.1.1	Visual
MINOR					
201	Overall length, max.	(a)		3.2	Gage
202	Width of pin slot, min.	(a)		3.2	Gage
203	Length of pin slot, min.	(a)		3.2	Gage
204	Evidence of poor workmanship	(a)		3.7	Visual

NOTES:
(a) Five (5) pieces per cavity (see 4.5.7 and 4.5.9).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63406 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.17	Plunger Assembly	1 OF 1	11836271
			NEXT HIGHER ASSEMBLY 11836270

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Pin fails to withstand pushout force	5		3.2	4.5.6
102	Detent retainer fails to withstand pushout force	5		3.2	4.5.6
MINOR					
201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRSMR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.18	Delay Module, Impact		11836270
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Height of protrusion, max.		0.40%	3.2	Gage
102	Outside diameter, max.		0.40%	3.2	Gage
103	Height from bottom of housing to the top of housing cover, max.		0.40%	3.2	Gage
104	Nonarming test	(a)	100%	3.2	4.5.3
105	Arming test	(a)	100%	3.2	4.5.2
106	Drop test	50(b)		3.3	4.5.1
107	Jolt and Jumble	9		3.4	4.5.4
108	Transportation Vibration	9		3.5	4.5.5
109	Cover fails to withstand pushout force	5		3.2	4.5.6
MINOR					
201	Evidence of poor workmanship		0.65%	3.7	Visual
202	Lot identification nomenclature missing or inadequate		0.65%	3.2	Visual

NOTES:
(a) Arming shall be performed before non-arming.
(b) Double Sampling Plan: 50-0-2, 100-1-2

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Jolt and jumble test.

4.4.3.1.1 Beginning with the first lot produced and continuing until three consecutive lots have been found acceptable, a sample of eighteen (18) modules shall be selected from each lot and tested in accordance with 4.5.4. If any module fails to comply with the requirements of the test, the lot shall be rejected.

4.4.3.1.2 After three consecutive lots have met the criteria specified in 4.4.3.1.1, the sample size shall be reduced to 9 and tested per 4.5.4. If any module fails to comply with the requirements of the test, the lot shall be rejected and testing shall revert to 4.4.3.1.1.

4.4.3.2 Transportation vibration test.

4.4.3.2.1 Beginning with the first lot produced and continuing until three consecutive lots have been found acceptable, a sample of fifteen (15) modules shall be selected from each lot and tested in accordance with 4.5.5. If any module fails to comply with the requirements of the test, the lot shall be rejected. All modules shall be drop tested as specified in 4.5.1.

4.4.3.2.2 After three consecutive lots have complied with the criteria of 4.4.3.2.1, the sample size shall be reduced to 9 and test per 4.5.5. If any module fails to comply with the requirements of the test, the lot shall be rejected and testing shall revert to 4.4.3.2.1. All modules shall be drop tested as specified in 4.5.1.

4.4.4 Inspection equipment. The equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the table starting with 4.4.2.1. The contractor shall submit for approval equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and Section 6 herein.

4.5 Methods of inspection.

4.5.1 Drop test. Use accepted armed modules from the arming test (see 4.5.2). The armed module shall be dropped, forward end down, from a maximum height of sixteen (16) inches, onto a steel plate. The module may be guided, initially, to maintain proper orientation. Any module in which the firing pin

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

has not been released shall be classed defective. If more than one defective is found in the sample of fifty (50) units, the lot shall be rejected. If only one (1) defective is found in the first sample of fifty (50) units, a second sample of fifty (50) units shall be tested and the lot rejected if any additional defectives are found. Modules subjected to this test shall not be returned to the lot.

4.5.2 Arming. The unarmed delay module, impact shall be rotated, in a vertical position with the firing pin pointing up, at a speed of 2,025 rpm max. for 5 seconds max. After the test, the module shall be examined for proper arming, i.e., detent lock in armed position as shown in Dwg. 11836270. Any module which does not arm shall be classed defective and removed from the lot. Following inspection, the module shall be restored to the unarmed position.

4.5.3 Non-arming. The unarmed delay module, impact shall be rotated, in a vertical position with the firing pin pointing up, at a speed of 1,075 rpm min. for 5 seconds min. After the test, the module shall be examined for the safe, unarmed position, i.e., firing pin safe and spin detents in unarmed position per Dwg. 11836270. Any module which has armed shall be classed defective and removed from the lot.

4.5.4 Jolt and jumble test. The module shall be assembled in the M739 inert fuze (see 6.5) and subjected to the Jolt Test in accordance with MIL-STD-331, Test 101.1 and without disassembly shall then be subjected to the Jumble Test in accordance with MIL-STD-331, Test 102.1. The fuze shall then be disassembled to remove the delay module for inspection to determine compliance with the MIL-STD. As a minimum inspection requirement, the firing pin shall be in the safe position and the spin detents shall be in the unarmed position. If any module is classed defective, the lot shall be rejected. Components of the M739 Fuze (inert) used as the test vehicle shall be considered reusable from lot to lot of delay modules.

4.5.5 Transportation vibration test. The Module shall be assembled in the M739 Inert Fuze (see 6.5) and shall be subjected to the Transportation Vibration Test in accordance with MIL-STD-331, Test 119, Procedure 1, using equal numbers of modules at each required temperature, when testing to 4.4.3.2.1. The delay module shall then be removed from the fuze and subjected to the drop test in accordance with 4.5.1. NOTE: When testing to 4.4.3.2.2, use MIL-STD-331, Test 119, Procedure 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

4.5.6 Load test. The specified load shall be applied in the direction specified on the applicable drawing using a suitable test fixture. Any assembly in which any part moves, deforms, becomes loose or detaches shall be classed defective and the lot shall be rejected. Assemblies subjected to this test shall not be returned to the lot. Note: For the load test on the pivot pin, detent retainer and slider spring retainer, some deformation of the part is permitted, provided the part does not detach from any staked area.

4.5.7 Die check for cast parts. A sample of at least five (5) parts from each cavity shall be inspected for compliance with all dimensional requirements of the applicable component drawing to qualify a new or reworked cavity for use in production. Individual cavity identification must be provided. If any defective parts are found during qualification of the cavity, the cavity producing the defective part shall not be used in production. All cavities formerly removed from production because of some fault may, after reworking, be returned to production providing they pass the qualification test. When production from a cavity reaches 100,000 pieces since the last qualification test, a sample of five (5) parts from that cavity shall be subjected to the qualification test.

4.5.8 Die check for stamped parts. A sample of at least five (5) parts from each punch shall be inspected for compliance with all dimensional requirements of the applicable component drawing to qualify a new or reworked tool for use in production. If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production. All tools removed from production because of some fault may, after reworking, be returned to production providing they pass the above qualification test. When production reaches 100,000 pieces since the last qualification test, a sample of five (5) parts shall be subjected to the qualification test.

4.5.9 Dimensional control of cast parts. As a control of each cavity during production, five (5) or more parts from each cavity shall be inspected during each production run. A production run is defined as that period of operation of the die from the time the die has reached proper operating temperature until the die has cooled below that temperature. Of the five (5) or more samples to be inspected, one shall be selected at the start, one at the end, and the others during the production run. As a control of each cavity during production, the parts shall be inspected to the requirements listed on the applicable Classification of Defects and Test charts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging requirements. Packaging shall be as specified for level B of MIL-STD-1169.

6. NOTES

6.1 Ordering data. See MIL-A-48078.

6.2 Intended use. The components covered by this specification are intended for various artillery fuzes.

6.3 Submission of inspection equipment for design approvals. See MIL-A-48078. Submit designs as required to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, NJ 07801.

6.4 Submission of first article samples. Instructions as to the location for evaluation of first article samples shall be obtained from the Contracting Officer. Upon receipt of such request, the Contracting Officer shall advise U.S. Army Armament Research and Development Command and instructions will be issued accordingly. All inquiries shall be forwarded to: Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAM-V.

6.5 Assembly of delay modules in M739 fuze. Use Fuze Body Assembly (Dwg. 9258606) less M1 Delay Assembly (Dwg. 9311193-1), Closing Screw (Dwg. 9258611) and less S & A Module and Retainer Assembly (Dwg. 9282958). Assemble the Delay Module to the fuze body with forward end of module towards front end of fuze. Then assemble the closing Screw and an inert S & A Module and Retainer Assembly to the fuze body, starting the threads by hand and then torquing to the drawing requirement. Assemblies shall be completed with inert booster pellets and booster cups (Dwg. 9258607).

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 1390-A254

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-D-63406 (AR) Delay Module, Impact, Metal PartsAssembly, and Packing

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

COMMANDER
US ARMY ARMAMENT RESEARCH & DEVELOPMENT COMMAND
ATTN: DRDAR-QAR
DOVER, NJ 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.