NOT MEASURMENT SENSITIVE

MIL-M-63005C (AV)
09 December 1993
Superseding
MIL-M-63005B
21 Jun 1991

MILITARY SPECIFICATION
MANUALS, TECHNICAL: PREPARATION FOR SHIPMENT OF ARMY AIRCRAFT

This limited coordination military specification prepared by the U.S. Army Aviation and Troop Command for use by the Department of the Army and is available for use by all departments and agencies of the Department of Defense.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Aviation and Troop Command, ATTN: AMSAT-R-EDS, 4300 Goodfellow Blvd., St. Louis, Missouri 63120-1798, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AREA TMSS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

1. SCOPE

This specification prescribes the minimum requirements for the preparation of technical manuals that provide preparation for shipment guidance for the movement of Army aircraft. These instructions establish the format for the technical manual. They are not requirements applicable to the design or construction of the materiel.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents, of the issue in effect on the date of the invitation for bids, form a part of this specification to the extent specified herein:

2.1.1 Military Specifications.

MIL-M-38784	Manuals, Technical: General Style and Format Requirements
MIL-M-63038	Manual, Technical, Organization or Aviation Unit, Direct Support or Aviation Intermediate and General Support Maintenance

2.1.2 Military Standards:

MIL-STD-12	Abbreviations for Use on Drawings and in Technical Type Publications
MIL-STD-100	Engineering Drawing Practices
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-209	Slinging Eyes and Attachments for Lifting and Tying Down Military Equipment
MIL-STD-1367	Packaging, Handling, Storage and Transportability Program Requirements for Systems and Equipment

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

MILITARY HANDBOOKS

MIL-HDBK-63038-1	Technical Manual writing Handbook
MIL-HDBK-63038-2	Technical Writing Style Guide

2.1.3 Other publications:

DEPARTMENT OF DEFENSE

DOD 5200.20	Distribution Statements Other Than Security) on Technical Documents
DOD 5220.22M	Industrial Security Manual for Safeguarding Classified information

DEPARTMENT OF TRANSPORTATION

Code of Federal Regulations, Title 46, Part 146 (water)

Code of Federal Regulations, Title 49, Parts 170-179 (motor and rail)

DEPARTMENT OF THE ARMY

AR 310-3	Preparation, Coordination, and Approval of Department of the Army Publications
AR 310-25	Dictionary of United States Army Terms
AR 310-50	Authorized Abbreviations and Brevity Codes Manual
DA PAM 738-751	Functional Users Manual for the Army Maintenance Management System-Aviation (TAMMS-A)
TM 38-250 (AFR 71-4)	Packaging and Handling of Dangerous Materials for Transportation by Military Aircraft

(Copies of documents required by contractors with specific procurement functions should be obtained from procuring activity or as directed by the contracting officer.)

2.2 Conflict with other documents: Where the requirements of

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

MIL-M-38784 or any other applicable publication covering preparation of technical manual's conflict with the style and formats requirements specified herein, the requirements of this specification shall apply. No part of this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General: Requirements for the preparation of preparation for shipment manuals shall be generally as specified in military specification MIL-M-38784.

3.1.1 Title, contents, and arrangement: The manual shall contain all essential information required by personnel engaged in preparing and loading aircraft for shipment by all modes worldwide. The title shall be "Preparation for Shipment of Army Model..." followed by the model and nomenclature of the aircraft. The text shall, as a minimum, contain the information elements listed in paragraph 3.2 and described in paragraph's 3.2.1 through 3.2.21.12 herein, unless otherwise specified.

3.1.1.1 Classified information: Classified information shall not be included.

3.1.1.2 Government furnished material: Information provided by the Government for inclusion in the manual shall be reviewed and altered as required by the contractor to assure its conformance with the style and format of this specification. No changes, other than editorial, shall be made without prior approval of the government. All material furnished by the government or prepared by the contractor shall remain the property of the government.

3.1.1.3 Publication number: The publication number shall be the same as the TM number applied to the aircraft system, followed by the letter suffix "-S".

3.1.1.4 Abbreviations: Abbreviations shall be held to a minimum and used only when their meaning is unquestionably clear. They shall be limited to the standard forms listed in AR 310-50 for text, tables, and text related material, and MIL-STD-12 for drawings, illustrations, charts, graphs, and other graphic presentations.

3.1.1.5 References: Procedures for towing, ground handling, operation of aircraft brakes, wing walker requirements, operation of ground handling equipment, rigging and hoisting, and safety considerations shall be completely included, along with appropriate illustrations in the manual under preparation. Other required procedures contained in AVUM maintenance manuals may be referenced by providing the publication number. Duplication of material within the manual under preparation will be kept to a minimum. When a procedure has been previously included in the manual, it may be referenced by the appropriate paragraph,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

been obtained, preparation of reproducible copy, including mechanized methods, leading and spacing, page sizes, reproduction areas, headings, indentation, and so forth, shall be as specified in MIL-M-38784 or as directed in the statement of work portion of the contract.

3.1.6 Artwork: The preparation of artwork, including illustrations, line drawings, continuous tone artwork, retouching, mounting, cropping, call-out lines, and so forth, shall be as specified in MIL-M-38784.

3.1.6.1 Illustration composition: In composing the parts of an illustration, the handling of the subject is dependent upon the purpose of the illustration. The subject of the illustration shall be displayed to the best advantage consistent with the illustration's purpose and the limitations of the drawing methods used. If possible, illustration subjects should be displayed from a normal viewing position. When it is necessary to show a detail that cannot be viewed from its natural position some type of orientation or identification view should be used.

3.1.6.2 Color in artwork: Shading, patterns, crosshatching, dots, and so forth, in black and white, shall be used in place of colors on original artwork and halftones.

3.1.6.3 Integral typography: Lettering and type on original artwork shall be well-defined and large enough to be easily read when the illustration is reproduced at page size. Lettering and type shall be in capital letters of the sans serif style and shall be at least a 6-point type size on the printed page. A desirable minimum is 8 points. Spacing of letters and words shall be controlled to insure clear, legible copy.

3.1.6.4 Keys for illustrations: Keys shall, where feasible, be included on the illustration. Where keys are too numerous or the explanations too lengthy to fit within the illustration cropped area without crowding, they shall be placed in tabular form immediately above or below the illustration or on the facing page. These tables shall be considered as a text function.

3.1.7 Revisions and changes: Revisions or changes shall be handled as specified in MIL-M-38784. The manual shall be revised or changed semi-annually. Considerations addressed in changes include:

a. Production changes

b. New models

c. Significant errors in text

d. Engineering changes

e. Corrections or improvements generated through reviews by

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

the Government

3.2 Contents and format: Each aircraft preparation for shipment manual shall apply to a single aircraft series. Specific requirements and procedures relating to shipment by cargo aircraft, vessel, truck, crated shipment, containerized shipment, and external transport by helicopter shall be detailed. Cleaning, disassembly, preservation, marking, preparation of shipper prepared documents, loading, tie down, unloading, depreservation, and reassembly procedures necessary for tactical, minimum disassembly logistical, and maximum density logistical movements shall be described. Minimum information and formats for aircraft Preparation for Shipment Technical Manuals shall be as follows:

a. Cover/Title Page

b. Distribution Statement

c. Warning Page

d. Table of Contents

e. Reporting of Errors Statement

f. List of Illustrations

g. List of Tables

h. Chapter I, Introduction

(1) Section I, Purpose and Scope

(2) Section II, General

(3) Section III, Aircraft Description

(4) Section IV, Shipping Characteristics

(5) Section V, Ground Handling

(6) Section VI, Safety

(7) Section VII, Check Sheets

i. Chapter 2, Shipment by Cargo Aircraft

(1) Section I, General

(2) Section II, Shipment by C-5 Aircraft

(3) Section III, Shipment by C-17 Aircraft

(4) Section IV, Shipment by C-141 Aircraft

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

(5) Section V, Shipment by C-130 Aircraft

j. Chapter 3, Shipment by Vessel

(1) Section I, General

(2) Section II, Tactical Shipment

(3) Section III, Logistical Shipment

(4) Section IV, Shipment by Landing Platform Helicopter

k. Chapter 4, Shipment by Truck

(1) Section I, General

(2) Section II, Tactical (Short Haul) Transport by Truck

(3) Section III, Logistical (Long Haul) Transport by Truck and Inter modal Container Shipment

l. Chapter 5, Crated and Inter Modal Container Shipment

(1) Section I, General

(2) Section II, Aircraft Preparation

(3) Section III, Grating

(4) Section IV, Uncrating and Assembly

m. Chapter 6, Preservation and Packaging

(1) Section I, General

(2) Section II, Aircraft Cleaning

(3) Section III, Preservation of Aircraft

(4) Section IV, Preservation and Packaging of Components

(5) Section V, Marking and Preparation of Shipping Documents

(6) Section VI, Depreservation

n. Chapter 7, Local Manufacture Transportability Equipment

o. Chapter 8, Operator and Maintenance Instructions with Repair Parts and Special Tools List for Transportability Equipment

p. Chapter 9, External Transport by Helicopter (Aerial Recovery)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

(1) Section I, General

(2) Section II, Single Cargo Hook Hard Point Lift (Primary Method)

(3) Section III, Single Cargo Hook Hard point Lift (Alternate Method)

(4) Section IV, Dual Cargo Hook Hard Point Lift (Primary Method)

(5) Section V, Dual Cargo Hook Hard Point Lift (Alternate Method)

(6) Section VI, Single Cargo Hook Belly Band Method

(7)Section VII, Structurally Damaged Aircraft

q. Appendices

(1) Appendix A, References

(2) Appendix B, Preservation/Depreservation Check sheets

(3) Appendix C, Weight and Balance Information for Transportability

(4) Appendix D, Consumable Materials List

(5) Appendix E, Special Tools and Equipment List

(6) Appendix F, Quarantine Inspection/Customs Clearance

(7) Appendix G, Aircraft Protective Covering

3.2.1 Cover/title page: The reproducible copy for the front cover/title page shall be in accordance with MIL-M-38784. Publication accessing may be included as detailed in MIL-HDBK-63038-1.

3.2.2 Warning page: A warning page will be prepared in accordance with MIL-M-38784.

3.2.3 Table of contents: The table of contents shall list the chapters, sections, and paragraphs by number and title in the order in which they occur in the manual. A manual without front cover accessing aids will contain a table of contents prepared in accordance with MIL-M-38784. When front cover accessing aids are used, the table of contents will be prepared as detailed in MIL-HDBK-63038-1.

3.2.3.1 Reporting of errors statement: A reporting of errors statement as follows shall head the above table of contents page:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

"Reporting of errors and recommending improvements. You can help improve this manual. If you find any mistakes or if you know of a way to improve the procedures, please let us know. Mail a letter or DA Form 2028-2 Recommended Changes to Equipment Technical Manuals, to Commander, U.S. Army Aviation and Troop Command, ATTN: AMSAT-I-MP, 4300 Goodfellow Blvd., St. Louis, MO 63120-1798. A reply will be furnished to you."

3.2.3.2 One overprinted sample of DA Form 2028-2 and three pre addressed tear out DA Form 2028-2 shall be included at the back of each manual.

3.2.4 List of illustrations: A list of illustrations shall be included after the table of contents. Illustrations shall be listed by title and number as they appear in the manual in accordance with MIL-M-38784.

3.2.5 List of tables: A list of tables shall be included after the list of illustrations. Tables shall be listed by title and number as they appear in the manual in accordance with MIL-M-38784.

3.2.6 Chapter 1, introduction: This chapter shall include the following:

3.2.6.1 Section I, Purpose and Scope: This section shall state why the manual was prepared, what it covers, who will use it, and its applicability.

3.2.6.2 Section II, General: This section shall include general administrative information relating to the use of the manual including:

3.2.6.2.1 Description and use of this manual: In this paragraph, describe the layout and use of the manual. For example, indicate sections that are general in nature and sections that apply to only specific modes.

3.2.6.2.2 Classified materials: In this paragraph indicate classified items that are applicable to the specific aircraft and handling requirements.

3.2.6.2.3 Warnings, cautions, and notes: This paragraph shall state the definitions of warnings, cautions, and notes as stated in MIL-M-38784.

3.2.6.2.4 Deviations: This paragraph shall include the statement "Deviations from the procedures of this manual must be approved by U.S. Army Aviation and Troop Command. The point of contact for deviations and clarification is: Commander, U.S. Army Aviation and Troop Command, ATTN: AMSAT-I-SDP, 4300 Goodfellow Blvd., St. Louis, MO 63120-1798, commercial telephone (314) 263-2372 or DSN 693-2372."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.2.6.3 Section III, Aircraft Description: This section shall introduce the reader to the aircraft. It shall include a description of the aircraft, its intended use, and operational characteristics/capabilities, as well as, identification drawings including side elevation, end elevation, and top view drawings. Difference in models, if applicable, and other pertinent general information shall be provided. The reader shall be referred to operator and organizational maintenance manuals and other pertinent publications listed in appendix A of the manual for additional technical information. Approximate empty weight of the aircraft will be included.

3.2.6.3.1 Line drawings: Left side, front, and top view drawings shall be prepared for the aircraft in its operational configuration. All three views shall be on the same page and be the only material presented on the page. For manuals covering different models exhibiting external differences, drawings shall be included for each model.

3.2.6.3.2 Scale: The drawings in this section shall not be to a specific scale. The scale shall be as large as possible consistent with the requirement of having all three views on the same page. Size shall be indicated by use of a graphic (bar) scale.

3.2.6.3.3 Dimensional data: All dimensions will be shown to the nearest 1/10th inch. The following dimensions will be shown:

a. Lateral Dimensions

(1) Landing gear width

(2) Wingspan (if applicable)

(3) Propeller diameter (if applicable)

(4) Fuselage (maximum width)

(5) Main rotor blade chord (if applicable)

(6) Horizontal stabilizer span (if applicable)

b. Longitudinal Dimensions

(1) Fuselage length

(2) Overall length (maximum)

(3) Main rotor diameter(s)

(4) Tail rotor diameter (if applicable)

(5) Wing chord (if applicable)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

(6) Horizontal stabilizer chord (if applicable)

(7) Distance from both ends to centerline of nearest wheel or tip of skid as applicable

(8) Centerline of front wheels to centerline of rear wheels (if applicable)

(9) Skid length (if applicable)

c. Vertical Dimensions

(1) Ground to fuselage (minimum)

(2) Ground to fuselage at midpoint between landing gear (if applicable)

(3) Ground to propeller (minimum)

(4) Ground to top of vertical stabilizer (maximum)

(5) Ground to tip of tail rotor (maximum, if applicable)

(6) Ground to tip of main rotor (minimum)

(7) Ground to top of main rotor

(8) Maximum height

(9) Ground to bottom of wing (if applicable)

(10) Ground to bottom of horizontal stabilizer (if applicable)

d. Additional dimensions relevant to transportability clearance.

3.2.6.4 Section IV, Shipping Characteristics: This section shall present a brief overview of the modes of shipment and include information applicable to more than one mode of shipment and deployment planning.

3.2.6.4.1 Flight delivery: This paragraph shall provide a statement indicating self-deployment as the preferred method of delivery. Information on maximum range, availability of auxiliary fuel systems, and their capabilities will be included.

3.2.6.4.2 Modes of shipment: This paragraph shall describe the modes of shipment available for transporting this aircraft (cargo aircraft, surface vessel, truck, helicopter, containerized, and crated shipment), and direct the reader to the appropriate chapter in this manual.

3.2.6.4.3 Types of shipment: This paragraph shall define the types of shipment applicable to this aircraft when shipped by

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

cargo aircraft and vessel. The types to be considered are tactical (flyable or nearly flyable), minimum disassembly logistical shipment, and maximum density logistical shipment.

3.2.6.4.4 Tabular data: Construct a table comparing number of personnel, and total man-hours required to prepare, load, tie down, unload, and prepare for flight one aircraft for each mode and type of shipment.

3.2.6.4.5 Tie downs: This paragraph shall include a diagram of the aircraft showing the location and maximum strength of tie down points. Strengths will be shown in fore and aft in longitudinal, left and right in lateral, and up and down in vertical planes. General tie down methodology shall be presented using diagrams as required.

3.2.6.4.6 Disassembly: This paragraph shall refer the reader to the appropriate technical manuals for disassembly. A table shall be presented comparing component removal required for each type and mode of shipment.

3.2.6.4.7 Unusual characteristics: This paragraph shall list and explain aircraft peculiar equipment requiring special environmental, handling and/or security precautions.

3.2.6.4.8 Transportability equipment and consumable materials: This paragraph shall refer the reader to Chapter 7 for local manufacture transportability equipment, Chapter 8 for transportability equipment operator and maintenance instructions, Appendix D for the consumable materials list, and Appendix E for the special tools list.

3.2.6.4.9 International shipment: Refer the reader to Appendix F for information on customs and quarantine clearance.

3.2.6.5 Section V, Ground Handling: This section shall include all information concerning towing and maneuvering the aircraft from TM 55-1520-204-251 and applicable operators and maintenance manuals. This information shall be included in its entirety including illustrations. This paragraph shall not require the reader to reference these procedures. Included shall be applicable information on operation of ground handling equipment, towing, maneuvering, operation of aircraft brakes, wing walker requirements, and safety.

3.2.6.6 Section VI, Safety: This section shall include relevant general safety information applicable to all modes of shipment. The applicable chapters, sections, and paragraphs in the manual shall be referenced concerning safety considerations for specific modes of shipment.

3.2.6.7 Section VII, Check Sheets: This section shall provide preparation, use, and disposition instructions for check sheets prepared on DA Form 2408-13-2-E as shown in Appendix B. Example

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

check sheets are to be provided for air shipment, vessel shipment, and transport by truck. Items that apply only to depreservation shall be included on the form and the appropriate status symbol will be entered at the time the aircraft is prepared for shipping. The entry will be signed off as required upon depreservation. Instructions provided shall be in accordance with DA PAM 738-751 instructions for DA Form 2408-13-2-E.

3.2.7 Chapter 2, shipment by cargo aircraft: This chapter shall specify all requirements for tactical shipment, minimum disassembly logistical shipment, maximum density logistical shipment, and palletized shipment in C-5A, C-17, C-141, and C-130 aircraft as applicable. It shall contain the following:

3.2.7.1 Section I, General: This section shall include all information of a general nature applying to the transport of the Army aircraft in cargo aircraft, and an overview of requirements. It shall include the following:

3.2.7.1.1 Types of shipment: This paragraph will define tactical (flyable) shipment, minimum disassembly logistical shipment, maximum density logistical shipment, and palletized shipment as applicable to the aircraft and the relative merits and disadvantages of each. It will indicate which cargo aircraft may be used for shipment and the aircraft densities for each cargo aircraft for each type of shipment. In addition to the verbiage, a comparative table will be presented. Air Force cargo restraint criteria will be included.

3.2.7.1.2 Functions of cargo aircraft crew: This paragraph shall list Air Force cargo aircraft crew responsibilities and the type and limits of assistance that Army personnel may expect. The following functions shall be included:

3.2.7.1.2.1 Preparing the cargo aircraft for loading and unloading.

3.2.7.1.2.2 Rig and operation all loading/offloading aids that are part of the cargo aircraft.

3.2.7.1.2.3 Designate aircraft and equipment locations within the cargo aircraft.

3.2.7.1.2.4 Provide tie down devices.

3.2.7.1.2.5 Inspect and determine acceptability of tie downs.

3.2.7.1.3 Functions of the Army loading team: This paragraph shall contain an overview of the responsibilities of the Army loading team. The following functions shall be included:

3.2.7.1.3.1 Coordinate with U.S. Army Aviation and Troop Command (ATCOM) the number and type of aircraft to be shipped, the cargo

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

aircraft to be used, and the date and time of the movement.

3.2.7.1.3.2 Plan all aspects of the move so that required materials, tools, equipment, and manpower are available.

3.2.7.1.3.3 Prepare the aircraft for shipment and insure that fuel on board does not exceed 150 gal or 3/4 full per tank, whichever is less.

3.2.7.1.3.4 Insure that Army aircraft are ready for loading on schedule.

3.2.7.1.3.5 Mark Center of Gravity (C.G.) and weight on each side of the aircraft fuselage and provide the weight of each aircraft and major component in loading configuration. (Refer reader to information provided in 3.2.7.1.8 below). Insure that shipping weight does not exceed the maximum certified for shipment.

3.2.7.1.3.6 Provide all necessary dunnage, shoring, and/or ramps required to load aircraft and protect cargo aircraft floor.

3.2.7.1.3.7 Furnish rig, and operate loading devices not integral to the cargo aircraft.

3.2.7.1.3.8 Furnish and operate auxiliary lighting necessary for night loading.

3.2.7.1.39 Load Army aircraft on cargo aircraft.

3.2.7.1.3.10 Furnish cargo aircraft commander with DD Form 1387-2 in accordance with TM 38-250.

3.2.7.1.3.11 Prepare manifest itemizing weight and location of aircraft, equipment and disassembled components, stowed within the cargo aircraft.

3.2.7.1.3.12 Be prepared to demonstrate that disassembled components are packaged correctly and secured in accordance with Air Force restraint requirements.

3.2.7.1.3.13 Unload aircraft at destination.

3.2.7.1.3.14 Depreserve, assemble, and prepare aircraft for flight.

3.2.7.1.4 Equipment requirements: Refer the reader to Appendix E for a comprehensive list of tools and equipment applicable to transport by cargo aircraft. Refer to tables in text for information on specific requirements.

3.2.7.1.5 Material requirements: Refer the reader to Appendix D for the consumable materials list. Refer to tables in text for specific requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.2.7.1.6 Manpower requirements: Refer the reader to tables in this chapter for estimates for specific configurations.

3.2.7.1.7 Facility requirements: Indicate specific requirements such as shelter, fire protection, electrical power, grounding, and fresh water.

3.2.7.1.8 Weight and balance: Indicate the requirement for providing the weight and center of gravity of the aircraft to load master. Indicate that either below procedure is acceptable. Provide warning concerning the critical nature of determining accurate weight and balance.

3.2.7.1.8.1 Weighing the aircraft: Provide procedures for weighing the aircraft in its shipping configuration. Reference appropriate chapter in maintenance manual and note any exceptions. Reference appropriate instructions for computing center of gravity based on actual weight.

3.2.7.1.8.2 Computing aircraft weight: Provide procedures for computing aircraft weight and center of gravity in its shipping configuration, in Appendix C. Reference instructions in appropriate maintenance manual.

3.2.7.1.9 Security: Provide specific security instructions relevant to air shipment of aircraft and on board systems.

3.2.7.1.10 Safety: Indicate general safety considerations applicable to shipment by cargo aircraft.

3.2.7.2 Section II, Shipment by C-5A: This section shall contain all information specific to transporting the aircraft by C-5 transport.

3.2.7.2.1 Characteristics: This paragraph shall provide a brief introduction to the C-5 aircraft, its physical characteristics, and its operational capabilities.

3.2.7.2.1.1 Line drawings: Line drawings shall be included showing the cargo aircraft in its operational configuration and configured for loading. Drawings of the operational configuration shall provide overall dimensional data on the C-5 airplane including height, wingspan, and length. Drawings of the loading configuration shall provide all dimensions critical to loading, including ramp dimensions and angles.

3.2.7.2.1.2 Capability: A general statement shall be made as to the number of aircraft the C-5 can transport each for tactical transport, minimum disassembly logistical transport, maximum density logistical transport, and palletized shipment. Provide the maximum certified shipping weight of the aircraft for transport by C-5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.2.7.2.1.3 Preparation of the C-5: This subparagraph shall include any responsibilities that Army personnel have in preparation of the cargo aircraft. Included shall be all requirements for ramps and shoring required for loading and/or protection of the cargo aircraft floor. All materials and equipment listed shall be included in the paragraph in this section on required resources and in Appendix D or E as appropriate. Diagrams or drawings will be included to show placement as necessary. Include procedures for calculating shoring dimensions.

3.2.7.2.1.4 Safety: This subparagraph shall detail safety considerations applicable to shipment by C-5 aircraft. Included shall be jet blast, engine intake, and noise hazard diagrams for the C-5.

3.2.7.2.2 Preparing the aircraft: This paragraph shall detail all requirements for preparing the aircraft to be shipped by C-5. Instructions shall be included for tactical shipment, minimum disassembly logistical shipment, maximum density logistical shipment, and palletized shipment as applicable.

3.2.7.2.2.1 Line drawings: Drawings shall be provided as detailed in 3.2.6.3.1 of this specification for aircraft prepared for each type of shipment. Scale will be as specified in 3.2.6.3.2 and dimensioning will be as specified in 3.2.6.3.3.

3.2.7.2.2.2 Required resources: Resources required to ship the aircraft shall be detailed. Quantities shall be shown both for shipping one aircraft and shipping a full load. Notes will be provided to indicate unit requirements such as 1 each required per C-5 shipment, 1 each required per aircraft shipped, 1 each required per 5 aircraft shipped, etc. This information shall be provided for each type of shipment.

3.2.7.2.2.2.1 Equipment: All tools and equipment shall be listed by noun nomenclature and reference number. The reader shall be directed to Appendix E for part and national stock numbers, Chapter 7 for local manufacture equipment and Chapter 8 for equipment operation instructions as applicable. A table shall be included providing comparative quantity data for equipment for each type of shipment as required by item 3.2.7.2.2.2 of this specification.

3.2.7.2.2.2.2 Consumable materials: All consumable materials shall be listed by noun nomenclature and reference number. The reader shall be directed to Appendix D for part number, unit of issue, and national stock number information. A table shall be included providing comparative data for consumable materials, for each type of shipment, as required by item 3.2.7.2.2.2 above.

3.2.7.2.2.2.3 Manpower requirements: A break out shall be provided for each element and task required to be accomplished to prepare for shipment, load, tie down, unload, and prepare the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

aircraft for flight. Personnel requirements, man-hours, and elapsed time shall be provided in a comparative table for each type of shipment.

3.2.7.2.2.3 Preservation and packaging: The reader shall be directed to Chapter 6 for detailed information on preservation and packaging.

3.2.7.2.2.4 Disassembly: All tasks required for aircraft preparation for each type of shipment shall be listed in the order of accomplishment. The appropriate chapter and paragraph of the maintenance manual shall be referenced for each task. Tasks that are transportability peculiar shall be completely described with drawings, or diagrams as necessary. The reader shall be referred to the appropriate paragraph of Chapter 6 of this manual or the appropriate paragraph of the maintenance manual for packaging and preservation instructions.

3.2.7.2.2.5 Load plan: A scale drawing of the floor plan of the aircraft to be shipped shall be included showing the location of and method of securing each item stowed inside. If required for clarification of the internal loading, elevations, and/or perspective drawings shall be included.

3.2.7.2.3 Loading: This paragraph shall provide detailed information required to load the aircraft on a C-5. A subparagraph will be provided for each applicable type of shipment containing required critical dimension clearance diagrams for loading and ramp and shoring placement. Also included shall be a cargo floor diagram of the C-5 with the placement of each aircraft shown for each type of shipment. Step by step instructions shall be provided for loading each aircraft and component. All equipment used shall be described and pictured. Indicate equipment that is provided by the Air Force.

3.2.7.2.4 Tie down: This paragraph shall contain all information required to tie down the aircraft and components.

3.2.7.2.4.1 General: This subparagraph shall include general information on tie down procedures, restrictions, and requirements.

3.2.7.2.4.2 Equipment: This subparagraph shall detail equipment and material requirements for shoring and tie down of aircraft and components. All equipment used shall be described and pictured as required. Instructions for use shall be provided. A comparative table shall be provided listing quantities required to ship one aircraft and also a full load of aircraft for each type of shipment. Notes shall be provided to indicate equipment quantities per unit shipped. Equipment provided by the Air Force shall be so noted.

3.2.7.2.4.3 Procedures: Detailed procedures for tie down shall be included in this subparagraph. Describe and picture tie down

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

points on the aircraft to be shipped. Provide plan, front, rear, and side views to show tie down installation.

3.2.7.2.5 Unloading: Provide step by step procedures for unloading the C-5 for each applicable type of shipment.

3.2.7.2.6 Depreservation and assembly: Provide step by step procedures for depreservation, assembly, and returning the aircraft to flyable status. Reference appropriate maintenance publications by chapter and paragraph for each step. Tasks that are transportability peculiar shall be completely described with drawings and diagrams provided as necessary.

3.2.7.3 Section III, Shipment by C-17: This section shall contain all information specific to transporting the aircraft by C-17 cargo aircraft.

3.2.7.3.1 Characteristics: This paragraph shall provide a brief introduction to the C-17 aircraft. It shall include a description of the aircraft, its physical characteristics, and its operational capabilities.

3.2.7.3.1.1 Line drawings: Line drawings shall be included showing the cargo aircraft in its operational configuration and configured for loading. Drawings of the operational configuration shall provide overall dimensional data on the C-17 airplane including height, wingspan, and length. Drawings of the loading configuration shall provide all dimensions critical to loading.

3.2.7.3.1.2 Capability: A general statement shall be made as to the number of aircraft the C-17 can transport each for tactical transport, minimum disassembly logistical transport, maximum density logistical transport, and palletized shipment. Provide the maximum certified shipping weight of the aircraft for transport by C-17.

3.2.7.3.1.3 Preparation of the C-17: This subparagraph shall include any responsibilities that Army personnel have in preparation of the cargo aircraft. Included shall be all requirements for ramps and shoring required for loading and/or protection of the cargo aircraft floor. All materials and equipment listed shall be included in the paragraph in this section on required resources and in Appendix D or E as appropriate. Diagrams or drawings shall be included to shorn placement as necessary. Include procedures on calculating shoring dimensions.

3.2.7.3.1.4 Safety: This subparagraph shall detail safety considerations applicable to shipment by C-17 aircraft. Included shall be jet blast, engine intake, and noise hazard diagrams for the C-17.

3.2.7.3.2 Preparing the aircraft: This paragraph shall detail

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

all requirements for preparing the aircraft to be shipped by C-17. Instructions shall be included for tactical shipment, minimum disassembly logistical shipment, maximum density logistical shipment, and palletized shipment as applicable.

3.2.7.3.2.1 Line drawings: Drawings shall be provided as detailed in 3.2.6.3.1 of this specification for aircraft prepared for each type of shipment. Scale shall be as specified in 3.2.6.3.2 and dimensioning shall be as specified in 3.2.6.3.3.

3.2.7.3.2.2. Required resources: Resources required to ship the aircraft shall be detailed. Quantities shall be shown both for shipping one aircraft and shipping a full load. Notes shall be provided to indicate unit requirements such as 1 each required per C-17 shipment, 1 each required per aircraft shipped, 1 each required per 5 aircraft shipped, etc. This information shall be provided for each type of shipment.

3.2.7.3.2.2.1 Equipment: All tools and equipment shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix E for part and national stock numbers, Chapter 7 for local manufacture equipment, and Chapter 8 for equipment operation instructions as applicable. A table shall be included providing comparative quantity data for equipment for each type of shipment as required by item 3.2.7.3.2.2 of this specification.

3.2.7.3.2.2.2 Consumable materials: All consumable materials shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix D for part number, unit of issue, and national stock number information. A table shall be included providing comparative data for consumable materials, for each type of shipment, as required by item 3.2.7.3.2.2 above.

3.2.7.3.2.2.3 Manpower requirements: A break out shall be provided for each element and task required to be accomplished to prepare for shipment, load, tie down, unload, and prepare the aircraft for flight. Personnel requirements, man-hours, and elapsed time shall be provided in a comparative table for each type of shipment.

3.2.7.3.2.3 Preservation and packaging: The reader shall be directed to Chapter 6 for detailed information on preservation and packaging.

3.2.7.3.2.4 Disassembly: All tasks required for aircraft preparation for each type of shipment shall be listed in the order of accomplishment. The appropriate chapter and paragraph of the maintenance manual shall be referenced for each task. Tasks that are transportability peculiar shall be completely described with drawings and diagrams as necessary. The reader shall be referred to the appropriate paragraph of Chapter 6 of this manual or the appropriate paragraph of the maintenance manual for packaging and preservation instructions.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

3.2.7.3.2.5 Load plan: A scale drawing of the floor plan of the aircraft to be shipped shall be included showing the location and method of securing each item stowed inside. If required for clarification of the internal loading, elevations and/or perspective drawings shall be included.

3.2.7.3.3 Loading: This paragraph shall provide detailed information required to load the aircraft on a C-17. A subparagraph shall be provided for each applicable type of shipment containing required critical dimension clearance diagrams for loading and ramp and shoring placement. Also included shall be a cargo floor diagram of the C-17 with the placement of equipment and each aircraft shown for each type of shipment. Step by step instructions shall be provided for each aircraft and piece of equipment loaded. All equipment used shall be described and pictured. Indicate equipment that is provided by the Air Force.

3.2.7.3.4 Tie down: This paragraph shall contain all information required to tie down the aircraft, equipment, and components.

3.2.7.3.4.1 General: This subparagraph shall include general information on tie down procedures, restrictions and requirements.

3.2.7.3.4.2 Equipment: This subparagraph shall detail equipment and material requirements for shoring and tie down of aircraft and components. All equipment used shall be described and pictured as required. Instructions for use shall be provided. A comparative table shall be provided listing quantities required to ship one aircraft and also a full load of aircraft for each type of shipment. Notes shall be provided to indicate quantities per unit shipped. Equipment provided by the Air Force will be so noted.

3.2.7.3.4.3 Procedures: Detailed procedures for tie down shall be included in this subparagraph. Describe and picture tie down points on the aircraft to be shipped. Provide plan, front, rear, and side views to show tie down installation.

3.2.7.3.5 Unloading: Provide step by step procedures for unloading the C-17 for each applicable type of shipment.

3.2.7.3.6 Depreservation and assembly: Provide step by step procedures for depreservation, assembly, and returning the aircraft to flyable status. Reference appropriate maintenance publications by chapter and paragraph for each step. Tasks that are transportability peculiar shall be completely described with drawings and diagrams provided as necessary.

3.2.7.4 Section IV, Shipment by C-141: This section shall contain all information specific to transporting the aircraft by

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

requirements relevant to containerized shipment of the aircraft

C-141 cargo aircraft.

3.2.7.4.1 Characteristics: This paragraph shall provide a brief introduction to the C-141 aircraft. It shall include a description of the aircraft, its physical characteristics, and its operational capabilities.

3.2.7.4.1.1 Line drawings: Line drawings shall be included showing the cargo aircraft in its operational configuration and configured for loading. Drawings of the operational configuration shall provide overall dimensions data on the C-141 airplane including height, wingspan, and length. Drawings of the loading configuration shall provide all dimensions critical to loading.

3.2.7.4.1.2 Capability: A general statement shall be made as to the number of aircraft the C-141 can transport each for tactical transport, minimum disassembly logistical transport, maximum density logistical transport, and palletized shipment. Provide the maximum certified shipping weight of the aircraft for transport by C-141.

3.2.7.4.1.3 Preparation of the C-141: This subparagraph shall include any responsibilities that Army personnel have in preparation of the cargo aircraft. Included shall be all requirements for ramps and shoring required for loading and/or protection of the cargo aircraft floor. All materials and equipment listed shall be included in the paragraph in this section on required resources and in Appendix D or E as appropriate. Diagrams or drawings shall be included to show placement as necessary. Include procedures for calculating shoring dimensions.

3.2.7.4.1.4 Safety: This subparagraph shall detail safety considerations applicable to shipment by C-141 aircraft. Included shall be jet blast, engine intake, and noise hazard diagrams for the C-141.

3.2.7.4.2 Preparing the aircraft: This paragraph shall detail all requirements for preparing the aircraft to be shipped by C-141. Instructions shall be included for tactical shipment, minimum disassembly logistical shipment, maximum density logistical shipment, and palletized shipment as applicable.

3.2.7.4.2.1 Line drawings: Drawings shall be provided as detailed in 3.2.6.3.1 of this specification for aircraft prepared for each type of shipment. Scale shall be as specified in 3.2.6.3.2 and dimensioning shall be as specified in 3.2.7.3.3.

3.2.7.4.2.2 Required resources: Resources required to ship the aircraft shall be detailed. Quantities shall be shown both for shipping 1 aircraft and shipping a full load. Notes shall be provided to indicate unit requirements such as 1 each required per C-141 shipment, 1 each required per aircraft shipped, 1 each

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

required per 5 aircraft shipped, etc. This information shall be provided for each type of shipment.

3.2.7.4.2.2.1 Equipment: All tools and equipment will be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix E for part and national stock numbers, Chapter 7 for local manufacture equipment, and Chapter 8 for equipment operation instructions as applicable. A table shall be included providing comparative quantity data for equipment for each type of shipment as required by item 3.2.7.4.2.2 of this specification.

3.2.7.4.2.2.2 Consumable materials: All consumable materials shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix D for part number, unit of issue, and national stock number information. A table shall be included providing comparative data for consumable materials, for each type of shipment, as required by item 3.2.7.4.2.2 above.

3.2.7.4.2.2.3 Manpower requirements: A break out shall be provided for each element and task required to be accomplished to prepare for shipment, load, tie down, unload, and prepare the aircraft for flight. Personnel requirements, man-hours, and elapsed time shall be provided in a comparative table for each type of shipment.

3.2.7.4.2.3 Preservation and packaging: The reader shall be directed to Chapter 6 for detailed information on preservation and packaging.

3.2.7.4.2.4 Disassembly: All tasks required for aircraft preparation for each type of shipment shall be listed in the order of accomplishment. The appropriate chapter and paragraph of the maintenance manual shall be referenced for each tack. Tasks that are transportability peculiar shall be completely described with drawings or diagrams as necessary. The reader shall be referred to the appropriate paragraph of Chapter 6 of this manual or the appropriate paragraph of the maintenance manual for packaging and preservation instructions.

3.2.7.4.2.5 Load plan: A scale drawing of the floor plan of the aircraft to be shipped shall be included showing the location of and method of securing of each item stowed inside. If required for clarification of the internal loading, elevations and/or perspective, drawings shall be included.

3.2.7.4.3 Loading: This paragraph shall provide detailed information required to load the aircraft on a C-141. A subparagraph shall be provided for each applicable type of shipment containing required critical dimension clearance diagrams for loading and ramp and shoring placement. Also included shall be a cargo floor diagram of the C-141 with the placement of equipment and each aircraft shown for each type of shipment. Step by step instructions shall be provided for

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

b. Forms and records. (See 3.3.2.1b)

loading each aircraft and component. All equipment used shall be described and pictured. Indicate equipment that is provided by the Air Force.

3.2.7.4.4 Tie down: This paragraph shall contain all information required to tie down the aircraft and components.

3.2.7.4.4.1 General: This subparagraph shall include general information on tie down procedures, restrictions, and requirements.

3.2.7.4.4.2 Equipment: This subparagraph shall detail equipment and material requirements for shoring and tie down of aircraft and components. All equipment used shall be described and pictured as required. Instructions for use shall be provided. A comparative table shall be provided listing quantities required to ship one aircraft and also a full load of aircraft for each type of shipment. Notes shall be provided to indicate quantities per unit shipped. Equipment provided by the Air Force shall be so noted.

3.2.7.4.4.3 Procedures: Detailed procedures for tie down shall be included in this subparagraph. Describe and picture tie down points on the aircraft to be shipped. Provide plan, front, rear, and side views to show tie down installation.

3.2.7.4.5 Unloading: Provide step by step procedures for unloading the C-141 for each applicable type of shipment.

3.2.7.4.6 Depreservation and assembly: Provide step by step procedures for depreservation, assembly, and returning the aircraft to flyable status. Reference appropriate maintenance publications by chapter and paragraph for each step. Tasks that are transportability peculiar shall be completely described with drawings and diagrams provided as necessary.

3.2.7.5 Section V, Shipment by C-130: This section shall contain all information specific to transporting the aircraft by C-130 cargo aircraft.

3.2.7.5.1 Characteristics: This paragraph shall provide a brief introduction to the C-130 aircraft. It will include a description of the aircraft, its physical characteristics, and its operational capabilities.

3.2.7.5.1.1 Line drawings: Line drawings shall be included showing the cargo aircraft in its operational configuration and configured for loading. Drawings of the operational configuration shall provide overall dimensional data on the C-130 airplane including height, wingspan, and length. Drawings of the loading configuration shall provide all dimensions critical to loading.

3.2.7.5.1.2 Capability: A general statement shall be made as to

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

the number of aircraft the C-130 can transport each for tactical transport, minimum disassembly logistical transport, maximum density logistical transport, and palletized shipment. Provide the maximum certified shipping weight for transport of the aircraft by C-130.

3.2.7.5.1.3 Preparation of the C-130: This subparagraph shall include any responsibilities that Army personnel have in preparation of the cargo aircraft. Included shall be all requirements for ramps and shoring required for loading and/or protection of the cargo aircraft floor. All materials and equipment list shall be included in the paragraph in this section on required resources and in Appendix D or E as appropriate. Diagrams or drawings shall be included to show placement as necessary. Include procedures for calculating shoring dimensions.

3.2.7.5.1.4 Safety: This subparagraph shall detail safety considerations applicable to shipment by C-130 aircraft. Included shall be prop blast, engine intake, and noise hazard diagrams for the C-130.

3.2.7.5.2 Preparing the aircraft: This paragraph shall detail all requirements for preparing the aircraft to be shipped by C-130. Instructions shall be included for tactical shipment, minimum disassembly logistical shipment, maximum density logistical shipment, and palletized shipment as applicable.

3.2.7.5.2.1 Line drawings: Drawings shall he provided as detailed in 3.2.6.3.1 of this specification for aircraft prepared for each type of shipment. Scale shall be as specified in 3.2.6.3.2 and dimensioning shall be as specified in 3.2.6.3.3.

3.2.7.5.2.2 Required resources: Resources required to ship the aircraft shall be detailed. Quantities shall be shown both for shipping one aircraft and shipping a full load. Notes will be provided to indicate unit requirements such as 1 each required per C-130 shipment, 1 each required per aircraft shipped, etc. This information shall be provided for each type of shipment.

3.2.7.5.2.2.1 Equipment: All tools and equipment shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix E for part and national stock numbers, Chapter 7 for local manufacture equipment, and Chapter 8 for equipment operation instructions as applicable. A table shall be included providing comparative quantity data for equipment for each type of shipment required by item 3.2.7.5.2.2 of this specification.

3.2.7.5.2.2.2 Consumable materials: All consumable materials shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix D for part number, unit of issue, and national stock number information. A table shall be included providing comparative data for consumable materials, for

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

each type of shipment, as required by item 3.2.7.5.2.2 above.

3.2.7.5.2.2.3 Manpower requirements: A break out shall be provided for each element and task required to be accomplished to prepare for shipment, load, tie down, unload, and prepare the aircraft for flight. Both man-hours and elapsed time shall be provided in a comparative table for each type of shipment.

3.2.7.5.2.3 Preservation and packaging: The reader shall be directed to Chapter 6 for detailed information on preservation and Packaging.

3.2.7.5.2.4 Disassembly: All tasks required for aircraft preparation for each type of shipment shall be listed in the order of accomplishment. The appropriate chapter and paragraph of the maintenance manual shall be referenced for each task. Tasks that are transportability peculiar shall be completely described with drawings or diagrams as necessary. The reader shall be referred to the appropriate paragraph of Chapter 6 of this manual or the appropriate paragraph of the maintenance manual for packaging and preservation instructions.

3.2.7.5.2.5 Load plan: A scale drawing of the floor plan of the aircraft to be shipped shall be included showing the location of each item stowed inside. If required for clarification of the internal loading, elevations and/or perspective drawings shall be included.

3.2.7.5.3 Loading: This paragraph shall provide detailed information required to load the aircraft on a C-130. A subparagraph shall be provided for each applicable type of shipment containing required critical dimension clearance diagrams for loading and ramp and shoring placement. Also included shall be a cargo floor diagram of the C-130 with the placement of equipment and each aircraft shown for each type of shipment. Step by step instructions shall be provided for loading each aircraft and component. All equipment used shall be described and pictured. Indicate equipment that is provided by the Air Force.

3.2.7.5.4 Tie down: This paragraph shall contain all information required to tie down the aircraft and components.

3.2.7.5.4.1 General: This subparagraph shall include general information on tie down procedures, restrictions, and requirements.

3.2.1.5.4.2 Equipment: This subparagraph shall detail equipment and material requirements for shoring and tie down of aircraft and components. All equipment used shall be described and pictured as required. Instructions for use shall be provided. A comparative table shall be provided listing quantities required to ship one aircraft and also a full load of aircraft for each type of shipment. Notes shall be provided to indicate quantities

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

per unit shipped. Equipment provided by the Air Force shall be so noted.

3.2.7.5.4.3 Procedures: Detailed procedures for tie down shall be included in this subparagraph. Describe and picture tie down points on the aircraft to be shipped. Provide plan, front, rear, and side views to show tie down installation.

3.2.7.5.5 Unloading: Provide step by step procedures for unloading the C-130 for each applicable type of shipment.

3.2.7.5.6 Depreservation and assembly: Provide step by step procedures for depreservation, assembly, and returning the aircraft to flyable status. Reference appropriate maintenance publications by chapter and paragraph for each step. Tasks that are transportability peculiar shall be completely described with drawings and diagrams provided as necessary.

3.2.8 Chapter 3, shipment by vessel: This chapter shall specify all requirements for tactical shipment, logistical shipment for vessel shipment of the aircraft by Lift On/Lift Off (LOLO) ships, Rollo On/Roll Off (RORO) ships, and Landing Platform Helicopter (LPH) ships.

3.2.8.1 Section I, General: This section shall include all information of a general nature applying to the transport of Army aircraft by vessel, and an overview of requirements. It shall include the following:

3.2.8.1.1 Types of shipment: This paragraph shall define tactical (flyable) shipment, logistical shipment, and the relative merits and disadvantages of each. The reader shall be referred to Chapter 5 for crated and inter modal container shipment.

3.2.8.1.2 Responsibilities of Military Traffic Management Command (MTMC): This paragraph shall list and explain MTMC responsibilities with respect to shipping aircraft. The following shall be included:

3.2.8.1.2.1 Shipping arrangements: When contacted by the appropriate command, the MTMC Commander will arrange with the Military Sealift Command (MSC) Commander for vessel shipment.

3.2.8.1.2.2 Preparation of loading plan and manifest: The MTMC will prepare the shipment loading plan and manifest based on information provided by the Army loading team.

3.2.8.1.2.3 Loading and tie down: The MTMC will make arrangements with a stevedore activity or commercial stevedore firm to load and tie down aircraft. The MTMC and MSC will supervise all loading and tie down procedures.

3.2.8.1.3 Functions of marine terminal personnel: This

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

paragraph shall list the functions that the Army loading team may expect Marine terminal personnel to accomplish. It shall include:

3.2.8.1.3.1 Prepare the vessel for loading.

3.2.8.1.3.2 Provide all necessary dunnage, shoring, and/or ramps required for loading and unloading.

3.2.8.1.3.3 Rig and operate all loading/offloading devices.

3.2.8.1.3.4 Perform all loading and offloading functions.

3.2.8.1.3.5 Tie down aircraft.

3.2.8.1.4 Functions of the Army loading team: This paragraph shall contain an overview of the responsibilities of the Army loading team. The following shall be included:

3.2.8.1.4.1 Coordinate with MTMC the number, type, and weight of aircraft to be shipped, the vessel to be used, and the date and time of shipping.

3.2.8.1.4.2 Plan all aspects of the move so that required materials, tools, equipment, and manpower are available.

3.2.8.1.4.3 Prepare the aircraft for shipment.

3.2.8.1.4.4 Insure that aircraft are ready for loading on schedule.

3.2.8.1.4.5 Provide technical assistance to MTMC as required on ground handling, loading, and tie down.

3.2.8.1.4.6 Insure that provisions are made for enroute maintenance and daily tie down inspections by Army escort personnel.

3.2.8.1.4.7 Provide technical assistance to MTMC as required on ground handling and unloading at destination.

3.2.8.1.4.8 Depreserve, assemble, and prepare aircraft for flight upon arrival at destination.

3.2.8.1.5 Equipment requirements: Refer the reader to Appendix E for a comprehensive list of tools and equipment applicable to shipping the aircraft by vessel, and the appropriate tables in the text for information on specific requirements.

3.2.8.1.6 Material requirements: Refer the reader to Appendix D for the consumable materials list. Refer to tables in this chapter for specific requirements.

3.2.8.1.7 Manpower requirements: Refer the reader to

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

appropriate tables in this chapter for estimates for specific configurations.

3.2.8.1.8 Facility requirements: Indicate specific requirements for aircraft preparation such as shelter, fire protection, electrical power, grounding, and fresh water.

3.2.8.1.9 Aircraft security: Provide specific security instructions relevant to vessel shipment of aircraft and onboard systems.

3.2.8.1.10 Safety: Indicate general safety considerations applicable to shipment by vessel.

3.2.8.1.11 Characteristics: This paragraph shall provide an introduction and general information pertaining to vessel shipment. It shall include the following:

3.2.8.1.11.1 Vessel survey: Include the following statement: "Because of the wide variety of vessel designs, the ship to be used must be surveyed. The physical characteristics of the vessel will determine its capabilities. In the predeployment survey note layout of tie down fittings, hatch, hold, and door clearances, ventilation systems, fire fighting equipment, and capabilities of lifting devices. Ramp angles and ship construction must be surveyed to determine if **Roll On**/Roll Off (RORO) operations are feasible. Suitability of the below deck environmental conditions must also be determined.

3.2.8.1.11.2 Capability: Include the following statement: "The number of aircraft that can be shipped in a given vessel is determined by the type of aircraft, the configuration of the aircraft (tactical vs. logistical), and other cargo on board the ship. Stowage of aircraft is normally limited to the first deck below the weather deck, due to vessel trim considerations."

3.2.8.1.11.3 Above deck shipment: Include the following statement: "Shipment of aircraft above deck (on the weather deck) is considered a high risk option. It should only be used under exceptional conditions because damage to the aircraft is likely."

3.2.8.2 Section II, Tactical Shipment: This section shall contain all information specified to transporting the aircraft by vessel in a tactical (minimum disassembly) configuration.

3.2.8.2.1 Preparing the aircraft: This paragraph shall detail all requirements for preparing the aircraft for tactical shipment by vessel.

3.2.8.2.1.1 Line drawings: Line drawings shall be provided as detailed in 3.2.6.3.1 of this specification for aircraft prepared for shipment. Scale shall be as specified in 3.2.6.3.2 and dimensioning shall be as specified in 3.2.6.3.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.2.8.2.1.2 Required resources: Resources required to ship the aircraft shall be detailed. Quantities shall be shown both for shipping one aircraft and shipping a full load. Notes shall be provided to indicate unit requirements such as 1 each required per vessel shipment, 1 each required per aircraft shipped, 1 each required per 5 aircraft shipped, etc.

3.2.8.2.1.2.1 Equipment: All tools and equipment shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix E for part numbers and national stock numbers, Chapter 7 for local manufacture equipment, and Chapter 8 for equipment operation instructions as applicable.

3.2.8.2.1.2.2 Consumable materials: All consumable materials shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix D for part number, unit of issue, and national stock number information.

3.2.8.2.1.2.3 Manpower requirements: A break out shall be provided for each element and task required to be accomplished to prepare for shipment, load, tie down, unload, and prepare the aircraft for flight.

3.2.8.2.1.3 Preservation and packaging: The reader shall be directed to Chapter 6 for detailed information on preservation and packaging and Appendix G for aircraft protective covering.

3.2.8.2.1.4 Disassembly: All tasks required far aircraft preparation for each type of shipment shall be listed in the order of accomplishment. The appropriate chapter and paragraph of the maintenance manual shall be referenced for each task. Tasks that are transportability peculiar shall be completely described with drawings or diagrams as necessary. The reader shall be referred to the appropriate paragraph of the maintenance manual or Chapter 6 of this manual for packaging and preservation instructions.

3.2.8.2.1.5 Load plan: If components and/or equipment are required to be placed inside the aircraft for shipment, a scale diagram of the aircraft shall be provided showing component placement and security. Elevations and/or perspective drawings shall be included if required for clarification.

3.2.8.2.2 Loading: This paragraph shall provide detailed information required to load the aircraft.

3.2.8.2.2.1 Lift on/lift off (LOLO) operations:

3.2.8.2.2.1.1 Rigging: Detailed instructions shall be included for installing hoisting equipment and tag lines (guide ropes) on the aircraft. Diagrams and/or drawings shall be included as

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

required for clarification. Rigging procedures shall be complete and not reference other publications.

3.2.8.2.2.1.2 Hoisting: Step by step instructions shall be provided for loading each aircraft and piece of equipment on board the SEABEE barge. Instructions for maintaining hatch clearance shall be provided as required. Diagrams and/or drawings shall be provided as required for clarification. Hoisting procedures will be complete and not reference other publications.

3.2.8.2.2.2 Roll on/roll off (RORO) operations: Refer the reader to the appropriate paragraphs of chapter 1 on ground handling. Provide the maximum ramp angles that the helicopter can negotiate without shoring.

3.2.8.2.2.3 Placement: A plan drawing of the deck shall be provided indicating the placement of aircraft and components.

3.2.8.2.3 Tie down: This paragraph shall contain all information required to tie down aircraft and components.

3.2.8.2.3.1 General: This subparagraph shall include general information on tie down procedures, restrictions, and requirements.

3.2.8.2.3.2 Equipment: This subparagraph shall detail equipment and material requirements for shoring and tie down of aircraft and components. All equipment used shall be described and pictured as required. Instructions for use shall be provided. A comparative table shall be provided listing quantities required to ship one aircraft and also a full load of aircraft for each type of shipment. Notes shall be provided to indicate quantities required per unit shipped. Equipment provided by the Marine terminal facility shall he so noted.

3.2.8.2.3.3 Procedures: Detailed procedures for tie down shall be included in this subparagraph. Describe and picture tie down points on the aircraft to be shipped. Provide plan, front, rear, and side views to show tie down installation. Show the use of "dead man" chains to provide additional vessel mooring points."

3.2.8.2.4 Unloading: This paragraph shall provide all information required to offload the helicopter both for Lift On/Lift Off and Roll On/Roll Off operations.

3.2.8.2.5 Depreservation and assembly: Provide step by step procedures for depreservation, assembly, and returning the aircraft to flyable status. Reference appropriate maintenance publications by chapter and paragraph for each step. Tasks that are transportability peculiar shall be completely described with drawings and/or diagrams provided as necessary.

3.2.8.3 Section III, Logistical Shipment: This section shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

contain all information specific to transporting the aircraft in a logistical shipment (maximum density) configuration.

3.2.8.3.1 Preparing the aircraft: This paragraph shall detail all requirements for preparing the aircraft for logistical shipment by vessel.

3.2.8.3.1.1 Line drawings: Line drawings shall be provided as detailed in 3.2.6.3.1 of this specification for aircraft prepared for shipment. Scale shall be as specified in 3.2.6.3.2 and dimensioning shall be as specified in 3.2.6.3.3.

3.2.8.3.1.2 Required resources: Resources required to ship the aircraft shall be detailed. Quantities shall be shown both for shipping one aircraft and shipping a full load. Notes shall be provided to indicate unit requirements such as 1 each required per vessel shipment, 1 each required per aircraft shipped, 1 each required per 5 aircraft shipped, etc.

3.2.8.3.1.2.1 Equipment: All tools and equipment shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix E for part numbers and national stock numbers, Chapter 7 for local manufacture equipment, and Chapter 8 for equipment operation instructions as applicable.

3.2.8.3.1.2.2 Consumable materials: All consumable materials shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix D for part number, unit of issue, and national stock number information.

3.2.8.3.1.2.3 Manpower requirements: A break out shall be provided for each element and task required to be accomplished to prepare for shipment, load, tie down, unload, and prepare the aircraft for flight.

3.2.8.3.1.3 Preservation and packaging: The reader shall be directed to Chapter 6 for detailed information on preservation and packaging and Appendix G for aircraft protective covering.

3.2.8.3.1.4 Disassembly: All tasks required for aircraft preparation for each type of shipment shall be listed in the order of accomplishment. The appropriate chapter and paragraph of the maintenance manual shall be referenced for each task. Tasks that are transportability peculiar shall be completely described with drawings or diagrams as necessary. The reader shall be referred to the appropriate paragraph of the maintenance manual or Chapter 6 of this manual for packaging and preservation instructions.

3.2.8.3.1.5 Load plan: If components and/or equipment are required to be placed inside the aircraft for shipment, a scale diagram of the aircraft shall be provided showing component placement and security. Elevations and/or perspective drawings will be included if required for clarification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.2.8.3.2 Loading: This paragraph shall provide detailed information required to load the helicopter for vessel shipment.

3.2.8.3.2.1 Lift on/lift off (LOLO) operations:

3.2.8.3.2.1.1 Rigging: Detailed instructions shall be included for installing hoisting equipment and tag lines (guide ropes) on the aircraft. Diagrams and/or drawings shall be provided as required for clarification.

3.2.8.3.2.1.2 Hoisting: Step by step instructions shall be provided for loading each aircraft and piece of equipment on board the LASH lighter. Instructions for maintaining hatch clearance shall be provided as required. Diagrams and/or drawings shall be provided as required for clarification.

3.2.8.3.2.2 Roll on/roll off (RORO) operations: Refer the reader to the appropriate paragraphs of chapter 1 on Ground Handling. Provide the maximum ramp angels that the helicopter can negotiate without shoring.

3.2.8.3.2.3 Placement: A plan drawing of the deck shall be provided indicating the placement of aircraft and components.

3.2.8.3.3 Tie down: This paragraph shall contain all information required to tie down aircraft and components. Show the use of "dead man" chains to provide additional vessel mooring points.

3.2.8.3.3.1 General: This subparagraph shall include general information on tie down procedures, restrictions, and requirements.

3.2.8.3.3.2 Equipment: This subparagraph shall detail equipment and material requirements for shoring and tie down of aircraft and components. All equipment used shall be described and pictured as required. Instructions for use shall be provided. A comparative table shall be provided listing quantities required to ship one aircraft and also a full load of aircraft for each type of shipment. Notes shall be provided to indicate quantities required per unit shipped. Equipment provided by the Marine terminal facility shall be so noted.

3.2.8.3.3.3 Procedures: Detailed procedures for tie down shall be included in this subparagraph. Describe and picture tie down points on the aircraft to be shipped. Provide plan front, rear, and side views to show tie down installation.

3.2.8.3.4 Unloading: This paragraph shall provide all information necessary to offload the helicopter both for Lift On/Lift Off and Roll On/Roll Off operations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.2.8.3.5 Depreservation and assembly: Provide step by step procedures for depreservation, assembly, and returning the aircraft to flyable status. Reference appropriate maintenance publications by chapter and paragraph for each step. Tasks that are transportability peculiar shall be completely described with drawings and diagrams provided as necessary.

3.2.8.4 Section IV, Shipment by Landing Platform Helicopter (LPH): This section shall contain information specific to transport by and operation from the LPH vessel.

3.2.8.4.1 Preparing the aircraft: This paragraph shall detail all requirements for preparing the aircraft for LPH operations.

3.2.8.4.1.1 Line drawings: Line drawings shall be provided as detailed in 3.2.6.3.1 of this specification for aircraft prepared for shipment. Scale shall be as specified in 3.2.6.3.2 and dimensioning shall be as specified in 3.2.6.3.3.

3.2.8.4.1.2 Required resources: Resources required to ship the aircraft shall be detailed. Quantities shall be shown both for shipping one aircraft and shipping a full load. Notes shall be provided to indicate unit requirements such as one each required per vessel shipment, one each required per aircraft shipped, one each required per five aircraft shipped, etc.

3.2.8.4.1.2.1 Equipment: All tools and equipment shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix E for part numbers and national stock numbers, Chapter 7 for local manufacture equipment, and Chapter 8 for equipment operation instructions, as applicable.

3.2.8.4.1.2.2 Consumable materials: All consumable materials shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix D for part number, unit of issue, and national stock number information.

3.2.8.4.1.2.3 Manpower requirements: A break out shall be provided for each element and task required to be accomplished to prepare for shipment, load, tie down, unload, and prepare the aircraft for flight.

3.2.8.4.1.3 Preservation and packaging: Detailed preservation procedures shall be provided for maintaining an operational aircraft in a corrosive environment. Inspections shall be indicated as necessary. State "Protective covering is not normally used in conjunction with LPH operations".

3.2.8.4.1.4 Disassembly: All tasks required for aircraft preparation for shipment shall be listed in the order of accomplishment. The appropriate chapter and paragraph of the maintenance manual shall be referenced for each task. Tasks that are transportability peculiar shall be completely described with drawings or diagrams as necessary.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the current version before use.

3.2.8.4.1.5 Load plan: If components and/or equipment are required to be placed inside the aircraft for shipment, a scale diagram of the aircraft shall be provided showing component placement and security.

3.2.8.4.2 Loading: This paragraph shall provide detailed information required to load the aircraft on a LPH vessel.

3.2.8.4.2.1 Rigging: Detailed instructions shall be included for installing hoisting equipment and tag lines (guide ropes) on the aircraft.

3.2.8.4.2.2 Hoisting: Step by step instructions shall be provided for loading each aircraft and piece of equipment on board the LPH vessel. Instructions for maintaining hatch clearance shall be provided as required. Diagrams and/or drawings shall he provided as required for clarification.

3.2.8.4.2.3 Placement: A plan drawing shall be provided indicating the relative placement of each aircraft and component for maximum density for each type of shipment.

3.2.8.4.3 Tie down: This paragraph shall contain all information required to tie down aircraft and components.

3.2.8.4.3.1 General: This subparagraph shall include general information on tie down procedures, restrictions, and requirements.

3.2.8.4.3.2 Equipment: This subparagraph shall detail equipment and material requirements for shoring and tie down of aircraft and components. All equipment `used shall be described and pictured as required. Instructions for use shall be provided. A comparative table shall be provided listing quantities required to ship one aircraft and also a full load of aircraft for each type of shipment. Notes shall be provided to indicate quantities required per unit shipped. Equipment provided by marine terminal facility shall be so noted.

3.2.8.4.3.3 Procedures: Detailed procedures for tie down shall be included in this subparagraph. Describe and picture tie down points on the aircraft to be shipped. Provide plan, front, rear, and side views to show tie down installation.

3.2.8.4.4 Unloading: Provide step by step procedures for unloading the LPH.

3.2.8.4.5 Depreservation and assembly: Provide step by step procedures for depreservation, assembly, and returning the aircraft to flyable status. Reference appropriate maintenance publications by chapter and paragraph for each step. Tasks that are transportability peculiar shall be completely described with drawings and diagrams provided as necessary.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

3.2.9 Chanter 4, transportability by truck: This chapter shall specify all requirements for aircraft recovery and tactical and logistical shipment by truck.

3.2.9.1 Section I, General: This section shall present all information of a general nature pertaining to shipment by truck. It shall include the following:

3.2.9.1.1 Types of shipment: This paragraph shall define the various types of truck shipment for aircraft (i.e. air ride/non-air ride suspension, low boy, M-270, etc.)

3.2.9.1.1.1 Tactical (short haul) truck shipment: This is defined as short haul (not to exceed 100 miles) shipment (including aircraft recovery) by Army M270A1 semi-trailer. It is intended to evacuate a disabled aircraft to a maintenance base for repair or preparation for a different mode of transport. In this configuration, the load shall not normally exceed maximum waiverable U.S. highway limits.

3.2.9.1.1.2 Logistical (long haul) truck shipment: Logistical truck shipment is defined as long haul (in excess of 100 miles) shipment by standard commercial, 30 inch high, low boy semi-trailer. It is intended to evacuate a disabled aircraft to a maintenance facility. In this configuration the load will not normally exceed commercial legal U.S. limits. Serviceable aircraft may be shipped by Logistical Truck mode when prepared in accordance with these procedures

3.2.9.1.2 Shipment of damaged aircraft: Include the statement: "For technical assistance in preparing structurally damaged aircraft for shipment contact Commander, U.S. Army Aviation and Troop Command, ATTN: AMSAT-I-SDP, 4300 Goodfellow Blvd., St. Louis, MO 63120-1798, telephone (314) 263-2372 or DSN 693-2372."

3.2.9.1.3 Responsibilities of the shipper: This paragraph shall contain an overview of the responsibilities of the shipper. The following functions shall be included:

3.2.9.1.3.1 Coordinate movement: Coordinate all shipments through the supporting transportation office.

3.2.9.1.3.2 Coordinate lifting device: Coordinate through Command channels for the availability of appropriate lifting devices for loading as required. Coordinate with receiving activity to insure the availability of appropriate lifting devices for unloading upon receipt, as required.

3.2.9.1.3.3 Prepare aircraft: Prepare the aircraft for shipment.

3.2.9.1.3.4 Equipment and materials: Provide all necessary equipment and materials to prepare, load, and secure aircraft to

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

trailer.

3.2.9.1.3.5 Rig aircraft: Furnish and rig all lifting devices.

3.2.9.1.3.6 Load aircraft: Provide lifting device operator with technical assistance in lifting the aircraft.

3.2.9.1.3.7 Secure aircraft: Secure aircraft and components to trailer in accordance with this manual.

3.2.9.1.4 Equipment requirements: Refer the reader to Appendix E for a comprehensive list of tools and equipment applicable to transport by truck. Refer to tables in this chapter for information on specific requirements.

3.2.9.1.5 Material requirements: Refer the reader to Appendix D for the consumable materials list. Refer to tables in this chapter for specific requirements for transportation by truck.

3.2.9.1.6 Manpower requirements: Refer the reader to tables in this chapter for estimates for specific configurations.

3.2.9.1.7 Facility requirements: Indicate specific requirements such as shelter, fire protection, electrical power, grounding, and fresh water.

3.2.9.1.8 Security: Provide specific security instructions relevant to transportation by truck of aircraft and on board systems.

3.2.9.1.9 Safety: This paragraph shall contain safety considerations applicable to shipment by truck.

3.2.9.2 Section II, Aircraft Recovery and Tactical Transport: This section shall contain all information relevant to tactical shipment and recovery of the aircraft by truck.

3.2.9.2.1 General: This paragraph shall provide an introduction to the M270A1 semi-trailer, its limitations, and capabilities.

3.2.9.2.1.1 Line drawings: Left side, front, and top view drawings shall be prepared for the aircraft properly prepared for shipment and secured to the M270A1 trailer. Drawings shall be in accordance with 3.2.6.3.1 of this specification.

3.2.9.2.1.1.1 Scale: Scale of the drawings shall be in accordance with 3.2.6.3.2 of this specification.

3.2.9.2.1.1.2 Dimensions: Provide length, height, and width dimensions for trailer, and overall length, height, and width dimensions for load.

3.2.9.2.1.2 Capabilities and limitations: This subparagraph shall discuss limitations for the loaded trailer such as terrain,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

surface, slope, speed, weight, and permit requirements.

3.2.9.2.1.3 Highway permits: The purpose of this subparagraph is to assist the shipper in obtaining highway permits. It shall include the following information:

3.2.9.2.1.3.1 Responsibilities: Include "It is the responsibility of the shipper to insure that required highway permits are obtained. Permits and routing information are obtained by contacting the supporting Transportation Office. The supporting Transportation Officer will provide necessary coordination with Military Traffic Management Command (MTMC) and local authorities. The shipper will provide the Transportation Officer details and characteristics of the shipment in accordance with AR 55-162 for CONUS shipments and local directives for OCONUS shipments."

3.2.9.2.1.3.2 Load characteristics: Provide overall dimensions, gross weight, and axle load and spacing for the shipment.

3.2.9.2.2 Preparing the aircraft: This paragraph shall detail all requirements for preparing the aircraft for tactical shipment/recovery by truck.

3.2.9.2.2.1. Required resources: Resources required to ship the aircraft shall be detailed with quantities shown.

3.2.9.2.2.1.1 Equipment: All tools and equipment shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix E for part numbers and national stock numbers, Chapter 7 for local manufacture equipment, and Chapter 8 for equipment operation instructions as applicable. A table shall be provided indicating the item and quantity required.

3.2.9.2.2.1.3 Manpower requirements: A break out shall be provided for each element and task required to be accomplished to prepare for shipment, load, tie down, unload, and assemble the aircraft. Personnel requirements, man-hours, and elapsed time shall be provided in a table.

3.2.9.2.2.2 Preservation and packaging: The reader shall be directed to Chapter 6 for detailed information on preservation and packaging and Appendix G for aircraft protective covering.

3.2.9.2.2.3 Disassembly: All tasks required for aircraft preparation shall be listed in the order of accomplishment. The appropriate chapter and paragraph of the maintenance manual shall be referenced for each task. Tasks that are transportability peculiar shall be completely described with drawings or diagrams as necessary. The reader shall be referred to the appropriate paragraph of the maintenance manual or Chapter 6 of this manual for packaging and preservation instructions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

the number of users per equipment of the

3.2.9.2.2.3.1 Load plan: If components and/or equipment are required to be placed inside the aircraft for shipment, a scale diagram of the aircraft shall be provided showing component placement and security. Elevations and/or perspective drawings shall be included if required for clarification.

3.2.9.2.3 Loading: This paragraph shall provide detailed information required to load the aircraft on the semi-trailer.

3.2.9.2.3.1 Rigging: Detailed instructions shall be included for installing hoisting equipment and tag lines (guide ropes) on the aircraft. Diagrams and/or drawings shall be included as required for clarification.

3.2.9.2.3.2 Hoisting: Step by step instructions shall be provided for loading the aircraft and each piece of equipment on board the trailer. Diagrams and/or drawings shall be provided as required for clarification.

3.2.9.2.3.3 Placement: A plan drawing of the trailer shall be provided indicating the placement of the aircraft and each component. If ballast is required, the amount and placement shall be detailed.

3.2.9.2.3.4 Tie down: This paragraph shall contain all information required to tie down the aircraft and components.

3.2.9.2.3.4.1 General: This subparagraph shall include general information on tie down procedures, restrictions, and requirements

3.2.9.2.3.4.2 Equipment: This subparagraph shall detail equipment and material requirements for shoring and tie down of aircraft and components. All equipment used shall be described and pictured as required. Instructions for use shall be provided. A table shall be provided listing quantities required.

3.2.9.2.3.4.3 Procedures: Detailed procedures for tie down shall be included in this subparagraph. Describe and picture tie down points on the aircraft to be shipped. Provide plan, front, rear, and side views to show tie down installation.

3.2.9.2.4 Unloading: Provide step by step procedures for unloading the aircraft and components.

3.2.9.2.5 Depreservation and assembly: Provide step by step procedures for depreservation and assembly. Reference appropriate maintenance publications by chapter and paragraph for each step. Tasks that are transportability peculiar shall be completely described with drawings and diagrams provided as necessary.

3.2.9.3 Section III, Logistical Transport by Truck: This section shall contain all information relevant to logistical

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

shipment of the aircraft by truck.

3.2.9.3.1 General: This paragraph shall provide an introduction to the standard commercial, 30 inch high, lowboy semi-trailer, its limitations, and its capabilities.

3.2.9.3.1.1 Line drawings: Left side, front, and top view drawings shall be prepared for the aircraft properly prepared for shipment and secured to the semi-trailer. Drawings shall be in accordance with 3.2.6.3.1 of this specification.

3.2.9.3.1.1.1 Scale: Scale of the drawings shall be in accordance with 3.2.6.3.2 of this specification.

3.2.9.3.1.1.2 Dimensions: Provide length, height, and width dimensions for the trailer, aid overall length, height, and width dimensions for the load.

3.2.9.3.1.2 Capabilities and limitations: This subparagraph shall discuss limitations for the loaded trailer such as terrain, surface, slope, speed, weight, and permit requirements.

3.2.9.3.1.3 Highway permits: The purpose of this subparagraph is to assist the shipper in obtaining highway permits. It shall include the following information:

3.2.9.3.1.3.1 Responsibilities: Include "It is the responsibility of the shipper to insure that required highway permits are obtained. Permits and routing information are obtained by contacting the supporting Transportation Office. The supporting Transportation Officer will provide necessary coordination with Military Traffic Management Command (MTMC) and local authorities. The shipper will provide the Transportation Officer details and characteristics of the shipment in accordance with AR 55-162 for CONUS shipments and local directives for OCONUS shipments."

3.2.9.3.1.3.2 Load characteristics: Provide overall dimensions, gross weight, and axle load and spacing for each load configuration.

3.2.9.3.2 Preparing the aircraft: This paragraph shall detail all requirements for preparing the aircraft for Logistical Long Haul Shipment by Truck.

3.2.9.3.2.1 Required resources: Resources required to ship the aircraft shall be detailed with quantities shown.

3.2.9.3.2.1.1 Equipment: All tools and equipment shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix E for part numbers and national stock numbers, Chapter 7 for local manufacture equipment, and Chapter 8 for equipment operation instructions, as applicable. A table shall be provided indicating the item and quantity

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

required.

3.2.9.3.2.1.2 Consumable materials: All consumable materials shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix D for part number, unit of issue, and national stock number information. A table shall be included providing quantity data for consumable materials.

3.2.9.3.2.1.3 Manpower requirements: A break out shall be provided for each element and task required to be accomplished to prepare for shipment, load, tie down, unload, and assemble the aircraft. Personnel requirements, man-hours, and elapsed time shall be provided in a table.

3.2.9.3.2.2 Preservation and packaging: The reader shall be directed to Chapter 6 for detailed information on preservation and packaging and Appendix G for aircraft protective covering.

3.2.9.3.2.3 Disassembly: All tasks required for aircraft preparation shall be listed in the order of accomplishment. The appropriate chapter and paragraph of the maintenance manual shall be referenced for each task. Tasks that are transportability peculiar shall be completely described with drawings or diagrams as necessary. The reader shall be referred to the appropriate paragraph of the maintenance manual or Chapter 6 of this manual for packaging and preservation instructions.

3.2.9.3.2.4 Load plan: If components and/or equipment are required to be placed inside the aircraft for shipment, a scale diagram of the aircraft shall be provided showing component placement and security. Elevations and/or perspective drawings shall be included if required for clarification.

3.2.9.3.3 Loading: This paragraph shall provide detailed information required to load the aircraft on the semi-trailer.

3.2.9.3.3.1 Rigging: Detailed instructions shall be included for installing hoisting equipment and tag lines (guide ropes) on the aircraft. Diagrams and/or drawings shall be included as required for clarification.

3.2.9.3.3.2 Hoisting: Step by step instructions shall be provided for loading the aircraft and each piece of equipment on board the trailer. Diagrams and/or drawings shall be provided as required for clarification.

3.2.9.3.3.3 Placement: A plan drawing of the trailer shall be provided indicating the placement of the aircraft and each component. If ballast is required, the amount, type, and placement shall be detailed.

3.2.9.3.3.4 Tie down: This paragraph shall contain all information required to tie down aircraft and components.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.2.9.3.3.4.1 General: This subparagraph shall include general information on tie down procedures, restrictions, and requirements.

3.2.9.3.3.4.2 Equipment: This subparagraph shall detail equipment and material requirements for shoring and tie down information in Chapter 6 as appropriate. In addition it shall include the following:

3.2.10.1.3.3.1 Use no hooks: Mark each side and end of each crate with 2 inch stenciled letters "USE NO GRAB HOOKS".

3.2.10.1.3.3.2 Opening instructions: Stencil opening instructions in 1 inch letters on one end of each crate.

3.2.10.1.3.3.3 Center of balance: Indicate the center of balance of loaded crates with a painted black strip 1 inch wide on each side, extending upward 3 inches from lower edge of sheeting. Stencil "CENTER OF BALANCE" in 1 inch letters adjacent to the strips.

3.2.10.1.3.3.4 Sling points: Indicate sling points by conspicuous arrows and "SLING HERE" in 1 inch letters for each step. Tasks that are transportability peculiar shall be completely described with drawings and diagrams provided as necessary.

3.2.10 Chapter 5, crated and intermodal container shipment: Procedures applicable to crated shipment and intermodal container shipment shall be covered in this chapter.

3.2.10.1 Section I, Crated Shipment: Procedures applicable to crated shipment shall be included in this section. If crated shipment procedures are not required for the aircraft, include the statement "Crated shipment is not applicable to Army model..." followed by model and nomenclature of the aircraft.

3.2.10.1.1 Characteristics: This paragraph shall include the intended use of crated shipment, intended modes of transport, and the advantages and disadvantages of crated shipment.

3.2.10.1.1.1 Handling methods: Identify handling methods such as lifting. Handling devices shall be identified, described, and pictured as required.

3.2.10.1.1.2 Security requirements: Special security requirements relevant to crated shipment of the aircraft and components shall be included.

3.2.10.1.1.3 Facility requirements: Provide information on facility requirements such as shelter, overhead crane, electricity, etc., required during crating of the aircraft.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.2.10.1.1.4 Required resources: Resources required to crate and ship the aircraft shall be detailed in this section. Quantities required for each item shall be included.

3.2.10.1.1.4.1 Equipment: All tools and equipment required shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix E for part numbers and national stock numbers, Chapter 7 for local manufacture equipment, and Chapter 8 for equipment operation instructions, as applicable.

3.2.10.1.1.4.2 Consumable materials: All consumable materials shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix D for part number, unit of issue, and national stock number information.

3.2.10.1.1.4.3 Manpower requirements: A break out shall be provided for each element and task required to prepare for shipment, disassemble, preserve, crate, uncrate, assemble, and return the aircraft to flyable status. Personnel requirements, man-hours, and elapsed time shall be provided in a table.

3.2.10.1.2 Aircraft preparation: This paragraph shall provide all information required to prepare the aircraft for crating.

3.2.10.1.2.1 Preparation for storage: Provide step by step instructions for preparing the aircraft for intermediate storage. Reference applicable paragraphs in maintenance manuals and Chapter 6 of this manual as appropriate.

3.2.10.1.2.2 Disassembly: This paragraph shall provide step by step instructions for aircraft disassembly required for crated shipment. Procedures in the maintenance manual shall be referenced by paragraph. For procedures peculiar to crated shipment and/or transportability, detailed instructions shall be included with drawings and diagrams as required for clarification.

3.2.10.1.3 Crating: This paragraph shall include dimensioned drawings and all instructions for constructing the crate, packing the helicopter and components, and marking the crates.

3.2.10.1.3.1 Crate construction: Include the materials list, working drawings, and step by step instructions for constructing the crates.

3.2.10.1.3.2 Packing: Include step by step instructions for packing the aircraft and components. A drawing will be included showing completed crating.

3.2.10.1.3.3 Marking: This subparagraph shall contain marking information. It shall reference information in Chapter 6 as appropriate. In addition it shall include the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

removing rigging and assembly of helicopter. Provide detailed

3.2.10.1.3.3.1 Use no hooks: Mark each side and end of each crate with 2 inch stenciled letters "USE NO GRAB HOOKS".

3.2.10.1.3.3.2 Opening instructions: Stencil opening instructions in 1 inch letters on one end of each crate.

3.2.10.1.3.3.3 Center of balance: Indicate the center of balance of loaded crates with a painted black strip 1 inch wide on each side, extending upward 3 inches from lower edge of sheeting. Stencil "CENTER OF BALANCE" in 1 inch letters adjacent to the strips.

3.2.10.1.3.3.4 Sling points: Indicate sling points by conspicuous arrows and "SLING HERE" in 1 inch letters.

3.2.10.1.3.3.5 Preservation date: Stencil in one inch letters adjacent to inspection doors: "PRESERVED FOR INTERMEDIATE STORAGE. REPRESERVE IF NOT ACTIVATED BY..." followed by the date 180 days after the aircraft was preserved.

3.2.10.1.3.3.6 MIL-STD-129 Preservation Method and Level of Protection: Mark for level of preservation and packaging "C/C".

3.2.10.1.4 Unpacking and assembly: Provide step by step instructions for uncrating, assembly, depreservation, and returning the aircraft to flyable status. Reference applicable procedures in maintenance manuals and Chapter 6 of this manual. For tasks unique to crated shipment, and/or transportability, detailed procedures shall be provided to include drawings and diagrams as required.

3.2.10.2 Section II, Inter Modal Container Shipment: This section will contain all information specific to containerized transport of the aircraft. If containerized shipment is not required for this aircraft, include the statement: "Inter modal container shipment is not applicable to Army model..." followed by model and nomenclature of the aircraft.

3.2.10.2.1 Characteristics: This paragraph shall provide an introduction to inter modal containers. It shall provide a description of available containers. It shall also include the intended use of containerized shipment and the advantages and disadvantages of containerized shipment.

3.2.10.2.1.1 Line drawings: Line drawings of the applicable containers shall be included showing the interior dimensions.

3.2.10.2.1.2 Security requirements: Special security requirements relevant to containerized shipment of the aircraft and components shall be included.

3.2.10.2.1.3 Facility requirements: Provide information on facility requirements such as shelter, overhead crane, electricity, etc., required during loading of the aircraft into a

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

container.

3.2.10.2.1.4 Safety requirements: Indicate safety considerations applicable to containerized shipment.

3.2.10.2.2. Preparing the aircraft: This paragraph shall detail all requirements for preparing the aircraft for containerized shipment.

3.2.10.2.2.1 Line drawings: Line drawings shall be provided as detailed in 3.2.6.3.1 of this specification for aircraft prepared for containerized shipment. Scale will be as specified in 3.2.6.3.2 and dimensioning will be as specified in 3.2.6.3.3.

3.2.10.2.2.2 Required resources: Resources required to containerize and ship the aircraft shall be detailed in this section. Quantities required for each item shall be included.

3.2.10.2.2.2.1 Equipment: All tools and equipment required shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix E for part numbers and national stock numbers, Chapter 7 for local manufacture equipment, and Chapter 8 for equipment operation instructions as applicable.

3.2.10.2.2.2.2 Consumable materials: All consumable materials shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix D for part number, unit of issue, and national stock number information.

3.2.10.2.2.2.3 Manpower requirements: A break out shall be provided for each element and task required to prepare, disassemble, preserve, crate, uncrate, assemble, and return aircraft to flyable status. Personnel requirements, man-hours, and elapsed time shall be provided in a table.

3.2.10.2.2.3 Preservation and packaging: The reader shall be directed to Chapter 6 for detailed information on preservation and packaging and Appendix G for aircraft protective covering.

3.2.10.2.2.4 Disassembly: All tasks required for aircraft preparation shall be listed in the order of accomplishment. The appropriate chapter and paragraph of the maintenance manual shall be referenced for each task. Tasks that are transportability peculiar shall be completely described with drawings or diagrams as necessary. The reader shall be referred to the appropriate paragraph of the maintenance manual or Chapter 6 of this manual for packaging and preservation instructions.

3.2.10.2.2.5 Load plan: If components and/or equipment are required to be placed inside the aircraft for shipment, a scale diagram of the aircraft shall be provided showing component placement and security. Elevations and/or perspective drawings shall be included if required for clarification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.2.10.2.3 Loading: This paragraph shall provide detailed information required to load the aircraft in an inter modal container. Step by step instructions shall be provided for loading each aircraft and piece of equipment in the container. Instructions for maintaining wall clearance shall be provided as required. Diagrams and/or drawings will be provided as required for clarification. A plan drawing of the container shall be provided indicating the placement of each aircraft and component.

3.2.10.2.4 Tie down: This paragraph shall contain all information required to tie down aircraft and components in the container.

3.2.10.2.4.1 General: This subparagraph shall include general information on tie down procedures, restrictions, and requirements.

3.2.10.2.4.2 Equipment: This subparagraph shall detail equipment and material requirements for the tie down of aircraft and components. All equipment used shall be described and pictured as required. Instructions for use will be provided.

3.2.10.2.4.3 Procedures: Detailed procedures for tie down shall be included in this subparagraph. Describe and picture tie down points on the aircraft to be shipped. Provide plan, front, rear, and side views to show tie down installation.

3.2.10.2.5 Unloading: Provide step by step procedures for unloading the container.

3.2.10.2.6 Depreservation and assembly: Provide step by step procedures for depreservation, assembly, and returning the aircraft to flyable status. Reference appropriate maintenance publications by chapter and paragraph for each step. Tasks that are transportability peculiar will be completely described with drawings and diagrams provided as necessary.

3.2.11 Chapter 6, Preservation and Packaging: This chapter will contain specific cleaning, preservation, packaging, marking, and depreservation instructions for preparing the aircraft for shipment, and returning it to flyable status.

3.2.11.1 Section I, General: This section shall explain the concepts used in preparation of these instructions. It shall state that in addition to the mode of transportation involved, the length of time an aircraft shall remain inactive is a primary concern. State the concepts used in the development of the different types of storage developed for maintenance manuals and relate them to preservation for shipment.

3.2.11.2 Section II, Aircraft Cleaning: This section shall contain the reasons for cleaning the aircraft, required materials and equipment, and step by step procedures.

Source: https://assist.dla.mil -- Downloaded: 20261O-26T04:24Z
Check the source to verify that this is the current version before use.

specified in the manual. When specified by the contracting

3.2.11.2.1 General: This paragraph shall contain the reasons for cleaning the aircraft and what may happen if it is not done properly.

3.2.11.2.2 Resources: This paragraph shall present the resources required for cleaning the aircraft and provide an estimate of the personnel requirements, man-hours, and elapsed time to clean the aircraft.

3.2.11.2.2.1 Equipment: List equipment required for complete aircraft cleaning by noun nomenclature and reference numbers. Direct the reader to Appendix E for part numbers and national stock numbers.

3.2.11.2.2.2 Materials: List materials required for complete aircraft cleaning by noun nomenclature, reference number, and quantity. Direct the reader to Appendix D for part number, national stock number, and unit of issue information.

3.2.11.2.3 Procedures: Prepare step by step procedures for cleaning the aircraft in preparation for shipment. Reference specific procedures in maintenance manuals by paragraph as required.

3.2.11.3 Section III, Preservation: Provide procedures for preserving the aircraft based on the projected period of inactivity. These periods shall be the same as the terms of storage developed in the maintenance manuals. Reference protective covering for vessel and truck shipment as provided in Appendix G.

3.2.11.3.1 General: Provide rationale for preserving the aircraft for the various periods of inactivity.

3.2.11.3.2 Resources: This paragraph shall state the resources required to preserve the aircraft for shipment.

3.2.11.3.2.1 Equipment: List equipment required for preservation of the aircraft by noun nomenclature and reference numbers. Refer the reader to Appendix E for part number and unit of issue information. Provide a comparative table indicating required equipment for each term of inactivity.

3.2.11.3.2.2 Materials: List materials used in preserving the aircraft by noun nomenclature and reference numbers. Refer the reader to Appendix D for part number and unit of issue information. Provide a comparative table indicating required materials for each term of inactivity.

3.2.11.3.2.3 Manpower: Provide manpower estimates for preserving the aircraft for each task and each term of inactivity. Information shall be presented in a tabular format.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.2.11.3.3 Procedures: Provide step by step procedures for each term of inactivity. Reference procedures in the maintenance manual, as applicable.

3.2.11.4 Section IV, Preservation and Packaging of Components: This section shall provide instructions for Preservation and packaging of removed components.

3.2.11.4.1 Procedures: Procedures shall be provided for preservation and packaging of each component that may be removed from the aircraft for shipping. These procedures shall be complete and referenced by the various chapters in this manual.

3.2.11.4.2 Resources: This paragraph shall present resources required to package and preserve components.

3.2.11.4.2.1 Manpower: A table shall be prepared indicating man-hours and elapsed time to complete preservation and packaging operations for each component that may require removal.

3.2.11.4.2.2 Packaging: Special containers used for transportability, if any, shall be described in this paragraph, and listed in Appendix E. Locally manufactured containers with multiple transportability mode usage shall be described. Drawings, materials lists, and construction procedures shall be contained in Chapter 7, and referenced.

3.2.11.5 Section V, Marking and Preparation of Shipping Documents: This section shall contain all information pertaining to marking and labeling the aircraft and components in accordance with MIL-STD-129. Also included shall be instructions for completing shipper prepared shipping documents.

3.2.11.5.1 Components: As minimum, provide the following instructions.

3.2.11.5.1.1 Identification: Identify each removed component with the serial number of the aircraft it was removed from and the components condition.

3.2.11.5.1.2 Color coding: Insure that rotor blades and controls are properly color coded prior to removal to insure that they will be installed in the proper position.

3.2.11.5.2 Center of balance: Mark the center of gravity (CG) on the aircraft and major components (air shipment).

3.2.11.5.3 Preservation information: Tag each aircraft in a conspicuous location with the following: "AIRCRAFT PRESERVED FOR UP ..." followed by the number of days applicable to applied preservation. "REPRESERVE IF NOT ACTIVATED BY..." followed by the date the appropriate number of days after the preservation date. The same information shall be included with the shipping documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.2.11.5.4 Shipping documents: Include examples and information on preparing and attaching required shipper prepared shipping documents.

3.2.11.6 Section VI, Depreservation: This section shall contain information specific to depreservation of the aircraft.

3.2.11.6.1 Components: This paragraph shall provide all instructions for the depreservation of components prior to assembly.

3.2.11.6.2 Aircraft: This paragraph shall provide all instructions for depreserving the assembled aircraft.

3.2.12 Chapter 7, Local Manufacture Transportability Equipment: This chapter shall include drawings, materials lists, instructions, and manpower requirements for the construction of local manufacture equipment, fixtures, and/or boxes. If local manufacture transportability equipment is not used with the aircraft, the following statement shall be included: "Local manufacture transportability equipment does not apply to Army model..." followed by model and nomenclature of the aircraft.

3.2.13 Chapter 8, Operator and Maintenance Instructions with Repair Parts and Special Tools List for Transportability Equipment including Depot Level Repair Parts: This chapter shall provide information on the operation and maintenance of transportability peculiar tools and equipment. Transportability peculiar equipment is defined as equipment unique to transportability functions and not authorized for maintenance tasks.

3.2.13.1 Section I, Operator Instructions: This section shall provide detailed instructions on the proper installation and use of all transportability equipment. Separate instructions shall be provided for the disassembly of equipment and special packaging for the return of transportability equipment to the specialized control point. A separate paragraph shall be included for each item.

3.2.13.2 Section II, Repair/Overhaul Procedures: This section shall include unit, intermediate, and depot repair/overhaul procedures for transportability equipment.

3.2.13.3 Section III, Repair Parts and Special Tools List: This section shall be arranged in figure and item number sequence. It shall provide an illustrated breakdown and tabular listing. The tabular listing shall reflect illustration figure and item number, SMR Code, NSN, CAGE, Part Number, Description, Unit of Issue, and Quantity Required in Unit. A separate subsection shall be provided for each item of transportability equipment and in the same format as the aircraft RPSTL.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.2.14 Chapter 9, External Transport by Helicopter (Aerial Recovery): This chapter shall provide all information required to rig the aircraft for external transport by helicopter. A list of tools, equipment, and consumable materials required for each method of transport will be included. Also included will be a description of the load characteristics and flight parameters for each method of transport.

3.2.14.1 Section I, General: This section shall present all information of a general nature pertaining to external transport of the aircraft by helicopter. It shall include, as a minimum:

3.2.14.1.1 Types of Transport: This paragraph shall present the types of helicopters capable of providing external transport of the aircraft and an overview of the types of rigging available. Verbal and tabular data shall be provided indicating the relative merits and disadvantages of each.

3.2.14.1.2 Functions of the Aircraft Recovery Team:

3.2.14.1.2.1 Coordinate with the recovery aircraft crew the type weight, location, and condition of the aircraft to be recovered.

3.2.14.1.2.2 Provide all equipment and materials required to prepare and rig disabled aircraft.

3.2.14.1.2.3 Prepare and rig disabled aircraft for transport.

3.2.14.1.2.4 Provide hook up of disabled aircraft to recovery helicopter.

3.2.14.1.3 Equipment requirements: Refer the reader to Appendix E for a comprehensive list of tools and equipment applicable to external transport of the aircraft by helicopter, and the appropriate tables in the text for information on specific requirements.

3.2.14.1.4 Material requirements: Refer the reader to Appendix D for the consumable materials list. Refer to tables in this chapter for specific requirements.

3.2.14.1.5 Manpower requirements: Refer the reader to appropriate tables in this chapter for estimates for specific configurations.

3.2.14.1.6 Safety: Provide general safety considerations applicable to external transport by helicopter.

3.2.14.2 Section II, Single Cargo Hook Hard Point Lift (Primary Method: This section shall provide an introduction to transporting the aircraft using rotor head and/or airframe hard points and a recovery helicopter equipped with a single cargo hook. If both rotor head and airframe hard point attachments are applicable, provide a separate paragraph for each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.2.14.2.1 Characteristics: This paragraph shall provide specific information stating the recovery helicopters appropriate for this type lift. State particular considerations applicable to this type lift.

3.2.14.2.1.1 Load description: Provide information regarding the characteristics of the aircraft transported in this configuration, including in-flight characteristics and weight.

3.2.14.2.1.2 Flight parameters: Provide information regarding flight parameters of each type recovery helicopter applicable to this lift method. Include parameters such as air speed, angle of bank, and maximum wind during pickup.

3.2.14.2.2 Preparing the aircraft: This paragraph shall detail all requirements for preparing the aircraft for external transport by helicopters using single cargo hook hard point lift.

3.2.14.2.2.1 Required resources: Resources required to prepare and rig the aircraft for external transport shall be detailed in this paragraph.

3.2.14.2.2.1.1 Equipment: All tools and equipment required for this method of external lift shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix E for part numbers and national stock numbers, Chapter 7 for local manufacture equipment, and Chapter 8 for equipment operation instructions as applicable.

3.2.14.2.2.1.2 Consumable materials: All consumable materials shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix D for part numbers, unit of issue, and national stock number information.

3.2.14.2.2.1.3 Manpower requirements: A break out shall be provided for each element and task required to be accomplished to prepare the aircraft and rig it for transport.

3.2.14.2.2.2 Disassembly: All tasks required for aircraft preparation shall be listed in the order of accomplishment. The appropriate chapter and paragraph of the maintenance manual shall be referenced for each task. Tasks that are transportability peculiar shall be completely described with drawings or diagrams as necessary.

3.2.14.2.2.3 Load plan: If components are required to be placed inside the aircraft to be transported, a scale diagram of the aircraft shall be provided showing component placement and security. Elevations and/or perspective drawings shall be included if required for clarification.

3.2.14.2.2.4 Rigging: Detailed instructions shall be included for installing rigging equipment on the aircraft to be

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

transported. Drawings and/or diagrams shall be included as required for clarification. Drawing shall provide detailed information on sling leg dimensions and link count.

3.2.14.2.2.5 Hook up: Detailed instructions shall be provided for hook up of the rigged aircraft to the helicopter transport. Provide personnel duties as well as specific safety precautions.

3.2.14.2.2.6 Assembly: Provide step by step instructions for removing rigging and assembly of helicopter. Provide detailed instructions for any required special inspections. Reference appropriate maintenance publications by chapter and paragraph for each task. Tasks that are transportability peculiar shall be completely described with drawings and/or diagrams provided as necessary.

3.2.14.3 Section III, Single Cargo Hook Hard Point Lift (Alternate Method): This section shall provide an introduction to transporting the aircraft using rotor head and/or airframe hard points and a recovery helicopter equipped with a single cargo hook. This section shall only be applicable if both rotor head and airframe hard point attachments are applicable to the aircraft.

3.2.14.3.1 Characteristics: This paragraph shall provide specific information stating the recovery helicopters appropriate for this type lift. State particular considerations applicable to this type lift.

3.2.14.3.1.1 Load description: Provide information regarding the characteristics of the aircraft transported in this configuration including in-flight characteristics and weight.

3.2.14.3.1.2 Flight parameters: Provide information regarding flight parameters of each type recovery helicopter applicable to this lift method. Include parameters such as air speed, angle of bank, and maximum wind during pickup.

3.2.14.3.2 Preparing the aircraft: This paragraph shall detail all requirements for preparing the aircraft for external transport by helicopter using single cargo hook hard point lift.

3.2.14.3.2.1 Required resources: Resources required to prepare and rig the aircraft for external transport shall be detailed in this paragraph.

3.2.14.3.2.1.1 Equipment: All tools and equipment required for this method of external lift shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix E for part numbers and national stock numbers, Chapter 7 for local manufacture equipment, and Chapter 8 for equipment operation instructions as applicable.

3.2.14.3.2.1.2 Consumable materials: All consumable materials

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix D for part numbers, unit of issue, and national stock number information.

3.2.14.3.2.1.3 Manpower requirements: A break out shall be provided for each element and task required to be accomplished to prepare the aircraft and rig it for transport.

3.2.14.3.2.2 Disassembly: All tasks required for aircraft preparation shall be listed in the order of accomplishment. The appropriate chapter and paragraph of the maintenance manual shall be referenced for each task. Tasks that are transportability peculiar shall be completely described with drawings or diagrams as necessary.

3.2.14.3.2.3 Load plan: If components are required to be placed inside the aircraft to be transported, a scale diagram of the aircraft shall be provided showing component placement and security elevations and/or perspective drawings shall be included if required for clarification.

3.2.14.3.2.4 Rigging: Detailed instructions shall be included for installing rigging equipment on the aircraft to be transported. Drawings and/or diagrams shall be included as required for clarification. Drawing shall provide detailed information on sling leg dimensions and link count.

3.2.14.3.2.5 Hook up: Detailed instructions shall be provided for hook up of the rigged aircraft to the helicopter transport. Provide personnel duties as well as specific safety precautions.

3.2.14.3.2.6 Assembly: Provide step by step instructions for removing rigging and assembly of helicopter. Provide detailed instructions for any required special inspections. Reference appropriate maintenance publications by chapter and paragraph for each task. Tasks that are transportability peculiar shall be completely described with drawings and/or diagrams provided as necessary.

3.2.14.4 Section IV, Dual Cargo Hook Hard Point Lift (Primary Method): This section shall provide an introduction to transporting the aircraft using rotor head and/or airframe hard points and a recovery helicopter equipped with a dual cargo hook system. If both rotor head and airframe hard point attachments are applicable, provide a separate paragraph for each.

3.2. 14.4.1 Characteristics: This paragraph shall provide specific information stating the recovery helicopters appropriate for this type lift. State particular considerations applicable to this type lift.

3.2.14.4.1.1 Load description: Provide information regarding the characteristics of the aircraft transported in this configuration including in-flight characteristics and weight.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the current version before use.

3.2.14.4.1.2 Flight parameters: Provide information regarding flight parameters of each type recovery helicopter applicable to this lift method. Include parameters such as air speed, angle of bank, and maximum wind during pickup.

3.2.14.4.2. Preparing the aircraft: This paragraph shall detail all requirements for preparing the aircraft for external transport by helicopter using dual cargo hook hard point lift.

3.2.14.4.2.1 Required resources: Resources required to prepare and rig the aircraft for external transport shall be detailed in this paragraph.

3.2.14.4.2.1.1 Equipment: All tools and equipment required for this method of external lift shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix E for part numbers and national stock numbers, Chapter 7 for local manufacture equipment, and Chapter 8 for equipment operation instructions as applicable.

3.2.14.4.2.1.2 Consumable materials: All consumable materials shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix D for part numbers, unit of issue, and national stock number information.

3.2.14.4.2.1.3 Manpower requirements: A break out shall be provided for each element and task required to be accomplished to prepare the aircraft and rig it for transport.

3.2.14.4.2.2 Disassembly: All tasks required for aircraft preparation shall be listed in the order of accomplishment. The appropriate chapter and paragraph of the maintenance manual shall be referenced for each task. Tasks that are transportability peculiar shall be completely described with drawings or diagrams as necessary.

3.2.14.4.2.3 Load plan: If components are required to be placed inside the aircraft to be transported, a scale diagram of the aircraft shall be provided showing component placement and security. Elevations and/or perspective drawings shall be included if required for clarification.

3.2.14.4.2.4 Rigging: Detailed instructions shall be included for installing rigging equipment on the aircraft to be transported. Drawings and/or diagrams shall be included as required for clarification. Drawing shall provide detailed information on sling leg dimensions and link count.

3.2.14.4.2.5 Hook up: Detailed instructions shall be provided for hook up of the rigged aircraft to the helicopter transport. Provide personnel duties as well as specific safety precautions.

3.2.14.4.2.6 Assembly: Provide step by step instructions for

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the current version before use.

removing rigging and assembly of helicopter. Provide detailed instructions for any required special inspections. Reference appropriate maintenance publications by chapter and paragraph for each task. Tasks that are transportability peculiar shall be completely described with drawings and/or diagrams provided as necessary.

3.2.14.5 Section V, Dual Cargo Hook Hard Point Lift (Alternate Method): This section shall provide an introduction to transporting the aircraft using rotor head and/or airframe hard points and a recovery helicopter equipped with a dual cargo hook. This section shall only be applicable if both rotor head and airframe hard point attachments are applicable to the aircraft.

3.2.14.5.1 Characteristics: This paragraph shall provide specific information stating the recovery helicopters appropriate for this type lift. State particular considerations applicable to this type lift.

3.2.14.5.1.1 Load description: Provide information regarding the characteristics of the aircraft transported in this configuration including in-flight characteristics and weight.

3.2.14.5.1.2 Flight parameters: Provide information regarding flight parameters of each type recovery helicopter applicable to this lift method. Include parameters such as air speed, angle of bank, and maximum wind during pickup.

3.2.14.5.2 Preparing the aircraft: This paragraph shall detail all requirements for preparing the aircraft for external transport by helicopters using dual cargo hook hard point lift.

3.2.14.5.2.1 Required Resources: Resources required to prepare and rig the aircraft for external transport shall be detailed in this paragraph.

3.2.14.5.2.1.1 Equipment: All tools and equipment required for this method of external lift shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix E for part numbers and national stock numbers, Chapter 7 for local manufacture equipment, and Chapter 8 for equipment operation instructions as applicable.

3.2.14.5.2.1.2 Consumable materials: All consumable materials shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix D for part numbers, unit of issue, and national stock number information.

3.2.14.5.2.1.3 Manpower requirements: A break out shall be provided for each element and task required to be accomplished to prepare the aircraft and rig it for transport.

3.2.14.5.2.2 Disassembly: All tasks required for aircraft preparation shall be listed in the order of accomplishment. The

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the current version before use.

appropriate chapter and paragraph of the maintenance manual shall be referenced for each task. Tasks that are transportability peculiar shall be completely described with drawings or diagrams as necessary.

3.2.14.5.2.3 Load plan: If components are required to be placed inside the aircraft to be transported, a scale diagram of the aircraft shall be provided showing component placement and security. Elevations and/or perspective drawings shall be included if required for clarification.

3.2.14.5.2.4 Rigging: Detailed instructions shall be included for installing rigging equipment on the aircraft to be transported. Drawings and/or diagrams shall be included as required for clarification. Drawing shall provide detailed information on sling leg dimensions and link count.

3.2.14.5.2.5 Hook up: Detailed instructions shall be provided for hook up of the rigged aircraft to the helicopter transport. Provide personnel duties as well as specific safety precautions.

3.2.14.5.2.6 Assembly: Provide step by step instructions for removing rigging and assembly of helicopter. Provide detailed instructions for any required special inspections. Reference appropriate maintenance publications by chapter and paragraph for each task. Tasks that are transportability peculiar shall be completely described with drawings and/or diagrams provided as necessary.

3.2.14.6 Section VI, Single Cargo Hook Belly Band Lift: This section shall provide an introduction to transporting the aircraft using belly band type rigging and a recovery helicopter equipped with a single cargo hook.

3.2.14.6.1 Characteristics: This paragraph shall provide specific information stating the recovery helicopters appropriate for this type lift. State particular considerations applicable to this type lift.

3.2.14.6.1.1 Load description: Provide information regarding the characteristics of the aircraft transported in this configuration including in-flight characteristics and weight.

3.2.14.6.1.2 Flight parameters: Provide information regarding flight parameters of each type recovery helicopter applicable to this lift method. Include parameters such as air speed, angle of bank, and maximum wind during pickup.

3.2.14.6.2 Preparing the aircraft: This paragraph shall detail all requirements for preparing the aircraft for external transport by helicopters using belly band rigging.

3.2.14.6.2.1 Required resources: Resources required to prepare and rig the aircraft for external transport shall be detailed in

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

this paragraph.

3.2.14.6.2.1.1 Equipment: All tools and equipment required for this method of external lift shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix E for part numbers and national stock numbers, Chapter 7 for local manufacture equipment, and Chapter 8 for equipment operation instructions as applicable.

3.2.14.6.2.1.2 Consumable materials: All consumable materials shall be listed by noun nomenclature and reference numbers. The reader shall be directed to Appendix D for part numbers, unit of issue, and national stock number information.

3.2.14.6.2.1.3 Manpower requirements: A break out shall be provided for each element and task required to be accomplished to prepare the aircraft and rig it for transport.

3.2.14.6.2.2 Disassembly: All tasks required for aircraft preparation shall be listed in the order of accomplishment. The appropriate chapter and paragraph of the maintenance manual shall be referenced for each task. Tasks that are transportability peculiar shall be completely described with drawings or diagrams as necessary.

3.2.14.6.2.3 Load plan: If components are required to be placed inside the aircraft to be transported, a scale diagram of the aircraft shall be provided showing component placement and security. Elevations and/or perspective drawings shall be included if required for clarification.

3.2.14.6.2.4 Rigging: Detailed instructions shall be included for installing rigging equipment on the aircraft to be transported. Drawings and/or diagrams shall be included as required for clarification. Drawing shall provide detailed information on sling dimensions and link count.

3.2.14.6.2.5 Hook Up: Detailed instructions shall be provided for hookup of the rigged aircraft to the helicopter transport. Provide personnel duties as well as specific safety precautions.

3.2.14.6.2.6 Assembly: Provide step by step instructions for removing rigging and assembly of helicopter. Provide detailed instructions for any required special inspections. Reference appropriate maintenance publications by chapter and paragraph for each task. Tasks that are transportability peculiar shall be completely described with drawings and/or diagrams provided as necessary.

3.2.14.7 Structurally damaged aircraft: Include the statement: "When structural damage causes doubt as to the successful use of the procedures in this chapter contact U.S. Army Aviation and Troop Command, 4300 Goodfellow Blvd., ATTN: AMSAT-I-SDP, St. Louis, MO 63120-1798, commercial telephone (314) 263-2372 or DSN

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

693-2372."

3.2.15 Appendix A, References: Appendix A shall list all references mentioned in or used with this manual.

3.2.16 Appendix B, Preservation/Depreservation Check Sheet: Appendix B shall contain a statement referring the reader to the appropriate paragraph in Chapter 1 for check sheet preparation and disposition instructions. Included in Appendix B shall be a preservation/depreservation check sheet each for cargo aircraft transport, vessel transport, truck transport, and external transport by helicopter. Each check sheet shall list all steps necessary to disassemble, preserve, assemble, depreserve, and prepare the aircraft for flight for the most rigorous type of preparation for each mode of shipment.

3.2.17 Appendix C, Weight and Balance Information for Transportability: Appendix C shall contain all weight and arm data required to compute weight and balance data for all types of transport by cargo aircraft.

3.2.18 Appendix D, Consumable Materials List: Appendix D shall alphabetically list all consumable materials used in disassembly, packaging, loading, tie down, unloading, depreservation, and assembly of aircraft for all types and modes of shipment. List will include noun nomenclature, national stock number, part number, specification number, source, unit of issue and quantity of issue. Provide a remarks section to include quantity required per aircraft and application. Provide stock numbers for quantities or units of issue available.

3.2.19 Appendix E, Special Tools and Equipment List: Appendix E shall alphabetically list all tools and equipment used in disassembly, preservation, loading, tie down, unloading, depreservation, and assembly of the aircraft for all types and modes of shipment. List shall include noun nomenclature, national stock number, part number, and line item number, as applicable. A remarks section will be included indicating the quantity required, if the item is local manufacture, if the item is part of a kit or set, and the level of support where the item is available (AVUM, AVIM, or Depot). If the item is part of a set or kit, the nomenclature, national stock number, and line item number of the kit will be included in the remarks section as either transportability peculiar ("TP") of multi-purpose ("MP"). Multi-purpose tools and equipment are those items used for both transportability and maintenance functions.

3.2.20 Appendix F, Quarantine Inspection/Customs Clearance: This Appendix shall outline procedures for preparing the aircraft and removed components for quarantine inspection, and their deprocessing at destination. Step by step procedures shall be included and in accordance with AR 40-12 and TM 5-632. Also included in this Appendix shall be procedures for customs clearance.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the current version before use.

3.2.21 Appendix G, Heat Shrink Film Protective Covering: Appendix G shall provide procedures to assist personnel in the installation of protective covering on the aircraft.

3.2.21.1 General: This paragraph shall provide general information on the use of heat shrink protective covering.

3.2.21.2 Safety: This paragraph shall identify required safety procedures for application of heat shrink film.

3.2.21.3 Helicopter preparation: This paragraph shall provide instructions for the preparation of the aircraft for the application of heat shrink film. Instructions for required padding shall also be included.

3.2.21.4 Application of film: This paragraph shall describe the characteristics of the film, the operation of the heat cannon, and the procedures for covering, fusing, shrinking and inspecting the covering.

3.2.21.5 Fuel and battery vents: This paragraph shall provide procedures to insure that fuel and battery vents are vented to atmosphere during shipment.

3.2.21.6 Installation of ventilators: Provide information on the requirements to vent the covering and instructions for the installation of ventilators.

3.2.21.7 Hoisting: Provide procedures for hoisting the aircraft with the shrink film covering installed.

3.2.21.8 Tie down points: Provide instructions for restraining the aircraft with shrink film covering installed.

3.2.21.9 Enroute maintenance: Provide instructions for enroute maintenance of the shrink film.

3.2.21.10 Removal of shrink film: Provide procedures for the removal of shrink film covering.

3.2.21.11 Resources: Tables shall be provided indicating the resources required for the heat shrink film process.

3.2.21.11.1 Tools and equipment: A table shall be provided indicating required tools and equipment and the item's reference number, noun nomenclature, national stock number, part number, and source. Tools and equipment shall also be listed in Appendix E.

3.2.21.11.2 Consumable materials: A table shall be provided listing required consumable materials. The list shall include the material's reference number, noun nomenclature, national stock number, part number, source, unit of issue, quantity of

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

issue, and quantity required per aircraft. Consumable materials shall also be directed to Chapter 6 for detailed information on preservation and packaging and Appendix G for aircraft protective covering.

3.2.21.11.3 Manpower: Provide an estimate of required man-hours and elapsed time for application and removal of heat shrink film.

3.2.21.12 Safety check sheet: A safety check sheet shall be developed for the application of heat shrink film. These requirements shall be included in the preservation/depreservation check sheets for truck and vessel shipment in Appendix B.

4. QUALITY ASSURANCE PROVISIONS:

The requirements of MIL-M-38784 are applicable.

4.1 General: During the course of preparation, the Government may review, at its option, the progress made on the manuscript at various stages of completion at the contractor's facility or a Government facility. The principle checks and reviews are Contractor Guidance Checks, Validation, Verification, and Final Acceptance Review.

4.1.1 Contractor guidance checks: At the convenience of the Government, the Government representative may perform periodic checks of text and illustrations at the contractor's facility. The contractor shall present the material for the checks upon request. All suggestions made by the Government representative shall be incorporated into the manuscript.

4.1.2 Validation: Validation requirements shall conform to paragraph 4.5.1 of MIL-M-63038. Government representatives may witness the contractor's validation effort thereby accomplishing certification. U.S. Army Aviation and Troop Command (AMSAT-I-SDP) is the Government technical representative for validation witness.

4.1.3 Verification: Verification requirements shall conform to paragraph 4.5.2 of MIL-M-63038. U.S. Army Aviation and Troop Command (AMSAT-I-SDP) is the Government technical representative authorized to certify verification. All procedures, to include external transport by helicopter, are subject to verification unless specifically excluded in contract documents.

4.1.3.1 Site: The verification shall be held at a site specified by the Government.

4.1.3.2 Contractor support:

4.1.3.2.1 Personnel: The contractor shall be required to have personnel in attendance technically qualified to make decisions.

4.1.3.2.2 Materials list: The contractor shall identify all

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

hardware, consumable materials, tools, and equipment required to perform a 100% verification of the manual. Required items shall be listed by part number and manufacturer.

4.1.4 Final acceptance review:

4.1.4.1 Acceptance: Final acceptance of all material delivered for publication will be made by the Contracting Officer's Representative (COR) at the U.S. Army Aviation and Troop Command, by returning a signed copy of the associated DD Form 250 to the Contractor. Acceptance will only be accomplished after technical verification by U.S. Army Aviation and Troop Command, ATTN: AMSAT-I-SDP.

4.1.4.2 Rework:

4.1.4.2.1 In the event that material is returned for rework as a result of final review at the U.S. Army Aviation and Troop Command, the rejection will be made within 30 days. The contractor shall correct all pages containing errors and furnish the corrected material within 20 days after receipt of notification of the change(s) required.

4.2 Acceptance and rework criteria:

4.2.1 Acceptance criteria: Acceptance of any source data requires that it be free of technical errors and that it be prepared in accordance with applicable specifications, regulations, and instructions cited herein.

4.2.2 Rework criteria: Errors of the following types will be cause for corrections.

4.2.2.1 Inconsistent writing style, level of writing, and extent of coverage.

4.2.2.2 Inconsistent terminology and nomenclature.

4.2.2.3 Improperly sized art and poor integration of art and text.

4.2.2.4 Inconsistent references, typographical errors, misspelled words, and defective type.

4.2.2.5 Incomplete information on procedures.

4.2.2.6 Improper use of or failure to use warnings, cautions, and notes where applicable.

4.2.2.7 Conflicting call outs and legends for illustrations and leader lines terminating incorrectly.

4.2.2.8 Failure to comply with the contents of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

4.2.2.9 Failure to make all corrections, including editorial corrections to a page.

4.2.2.10 Information or procedures inconsistent with current Army procedures or policy.

4.2.2.11 Incorrect information.

5. DELIVERY:

Preliminary Draft and Final Draft copies will be forwarded as specified below to Commander, U.S. Army Aviation and Troop Command, ATTN: AMSAT-I-MTA, 4300 Goodfellow Blvd., St. Louis, MO 63120-1798.

5.1 Preliminary draft: Five reproduced copies, with art work in place, will be forwarded 30 days prior to verification.

5.2 Final copy: One negative reproducible copy and 5 reproduced copies (reproduced from the negatives) shall be forwarded to U.S. Army Aviation and Troop Command (ATCOM) within 30 days after receipt of Government comments generated from verification. All source data furnished by the Government shall be returned with the final copy.

5.3 Review: The Government will review the final material and indicate acceptance or return for corrections within 30 days of receipt. In the event the data is returned for corrections, a maximum of twenty calendar days shall be allowed for the contractor to make the required corrections and return the final copy to U.S. Army Aviation and Troop Command (ATCOM) .

5.4 Preparation for delivery: The requirements of MIL-M-38784 are applicable.

6. NOTES:

6.1 Intended use: Aircraft Preparation for Shipment Technical Manuals prepared in accordance with the general style and format requirements of this specification are intended for use in the shipment of aircraft that are in military service by all modes of transportation.

6.2 Ordering data: The provisions of MIL-M-38784 apply.

6.3 Definitions: The definitions provided in MIL-M-38784 apply.

6.4 Subject term (key word) listing.

AVIM
AVUM
Depreservation
Ground handling

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

Hoisting
Language style
Logistical movement
Marking
Preservation
Rigging
Safety
Towing
Transport
Wing Walker

6.5 Identification of changes: The changes in this specification are extensive; therefore, the changes have not been marked. Bidders and contractors are cautioned to evaluate the requirements of this specification based on the entire contents.

6.6 Additional information: Additional information and guidance may be obtained by contacting the Commander, U.S. Army Aviation and Troop Command, ATTN: AMSAT-I-MTA, other information may be obtained from the Standardization Branch, ATTN: AMSAT-R-EDS, 4300 Goodfellow Blvd., St. Louis, MO 63120-1798.

Custodians:

Army-AV

Preparing Activity

Army-AV

PROJECT NUMBER TMSS-A293

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-M-63005C(AV)	93/12/09

3. DOCUMENT TITLE
Manuals, Technical: Preparation for Shipment of Army Aircraft

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
US Army Aviation and Troop Command	(1) Commercial (314) 263-1613	(2) AUTOVON 693-1613
c. ADDRESS (Include Zip Code) ATTN: AMSAT-R-EDS 4300 Goodfellow Blvd. St. Louis MO 63120-1798	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 *Previous editions are obsolete.* 198-290

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T04:24Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.