NOT MEASUREMENT SENSITIVE

MIL-T-62674(AT)
10 May 1991

MILITARY SPECIFICATION

TRUCK, LIVING QUARTERS: SELF-CONTAINED, FORWARD CONTROL, DIESEL OR GASOLINE DRIVEN, 14,500 TO 16,500 POUNDS GVW, 4X2, COMMERCIAL

This specification is approved for use by the US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers a self-contained, mobile unit designed for use as a combination office and living-quarters. The vehicle is intended for use both on improved roads and for off road conditions. The vehicle shall be diesel or gasoline engine driven, with a four wheel, two rear wheel drive, forward control chassis having a minimum gross vehicle weight (GVW) of 14,500 to 16,500 pounds. If the overall length warrants, use of a rear tag axle is permissible. Vehicles procured under this specification are commercial items which shall be warranted by the manufacturer as specified in acquisition documents.

1.2 Classification. The vehicle class shall be determined by minimum overall length and minimum gross vehicle weight (GVW) rating as specified in table I (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-UED, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC-2320

DISTRIBUTION STATEMENT A. Approved for public use; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the current version before use.

Table I. Vehicle class.

Class	Overall Length	GVW
30	30 feet	14,500
33	33 feet	14,500
36	36 feet	16,500

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS
FEDERAL
A-A-393 - Extinguisher, Fire, Dry-Chemical (Hand Portable).
W-B-131 - Battery, Storage: Vehicular, Ignition, Lighting and Starting.
VV-F-800 - Fuel Oil, Diesel

MILITARY
MIL-T-5624 - Turbine Fuel, Aviation, Grades JP-4 and JP-5.
MIL-T-83133 - Turbine Fuel, Aviation, Kerosene Type, Grade JP-8.

STANDARDS
FEDERAL
FED-STD-297 - Rustproofing of Commercial (Nontactical) Vehicles.

MILITARY
MIL-STD-1223 - Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking and Data Plates Standards.

(Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from the Naval Publications and Forms Center, Military Specifications and Standards, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DEPARTMENT OF DEFENSE
Department of Defense Index of Specifications and Standards (DODISS).

(Copies of the DODISS are available on a yearly subscription basis either from the Government Printing Office for hard copy, or microfiche copies are available from the Director, Navy Publication and Printing Service Office, 700 Robbins Avenue, Philadelphia, PA 19111-5093).

DEPARTMENT OF TRANSPORTATION (DOT)
Federal Motor Carrier Safety Regulations.
Federal Motor Vehicle Safety Standards.

(Application for copies of DOT publications should reference the Code of Federal Regulations, 49 CFR, and the Federal Register, and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)
Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines.
Noise Emission Standards for Transportation Equipment - Medium and Heavy Trucks.

(Application for copies of EPA publications should reference the Code of Federal Regulations, 40 CFR, and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

THE EUROPEAN TYRE AND RIM TECHNICAL ORGANISATION (ETRTO)
Standards Manual

(Application for copies of the ETRTO publications should be addressed to the European Tyre and Rim Technical Organisation, 32, Avenue Brugmann, 1060 Brussels, Belgium.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)
NFPA No. 70 - National Electric Code.

(Application for copies of NFPA publications should be addressed to the National Fire Protection Association, Batterymarch Park, Quincy, MA 02269.)

SAE, INC.
SAE Standards and Recommended Practices

J350	- Spark Arrester Test Procedure for Medium Size Engines (DoD adopted).
J537	- Storage Batteries.
J551	- Performance Levels and Methods of Measurement of Electromagnetic Radiation from Vehicles and Devices (30-1000 MHz).
J588	- Turn Signal Lamps.
J589	- Turn Signal Switch.
J682	- Rear Wheel Splash and Stone Throw Protection (DoD adopted)
J688	- Truck Ability Prediction Procedure. (DoD adopted).
J1349	- Engine Power Test Code - Spark Ignition and Diesel.

(Application for copies of SAE publications should be addressed to SAE, INC., 400 Commonwealth Drive, Warrendale, PA 15096.)

THE TIRE AND RIM ASSOCIATION, INC.
Year Book.

(Application for copies of Tire and Rim Association publications should be addressed to The Tire and Rim Association, Inc., 175 Montrose West Ave., Copley, OH 44321.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Standard vehicle and accessories. Except as specified in 3.1.1 through 3.1.1.10, the vehicle, components, assemblies, and accessories to be delivered under the contract shall be standard or optional items, which meet

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

or exceed the requirements of this specification. Except as specified in 3.1.1 through 3.1.1.10, no removal, substitution or alteration of the chassis manufacturer's standard or optional chassis model components shall be made. All chassis items shall be as represented in the chassis manufacturer's technical data book. Special bodies or mounted equipment shall be as represented in the body and equipment manufacturer's technical data. Technical data shall be limited to specifications and technical material, identical to that furnished to the authorized company representatives for selection of vehicle models and components, and shall be available to the engineering offices of the procuring activity, prior to delivery of the items. The chassis model furnished shall be not older than the chassis manufacturer's current model on the date of invitation for bids.

3.1.1 Special requirements. In addition to the standard vehicle and components specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

3.1.1.1 Treatment and painting. The vehicle shall be treated and painted in accordance with MIL-STD-1223. As specified by the procuring activity for the appropriate military service (see 6.2), the exterior color shall be in accordance with MIL-STD-1223. When specified (see 6.2), color selection will be made after contract award from standard color charts to be supplied by the manufacturer.

3.1.1.2 Markings and data plates. As specified by the procuring activity for the appropriate military service (see 6.2), identification marking and data plates shall be in accordance with MIL-STD-1223. When specified (see 6.2), concealed markings shall be furnished.

3.1.1.3 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with FED-STD-297.

3.1.1.4 Drain plugs. Drain plugs installed in rear axles shall be of the permanent magnet type.

3.1.1.5 Wood treatment. As specified herein, wood shall be treated in accordance with MIL-STD-1223.

3.1.1.6 Towing devices. Towing devices consisting of two hooks, loops, eyes or pins or the chassis manufacturer's standard single center mounted eye or pin shall be mounted on the front of the vehicle. When specified (see 6.2), in addition, towing devices shall be mounted on the rear of the vehicle. All towing devices shall be frame rail mounted or reinforced back to each frame rail.

3.1.1.7 Wheel splash and stone throw protection. Rear end mud flaps shall be provided. A metal strip not less than 0.125 inch thick and not less than 1 inch wide, extending the entire width of the mud flap, shall

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

be installed to prevent the bolt heads or bolt nuts from damaging the mud flap. As an alternate method of attaching the mud flaps, tabs or clips with minimum surface contact dimensions of 1 inch high by 1.250 inch wide by 0.094 inch thick shall be furnished at each bolt. Mud flap installations shall conform to the rear wheel splash and stone throw protection provisions of SAE J682.

3.1.1.8 Spark Arrester. The vehicle shall be furnished with an exhaust system spark arrester, except when the vehicle is equipped with a turbocharged engine. The spark arrester shall have an 80 percent arresting efficiency when rated in accordance with SAE J350.

3.1.1.9 Blackout curtains. When specified (see 6.2), blackout curtains or screens shall be provided to allow operation, during blackout conditions, of all the interior domelights and fluorescent lights to the rear of the driver's seat. Full height transverse blackout screens or curtains shall be provided to cover the full width of the interior at the rear of the driver's seat. Blackout curtains or screens shall be provided for all exterior windows to the rear of the driver's seat.

3.1.1.10 Brake lights. At least one pair of brake lights shall override the four-way emergency flasher or the two systems shall be independent of each other. Modifications to the manufacturer's standard product to accommodate this requirement shall not compromise conformance to any Federal Motor Carrier Safety Regulation referenced herein or to any Federal Motor Vehicle Safety Standard. If additional lights are added to the vehicle, the lights shall be selected from the chassis manufacturer's standard matching hardware.

3.2 General design.

3.2.1 Federal Motor Vehicle Safety Standards. The vehicle and furnished accessories shall comply with all Federal Motor Vehicle Safety Standards in effect on the date of manufacture.

3.2.2 Air pollution control. The vehicle shall comply with EPA Regulations governing Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines in effect on the date of manufacture. In addition, vehicles destined for California shall comply with State of California regulations governing air pollution control in effect on the date of manufacture.

3.2.3 Sound level. The cab interior sound level shall not exceed 84 db(A) when measured in accordance with Federal Motor Carrier Safety Regulation 393.94. The vehicle exterior sound level shall conform to EPA Noise Emission Standards for Transportation Equipment, Medium and Heavy Trucks.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

3.2.4 Curb weight. The curb weight shall include the weight of the chassis and body, with all attachments, accessories, and equipment; and a full complement of fuel, lubricants and coolant.

3.2.5 Gross vehicle weight. Gross vehicle weight (GVW) shall consist of curb weight, operator and passenger weight (computed at 175 pounds each), and a payload evenly distributed in the body area to provide not less than the specified GVW.

3.2.6 Weight distribution. The distribution of the GVW for the purpose of establishing suspension, axle and tire capacity shall be determined with the payload uniformly distributed over the payload area.

3.2.7 Wheelbase. The wheelbase shall be not less than 178 inches, measured between the centerlines of the front and rear axles. The wheelbase shall not be measured from the tag axle, if provided, nor from the centerline between the tag axle and the rear axle. The wheelbase shall be compatible with the body model furnished.

3.2.8 Ratings. Vehicle ratings shall be the manufacturer's published ratings. Component and vehicular ratings shall not be raised to meet the requirements of this specification. When published ratings are not available, verification of ratings shall be available to the engineering office of the procuring activity.

3.2.9 Overall width. The overall width of the vehicle, exclusive of tires and safety related items such as mirrors, lights and reflectors, shall be not more than 96 inches. The width over the tires shall be not more than 100 inches.

3.2.10 Strength. Materials, fabrication, and attachment of all vehicle equipment and furnishings shall be adequate to withstand working stresses including dynamic loads encountered in mobile operations and all normal usage.

3.2.11 Accessibility. The design of the vehicle and optional equipment shall permit access for routine servicing and shall permit access for replacement and adjustment of component parts and accessories with minimal disturbance of other components and systems.

3.2.12 Asbestos. Asbestos materials shall not be used in any form in any part of the vehicle.

3.3 Performance.

3.3.1 Speeds. High and low speed requirements shall be met with the truck loaded to specified GVW.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

3.3.1.1 High speed gradeability. The vehicle shall ascend a continuous 2.5 percent grade at 50 miles per hour (mph). Gradeability requirements shall be met with the main transmission in direct drive. Gradeability shall be verified with calculations in accordance with SAE J688 (see 6.3).

3.3.1.2 Maximum geared speed. The maximum geared speed at engine governed speed shall be not less than 58 mph. Conformance to geared speed specified shall be determined by calculating in accordance with the following formula:

$$\text{Maximum geared speed (mph)} = \frac{\text{Governed speed (rpm)}}{\text{Total gear reduction x tire factor (see 6.3).}}$$

3.3.2 Service brakes. The service brakes shall control and hold the vehicle, when loaded to its specified GVW, on a 30 percent grade. The service brakes shall stop the vehicle, loaded to specified GVW, within the stopping distance requirements of Federal Motor Carrier Safety Regulation 393.52.

3.4 Chassis components.

3.4.1 Engine. The engine furnished for the specified vehicle class shall be the chassis manufacturer's standard or optional engine for the commercial model truck which meets or exceeds the requirements of this specification.

3.4.1.1 Diesel engine. Unless otherwise specified (see 3.4.1.2), the vehicle shall be equipped with a liquid cooled, compression ignition, two-stroke or four-stroke cycle diesel engine, with not less than four cylinders. Engine net horsepower used in performance prediction calculations shall be determined in accordance with SAE J1349. The engine shall demonstrate the performance characteristics specified herein when using diesel fuel conforming to VV-F-800. In addition, when specified (see 6.2), the engine shall operate satisfactorily on grade JP-4 and grade JP-5 fuel conforming to MIL-T-5624 under emergency, short duration conditions and on grade JP-8 fuel conforming to MIL-T-83133 under normal conditions. A power loss when operating on JP-4, JP-5 or JP-8 is acceptable.

3.4.1.2 Gasoline engine. When specified (see 6.2), the vehicle shall be equipped with a liquid cooled, internal combustion, four-stroke cycle gasoline engine with not less than six cylinders. The engine furnished shall produce the required vehicle performance when operated on unleaded fuel with a research octane rating of 91, at an engine speed not more than the manufacturer's recommended operating speed. The engine shall be capable of warranted operation on unleaded fuel, when used in accordance with the operator's manual. Engine net horsepower used in performance prediction calculations shall be determined in accordance with SAE J1349. Unless otherwise required by foreign laws, vehicles for overseas use shall be capable of accepting and operating on leaded gasoline.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the current version before use.

3.4.1.3 Oil filter. A full flow or combination full flow and bypass oil filter with replacement element shall be furnished.

3.4.1.4 Governor. An engine governor shall be furnished and set and sealed to limit the engine to the engine manufacturer's maximum recommended operating speed.

3.4.1.5 Cooling system. The cooling system shall maintain the engine coolant at a temperature below the boiling point with the vehicle loaded to GVW and operated at an altitude of 10,000 feet above sea level or in an ambient air temperature of not less than 125 degrees Fahrenheit (°F). The coolant system shall include a surge tank or a coolant recovery reservoir of not less than two-quart capacity.

3.4.1.6 Coolant temperature control. Thermostatic control of engine coolant temperature shall be provided. On diesel engine driven vehicles, the control shall include complete thermostatic control of all coolant flow through the radiator.

3.4.1.7 Fan clutch. A fan clutch shall be provided. The fan clutch shall reduce the fan speed automatically when the fan is not required for engine cooling. The fan clutch shall be asbestos free.

3.4.1.8 Silicone rubber hoses. When specified (see 6.2), silicone rubber radiator and heater hoses shall be furnished.

3.4.1.9 Power plant heaters and fuel warmer. When specified (see 6.2), a coolant heater, an engine oil heater, and a fuel warmer (diesel engine driven vehicles only) shall be provided. Unless otherwise specified (see 6.2), a battery heater shall be provided when power plant heaters are specified. Heaters shall operate on 110 volts alternating current (ac), and shall be wired through a junction block, including a fuse or circuit breaker, to a single three-pronged (male), weatherproof, slave receptacle for receiving external power and grounding the vehicle. A three-wire connecting cable, 25 feet long and of adequate line capacity to supply power for all heater units simultaneously, shall be furnished. Connecting cable shall include a matching female connector at the vehicle end and a standard, three-pronged (two power plus one ground) male connector at the other end. Electrical apparatus shall conform to Federal Motor Carrier Safety Regulation 393.77(c)(7). The electrical insulation of the connecting cable shall withstand normal operating stresses in low ambient air temperatures (down to minus 60°F) without cracking or loss of dielectric capacity. All heater lead wires shall be installed without interfering with vehicle component operation and without loose excess wire. Provisions for stowage of the cable shall be provided in the vehicle cab. Heaters shall be furnished as follows:

(a) A coolant heater, 1,000-watt minimum rating, shall be installed in the engine block or in the lower coolant inlet hose. An engine thermostat with an operating range of 170°F to 195°F shall be installed.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

(b) An oil pan heater of the permanent external surface mount, permanent in-pan mount, or immersion type that meets the following requirements, shall be installed:
  (1) Not less than 22 watts per quart heating capacity
  (2) Not more than 18 watts per square inch heating capacity
  (3) Thermal balance design or thermostat control providing for uninterrupted operation
  (4) Provision for mounting below minimum service oil level.

(c) The battery heater shall have a capacity adequate to maintain the battery electrolyte at a temperature of not less than 10°F during vehicle exposure in ambient air temperature as low as minus 60°F, and shall embody a thermostat to limit the temperature of the electrolyte to not more than 80°F.

(d) A fuel warmer or pre-heater shall be provided on diesel engine driven vehicles to prevent clogging of fuel filters due to wax crystallization in the fuel. The fuel warmer shall use engine coolant to transfer sufficient heat to the diesel fuel to heat it from an inlet temperature of minus 40°F to an outlet temperature of plus 9°F, with a fuel flow rate not less than the maximum fuel demand of the engine fuel system. A coolant shutoff valve shall be provided for the coolant inlet side of the fuel warmer unit.

3.4.1.10 Fuel fired engine preheater. When specified (see 6.2), for diesel engine driven vehicles, a diesel fuel fired engine coolant heater shall be furnished to preheat the engine. The heater shall include a timer, a thermostat and a circulating pump and shall be connected to the engine coolant system. The heater shall be capable of starting and operating at minus 60°F and shall heat the engine to plus 40°F from minus 60°F in not more than 1 hour. The system shall be equipped with a light, visible to the driver, to indicate that the preheater is operating.

3.4.2 Electrical system. The electrical system shall be in accordance with Federal Motor Carrier Safety Regulations 393.27 through 393.31 and 393.33.

3.4.2.1 Starting system. For diesel engine driven vehicles, a 12- or 24-volt direct current (dc) starting system, with a 12-volt dc lighting system shall be furnished. Engine starting equipment shall include an ether starting system, glow plug or electric grid heater. If an ether system is furnished in lieu of a glow plug or grid heater, it shall be of the measured shot type. The measured shot type ether system shall be key operated or manually operated from the driver's compartment and shall be inoperative with the engine warm. Complete provisions for a replaceable ether reservoir of not less than 12 fluid ounces shall be furnished. A reservoir need not be furnished.

3.4.2.2 Ignition system. For gasoline engine driven vehicles, a 12-volt dc ignition system shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:24Z
Check the source to verify that this is the current version before use.

3.4.2.3 Alternator. Unless otherwise specified (see 6.2) on diesel engine driven vehicles, a minimum 85-ampere alternator shall be furnished. The alternator output with the engine at engine idle speed shall be not less than 45 amperes. Unless otherwise specified (see 6.2) on gasoline engine driven vehicles, an alternator of not less than 100 amperes rated capacity, and which provides not less than 45 amperes dc output at normal engine idle speed, shall be furnished.

3.4.2.4 Lighting. All vehicle lights, reflectors, and wiring shall be as specified herein and shall conform to Federal Motor Carrier Safety Regulations 393.12, 393.13, 393.19, 393.20 and 393.22 through 393.26(d). Positioning and guarding shall permit normal replacement of the bulbs and lenses. Lights and reflectors shall not be mounted on vertical surface of rub rails (unless recessed and fully protected) or mounted on vehicle bumpers.

3.4.2.5 Turn signals. Turn signal lamps shall conform to SAE J588. Operating units shall conform to SAE J589, class A, and shall be mounted on the steering column. Turn signal units shall be installed in accordance with SAE J588. Turn signal operating units shall be self-cancelling type with a visible and audible type flash indicator.

3.4.2.6 Batteries. Each battery shall be of 12-volt potential. The total reserve capacity ratings and the total cold cranking ratings at 0°F, both measured in accordance with SAE J537, shall be not less than specified in table II. The batteries shall be of the maintenance free type having the maintenance-free characteristics listed in W-B-131.

Table II. Batteries

Engine Type	Reserve Capacity (Minutes)	Cold Cranking (Amperes)
Diesel	320	1200
Gasoline	100	450

3.4.2.7 Radio interference suppression. The vehicle shall be suppressed to limit electromagnetic radiation in accordance with SAE J551. Any body equipment emitting electromagnetic radiation shall be suppressed to the same level as the vehicle chassis.

3.4.3 Fuel system. The fuel system shall conform to Federal Motor Carrier Safety Regulations 393.65 and 393.67.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

3.4.3.1 Air cleaner. An air cleaner shall be furnished.

3.4.3.2 Fuel tank(s). Fuel tank(s) shall be of not less than 50 gallons total capacity (43 gallons for vehicles destined for California). When more than one tank is furnished on diesel engine driven vehicles, means shall be provided to assure an equalized fuel level in both tanks. When more than one tank is furnished on gasoline engine driven vehicles, a selector valve, connecting either tank to the engine fuel intake, shall be provided and means shall be provided to monitor the fuel level of either tank from a single fuel gage; or an equalizing pump shall be used to maintain the same fuel level in both tanks.

3.4.3.3 Fuel and water separator. The manufacturer's standard or optional fuel filter shall be provided. When specified (see 6.2), a fuel and water separator shall be furnished. The separator shall include a water coalescer and a drain valve. When a separator is required, a combination filter/separator unit may be furnished.

3.4.4 Exhaust system. The vehicle exhaust system conforming to Federal Motor Carrier Safety Regulation 393.83 shall be substantially constructed, effectively leakproof, and quiet in operation. Properly supported tailpipe shall extend to the rear bumper and shall be located to properly and effectively minimize the possibility of exhaust fumes entering the body. The exhaust system shall include muffler(s).

3.4.5 Automatic transmission. The vehicle shall be provided with an automatic transmission. The transmission shall include a hydraulic torque converter and not less than three forward gear ratios. Normal driving range selector position shall provide not less than three gear ratios without movement of the selector. The input torque capacity of the transmission shall be at least equal to the maximum torque delivered by the engine.

3.4.6 Driveline components. Driveline components shall be adequate to transmit the maximum delivered torque of the engine, as developed through the maximum gear train reduction.

3.4.7 Frame. The chassis frame shall be the manufacturer's heavy duty frame for the model vehicle furnished. Frame members shall provide sufficient structural strength in the chassis frame through increased resisting bending moment, to at least equal the load imposed with the vehicle loaded to specified GVW. The vehicle frame shall be capable of withstanding conditions produced during off road travel at low speeds. Chassis frame rails shall not protrude beyond the rear end of the vehicle.

3.4.8 Suspension. The vehicle shall be equipped with a suspension system with components having a rated capacity at least equal to the load imposed on each member, measured at the ground, with the vehicle loaded to specified GVW. When suspension capacity is rated at the spring pads, unsprung weight shall be deducted. Vehicle shall be equipped with heavy duty

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

hydraulic, double-acting shock absorbers at the front wheels. The suspension system shall resist vibration, road noise, tip and roll of the body. When specified (see 6.2), variable rate springs and adjustable shock absorbers shall be provided.

3.4.8.1 Air type rear suspensions. When specified (see 6.2), an air suspension system shall be furnished on the rear axle. The suspension system shall have none of the spring weight carried on anything other than air springs. No other spring medium such as leaf, coil, or rubber springs shall be used in conjunction with the air springs. The air suspension system shall incorporate two track bars and two torque rods to control lateral and longitudinal movement. Track bars and torque rods shall transmit driving and braking forces to the chassis. Each end of the track bars and torque rods shall be equipped with rubber bushings that do not require periodic lubrication. The suspension system shall incorporate leveling valve(s) with time delay to avoid constant air consumption. The system shall be equipped with air pressure quick release valves with controls in the cab. A hydraulic double-acting shock absorber shall be provided near each of the air bags. The air suspension system shall include locking devices to lock up the suspension to prevent damage when lifting and towing the vehicle. The suspension shall be provided with a mechanism at each wheel to assure lifting of the wheel and axle when jacking the vehicle from the applicable jacking location.

3.4.9 Axles. Axle ratings shall be at least equal to the load imposed on each axle, measured at the ground, with the vehicle loaded to specified GVW. The gear ratio shall provide performance specified in 3.3.1 through 3.3.1.3. When specified (see 6.2), the wheel bearings and axle spindles shall be oil lubricated. The hubcaps, except for driving axles, shall have a window for visual determination of oil level. Provisions for venting or withstanding internal pressure buildup and for replenishing the oil supply shall be provided.

3.4.9.1 Traction control. When specified (see 6.2), the vehicle shall be furnished with a traction control on the rear axle. The traction control shall actuate automatically to ensure that power is transmitted to the wheel having traction when the opposite wheel loses traction. Maximum traction capabilities shall be maintained at all times under each drive wheel for the life of the vehicle.

3.4.10 Wheels, rims, tires and tubes. Unless wide base tires are specified, the vehicle shall be equipped with single front and dual rear wheels. Rims and tire ratings shall conform to Tire and Rim Association or European Tyre and Rim Technical Organisation recommendations for the type and size of tires furnished. Multi-piece rims shall not be furnished. Rims and disc wheel sizes shall be the same for all wheels on each vehicle. Tire size and load range (ply rating) shall be the same for all tires on each vehicle. When specified (see 6.2), wide base type tires and wheels for the front and

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:24Z
Check the source to verify that this is the currentversion before use.

rear axles shall be provided in lieu of conventional front and dual rear wheels and tires. Wide base wheels shall be interchangeable without the use of an adapter. When specified (see 6.2), disc type wheels shall be furnished.

3.4.10.1 Tires. Tires shall be of the tubeless type with all terrain tread. Unless otherwise specified, low profile or standard profile tires may be furnished. When specified (see 6.2), low profile tires shall be furnished. Tires shall be of the steel belted radial type or when specified (see 6.2), bias ply. Tires shall be of rated capacity at least equal to the load imposed on each tire, measured at each wheel, at the ground, with the vehicle loaded to specified GVW. Tires and tire size designation systems shall conform to the Tire and Rim Association or to the European Tyre and Rim Technical Organisation recommendations.

3.4.10.2 Carrier for spare tire assembly. Unless otherwise specified (see 6.2), a carrier for a spare wheel or rim and tire assembly shall be installed in a readily accessible location on the vehicle. Threaded fasteners, when used to secure the spare tire in the carrier, shall be constructed of or plated with corrosion-resistant material. The carrier design shall enable safe removal or mounting of a spare wheel assembly using only the tools specified in 3.4.16.1. The carrier shall enable the safe removal and installation of the spare tire assembly from and to the vehicle and carrier without personnel positioning themselves or any part of their body under the spare tire assembly.

3.4.10.3 Spare wheel or rim. When specified (see 6.2), a spare wheel or rim shall be furnished. When a spare wheel or rim or a spare tire assembly is furnished on a vehicle without a carrier, it shall be stowed securely on the vehicle for shipment. When a spare tire assembly is specified, a spare wheel or rim shall be furnished.

3.4.10.4 Spare tire assembly. When specified (see 6.2), a spare tire assembly shall be furnished. The spare tire assembly shall include an inflated spare tire mounted on the spare wheel or rim. The spare tire shall be of the same size, tread design and load range (ply rating) as the tires furnished on the front axle of the vehicle.

3.4.10.5 Tire chain clearance. Tire chain clearance in accordance with SAE J683 shall be provided. Allowance for spring deflection shall be included.

3.4.11 Brakes. Brakes shall conform to Federal Motor Carrier Safety Regulations 393.40 through 393.43 and 393.45 through 393.52. Brake linings shall be of nonasbestos material.

3.4.11.1 Power-hydraulic brakes. The vehicle shall be equipped with power assisted, hydraulically actuated, four-wheel service brakes.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

3.4.11.1.1 Split hydraulic brake system. The power-hydraulic brake system shall be so arranged as to provide separate systems for at least two wheels and so designed and constructed that rupture or leakage type failure of any single pressure component of the service brake system, except structural failures of the brake master cylinder body, effectiveness indicator body, or other housing common to the divided system, will not result in complete loss of function of the vehicle brakes when force on the brake pedal is continued. "Pressure component" means any internal component of the brake master cylinder or master control unit, wheel brake cylinder, brake line, brake hose, or equivalent, except power assist components.

3.4.11.1.2 Indicator light. The split hydraulic brake system shall be equipped with an electrically operated red light mounted on the instrument panel to indicate system effectiveness. The light shall have an area of not less than 0.196 square inch. It shall illuminate before or upon application of the brakes when an actuating-pressure component of the system has sustained a loss of pressure. The indicator light system shall include a means for testing by the vehicle operator to assure that the light bulb is operable.

3.4.12 Parking brake. A manually operated parking brake shall be provided. The parking brake shall be capable of actuating the vehicle rear brakes. The hand control shall be located in an accessible location for the driver. The hand control shall be capable of manual adjustment.

3.4.13 Steering. Power steering shall be furnished.

3.4.14 Windshield wipers and washers. The vehicle shall be equipped with dual windshield wipers and windshield washers. Windshield wipers shall be the multispeed type and operated by electric motor(s).

3.4.15 Bumper. Unless the bumper is an integral part of the vehicle cab, a full width channel type front bumper shall be provided.

3.4.15.1 Rear end protection. The rear end of the vehicle shall be protected in accordance with Federal Motor Carrier Safety Regulations 393.86. A rear bumper shall be provided.

3.4.16 Tool stowage. Stowage space of sufficient size to accommodate a vehicle jack, hand tools, anti-skid chains and emergency reflective triangles shall be furnished. The stowage space shall provide for positive retainment of this equipment during vehicle operation. Stowage space for these tools shall be in a weatherproof location with a means of locking.

3.4.16.1 Tools. When specified (see 6.2), each vehicle shall be furnished with tools required for exchanging a mounted tire assembly with the spare assembly, and shall include at least a jack, jack handle and wheelnut wrench. The jack shall be of such closed height as to permit its location under an axle, or other satisfactory lift point, at any wheel with the tire

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:24Z
Check the source to verify that this is the currentversion before use.

flat. The jack, without blocking, shall be capable of raising any wheel of the loaded vehicle to a height adequate to permit removal and replacement of wheel and tire assembly.

3.4.17 Heater and defroster. A hot water heater shall be provided. The heater shall have fresh air intakes. Discharge outlets shall be provided to direct heated air to the floor and to defroster louvers. The heater shall be complete with blower and mounted controls convenient to the driver.

3.4.18 Ventilator. Ventilator(s), of the static type, capable of providing an adequate supply of fresh air and of properly ejecting foul air under all conditions of operation shall be provided. Vent openings shall be provided with a weather-proof cover with means for opening and closing the cover from inside the vehicle. Outside openings for heaters and ventilators shall be so located as to minimize entry of fumes, rain, road dust, and road wash.

3.4.19 Air conditioning. When specified (see 6.2), in addition to the requirements of 3.5.9, the vehicle shall be equipped with the manufacturer's standard automotive air conditioning system, including tinted windshield and tinted glass.

3.4.20 Engine compartment cover. An engine compartment insulated cover, providing access for engine and component maintenance, shall be provided. The engine compartment access cover shall be air tight and shall be heavily insulated for soundproofing.

3.4.21 Controls and operating mechanisms. All controls and operating mechanisms shall be located for left hand drive. Controls shall be complete and conveniently operable by the driver. Lever controls shall be designed and located to permit easy entrance and exit of the operator to and from the driver's compartment. Instruments and controls shall be identified as to their function and installed in a manner to facilitate removal and servicing. Instruments shall be visible to the driver when seated in the driving position.

3.4.22 Accessories and equipment. Chassis equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. The following minimum equipment shall be furnished:

(a) Key-operated ignition switch
(b) Ammeter, charging indicator or voltmeter
(c) Fuel gage
(d) Oil pressure gage or red indicator warning light
(e) Engine coolant temperature gage or high coolant temperature or low coolant level red indicator warning light
(f) High coolant temperature or low coolant level alarm buzzer
(g) Speedometer with recording odometer

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:24Z
Check the source to verify that this is the current version before use.

(h) Ash receptacle
(i) Dual sunvisors
(j) Map reading lamp, shaded
(k) Driver's compartment ventilator other than window
(l) Tachometer (for diesel engine driven vehicles).

3.4.23 Rearview mirrors. Outside rearview mirrors shall be mounted on each side of the cab. The mirrors shall be of the combination type having flat and convex areas. The flat portion shall have not less than 50 square inches of reflective area. The convex portion shall have not less than 25 square inches of reflective area and a radius of curvature of not less than 20 inches. The mirrors shall have not less than two supporting arms.

3.4.24 Horn. The manufacturer's standard electric horn shall be furnished.

3.4.25 Engine hour meter. When specified (see 6.2) an engine hour meter shall be furnished. The meter shall have a totalizing mechanism of not less than 9,999 hours for the chassis engine to register accurately the number of hours of operating time. The meter shall be of rugged construction to ensure continuous trouble-free performance under severe operating conditions. The engine hour meter shall be mounted on the cab instrument panel or in the engine compartment in a readable location.

3.4.26 Insect screen. When specified (see 6.2), an insect screen shall be provided on the front of the radiator. The screen shall be corrosion-resistant.

3.4.27 AM/FM radio. When specified (see 6.2), the manufacturer's standard AM/FM radio shall be provided.

3.5 Body. The body shall be mounted on a forward control chassis and shall have an integral driver's compartment and enclosed body. Upholstered bucket type driver's and passenger's seats with pedestals shall be furnished. The seats shall be adjustable fore and aft. The pedestals shall be provided with a positive locking mechanism to secure the seats in place. The body mounting shall be in accordance with the latest edition of the chassis manufacturer's body builders layout. The body furnished shall be the manufacturer's low profile design. A model with the vehicle body raised off the chassis frame rails for increased storage, commonly called a basement floor model, shall not be furnished.

3.5.1 Body dimensions. The vehicle body exterior and interior dimensions shall be as follows:

(a) Overall height shall be not more than 124 inches.
(b) Interior height shall be not less than 77 inches.
(c) Overall length shall be not less than 30 feet for class 30 vehicles, 33 feet for class 33 vehicles, and 36 feet for class 36 vehicles.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the current version before use.

3.5.2 Construction. The vehicle shall be manufactured in accordance with the highest standards of the industry. The body shall be custom built as specified, providing mobile combination field office and living quarters. The body design shall effectively exclude engine fumes and exhaust gases from the interior and shall provide safe and comfortable transportation for the passengers and the driver. The vehicle body shall provide a comfortable environment for working personnel for extended periods. The body structure shall be capable of resisting all generally and locally applied loads resulting from normal intended usage including low speed cross country travel, without excessive deflection, cracking, permanent deformation, loosening of joints, or premature fatigue failure. Where aluminum and steel surfaces come into contact, effective means shall be provided to prevent electrolytic action. All equipment and furnishings shall be secured to withstand mobile vehicle operations.

3.5.2.1 Structural framing. The body wall, floor and roof shall either be of semi-monoque construction, or the framing shall be 1-1/2 inch aluminum extrusions of nominal 0.125 inch thickness or not less than 1-1/2 inches square tubular aluminum or not less than 1-1/4 inches square tubular high tensile steel. Corners, window frames and door frames shall be reinforced and gusseted to prevent structural distortion. Wood shall not be used for any primary structural framing.

3.5.2.2 Structural floor framing. Floor crossmembers shall be adequately sized to support the body and payload without fracture or failure under all combinations of expected loading and shall conform to Federal Motor Carrier Safety Regulation 393.84. Additional crossmembers shall be provided, if required to support floor loads in critical stress areas.

3.5.2.3 Exterior wall material. The exterior wall skin material shall be either fiberglass or aluminum sheet of sufficient thickness to prevent permanent deformation or buckling. The exterior skin shall be properly attached to the body frame and shall be constructed in a manner to insure rainproof tightness. The exterior skin shall be free of surface roughness or buckling.

3.5.2.4 Roof. The roof shall be of one-piece construction with a rise at the center for efficient drainage. The roof shall be properly braced to prevent permanent deformation or buckling, and shall provide a fully weather-tight interior. The roof skin shall be either aluminum, fiberglass or a rubber-based material.

3.5.2.5 Floor. The floor shall be insulated and shall be sufficiently strong to support the imposed loads under all loading conditions. Galvanized steel, aluminum, fiberglass or other suitable material shall be installed on the underside of the body to fully enclose the floor area. Wood or plywood shall not be exposed to the environment. A sound deadening and vibration damping material shall be applied to the underside of the floor panels exposed to the road environment. The floor covering shall be the manufacturer's standard product.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

3.5.2.6 Interior panels. The interior of the body, sides, rear and ceiling shall be the manufacturer's standard product. The interior panels shall be dent resistant and properly fastened to the body frame and shall be sufficiently strong to prevent deformation or buckling. Pressed wood shall not be utilized.

3.5.2.7 Insulation. The interior of the body sides, front, rear and ceiling shall be insulated with a fire retardant material. The insulation shall be installed in such a manner to prevent sag or settling under all operating conditions. The insulation shall not promote the growth of fungus nor cause corrosion of steel or aluminum. The insulation shall be of sufficient thickness to meet the sound and temperature requirements specified herein.

3.5.3 Windows and doors. In addition to a driver's side door, a curbside door shall be provided behind the drivers compartment. A minimum of seven windows shall be provided. The windows shall be located in appropriate locations along the sides and at the rear of the vehicle body. The windows and doors shall be the manufacturer's standard product and shall be rattleproof and provided with fingertip control permitting easy opening and adjustment to various desired positions. When closed, the doors and windows shall be rainproof, waterproof and windproof. All windows shall be equipped with curtains of appropriate color to complement the interior decor.

3.5.3.1 Windshield. A windshield affording maximum practicable driver vision shall be installed at a slope sufficient to minimize external glare or reflections from inside the body. All exterior glass shall be tinted, heat absorbing safety glass.

3.5.4 Layout. The layout of the vehicle shall be the closest possible to the manufacturer's standard product, encompassing a minimum of modifications as necessary to accomodate an office area. The vehicle shall have, as a minimum, a combined living and office area, a galley, a bath area and a bedroom. Class 36 vehicles shall also have a dinette area. The general layout of the vehicle shall be with the combined living and office area forward, the galley central, and the bath area and bedroom aft. The vehicle shall have overhead cabinets along the length of the vehicle for storage. The furnishings shall be the manufacturer's standard product.

3.5.4.1 Living/office area. The vehicle shall be equipped with a sofa, an upholstered chair and a minimum 42 inches by 24 inches desk. The sofa shall be convertible to a bed. The desk shall be sturdy and shall not interfere with the conversion of the sofa to a bed or with any other furnishings. The chair shall swivel 360 degrees and shall be adjustable fore and aft. A minimum two-drawer filing cabinet shall be provided. All furnishings shall be properly attached to the vehicle.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:24Z
Check the source to verify that this is the currentversion before use.

3.5.4.2 Galley. The galley shall have a counter with a double stainless steel sink plumbed for hot and cold water. A refrigerator capable of operation on liquid propane gas (LPG) and 120 volts alternating current (ac) shall be provided. A minimum three burner stove with oven and a cover shall be provided. A microwave oven shall be provided. The galley shall have drawers, and under counter and overhead cabinets for storage. Class 36 vehicles shall also have a dinette area with seating for four people. The dinette shall convert to a bed.

3.5.4.3 Bath area. The bath area shall have a lavatory and a shower or tub. The lavatory shall contain a toilet, a sink with hot and cold faucets, and a medicine chest with mirrors. Cabinets for storage shall be provided. The tub or shower may be separate from the lavatory and shall be plumbed for hot and cold water.

3.5.4.4 Bedroom. The bedroom shall have a minimum double bed. The bedroom shall have a wardrobe or a closet as well as overhead cabinets for storage.

3.5.5 Electrical system. The electrical system shall be in accordance with NFPA No. 70, National Electrical Code, (NEC). The vehicle shall be wired to receive a minimum 50 ampere, 120 volt, 60 Hertz (Hz), ac, single phase power from an installed generator, or from a power source via a lead-in cable. A 25-foot cable of sufficient capacity to service all electrical requirements shall be furnished.

3.5.5.1 Wiring. All wiring shall be NEC standard plastic-jacketed, non-metallic sheathed cable with ground. Wiring shall be concealed yet easily accessible for repairs. Wiring and related devices shall be installed in a workmanlike manner, mechanically and electrically secure. Devices, lamps, and other equipment requiring periodic service shall be readily accessible and serviceable. Wiring shall be protected by grommets when passing through any hole or body framework. The wiring shall have sufficient capacity to support the required loads.

3.5.5.2 Distribution panel. A distribution panel for the electrical system shall be installed in a convenient location on the vehicle. The panel shall be rated at not less than 50 amperes. The panel shall receive 120 volt ac power from the generator or from a local power source. The panel shall also receive 12 volt dc power from the vehicle batteries. The panel shall be of adequate capacity to service all 120 volt ac and 12 volt dc requirements.

3.5.5.3 Power converter. An automatic power converter shall be provided. The power converter shall convert 120 volt ac power to 12 volt dc. The power converter shall be of adequate capacity to service all 12 volt dc requirements. The power converter shall be connected to the vehicle batteries for charging.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

3.5.5.4 Engine-generator. A 120 volt, 60Hz, single phase, ac power engine-generator shall be provided. The generator shall have a capacity of not less than 4 kilowatt (kW), and in addition, shall be adequate to meet all electrical requirements. The generator shall be operable from within the driver's compartment. The generator engine shall use the same fuel as the vehicle, and shall be supplied from the vehicle fuel tanks. Means shall be provided to assure the generator does not draw below 25 percent of the chassis fuel tank capacity.

3.5.5.4.1 Engine-generator compartment. The engine-generator compartment shall be located at the rear of the vehicle. The ceiling and back wall of the compartment shall be covered with fireproof material to prevent a generator fire from entering the vehicle. The compartment shall be designed to prevent noise and exhaust fumes from entering the vehicle. The compartment shall be vented for maximum exhaust and heat dissipation. The generator engine mounting shall minimize vibration.

3.5.5.5 Auxiliary batteries. In addition to the primary chassis starting system batteries, two 12-volt deep cycle batteries shall be furnished. The deep cycle batteries shall be the maintenance free type. Each battery shall have a total reserve capacity of not less than 115 minutes and a cold cranking capacity of not less than 375 amperes at 0°F.

3.5.5.6 Exterior lighting. When specified (see 6.2), spotlights, floodlights, or other specialized exterior lighting shall be furnished. The floodlights shall be removable for storage during transit. The floodlight installation shall be protected by ground fault interrupters.

3.5.5.7 Interior lighting. The manufacturer's standard interior lighting shall be provided. When specified (see 6.2), additional specialized lighting shall be furnished. Additional lighting shall be provided over the desk (see 3.5.4.1) to insure adequate illumination of the work area.

3.5.5.8 Back-up video camera system. When specified (see 6.2), the vehicle shall be furnished with a video camera system. The camera shall be mounted on the rear of the vehicle. A monitor shall be mounted on the dash. The system shall clearly show objects to the rear of the vehicle. The monitor shall have a grid screen indicating distance of objects and a day or night switch to adjust brightness for changing conditions for night driving. The system shall be activated whenever the transmission is in reverse gear.

3.5.5.9 Cellular telephone. When specified (see 6.2), a high quality cellular telephone shall be installed. The telephone equipment selected shall comply with all applicable Federal Communications Commission regulations.

3.5.5.10 Television sets. When specified (see 6.2), a built-in color television set (TV) shall be provided at the forward end of the vehicle. The set size shall be the manufacturer's standard, but shall be a

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

high-quality name brand type, not less than 12 inches in diagonal screen measurement. Remote control operation shall be furnished. When specified (see 6.2), a similar set shall be mounted in the rear of the vehicle in the bedroom.

3.5.5.11 Video cassette recorder (VCR). When specified, (see 6.2) a four-head VHS type video cassette recorder (VCR) shall be furnished and installed in close proximity to the television set. The same remote control unit shall operate both the TV and VCR. A holder shall be provided for the remote unit.

3.5.6 Plumbing. A plumbing system shall be installed. The plumbing system shall be designed to receive water from an installed fresh water tank. A pump to distribute the water shall be provided. The pump shall be capable of delivering water to all plumbing fixtures and devices in sufficient volume and pressure to enable them to function satisfactorily without undue noise, leakage, or loss of pressure. All water piping shall be subjected to adequate water and pressure tests to determine leakage or loss of pressure (see 4.4.6.4). The drain system shall be subjected to a leakage test (4.4.6.5).

3.5.6.1 Fresh water system. A minimum 50 gallon fresh water tank shall be installed within the underbody skirt compartment(s) and shall be readily accessible. The fresh water tank shall be protected from freezing during prolonged exposure to ambient temperatures of minus 20°F. A minimum 25 foot fresh water hose shall be provided. A minimum 6 gallon hot water tank shall be installed.

3.5.6.2 Waste water system. The plumbing system shall include a minimum 25 gallon grey water tank and a minimum 25 gallon black water tank. The grey water tank and black water tank shall be located within the underbody. Skirt compartments shall be readily accessible, and protected from freezing during prolonged exposure to ambient temperatures of minus 20°F. A minimum 15 foot, flexible sewer hose shall be provided. The sewer hose shall be a different diameter than the fresh water hose to prevent intermix.

3.5.7 Liquid petroleum gas tank. A minimum 80 pounds capacity liquid petroleum gas (LPG) tank shall be installed in the vehicle. The LPG tank shall be connected to the stove, furnace, refrigerator and hot water tank. A means of filling the LPG tank from the exterior of the vehicle shall be provided. A gas leak detection unit shall be provided.

3.5.8 Heating. A furnace rated at not less than 30,000 British thermal units (Btu's) per hour and with electric ignition shall be installed. Sufficient ducting shall be provided to insure a uniform temperature throughout the vehicle. The furnace shall be thermostatically controlled with the thermostat installed in a central location. The furnace shall be capable of maintaining an indoor temperature of 72°F during prolonged exposure to an ambient temperature of 0°F.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the current version before use.

3.5.9 Air conditioning. In addition to the automotive air conditioning, a minimum of two 13,500 Btu's per hour air conditioners shall be provided. The air conditioners shall be capable of maintaining an indoor temperature of 74°F under prolonged exposure to an ambient temperature of 100°F. All air shall pass through a filter system. Each unit shall be provided with a flexible tube installed to carry condensate run-off directly to the ground.

3.5.10 Accessories. The vehicle shall include all of the manufacturer's standard accessories. When specified (see 6.2), the vehicle shall also include any other special accessories, as required.

3.5.11 Fire extinguishers. A five-pound chemical type fire extinguisher conforming to Federal Motor Carrier Safety Regulation 393.95(a) shall be mounted in a convenient location near the curbside door. The fire extinguisher shall have an Underwriter's Laboratory rating of 2A:10B:C or more, shall include a metal safety pin and wire, and shall conform to type I, class 1, size 5 of A-A-393. Two 2-1/2 pound chemical type fire extinguishers shall be provided, one mounted in the generator compartment and one mounted in the driver's compartment. Each of these two fire extinguishers shall have an Underwriter's Laboratory rating of 5B:C or more, shall include a metal safety pin and wire and shall conform to type I, class 2, size 2-1/2 of A-A-393. All fire extinguishers shall permit visual determination of condition of charge.

3.5.12 Emergency reflective triangles. Three emergency reflective triangles conforming to Federal Motor Carrier Safety Regulation 393.95(f)(2)(i) shall be furnished and properly stowed.

3.5.13 Stabilizing jacks. Four electro-hydraulic stabilizing jacks with 12 inch pads shall be provided, one installed under each corner of the body. Each jack shall be rated at 25,000 pounds load capacity and shall be controlled from a central control panel in the body skirt. The jacks shall be capable of leveling and stabilizing the vehicle during stationary service.

3.5.13.1 Sight levels. Sight levels shall be provided at body rear and curbside to aid in leveling unit.

3.5.14 Underbody storage compartments. In addition to the spare wheel carrier compartment, the tool stowage compartment, and the water tanks compartment, all remaining available skirt space from the rear of the front wheels to the rear of the vehicle shall be used for additional storage compartments. Compartments shall be weatherproof and shall be accessible through a hinged door with holding device and flushmounted chrome lock or provision for padlocking. All compartment door locks furnished shall be operable with the same key.

3.6 Servicing and adjusting. Prior to acceptance of the vehicle by the Government inspector, the contractor shall service and adjust each vehicle and its mounted equipment for operational use including at least the

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

following: alinement of lights; adjustment of chassis engine, heating and air conditioning systems, and brake system; filling and charging of all batteries; alinement of front wheels; inflation of all tires; complete lubrication of chassis, engines, and running gear with grades of lubricants recommended for the ambient air temperature at the delivery point; servicing of engine cooling systems with a solution of ethylene glycol type antifreeze and water in equal parts by volume; and servicing of windshield washer reservoir with water and appropriate additives.

3.7 Workmanship. Defective components or parts and assemblies which have been repaired or modified to overcome deficiencies shall not be furnished. All parts shall exhibit no evidence of damage, multilation, or poor workmanship Damaged components or parts that have been subjected to rebuild or repairs shall not be used as replacement parts or components. All mounting devices such as bolts, nuts and rivets shall be complete and secured in accordance with the highest standards of industry.

3.7.1 Metal fabrication. Metal used in the fabrication of equipment shall be free from kinks and sharp bends. The straightening of material shall be done by methods that will not degrade the design strength of metal. Shearing and chipping shall be done neatly and accurately. All bends of a major character shall be made with controlled means in order to insure uniformity of size and shape.

3.7.2 Bolted connections. Bolt holes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts and screws shall be tight.

3.7.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of an approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and shall be in full contact with the surface of the member.

3.7.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the welds are subjected to proof and service loadings.

3.7.5 Paneling installation. All interior paneling shall be installed uniformly, free of misalinement, open seams, gaps, and uneven surfaces. Interior paneling shall be properly secured, free of misalined joiners,

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

edgings, waviness, dents, nicks, scratches, sharp edges, and other forms of deformation or surface defects. Exterior paneling shall be free of damaged or missing rivets. Exterior over-lapped sheet surfaces shall be sealed with sealing compound with uniform application.

3.7.6 Door and window installation. All exterior doors and windows shall be properly located, fitted and sealed to prevent entrance of air, dust and water. All windows and doors with associated hardware shall operate without binding. Window curtains shall be the appropriate color, durable material, free of uneven stitching, crooked seams, runs, tears, or color fade and shall be installed uniformly.

3.7.7 Installation of insulation. The insulation shall be installed in a manner excluding excessive voids, open spaces, rips, tears and other types of damage or defects. Wherever practical, the insulation shall be installed prior to the closing of spaces of the body interior. The insulation shall be installed and secured in a manner to retain the material in a permanent position under all operating conditions.

3.7.8 Floor installation and floor covering. The material used to enclose the floor area shall be securely installed and free of gaps, open seams, cuts, or open holes. All wood parts shall be free of cracks or splinters and thoroughly treated to provide full and uniform coverage. The material shall be applied to provide uniform coverage, free of thin or bare areas. The carpeting shall be installed securely and fitted without gaps, visible seams, bulges, frayed edges or color fade.

3.7.9 Electrical system installation. The electrical system shall be installed to provide proper routing for electrical wiring with clearances between wiring and applicable parts. All wiring shall be secured and fastened at all points of bending and protected against chafing and damage. Wiring shall be concealed and easily accessible for repairs. All circuits shall be properly grounded. Electrical wiring covering shall be free of cracks, cuts, kinks, frays, or similar defects. All wiring and outlets shall be securely installed, free of loose or faulty connections. Wall outlets and other receptacles shall be conveniently located and installed uniformly. All electrical appliances and fixtures shall be mounted securely and properly positioned to prevent damage during transit.

3.7.10 Air conditioning installation. Air conditioning units shall be securely roof mounted. The units shall be installed, fitted and sealed on the roof surface and shall be rainproof and weatherproof. The air conditioning units shall perform satisfactorily without vibration or undue noise.

3.7.11 Plumbing installation. The installed plumbing system (appliances, fixtures, devices and associated equipment) shall be capable of functioning satisfactorily without water leaks, excessive vibration, or undue

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

noise. All plumbing equipment shall be securely mounted and shall show no evidence of damage (scratches, dents, chipping). All draining plumbing shall be installed in a manner to prevent leakage.

3.7.12 Laminated surfaces. All laminated surfaces (formica counters, desks, etc.) shall be securely installed, properly fitted, alined and leveled with the floor surface. Laminated surfaces shall be free of delamination, scratches, mars, uneven surfaces, rough or chipped edges or corners and color fade. Counters, cabinets and desks shall be of rugged construction, properly alined and installed without any evidence of damage or deformation. Cabinet drawers shall be fitted to provide ease of operation without binding, interference or excessive side movement during opening and closing.

3.7.13 Upholstery and padding. Removable fitted pad coverings and upholstery shall be of durable materials and properly fitted. Upholstery shall meet the flammability requirements of FMVSS 302. All materials shall be free of rips, tears, splits, color fade, or stains. The color of the materials shall be coordinated with the applicable area. The padding material shall be evenly distributed, breathable and free of bumps, bulges, or other uneven surfaces.

3.7.14 Grabhandles and removable safety handrails. The grabhandles and handrails shall be of rigid construction and securely mounted. The surfaces shall be smooth, free of burrs, nicks and scratches.

3.7.15 Exhaust fan installation. Exhaust fans shall be securely mounted and fitted, free of gaps, openings, exposed electrical wiring or exposed insulation. The installation shall be rainproof and waterproof. The exterior sealant shall be uniform, neat in appearance and free of bare or thin areas. The exhaust fans shall operate without rattles, undue noises or malfunctions.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements (examinations and test) as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

specification shall not relieve the contractor of the responsibility for ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirement, however this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of observation of the operations to determine that practices, methods and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification criteria has been demonstrated.

4.3 First production vehicle inspection. To determine conformance to all the requirements of the contract, the first vehicle produced under the contract shall be subjected to in-process water spray test, road test, functional tests, inspections contained in table III. The inspections and road tests shall be conducted by the contractor, at or near his plant, under the direction and in the presence of Government representatives. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the contract.

4.3.1 Vehicle weight. The first production vehicle shall be weighed to determine the curb weight and distribution of the curb weight on the front and rear axles (see 3.2.4 and 3.2.5). The total imposed loads on the front and rear axles shall be computed by the contractor and verified by the Government, using the curb weight, the operator and passenger weight at 175 pounds each, and the payload required to provide the specified GVW. The calculated imposed loads on the front and rear axles shall be compared to the suspension, axle and tire load capacity ratings to determine if these components are of adequate capacity to meet contractual requirements.

4.3.2 Road test. To determine conformance to 3.3 through 3.3.2, the first production vehicle shall be road tested prior to the water spray test and after completion of the vehicle. The vehicle shall be road tested for a distance of not less than 50 miles. The vehicle shall attain speeds up to at least 55 mph. At least 20 percent of the road test distance shall be over dry, unimproved or gravel roads at speeds up to 20 mph. The vehicle shall be subjected to not less than three sudden stops from speeds of not less than 20 mph on a substantially level, dry, smooth surface free of loose material. The vehicle shall be observed for the specified stopping distance. Upon completion of the road test, the vehicle, components and accessories shall be examined for damage and coolant leakage. All equipment permanently installed or secured for transit shall be examined for damage.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

4.4.3 In-process water spray test. To determine conformance to 3.5.2.3, 3.5.2.4 and 3.5.3, each vehicle produced under the contract, shall be subjected to a water spray test. The water spray test shall be performed prior to installation of interior paneling and insulation. The vehicle shall be exposed to a 100 percent water spray for not less than 15 minutes. The spray shall be delivered by nozzles operating at not less than 25 pounds per square inch (psi) water pressure. The nozzles shall be sufficient in number and placed approximately 4 feet from the body to afford full coverage of sides, roof, front, rear and undercarriage of the body. The spray shall be applied simultaneously or section by section. All doors and windows shall be closed as in normal travel position. During the water spray test, all windows and paneling shall be observed for leakage into the interior of the vehicle. The interior of the underbody storage compartments shall be examined for leakage. Any evidence of leakage (water or moisture) shall be cause for rejection.

4.4.4 Truck body treatment and painting. A certification regarding the body cleaning, treating, prime painting and salt spray resistance testing, as required by MIL-STD-1223, shall be made to the Government representatives at the first production vehicle inspection.

4.4.5 Radio frequency suppression verification. The vehicle manufacturer shall indicate on the questionnaire (commercial vehicle engineering data) if the vehicle will be suppressed to limit electromagnetic radiation in accordance with SAE J551.

4.4.6 Functional tests. After completion of the road test, the following functional tests shall be conducted.

4.4.6.1 Electrical system test. To determine conformance to 3.5.5.1 through 3.5.5.4, the electrical system shall be subjected to a functional test. The satisfactory performance of the electrical system shall be verified, with the air conditioners operating, and all lighting and electrical equipment turned on. The lighting shall be observed during the phase-in operation of the air conditioners, to verify that the lighting does not fade and the air conditioning units perform satisfactory. The power and electric circuits shall be verified to assure that the power load is in accordance with the specified requirements and actual loads imposed.

4.4.6.2 Air conditioning test. To determine conformance to 3.5.9, the air conditioning system shall be subjected to a functional test. The air conditioning/vehicle body combination shall be tested under actual or simulated conditions at least as stringent as the specified requirements. Simulated conditions acceptable to the Government may be used. Performance of the air conditioning system shall be verified to determine that the system is capable of maintaining the inside of the vehicle body at an evenly circulated cooling temperature of 74°F maximum in 100°F outside ambient temperature. Inside temperature may be calculated either with the number of occupants required or with the use of a simulated heat load for sensible cooling.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

4.4.6.3 Heating test. To determine conformance to 3.5.8, the vehicle body heating system shall be subjected to a functional test. The electric fan blower heaters and vehicle body shall be tested under actual or simulated conditions at least as stringent as the specified requirements. Simulated conditions must be acceptable to the Government. Performance of the heating system shall be verified to determine that the heating system is capable of maintaining the inside body temperature at a minimum of 72°F midway between the floor and ceiling in 0°F outside ambient with no occupants.

4.4.6.4 Water system test. To determine conformance to 3.5.6, the water system shall be subjected to a hydrostatic test. The in-place water supply system and water heater with connections shall withstand a pump pressure of not less than 40 psi and not more than 50 psi for a period of not less than 30 minutes. The hydrostatic test shall be conducted with no evidence of leakage and no additional air or water being required to maintain the pressure. During the test period the water system shall be observed for leakage, undue noise and damage as a result of the test.

4.4.6.5 Water drain system test. To determine conformance to 3.5.6, the water drainage system shall be tested for leakage. With the main drain outlet capped, the sink shall be filled with water. After a period of not less than 30 minutes, the drain system shall be examined for leakage. Evidence of any leakage shall be cause for rejection.

4.4.6.6 Stabilizing jacks test. To determine conformance to 3.5.13, the stabilizing jacks shall be tested. With jacks in place, the adjustable jacks shall be operated to level and stabilize the vehicle. The jacks shall be observed for proper operation without binding or malfunctioning. The vehicle shall be observed to verify the jacks will provide adequate leveling and stability in relation to the ground, under normal stationary service.

4.4.7 Wood treatment certification. Manufacturer's records shall be available to verify that all wood requiring treatment in accordance with MIL-STD-1223 has been treated.

4.4.8 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample, and shall be the last vehicle shipped on the contract. The contractor shall maintain the vehicle in a serviceable condition for the duration of the contract.

4.5 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles under contract until corrective action has been taken.

4.6 Production vehicle inspection. Each production vehicle shall be subjected to dimensional inspection and operational tests as specified in section 3. The vehicle, associated controls and equipment shall be operated

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

to the extent necessary to verify compliance to contractual requirements. The contractor's inspection system, as a minimum, shall assure that the vehicle and attached equipment conforms to the dimensional and operational requirements and the vehicle is capable of meeting the requirements herein. For each vehicle under contract, the contractor shall make available to the Government, at the point of final acceptance, records acceptable to the Government. The records shall indicate that servicing and adjusting required by 3.6 have been accomplished.

4.6.1 Vehicle body inspection. Vehicle bodies installed on the chassis shall be inspected for the characteristics and defects contained in table III. All noted defects shall be corrected.

TABLE III. Characteristics and defects.

Characteristic	Major defects	Method of inspection
Exterior paneling	Unevenness, buckling, warping missing or damaged rivets, overlapped panel surfaces not sealed, excessive or sloppy application or sealing material, gage metal, surface defects (see 3.5.2.3 and 3.7.5).	Visual
Doors and door hardware	Improper fit, not alined, warpage, improper application of door seals, improper material, inoperative door hardware, surface defects (see 3.5.3 and 3.7.6)	Visual and operational
Windows	Sloppy installation of weather-weatherproof seals, windows not easily opened or adjusted to various positions, defective glass (cracks, scratches) (see 3.5.3 and 3.7.6)	Visual and operational
Interior panels	Unevenness, buckling, gaps, open seams, joiners, edgings, and molding improperly installed, surface defects (see 3.5.2.6 and 3.7.5)	Visual
Floor and floor covering	Gaps, waviness, cracks, bulges, open seams, inadequately secured, improper floor covering material, improper application of sound deadening material (see 3.5.2.5 and 3.7.8)	Visual

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the current version before use.

TABLE III. Characteristics and defects. - Continued

Characteristic	Major defects	Method of inspection
Stepwells	Hinge cover not flush with interior floor (when applicable), binding or interference of hinged cover or fold-out stair assembly (whichever is applicable) damaged, defective material, improper fit	Visual and functional
Electrical system	Sloppy or loose connections, improper wiring clearances, color code errors, incorrect capacity of circuit breaker box(es), wiring not fastened or clipped, incorrect wire size, faulty materials, faulty solder joints, sloppy installation, inoperative electrical controls, noisy (see 3.5.5 through 3.5.5.4 and 3.7.9)	Visual and functional
Floodlights installation	Not weatherproof, improper grounding, improper light wattage, sloppy installation, brackets not secure, brackets not located as specified, inoperative (see 3.5.5.6)	Visual and operational
Air conditioners, and controls	Air conditioners not mounted securely sloppy installation of controls, defective materials, malfunction of controls, vibration and undue noise of air conditioners (see 3.5.9 and 3.7.10)	Visual and operational
Plumbing system, components and fixtures	Improper assembly or installation, defective material, fixtures and components not mounted securely, malfunction of plumbing fixtures, water leaks, undue noise (see 3.5.6 through 3.5.6.2 and 3.7.11)	Visual and functional
Laminated surfaces (Formica) desks, counters and cabinets	Delamination, scratches, mars, color fade, unevenness, bulging, rough edges, not level with floor surface, not mounted securely, im-	Visual and functional

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

TABLE III. Characteristics and defects. - Continued

Characteristic	Major defects	Method of inspection
	proper assembly or installation, improper construction, improper counter height, binding and interference of desks and cabinet drawers (see 3.5.4.1 through 3.5.4.3 and 3.7.12)	
Bed, dinette sofa and chairs	Benches not sturdy or not rigid construction, improper installation, defective material interference with chair (see 3.5.4 through 3.5.4.4 and 3.7.12)	Visual and functional
Upholstery and padding	Sloppy installation, inferior material, uncomfortable, non-uniform fit, rips, splits, color fade, stains, color not coordinated with applicable area, material not durable (see 3.5.4 through 3.5.4.4 and 3.7.13)	Visual and tacticle
Grabhandles and safety handrails	Improper installation, not mounted securely, not rigid construction, grab handles and handrail surfaces not smooth (burrs, snags, scratches, rough areas) (see 3.7.14)	Visual and tacticle
Audio and visual accessories	Improper installation, loose connections, not installed in proper areas, exposed wiring or insulation, speakers not mounted securely, inconvenient location of volume controls, defective materials, malfunction of controls (see 3.5.5.8 through 3.5.5.11)	Visual and functional
Exhaust fans	Not mounted securely, improper locations, improper fit to interior panels, exposed wiring, exposed insulation, loose connection, improper fit to exterior panels (discharge openings), not weatherproof sloppy caulking, fans and controls not operative, vibration, rattles, undue noise	Visual and functional

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currenversion before use.

TABLE III. Characteristics and defects. - Continued

Characteristic	Major defects	Method of inspection
Curtains	Improper installation, not secure, not even, inferior material, color not appropriate, uneven stitching, tears, frays, color fade, stains (see 3.5.3 and 3.7.6)	Visual
Sealers and caulking	Sloppy application, improper amounts, improper material, not weatherproof or waterproof.	Visual
Fire extinguishers	Location not convenient, mounting not secure (see 3.5.11).	Visual

5. PACKAGING

5.1 Vehicle processing. The vehicle shall be processed for shipment, from manufacturer's plant to initial receiving activity, in accordance with the manufacturer's standard commercial practice.

6. NOTES

6.1 Intended use. Vehicles covered by this specification are intended for general non-tactical use by the Government as office and living quarters for personnel. The vehicles are intended for use both on improved roads and for off road conditions.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Class of vehicle required (see 1.2)
(c) Issues of DODISS to be cited in the solicitation and if required, the specific issues of individual documents referenced (see 2.1.1 and 2.2).
(d) Identification of appropriate service for painting (see 3.1.1.1).
(e) Exterior color selection after award of contract, if required (see 3.1.1.1).
(f) Identification of appropriate military service for marking (see 3.1.1.2)
(g) Concealed markings, if required (see 3.1.1.2)
(h) Rustproofing, if required (see 3.1.1.3).
(i) Towing devices on rear, if required (see 3.1.1.6).
(j) Blackout curtains, if required (see 3.1.1.9).
(k) Satisfactory operation on JP-4, JP-5, and JP-8 fuels, if required (see 3.4.1.1)

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:24Z
Check the source to verify that this is the currentversion before use.

(l) Gasoline engine, if required (see 3.4.1.2).
(m) Silicone rubber hoses, if required (3.4.1.8)
(n) Power plant heaters and fuel warmer, if required (see 3.4.1.9).
(o) If a battery heater is not required with power plant heaters (see 3.4.1.9)
(p) Fuel fired engine preheater, if required for a diesel driven engine (see 3.4.1.10).
(q) Alternator capacity, if other than as specified (see 3.4.2.3)
(r) Fuel and water separator, if required (see 3.4.3.3).
(s) Variable rate springs and adjustable shock absorbers, if required (see 3.4.8)
(t) Air type rear suspension, if required (see 3.4.8.1)
(u) Oil lubricated wheel bearings and axle spindles, if required (see 3.4.9).
(v) Traction control, if required (see 3.4.9.1).
(w) Wide base type front and rear tires and wheels, if required (see 3.4.10).
(x) Disc type wheels, if required (see 3.4.10).
(y) Low profile tires or bias ply tires, if required (see 3.4.10.1).
(z) If spare tire carrier is not required (see 3.4.10.2).
(aa) Spare wheel or rim, if required (see 3.4.10.3).
(ab) Spare tire assembly, if required (see 3.4.10.4).
(ac) Tools, if required (see 3.4.16.1).
(ad) Automotive type air conditioning, if required (see 3.4.19).
(ae) Engine hour meter, if required (see 3.4.25).
(af) Insect screen, if required (see 3.4.26).
(ag) AM/FM radio, if required (see 3.4.27).
(ah) Spotlight(s), if required (see 3.5.5.6).
(ai) Specialized interior lighting, if required (see 3.5.5.7).
(aj) Back-up video camera system, if required (see 3.5.5.8).
(ak) Cellular telephone, if required (see 3.5.5.9).
(al) A television set, if required (see 3.5.5.10).
(am) A second television set, if required (see 3.5.5.10).
(an) Video cassette recorder, if required (see 3.5.5.11).
(ao) Additional special accessories, as required (see 3.5.10).

6.3 Performance prediction. SAE Truck Ability Prediction Procedure computations and computations for maximum geared speed will be required by the contract. The SAE Work Sheet Item 1 should include vehicle model number, engine model number, and vehicle type and class. Unless other conditions are cited in the contract computations should be made for normal atmospheric pressure, normal ambient air temperature, and still, dry air. The factors to be used in predicting truck ability (see 3.3.1.1) are established as follows for the corresponding SAE Truck Ability Prediction Procedure Tables:

Table 1 - Tire Factor. This factor must relate to the size of tires furnished by the contractor in accordance with this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

Table 2 - Altitude Factor. 1.00
Table 3 - Rolling Factor. 1.613
Table 4 - Area Factor. 0.173
Table 5 - Velocity Factor. 250.0
Table 6 - Altitude Factor. 1.00
Table 7 - Chassis Friction Horsepower. Use applicable power unit GVW (to nearest, higher, 1,000 pounds) and the engine rpm (to nearest 100 revolutions) which is required for 50 mph geared speed. For GVW and engine speed beyond the range of this table, the following formula shall be used: FHP = 1+(0.0000007 rpm)(GVW)
Table 8 - Grade Factor. 0.75
Table 8A - Correction Factor. Not required.
Table 9 - Road Factor. 0.0.

6.4 Subject term (key word) listing.

Combined office and living quarters
Forward control chassis
Mobile office
Mobile living quarters

Custodian:
Army - AT

Preparing Activity:
Army - AT

Project Number 2320-A440

*U.S. GOVERNMENT PRINTING OFFICE: 1991--504-034/50315

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
U.S. Army Tank-Automotive Command
ATTN: AMSTA-UED
Warren, Michigan 48397-5000

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-T-62674(AT); Truck, Living Quarters: Self Contained, Forward Control, DED or GED, 14,500 to 16,500 Pounds GVW, 4x2, Commercial

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:24Z
Check the source to verify that this is the current version before use.