MILITARY SPECIFICATION

TEST MODE ASSEMBLY, ROCKET: M180 CRATERING DEVICE PROPELLANT TESTING

This specification is approved for use by all departments and agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the parts and assembly for one type of test mode assembly designated as Test Mode Assembly, Rocket: M180 Cratering Device Propellant Testing.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-1169 - Packaging, packing and marking for shipment of Inert Ammunition components

DRAWINGS (See 6.3)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9325862 - Test Mode Assembly, Rocket

FSC: 1340

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26 04:26Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material - Materials shall be in accordance with applicable drawings and specifications.

3.2 Assembly- The assembly shall comply with all requirements specified on drawing (dwg.) 9325862 and with all requirements specified in applicable specifications.

3.3 First Article Inspection- This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.4 Hydrostatic Inspection- Test mode assembly shall be fitted with a suitable seal and mounted on a suitable hydrostatic test fixture. Hydrostatic pressure shall be applied in accordance with the requirements of dwg. 9325862. The Test Mode Rocket Assembly shall then be disassembled and all parts inspected for cracks, distortion or any other evidence of failure or damage.

3.5 Workmanship- All parts and assemblies shall be fabricated and finished in a thorough workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required) , corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part or assembly nor shall they be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings and stampings shall be neat and sharply defined. (Required packing shall be dry).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspections- The responsibility for inspections shall comply with MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

4.2 Classification of Inspections- The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First Article Inspection

4.3.1 Submission- The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawing No.	Quantity
Retainer, forward	9325866	5
Head	9325867	5
Nozzle	9325863	5
Retainer, nozzle	9325864	5
Screw	9326728	5
Case	9325865	5
Gasket	9326071	5
Plate, retainer, rocket	9244408	5

4.3.2 Inspections to be performed - See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection- See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63262(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
	TEST MODE ASSEMBLY, ROCKET: M180 CRATERING DEVICE PROPELLANT TESTING				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Head (Dwg 9325867) Examination for Defects	5		3.2	4.4.2.2
	Retainer, forward (Dwg 9325866) Examination for Defects	5		3.2	4.4.2.1
	Nozzle (Dwg 9325863) Examination for Defects	5		3.2	4.4.2.3
	Retainer, Nozzle (Dwg 9325864) Examination for Defects	5		3.2	4.4.2.4
	Screw (Dwg 9326728) Examination for Defects	5		3.2	4.4.2.5
	Case (Dwg 9325865) Examination for Defects	5		3.2	4.4.2.6
	Gasket (Dwg 9326071) Examination for defects	5		3.2	4.4.2.7

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
	Continuation TEST MODE ASSEMBLY, ROCKET: M180 CRATERING DEVICE PROPELLANT TESTING				See Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Wrench (Dwg 9325868) Examination for Defects	5		3.2	4.4.2.8
	Plate, Retainer, Rocket (Dwg 9244408) Examination for Defects	5		3.2	4.4.2.9
	Hydrostatic Test	5		3.4	4.5.2

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. - See MIL-A-48078.

4.4.2 Examination. - See MIL-A-48078.

a. Sampling plans. - Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105D, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Retainer, Forward		9325866
			NEXT HIGHER ASSEMBLY 9325862

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter, min		0.4	3.2	Gage
102	Thread undercut diameter, max		0.4	3.2	Gage
103	Outside width, min		0.4	3.2	Gage
104	Inside depth, max		0.4	3.2	Gage
105	Pitch diameter of threads, max		0.4	3.2	Gage
106	Minor diameter of threads, max		0.4	3.2	Gage
107	Length of thread, min		0.4	3.2	Gage
108	Radius, min		0.4	3.2	Gage
109	True position of wrench slots		0.4	3.2	Gage
110	Width of wrench slots (4 places)		0.4	3.2	Gage
111	Length of wrench slots (4 places)		0.4	3.2	Gage
112	Pitch diameter, NPS thread, max		0.4	3.2	Gage
113	Minor diameter, NPS thread, max		0.4	3.2	Gage
114	Center diameter, full thru		0.4	3.2	Visual
Minor					
201	Pitch diameter, NPS thread, min		0.65	3.2	Gage
202	Evidence of poor workmanship		1.00	3.5	Visual
203	Protective finish missing or damaged		0.65	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63262(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Head		9325867
			NEXT HIGHER ASSEMBLY 9325862

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None				
Major					
101	Outside diameter, max		0.4	3.2	Gage
102	Width, max		0.4	3.2	Gage
103	Flatness of surface		0.4	3.2	Gage
104	True position, center hole		0.4	3.2	Gage
105	Pitch diameter of thread, max		0.4	3.2	Gage
106	Minor diameter of thread, max		0.4	3.2	Gage
Minor					
201	Minor diameter of threads, min		0.65	3.2	Gage
202	Chamfer correct (2 places)		0.65	3.2	Gage
203	Evidence of poor workmanship		1.00	3.5	Visual
204	Protective finish missing or damaged		0.65	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63262(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9325863
4.4.2.3	Nozzle				NEXT HIGHER ASSEMBLY 9325862
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None				
Major					
101	Outside diameter, max		0.4	3.2	Gage
102	Shoulder diameter, max		0.4	3.2	Gage
103	Shoulder depth, max		0.4	3.2	Gage
104	Inside diameter, forward, min		0.4	3.2	Gage
105	Throat diameter, min		0.4	3.2	Gage
106	Inside diameter, rear, min		0.4	3.2	Gage
107	Length, max		0.4	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.00	3.5	Visual
202	Protective finish missing or damaged		0.65	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63262(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9325864
4.4.2.4	Retainer, Nozzle				NEXT HIGHER ASSEMBLY 9325862
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None				
101	Inside diameter, min		0.4	3.2	Gage
102	Thread undercut diameter, min		0.4	3.2	Gage
103	Pitch diameter of threads, max		0.4	3.2	Gage
104	Minor diameter of threads, max		0.4	3.2	Gage
105	Outer diameter, min		0.4	3.2	Gage
106	Lip diameter, max		0.4	3.2	Gage
107	Lip depth, min		0.4	3.2	Gage
108	True position of wrench slots		0.4	3.2	Gage
109	Length to end of thread undercut from open end		0.4	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.00	3.5	Visual
202	Pitch diameter of threads, min		0.65	3.2	Gage
203	Thread relief		0.65	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63262(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Screw		9326728
			NEXT HIGHER ASSEMBLY 9325862

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None				
Major					
101	True position, center hole		Q4	3.2	Gage
102	Center hole diameter, min		Q4	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

11

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63262(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.6	CASE		9325865
			NEXT HIGHER ASSEMBLY 9325862

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None				
Major					
101	Length, min		0.4	3.2	Gage
102	Inside diameter, min		0.4	3.2	Gage
103	Outside diameter, min		0.4	3.2	Gage
104	Length of thread, min		0.4	3.2	Gage
105	Counterbore diameter, forward, min		0.4	3.2	Gage
106	Counterbore depth, forward, min		0.4	3.2	Gage
107	Counterbore diameter, rear, min		0.4	3.2	Gage
108	Counterbore depth, rear, min		0.4	3.2	Gage
109	Pitch deameter, max, both ends		0.4	3.2	Gage
110	Minor diameter, max, both ends		0.4	3.2	Gage
111	Thread undercut diameter, max (2 places)		0.4	3.2	Gage
Minor					
201	Pitch diameter, min, both ends		0.65	3.2	Gage
202	Evidence of poor workmanship		1.00	3.5	Visual
203	Protective finish missing or damaged		0.65	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63262(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9326071
4.4.2.7	Gasket				NEXT HIGHER ASSEMBLY 9325862
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None				
Major					
101	Outside diameter, max		0.4	3.2	Gage
102	Inside diameter, min		0.4	3.2	Gage
103	Width, max		0.4	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63262(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Wrench				9325868
					NEXT HIGHER ASSEMBLY
					9325862
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None				
Major					
101	True position, tongues		0.4	3.2	Gage
102	Tongue width, max		0.4	3.2	Gage
103	Tongue length, min		0.4	3.2	Gage
104	Width, min		0.4	3.2	Gage
105	Length, min		0.4	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0	3.5	Visual
202	Protective finish missing or damaged		0.65	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63262(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9244408
4.4.2.9	Plate, Retainer, Rocket				NEXT HIGHER ASSEMBLY 9325862
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None				
Major					
101	Diameter of center hole		0.4	3.2	Gage
102	True position of center hole		0.4	3.2	Gage
103	Outside diameter, max		0.4	3.2	Gage
104	Thickness of plate		0.4	3.2	Gage
105	Diameter of propellant cha ge holes		0.4	3.2	Gage
106	True position of 15 equally spaced holes		0.4	3.2	Gage
107	True position of 28 equally spaced holes		0.4	3.2	Gage
108	True position of 8 equally spaced holes		0.4	3.2	Gage
109	True position of 20 equally spaced holes		0.4	3.2	Gage
110	Depth of undercut		0.4	3.2	Gage-
Minor					
201	Countersink on center hole improper or missing		0.65	3.2	Visual
202	Chamfer missing or propellant change holes		0.65	3.2	Visual
203	Protective finish missing or damaged		0.65	3.2	Visual
204	Evidence of poor workmanship		1.00	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Testing - Testing and examination of the samples for First Article and quality Conformance are completely described in the First Article and Quality Conformance tables.

4.4.4 Inspection Equipment - The inspection equipment required to perform the examinations and tests prescribed herein is described in the Paragraph Reference/Inspection Method column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078.

4.5 Test Methods and Procedures

4.5.1 Materials, Components and Processes- Compliance with all requirements of section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts, subassemblies and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.1.1 Visual and Mechanical Inspections - The visual, manual and mechanical inspections and tests shall verify compliance with the requirements of sections 3 and 5 of this specification in accordance with 4.4.2 herein and Table I.

4.5.2 Hydrostatic Pressure Test - The Test Mode Rocket Assembly, dwg 9325862, shall be assembled and mounted on a suitable hydrostatic test fixture.

5. PREPARATION FOR DELIVERY

5.1 Packaging Inspection - The sampling and inspection of the preservation-packaging, packing and container marking shall be in accordance with the requirements of MIL-STD-1169.

6. NOTES

6.1 Ordering Data - See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

6.2 Submission of Designs for Approval- See MIL-A-48078. Submit equipment designs, as required, to Commander, ARRADCOM ATTN: DRDAR-QAA-I, Dover, New Jersey 07801.

6.3 Drawings. - Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 1340-A543

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-T-63262 Test Mode Assy, Rocket; M180 Cratering Device Propellant Testing

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

U.S. MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Armament R&D Command
ATTN: DRDAR-QAA
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.