MILITARY SPECIFICATION

WARHEAD, ILLUMINATING, M257, W/M442 FUZE (2.75INCH ROCKET ILLUMINATING FLARE)

This specification is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the quality assurance provisions and special requirements not covered by the drawings for one type of warhead designated as Warhead, 2.75 Inch Rocket Illuminating Flare, M257.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specification and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification for
MIL-F-70673	-	Fuze, Rocket, Base Detonating, M442

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament Munitions and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1340

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

STANDARDS

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-331	-	Fuze and Fuze Components, Environmental and Performance Tests for
MIL-STD-414	-	Sampling Procedures and Tables for Inspection by Variables for Percent Defective
MIL-STD-453	-	Inspection, Radiographic
MIL-STD-810	-	Environmental Test Methods

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

US ARMY ARMAMENT, RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER (ARDEC)

9332220	-	Warhead, 2.75 Inch Rocket Flare, M257
8883478	-	Cont, Ammo, Fiber, M518, for rocket Motor: 2.75 Inch, Mark 40 Mods, and Mark 4 and Mods
8883479	-	Box Packing Ammo for Rocket Motor, 2.75 Inch, Mark 40 and Mods, Mark 4 and Mods
9298733	-	Fuze, Rocket, Base Detonating, M442
9340646	-	Box, Fiber, Packing, Ammunition for Warhead, 2.75 Inch Rocket Flare, M257
9347035	-	Packing and Marking for Box, Wood, Wirebound Pallet Type, for Warhead 2.75 Inch Rocket Illuminating M257
9294519	-	Packing and Marking for Container, Ammunition, Fiber, M518 for Warhead 2.75 Inch Rocket Flare, M257 only
9394492	-	Packing and Marking for Box, Wood Packing Ammunition for Wrahead, 2.75 Inch Rocket Flare M257, Rocket Motor: 2.75 Inch, MK40 and Mods and MK4 and Mods
9340647	-	Pallet, (Boxed Type), for Warhead, 2.75 Inch Rocket: Illumination, M257

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

9357963	-	Box Packing Ammo for Rocket Motor, 2.75 Inch, MK66
12624792	-	Packing and Marking for Box, Wood Packing Ammunition for Warhead, 2.75 Inch Rocket Flare M257, Rocket Motor: 2.75 Inch, MK66
19-48-4116/80M	-	Unitization Procedures for Boxed Ammunition and Components on 4-Way Entry Pallets

(Copies of specifications, standards, handbooks, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on Drawing 9332220 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Metal and plastic defects. All of the components prior to painting or chemical treatment shall be free of surface imperfections on the interior and exterior surfaces of the part which are indications of discontinuities internal to the material. (Included are cracks, lube bursts, pipes, laminations, segregations, porosity, air holes, flakes, inclusions, and other internal defects.)

3.4 Ballistic test. The completely assembled round (warhead either with MK40 motor or MK66 motor) shall be ballistically tested to comply with the following requirements:

3.4.1 Function time. The time between rocket motor ignition and flare candle ignition shall be 13.5 $\pm$ 2.0 seconds with MK40 motor and 13 $\pm$ 2.0 seconds with MK66 motor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

3.4.2 Descent characteristic. The burning flare shall descend on the parachute for a minimum of 90.0 seconds, after ignition and before ground contact.

3.4.3 Flare burn time. The flare candle shall burn for a minimum of 100 seconds. Burn time upon ground impact may be included.

3.5 Illumination. The flare candle shall produce an average light output of 1 million candle power for a minimum of 95 seconds.

3.6 Rough handling. The warhead shall withstand rough handling when tested as specified in 4.5.2 and shall be safe to handle, fire, and dispose of. Warheads that are suitable to fire shall be assembled to rocket motors which have not been subjected to rough handling environments prior to firing. Firing of warheads shall be for informational purposes only.

3.7 Temperature. The warhead shall withstand exposure to a storage temperature of $+140^{o}F \pm 5^{o}F$, $-25^{o}F \pm 5^{o}$, and $70^{o}F \pm 5^{o}F$ for 8 hours minimum and shall comply with the ballistic test as specified in 4.5.13.

3.8 Secured cargo vibration. The warhead shall withstand exposure to secured cargo vibration as specified in 4.5.3 and shall comply with the ballistic test as specified in 4.5.13.

3.9 Helicopter vibration. The warhead shall withstand exposure to helicopter vibration as specified in 4.5.4 and shall comply with the ballistic test as specified in 4.5.13.

3.10 Warhead forty-foot drop test. The warhead shall be subjected to and must withstand the Forty-foot Drop Test as specified in MIL-STD-331.

3.11 Warhead leak test. The warhead shall not leak when subjected to the leakage test as specified in 4.5.6.

3.12 Radiographic quality. X-rays shall be taken in accordance with MIL-STD-453 and shall be of a quality which will permit proper evaluation as determined by the responsible technical agency of the Government. Minimum optical density of each radiograph in the area being inspected shall not be less than 1.25 and shall be within a density range that will permit proper identification of defects.

3.13 Functional straightness. Each warhead when attached to a dummy rocket motor shall be capable of passing through a gage 50.100 + 0.25 inches long, 2.7952 + .0020 inches in diameter, and straight within .0020 inches total.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

3.14 Gas generator non-function test. The gas generator shall not function when a static extraction force of 20 pounds is applied to the sear.

3.15 Gas generator and expulsion charge function test. The gas generator shall function and ignite the expulsion charge when tested as specified in this specification. The requirement for time delay is indicated on dwg. 9332277

3.16 M442 Fuze. All M442 fuzes shall have been subjected to and pass all the requirements of MIL-F-70673(AR).

3.17 Igniter assembly function test. The armed igniter assembly shall function upon application of force of 50 pounds minimum and 75 pounds maximum upon the cable. The boron pellets shall be fully consumed.

3.18 Zig-zag setback mechanism assembly non-arming test. The zig-zag setback mechanism assembly shall remain in the non-armed and safe condition after being subjected to an acceleration force of sixteen (16) g's plus or minus .5 g's for a duration of three (3) seconds min.

3.19 Zig-zag setback mechanism assembly arming test. The zig-zag setback mechanism assembly shall arm when subjected to an acceleration force of twenty-two (22) g's plus or minus .5 g's for a duration of one (1) second maximim.

3.20 Zig-zag setback mechanism assembly reset capability test. The setback weight shall be capable of returning to the unarmed position on its own after it has been partially armed.

3.21 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.22 Workmanship. The components and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, unblended radii, dirt, grease, rust, corrosion products and other foreign matter. The

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:26Z
Check the source to verify that this is the currentversion before use.

cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Surface coatings shall be continuous except for a few slight scratches not exposing base material. All required markings shall be neat and legible.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are made a part of this specification.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

Part Description	Drawing	Quantity
Cap, Retainer	9332256	10
Closure	9332258	10
Spring, Striker	9332263	10
Housing, Igniter	9332255	10
Arm, Striker	9332267	10
Pin, Firing	9332266	10
Assembly, Slider	9332264	10
Slider	9332262	10
Mechanism Assembly, Setback -Zig-Zag	9332273	25
Pin, Shear	9332261	10
Cushion	9332260	10
Wafer, Ignition	9332257	10
Assembly, Igniter	9332254	10
Raceway	9332270	10
Assembly, Charge	9298752	
Case	9332243	10
Case Assembly	9332242	10
Case Assembly, Insulated	9332241	10
Case Assembly, Tack Coated	9332240	10
Gas Generator	9332277	30
Case Assembly, Loaded	9332239	50
Candle and Parachute Assembly	9332222	10
Parachute, Main	9332251	10
Container, Deployment	9332252	10
Parachute Assembly	9332250	10
Insert, Main Parachute	9332249	10
Fitting and Cable Assembly	9332245	10
Separation and Drogue Release Assembly	9332221	10
Parachute, Drogue	9332236	10
Housing, Drogue Chute	9332230	10
Drogue and Housing Assembly	9332237	10
Adapter, Motor	9332226	10
Adapter Assembly, Motor	9332225	10
Motor Adapter & Fuze Assembly	9332224	10
Block, Retainer	9332231	10
Pin, Shear	9332281	10
Warhead, 2.75 Inch Rocket Flare M257	9332220	133

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

TABLE I - First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-W-63377(AR)

PARAGRAPH	TITLE: Warhead, 2.75 Inch Rocket Flare M257 and Components		SHEET 1 OF 8		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cap, Retainer (Dwg. 9332256)				
	Examination for Defects	10		3.2	4.4.2.1
	Closure (Dwg 9332258)				
	Examination for Defects	10		3.2	4.4.2.2
	Spring, Striker (Dwg 9332263)				
	Examination for Defects	10		3.2	4.4.2.3
	Torque Test	10		3.2	4.4.2.3
	Housing, Igniter (Dwg 9332255)				
	Examination for Defects	10		3.2	4.4.2.4
	Arm, Striker (Dwg 9332267)				
	Examination for Defects	10		3.2	4.4.2.5
	Pin, Firing (Dwg 9332266)				
	Examination for Defects	10		3.2	4.4.2.6

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

TABLE I - First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-W-63377(AR)

PARAGRAPH	TITLE Warhead, 2.75 Inch Rocket Flare M257 and Components		SHEET 2 OF 8		DRAWING NUMBER NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Assembly, Slider (Dwg 9332264) Examination for Defects	10		3.2	4.4.2.7
	Slider (Dwg 9332262) Examination for Defects	10		3.2	4.4.2.8
	Mechanism Assembly, Setback-Zig-Zag (Dwg 9332273) Examination for Defects Non-Arm Test Arming Test Setback Weight Reset Capability Test	25 25 25 25		3.2 3.2 3.2 3.2	4.4.2.9 4.4.2.9 4.4.2.9 4.4.2.9
	Pin, Shear (Dwg 9332261) Examination for Defects	10		3.2	4.4.2.10
	Cushion (Dwg 9332260) Examination for Defects	10		3.2	4.4.2.11

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

TABLE I - First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-W-63377(AR)

PARAGRAPH	TITLE: Warhead, 2.75 Inch Rocket Flare M257 and Components		SHEET 3 OF 8		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Wafer, Ignition (Dwg 9332257)				
	Examination for Defects	10		3.2	4.4.2.12
	Assembly, Igniter (Dwg 9332254)				
	Examination for Defects	10		3.2	4.4.2.13
	Pull and Function Test	10		3.2	4.4.2.13
	Raceway (Dwg 9332270)				
	Examination for Defects	10		3.2	4.4.2.14
	Assembly, Charge (Dwg 9298752)				
	Examination for Defects	10		3.2	4.4.2.15
	Case (Dwg 9332243)				
	Examination for Defects	10		3.2	4.4.2.16
	Case Assembly (Dwg 9332242)				
	Examination for Defects	10		3.2	4.4.2.17

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T04:26Z
Check the source to verify that this is the current version before use.

TABLE I - First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-W-63377(AR)

PARAGRAPH	TITLE: Warhead, 2.75 Inch Rocket Flare M257 and Components		SHEET 4 OF 8		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Case Assembly, Insulated (Dwg 9332241)				
	Examination for Defects	10		3.2	4.4.2.18
	Case Assembly, Tack Coated (Dwg 9332240)				
	Examination for Defects	10		3.2	4.4.2.19
	Gas Generator (Dwg 9332277)				
	Examination for Defects	30		3.2	4.4.2.20
	Output, Functioning	30		3.16	4.4.2.20
	Case Assembly, Loaded (Dwg 9332239)				
	Examination for Defects	50		3.2	4.4.2.21
	Flare Candle Output Test	50		3.2	4.4.2.21
	Candle and Parachute Assembly (Dwg 9332222)				
	Examination for Defects	10		3.2	4.4.2.22
	Swaged Oval Sleeve Pull Test	10		3.2	4.4.2.22
	Aft Swaged Oval Sleeve Pull Test	10		3.2	4.4.2.22

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

TABLE I - First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-W-63377(AR)

PARAGRAPH	TITLE: Warhead, 2.75 Inch Rocket Flare M257 and Components		SHEET 5 OF 8		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Parachute, Main (Dwg 9332251) Examination for Defects	10		3.2	4.4.2.23
	Container, Deployment (Dwg 9332252) Examination for Defects	10		3.2	4.4.2.24
	Parachute Assembly (Dwg 9332250) Examination for Defects	10		3.2	4.4.2.25
	Insert, Main Parachute (Dwg 9332249) Examination for Defects	10		3.2	4.4.2.26
	Fitting and Cable Assembly (Dwg 9332245) Examination for Defects	10		3.2	4.4.2.27
	Separation and Drogue Release Assembly (Dwg 9332221) Examination for Defects	10		3.2	4.4.2.28

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T04:26Z
Check the source to verify that this is the current version before use.

TABLE I - First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-W-63377(AR)

PARAGRAPH	TITLE: Warhead, 2.75 Inch Rocket Flare M257 and Components		SHEET 6 OF 8		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Parachute, Drogue (Dwg 9332236)				
	Examination for Defects	10		3.2	4.4.2.29
	Housing, Drogue Chute (Dwg 9332230)				
	Examination for Defects	10		3.2	4.4.2.30
	Drogue and Housing Assembly (Dwg 9332237)				
	Examination for Defects	10		3.2	4.4.2.31
	Pull Test on Swaged Sleeve	10		3.2	4.4.2.31
	Adapter, Motor (Dwg 9332226)				
	Examination for Defects	10		3.2	4.4.2.32
	Adapter Assembly, Motor (Dwg 9332225)				
	Examination for Defects	10		3.2	4.4.2.33
	Cable Pull Test	10		3.2	4.4.2.33

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

TABLE I - First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-63377(AR)

PARAGRAPH	TITLE: Warhead, 2.75 Inch Rocket Flare M257 and Components		SHEET 7 OF 8		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Motor Adapter & Fuze Assembly (Dwg 9332224)				
	Examination for Defects	10		3.2	4.4.2.34
	Block, Retainer (Dwg 9332231)				
	Examination for Defects	10		3.2	4.4.2.35
	Pin, Shear (Dwg 9332281)				
	Examination for Defects	10		3.2	4.4.2.36
	Warhead, 2.75 Inch Rocket Flare M257 (Dwg 9332220)				
	Examination for Defects	133(a		3.2	4.4.2.37
	Forty-foot drop	6		3.10	4.5.5
	Rough Handling test	36		3.6	4.5.2

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

TABLE I - First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-W-63377(AR)

PARAGRAPH	TITLE: Warhead, 2.75 Inch Rocket Flare M257 and Components		SHEET 8 OF 8		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Secured Cargo Vibration test	36		3.8	4.5.3
	Helicopter Vibration test	19		3.9	4.5.4
	Leak test	36		3.11	4.5.6
	Radiographic	97(b)		3.12	4.5.2/4.5.3/4.5.4/4.5.5
	Ballistic test	91(c)		3.4	4.5.13

NOTES: (a) Sum total of forty-foot drop, rough handling, secured cargo vibration helicopter vibration and leak tests.
(b) sum total of forty-foot drop, rough handling, secured cargo vibration, and helicopter vibration test.
(c) Sum total of leak, secured cargo vibration and helicopter tests. The First Article shall be rejected if nine (9) or more rounds fail the ballistic test requirements.

AMSMC Form 1570a, 1 Apr 85 Replaces DRDAR-QA Form 160a, 1 Jun 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

4.4.1 Inspection lot formation. Inspections lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of warheads shall contain:

a. Fuzes of one type, bearing the same interfix lot number from no more than two lots from one manufacturer.

b. The quantity of warheads in each production lot shall not exceed 6000.

c. Magnesium and explosive items furnished by a single manufacturer per item and each item identified by the same lot interfix number.

d. Metal parts from not more than two lots with the same interfix number from one manufacturer.

e. Plastic parts from not more than two lots with the same interfix number from one manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 9332256
4.4.2.1	Cap, Retainer		NEXT HIGHER ASSEMBLY 9332234

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thru hole diameter		.40%	3.2	Gage
102	Outside diameter		.40%	3.2	Gage
103	Pin hole diameter		.40%	3.2	Gage
104	Location, pin holes		.40%	3.2	Gage
105	Inside diameter at face		.40%	3.2	Gage
106	Outside diameter of groove		.40%	3.2	Gage
107	True position of groove diameter		.40%	3.2	Gage
108	Groove radius		.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Closure	1 OF 2	9332258
			NEXT HIGHER ASSEMBLY 9332254

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defnined				
Major					
101	Outside diameter		.40%	3.2	Gage
102	Outside diameter, step		.40%	3.2	Gage
103	Perpendicularity, step face to diameter of step		.40%	3.2	Gage
104	O-ring groove diameter		.40%	3.2	Gage
105	O-ring groove width		.40%	3.2	Gage
106	O-ring groove finish		.40%	3.2	Gage
107	Shear pin hole diameter		.40%	3.2	Gage
108	Shear pin hole true position		.40%	3.2	Gage
109	Shear pin hole depth		.40%	3.2	Gage
110	Zig-Zag post hole diameter		.40%	3.2	Gage
111	Zig-Zag post hole true position		.40%	3.2	Gage
112	Diameter of drive screw holes		.40%	3.2	Gage
113	True position of drive screw holes		.40%	3.2	Gage
114	Part to be transparent in area of shear pin and Zig-Zag post holes		.40%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9332258
4.4.2.2	Closure				NEXT HIGHER ASSEMBLY 9332254
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332263
4.4.2.3	Spring, Striker				NEXT HIGHER ASSEMBLY 9332264
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Torque test		.40%	3.2	Gage
Minor					
201	Wire diameter		.65%	3.2	Gage
202	Hole diameter		.65%	3.2	Gage
203	Width		.65%	3.2	Gage
204	Evidence of poor workmanship		.65	3.22	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Housing, Igniter	1 of 2	9332255
			NEXT HIGHER ASSEMBLY 9332254

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defnined				
Major					
101	Largest outside diameter		.40%	3.2	Gage
102	Second largest outside diameter		.40%	3.2	Gage
103	Third largest outside diameter		.40%	3.2	Gage
104	O-ring groove diameter		.40%	3.2	Gage
105	O-ring groove width		.40%	3.2	Gage
106	O-ring groove surface finish		.40%	3.2	Gage
107	Slider groove width		.40%	3.2	Gage
108	Slider groove depth		.40%	3.2	Gage
109	Slider groove true position		.40%	3.2	Gage
110	Inside diameter forward cavity		.40%	3.2	Gage
111	Surface finish forward cavity		.40%	3.2	Gage
112	Diameter of drive screw holes		.40%	3.2	Gage
113	True position of drive screw holes		.40%	3.2	Gage
114	Diameter of pin holes		.40%	3.2	Gage
115	True position of pin holes		.40%	3.2	Gage
116	Diameter of shear pin hole		.40%	3.2	Gage
117	True position of shear pin hole		.40%	3.2	Gage
118	Post hole diameter		.40%	3.2	Gage
119	Post hole true position				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Housing, Igniter	2 OF 2	9332255
			NEXT HIGHER ASSEMBLY 9332254

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
120	Set-back weight cavity diameter		.40%	3.2	Gage
121	Set-back weight cavity diameter true position		.40%	3.2	Gage
122	Vent hole missing		.40%	3.2	Gage
123	Primer output hole missing		.40%	3.2	Gage
124	Pellet cavity diameter		.40%	3.2	Gage
125	Cable bearing surface profile	10(a)		3.2	Optical
Minor					
201	Vent hole location		.65%	3.2	Gage
202	Primer output hole location		.65%	3.2	Gage
203	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:
(a) 10 per lot. Accept (0); Reject (1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332267
4.4.2.5	Arm, Striker				NEXT HIGHER ASSEMBLY 9332265
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defnined				
Major					
101	Diameter of pivot holes		.40%	3.2	Gage
102	True position of pivot holes		.40%	3.2	Gage
103	Diameter of rivet holes		.40%	3.2	Gage
104	True position of rivet hole		.40%	3.2	Gage
105	Width		.40%	3.2	Gage
106	Perpendicularity, face to two sides		.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332266
4.4.2.6	Pin, Firing				NEXT HIGHER ASSEMBLY 9332265
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defnined				
Major					
101	Pin diameter		.40%	3.2	Gage
102	Pin length		.40%	3.2	Gage
103	Length from bottom of pin to shank		.40%	3.2	Gage
Minor					
201	Shank diameter		.65%	3.2	Gage
202	Shank height		.65%	3.2	Gage
203	Rivet hole		.65%	3.2	Gage
204	Spherical radius, pin		.65%	3.2	Gage
205	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-63377(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332264
4.4.2.7	Assembly, Slider				NEXT HIGHER ASSEMBLY 9332254
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defnined				
Major					
101	Primer loose or not properly staked		.40%	3.2	Visual
102	Components missing		.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 9332262
4.4.2.8	Slider		NEXT HIGHER ASSEMBLY 9332264

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defnined				
Major					
101	Primer pocket diameter		.40%	3.2	Gage
102	Primer pocket depth		.40%	3.2	Gage
103	Thru hole diameter		.40%	3.2	Gage
104	Thru hole true position		.40%	3.2	Gage
105	Pivot pin hole diameter		.40%	3.2	Gage
106	Pivot pin true position		.40%	3.2	Gage
107	Perpendicularity of side to bottom face		.40%	3.2	Gage
108	Slider height		.40%	3.2	Gage
109	Slider width		.40%	3.2	Gage
110	Center cavity width		.40%	3.2	Gage
Minor					
201	Cable hole diameter		.65%	3.2	Gage
202	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332273
4.4.2.9	Mechanism Assembly, Setback-Zig-Zag				NEXT HIGHER ASSEMBLY 9332254
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Non-arm test		100%	3.18	4.5.10
2	Components missing		100%	3.2	Visual
3	Setback weight reset capability		100%	3.20	4.5.12
Major					
101	Pin not properly staked		.40%	3.2	Visual
102	Post diameter, top		.40%	3.2	Gage
103	Post diameter, bottom		.40%	3.2	Gage
104	Post length		.40%	3.2	Gage
105	Arming test		.40	3.19	4.5.11
Minor					
201	Weight diameter		.65%	3.2	GAge
202	Weight length		.65%	3.2	Gage
203	Evidence of poor workmanship		.65%	3.22	Visual
NOTES:					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332261
4.4.2.10	Pin, Shear				NEXT HIGHER ASSEMBLY 9332254
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defnined				
Major					
101	Pin diameter		.40%	3.2	Gage
102	Pin length		.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332260
4.4.2.11	Cushion				NEXT HIGHER ASSEMBLY 9332254
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defnined				
Major					
101	Surface density not uniform (Dwg Note 3)		.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332257
4.4.2.12	Wafer, Ignition				NEXT HIGHER ASSEMBLY 9332254
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defnined				
Major					
101	Surface improper (Dwg Note 3)	25(a)		3.2	Visual
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

(a) 25 per lot

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332254
4.4.2.13	Assembly, Igniter				NEXT HIGHER ASSEMBLY 9332222
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Set-back weight not in up position		100%	3.2	Visual
2	Firing pin not resting on cam		100%	3.2	Visual
3	Shear pin missing or not properly assembled		100%	3.2	Visual
4	Retaining ring not firmly seated		100%	3.2	Visual
Major					
101	Pull and function test	10		3.17	4.5.9
102	O-ring missing or not greased		.40%	3.2	Visual
103	Presence of foreign particles		.40%	3.2	Visual
Minor					
201	Cure time and temperature of adhesive		100%		Chart
202	Pin flush (Dwg Note 5)		.65%	3.2	Visual
203	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332270
4.4.2.14	Raceway				NEXT HIGHER ASSEMBLY 9332244
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defnined				
Major					
101	Thru hole obstruction		.40%	3.2	Visual
102	Inside diameter		.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-63377(AR)

PARAGRAPH	TITLE		SHEET	OF	DRAWING NUMBER
4.4.2.15	Assembly, Charge		1	1	9298752
					NEXT HIGHER ASSEMBLY 9332220
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defnined				
Major					
101	Ruptured container		.40%	3.2	Visual
102	Loose powder		.40%	3.2	Visual
103	Foreign materials		.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332243
4.4.2.16	Case				NEXT HIGHER ASSEMBLY 9332243
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defnined				
Major					
101	Surface imperfection		.40%	3.2	Visual
102	Wall thickness		.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332242
4.4.2.17	Case Assembly				NEXT HIGHER ASSEMBLY 9332241
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defnined				
Major					
101	Improper position of raceway		.40%	3.2	Gage
Minor					
201	Incorrect coiling direction of cable		.65%	3.2	Visual
202	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332241
4.4.2.18	Case Assembly, Insulated				NEXT HIGHER ASSEMBLY 9332240
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defnined				
Major					
101	Uniform coverage	10(a)		3.2	Visual
102	Cure time and temperature		100%	3.2	Chart
103	Shelf life		100%	3.2	Chart
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:
(a) 10 per day's production. Accept (0); Reject (1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332240
4.4.2.19	Case Assembly, Tack Coated				NEXT HIGHER ASSEMBLY 9332239
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defnined				
Major					
101	Liner quantity		.40%	3.2	Weight
102	Cure time and temperature		100%	3.2	Charts
103	Full coverage of liner		.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.20	Gas Generator				9332277
					NEXT HIGHER ASSEMBLY 9332237
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Non-function test		100%	3.14	4.5.7
Major					
101	Outside diameter		.40%	3.2	Gage
102	Diameter of retainer grooves		.40%	3.2	Gage
103	Distance between retainer grooves		.40%	3.2	Gage
104	Output, functioning	30(a)		3.15	4.5.8
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES: (a) 10 at +140°F ± 5°F; 10 at 70°F ± 5°F; 10 at -25°F ± 5°F. Test must be performed within 1 minute from the time the unit is removed from the conditioning box. Minimum temperature conditioning time is 4 hours.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332239
4.4.2.21	Case Assembly, Loaded				NEXT HIGHER ASSEMBLY 9332238
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Flare candle test	50		3.5	4.5.14
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332222
4.4.2.22	Candle and Parachute Assembly				NEXT HIGHER ASSEMBLY 9332220
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Forward oval sleeve position dimensions, incorrect		.40%	3.2	Gage
102	Swaged oval sleeve pull test	10(a)		3.2	Test
103	Aft swaged oval sleeve pull test	10(a)		3.2	Test
104	Assembly components loose after crimps or crimps incomplete or missing		.40%	3.2	Visual/Manual
105	Part missing or improperly installed		.40%	3.2	Visual
106	Tape not removed from parachute assembly		.40%	3.2	Visual
107	Loop incorrect or missing on pusher plate		.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:
(a) One (1) or more pull test failures shall reject the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332251
4.4.2.23	Parachute, Main				NEXT HIGHER ASSEMBLY 9332250
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Stitch type	20(a)		3.2	Visual
102	Stitching incorrect (Dwg notes 3, 4 & 5)	20(a)		3.2	Visual
103	Minimum breakstrength of vent center line (detail M)	20(a)		3.2	Gage
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:
(a) 20 per lot. Accept (0); Reject (1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332252
4.4.2.24	Container, Deployment				NEXT HIGHER ASSEMBLY 9332250
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None Defined				
Minor					
201	Edge not smooth		.65%	3.2	Visual
202	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332250
4.4.2.25	Parachute Assembly				NEXT HIGHER ASSEMBLY 9332252
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Presence of threads (Dwg notes 4 & 5)	10(a)		3.2	Visual
102	Presence of bights	10(a)		3.2	Visual
103	Improper folding techniques	10(a)		3.2	Visual
104	Presence of rubber band, tape & packing disc	10(a)		3.2	Visual
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:
(a) 10 per lot. Accept (0); Reject (1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332249
4.4.2.26	Insert, Main Parachute				NEXT HIGHER ASSEMBLY 9332222
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of "O" ring grooves		.40%	3.2	Gage
102	Width "O" ring grooves		.40%	3.2	Gage
103	Location of "O" ring grooves		.40%	3.2	Gage
104	Surface finish "O" ring grooves		.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332245
4.4.2.27	Fitting and Cable Assembly				NEXT HIGHER ASSEMBLY 9332242
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pull test on cable loop swage	10(a)		3.2	Test
102	Pull test on stop sleeve	10(a)		3.2	Test
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:
(a) One (1) or more pull test failures shall reject the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332221
4.4.2.28	Separation and Drogue Release Assembly				NEXT HIGHER ASSEMBLY 9332220
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	"O" ring or grease missing		.40%	3.2	Visual
102	Shear pin missing or not properly done (Dwg note 3)		.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual
NOTES:					

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332236
4.4.2.29	Parachute, Drogue				NEXT HIGHER ASSEMBLY 9332237
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Stitches (Dwg note 3, 4, 7, 8 & 9)	20(a)		3.2	Visual
102	Correct knots or attach line (View E)	20(a)		3.2	Visual
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:
(a) 20 per lot. Accept (0); Reject (1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.30	Housing, Drogue Chute	1 OF 1	9332230
			NEXT HIGHER ASSEMBLY: 9332237

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter "O" ring groove		.40%	3.2	Gage
102	True position of "O" ring groove		.40%	3.2	Gage
103	Width "O" ring groove		.40%	3.2	Gage
104	Finish "O" ring groove		.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332237
4.4.2.31	Drogue and Housing Assembly				NEXT HIGHER ASSEMBLY 9332221
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pull test on swaged sleeve	10(a)		3.2	Test
102	Parts missing or improperly installed		.40%	3.2	Visual
103	Break line damaged or knots incorrectly tied		.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:
(a) One (1) or more pull test failures shall reject the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 9332226
4.4.2.32	Adapter, Motor		NEXT HIGHER ASSEMBLY 9332225

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Base thread major diameter		.40%	3.2	Gage
102	Diameter of base at rear of thread		.40%	3.2	Gage
103	Runout of diameter of base		.40%	3.2	Gage
104	Length, minimum, face forward of thread to base		.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332225
4.4.2.33	Adapter Assembly, Motor				NEXT HIGHER ASSEMBLY 9332224
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Cable pull test	10(a)		3.2	Test
102	Stop sleeve not firmly affixed		.40%	3.2	Visual/Manual
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:
(a) One (1) or more pull test failures shall reject the lot. This test shall be performed on the First Article Sample only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.34	Motor Adapter & Fuze Assembly	1 OF 1	9332224
			NEXT HIGHER ASSEMBLY: 9332221

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Incorrect coil wrap		.40%	3.2	Visual
102	Incorrect number of spacer		.40%	3.2	Visual
103	Presence of fuze		.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332231
4.4.2.35	Block, Retainer				NEXT HIGHER ASSEMBLY 9332237
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Block outside diameter		.40%	3.2	Gage
102	Block height		.40%	3.2	Gage
103	Separation charge cavity diameter		.40%	3.2	Gage
104	Separation charge cavity depth		.40%	3.2	Gage
105	Gas generator thru hole diameter		.40%	3.2	Gage
106	Gas generator thru hole depth		.40%	3.2	Gage
107	Counterbore diameter		.40%	3.2	Gage
108	Counterbore depth		.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9332281
4.4.2.36	Pin, Shear				NEXT HIGHER ASSEMBLY 9332220 & 9332221
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Shank diameter		.40%	3.2	Gage
102	Expanded diameter		.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.37	Warhead, 2.75 Inch Rocket Flare M257				9332220
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	All pins not in place (Dwg note 3)		.40%	3.2	Visual
102	Evidence of physical damage		.40%	3.2	Visual
103	Marking missing, incomplete, or illegible		.40%	3.2	Visual
104	Leak test			3.11	4.5.6
105	Functional straightness of warhead and motor	Note 1		3.13	Gage
106	RTV not properly applied (Dwg note 7)		.40%	3.2	Visual
107	Paint on igniter closure		.40%	3.2	Visual
108	Ballistic test	36		3.4	4.5.13
Minor					
201	Evidence of poor workmanship		.65%	3.22	Visual

NOTES:

1. The number of sample units shall be fifty (50) samples per lot. Accept (1), reject (2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection.

PRECAUTION: This specification covers sampling and testing of chemical, toxic, or explosive materials which are potentially hazardous to personnel. Accordingly, it is emphasized that all applicable safety rules, regulations, and procedures must be followed in handling and processing these materials.

4.5.1 Materials, components and processes. Compliance with all requirements of section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all componentns (parts, subassemblies and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.1.1 Visual and mechanical inspections. The visual, manual and mechanical inspections and tests shall verify compliance with the requirements of Sections 3 and 5 of this specification in accordance with 4.4.2 herein and Table I.

4.5.2 Rough handling test. The rough handling test shall be performed as follows on each of thirty-six (36) warheads for First article Testing only.

Each warhead shall be packed in its shipping container (Dwg. No. 8883478). The test warheads are to be positioned at the top of the box with the warhead nose in one direction and dummy loads utilized in the other fiber containers. The warheads shall be equally divided and temperature conditioned to -25°F ± 5°F, 70°F ± 5°, and 140°F ± 5°F. The conditioning time shall be 8 hours minimum and 24 hours maximum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

Each box (Dwg. 9357963 or 8883479) shall be subjected to a seven-foot drop test. Each box shall be dropped seven feet onto a steel plate which is solidly supported by concrete. The orientations of the boxes on striking are:

a. Eighteen (18) warheads (6 boxes - 2 from each temeprature condition) warhead nose down (longitudinal axis 45° from vertical).

b. Eighteen (18) warheads(6 boxes - 2 from each temperature condition) warhead base down (longitudinal axis 45° from vertical).

No individual box shall be subjected to more than one drop. The drop equipment and stand shall be capable of providing an unimpeded free fall prior to striking the plate and permit rebounding. Prior to performing this drop test, the following is necessary.

a. X-ray each round in two planes, 90° opposed. Verify all components are secure and no armed fuzes are evident.

b. Visually verify that the zig-zag setback weight is in the up and safe position.

c. Before dropping, each packaged warhead and box shall be visually examined for evidence of incorrect packaging.

d. Mark each warhead with an X-ray plane.

e. Serialize each warhead.

After performing the drop test on all warheads, each round shall be x-rayed, utilizing the same plane reference established during x-ray prior to the drop test. A visual examination shall be performed. The first article shall be rejected if one or more warheads are found to be not safe, as a result of the effects of the seven-foot drop test.

If no safety hazard is noted, the warheads will be removed from the boxes and placed on an approved package tester in their fiber containers for the loose cargo test. The warheads shall not be tied down in any manner inside the tester. The warheads shall be equally divided and temperature conditioned to -25°F $\pm$ 5°F, 70°F $\pm$ 5°F, and +140°F $\pm$ 5°F. The conditioning time shall be 8 hours minimum and 24 hours maximum. The tester shall then be vibrated for 30 minutes at a frequency of 5.0 Hertz at 1.3 g's.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:26Z
Check the source to verify that this is the currenversion before use.

Following the loose cargo test, the warheads shall be subjected to visual and x-ray examination. The first article shall be rejected if one or more warheads are found to be not safe as a result of the effects of the loose cargo test.

If no safety hazard is noted, six warheads (two conditioned to each specified temperature) shall be subjected to an unpackaged 5-foot drop test onto a steel plate which is solidly supported by concrete. The drop orientations of the warheads (at each specified temperature) on striking will be:

a. One warhead nose down with longitudinal axis 45 degrees from vertical

b. One warhead nose down with longitudinal axis vertical.

Following the 5-foot drop test, the warheads shall be subjected to visual and x-ray examination. The first article shall be rejected if one or more warheads are found to be not safe as a result of the effects of the 5-foot drop test. If no safety hazard is noted, all thirty-six (36) warheads may be ballistically tested in accordance with 4.5.12 for informational purposes.

4.5.3 Secured cargo vibration test. The secured cargo vibration test shall be performed as follows on each of thirty-six (36) warheads for First Article Testing only.

The sample warheads shall be packaged in accordance with Dwg. 8883478 except that dummy 2.75 Inch Rocket Motors shall be substituted. The warheads shall be equally divided and temperature conditioned to -25°F ± 5°F, 70°F, ± 5°F, and 140°F ± 5°F. The conditioning time shall be 8 hours minimum and 24 hours maximum.

The shipping boxes (Dwg. 9357963 and 8883479) shall be subjected to the vibration test in accordance with Method 514.2-7 of MIL-STD-810C. Resonance testing does not apply.

Prior to performing this test the following is necessary:

a. Serialize each round.

b. X-ray each round in two planes 90° apart. Verify all components are secure and no armed fuzes are evident.

c. Visually verify that the zig-zag setback weight is in the up and safe position.

d. Mark each warhead with an x-ray plane.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

Following the vibration test, each round shall be x-rayed, utilizing the same plane reference established during x-ray prior to the vibration test. A visual examination shall be performed. the first article shall be rejected in one or more warheads are found to be not safe as a result of the effects of the secured cargo vibration test.

If no safety hazard is noted, the warheads shall be ballistically tested in accordance with 4.5.12.

4.5.4 Helicopter vibration test. The helicopter vibration test shall be performed in accordance with Method 514.2, Category d.3, procedure IIC, Table 514.2-IVA and Figures 514.2-4B, 4C, 5D, 4E, 4F of MIL-STD-810C on each of nineteen (19) warheads for First Article Testing only.

The sample warheads, assembled with dummy 2.75 Inch Rocket Motors, shall be loaded in a government furnished launcher.

Prior to performing this test the following is necessary:

a. Serialize each round.

b. X-ray each round in two planes 90° apart. Verify all components are secure and no armed fuzes are evident.

c. Visually verify that the zig-zag setback weight is in the up and safe position.

d. Mark each warhead with an x-ray plane.

e. Temperature condition each round to 70°F ± 5°F for a minimum of 8 hours.

Following the vibration test, each warhead shall be x-rayed, utilizing the same plane reference established during x-ray prior to the vibration test. A visual examination shall be performed. The first article shall be rejected in one or more warheads are found to be not safe as a result of the effects of the helicopter vibration test.

If no safety hazard is noted, the warheads shall be ballistically tested in accordance with 4.5.12 at a temperature of 70°F ± 5°F, or within ten (10) minutes of removal from a conditioning box set to 70°F ± 5°F if a conditioning box is necessary.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:26Z
Check the source to verify that this is the current version before use.

4.5.5 Warhead forty-foot drop test. The Forty-foot Drop Test shall be performed on each of six (6) warheads as specified in MIL-STD-331 for First Article Testing only. The warheads shall be packed and packaged in accordance with Dwg. 8883478 and Dwg. 9357963 or 8883479 except that dummy 2.75 Inch Rocket Motors shall be substituted. Each box shall be subjected to a forty-foot drop test. The orientations of the boxes on striking shall be:

a. Three (3) warheads (1 box) warhead nose down (longitudinal axis 45° from vertical).

b. Three (3) warheads (1 box) warhead nose down (longitudinal axis 45° from vertical).

No individual box shall be subjected to more than one drop. Prior to performing this drop test, the following is necessary:

a. X-ray each round in two planes 90° opposed. Verify all components are secure and no armed fuzes are evident.

b. Visually verify that the zig-zag setback weight is in the up and safe position.

c. Before dropping, each packaged warhead and box shall be visually examined for evidence of incorrect packaging.

d. Mark each warhead with an x-ray plane.

e. Serialize each warhead.

After performing the drop test on all warheads, each round shall be x-rayed, utilizing the same plane reference established during x-ray prior to the drop test. A visual examination shall be performed. Any round found unsafe shall cause the first article sample to be rejected.

4.5.6 Leak test. Thirty-six (36) warheads from the First Article Inspection and from each of the first two production lots and 24 warheads from each subsequent lot shall be subjected to the leak test. The warhead shall be tested in a water tank equipped for observation under vacuum. Water temperature shall be within the range of 45°F to 75°F.

The water tank shall be equipped so that the warhead must be raised above the water level while still under vacuum before the vacuum can be released and the warhead removed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

The warhead shall be submerged in a horizontal position to a depth of four to six inches below the surface of the water as measured from the upper surface of the warhead. The water tank shall then be subjected to a vacuum. Leaks are defined as a steady stream of bubbles escaping from the warhead.

The warhead shall not leak when exposed to a vacuum of 6.0 ± 1.0 inches of mercury pressure differential for a period of not less than 60 seconds. Warheads that meet the leak test requirement may be returned to the production lot.

Lot acceptance or rejection will be as follows:

Sample Size	Accept	Reject
36 units	3 failures	4 failures
24 units	2 failures	3 failures

4.5.7 Gas generator non-function test. For First Article, the gas generator sample shall be subjected to a static extraction force of 20 pounds on the sear. The First Article sample shall be rejected if one or more gas generator function. For production, each gas generator shall be subjected to a static extraction force of 10 pounds on the sear. The unit shall be considered defective if there is sear movement or gas generator function. All defective units shall be recorded and rejected from the lot.

4.5.8 Gas generator and expulsion charge function test. This test shall be performed with the gas generator and expulsion charge mounted on the retainer block. The retainer block in turn shall be held in an appropriate fixture. The sear shall be extract per Dwg. 9332277 except the angle of extraction must be maintained at 30° ± 2° as measured from center line. A gas generator shall be considered defective if the sear is not extracted per the requirements, the delay time is improper after extracting the sear, the body is broken after extracting the sear or no output functioning, or the output charge fails to ignite the expulsion charge. The lot shall be rejected if one or more gas generators are classed defective.

4.5.9 Igniter assembly functional test. Ten (10) igniter assemblies shall be selected from each eight hours production. Each assembly shall be armed by means acceptable to the government. No arming data shall be recorded. Each assembly shall then be subjected to a shear pin test by applying a force of forty (40) pounds minimum and sixty-five (65) pounds maximum to the cable assembly. This force shall be applied as indicated on the drawing. Any one igniter that does not function (boron pellets fail to fully function) after application of the specified pull force shall cause the previous eight hours of igniter assemblies to be rejected.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:26Z
Check the source to verify that this is the currentversion before use.

4.5.10 Ziz-zag setback mechanism assembly non-arm test. The zig-zag setback mechanism assembly shall be assembled to an approved test equipment. The equipment shall accelerate the zig-zag setback mechanism assembly to 16 g's plus or minus 0.50 g's for a minimum of 3 seconds in the direction specified on the drawing. The equipment shall be capable of restraining the movement of the setback weight until the desired level of G force has been reached. The setback weight shall remain in the unarmed and safe condition after the test. Any zig-zag setback mechanism assembly that fails the requirement shall be classed defective.

4.5.11 Zig-zag setback mechanism assembly arming test. The zig-zag setback mechansim assembly shall be assembled to an approved test equipment. The equipment shall accelerate the zig-zag setback mechanism assembly to 22 g's plus or minus 0.50 g's for a maximum of 1 second in the direction specified on the drawing. The equipment shall be capable of restraining the movement of the setback weight until the desired level of G force has been reached. The setback weight shall be in the armed and locked condition after the test. Any zig-zag setback mechanism assembly that fails the requirement shall be classed defective.

4.5.12 Zig-zag setback mechanism assembly reset capability test. The zig-zag setback mechanism assembly shall be held in a fixture. The setback weight shall be manually moved down the post a distance of .375" min and .400' max from the fully safe position and released. Observation shall be made for setback weight return to the fully safe position. Any zig-zag setback mechanism assembly that fails the requirement shall be classed defective.

4.5.13 Ballistic test. A sample of thirty-six (36) warheads shall be randomly selected. Each sample shall be equally divided and conditioned to the three temperatures specified (12 warheads at -25°F + 5°, 12 warheads at 70°F + 5°F, 12 warheads at 140°F + 5°F) and ballistically fired. Minimum conditioning time shall be 8 hours. A rocket motor shall be assembled to the warhead and temperature conditioned. The complete round may be removed from the conditioning cabinet and transported to a test site in an insulated container. Temperature limits as specified above, shall be maintained. Each firing shall occur within five minutes from the time the complete round is removed from the cabinet/container. A complete round left out of the conditioning cabinet/container over five minutes prior to firing shall be placed at ambient temperature for not less than eight hours and then reconditioned to the applicable temperature. The rocket shall be fired from a suitable launcher at a Q.E. of about 25° from the ground.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

A round shall be condsidered defective if it fails to function in accordance with any of the following requirements:

a. Function Time - The time between rocket motor ignition pulse and flare ignition (first light). This time shall be 13.0 ± 2.0 seconds or 13.5 ± 2.0 seconds depending on type of motor used (see 3.4.1). Time may be measured by means acceptable to the Government Technical Agency.

b. Descent Characteristic - The burning flare shall descend on the parachute for a minimum of 90 seconds, after ignition and before ground contact. Time may be measured by means acceptable to the Government Technical Agency.

c. Flare Burn Time - The flare candle shall burn for a minimum of 100 seconds. Burn time upon ground impact shall be included. Time may be measured by means acceptable to the Government Technical Agency.

Lot acceptance or rejection will be as follows:

Test	Sample Size	Accept	Reject
First Article	91	8 failures	9 failures
Production	36	5 failures	6 failures

4.5.14 Flare candle test. The Flare Candle Test shall be performed at the contractor's facility. A minimum of fifty (50) flare candles shall be selected for the first article quantity and subjected to an output test when static tested on a light measuring tower. In addition, from each production lot of flare candles produced, a minimum of fifty (50) flare candles shall be selected and subjected to an output test when static tested on a light measuring tower. Flare candles shall be accepted or rejected in accordance with MIL-STD-414, normal inspection, variability unknown, standard deviation method, Single Specification Limit Form 1, AQL = 6.5% (Table B-1).

The sample of candle assemblies shall be in accordance with Dwg. 9332239.

The samples shall be less Parachute Assembly and Igniter Assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation and packing.

5.1.1 Level A. The warhead shall be preserved and packaged in accordance with drawing 9294519.

5.1.2 Level B. The warhead shall be preserved and packaged in accordance with drawing 9294519.

5.1.3 Level C. The warhead shall be preserved and packaged in accordance with drawing 9340646.

5.2 Packing.

5.2.1 Level A. When shipping warheads with MK66 motors, packing shall be in accordance with drawing 12624792. When shipping warheads alone, packing shall be in accordance with drawing 9294492.

5.2.2 Level B. When shipping warheads with MK66 motors, packing shall be in accordance with drawing 12624792. When shipping warheads alone, packing shall be in accordance with drawing 9294492.

5.2.3 Level C. The packages in 5.1.3 shall be packed in accordance with drawing 9347035.

5.3 Marking.

5.3.1 Level A. Marking shall be in accordance with drawings 9294519, 9294492, and 12624792.

5.3.2 Level B. Marking shall be in accordance with drawings 9294519, 9294492, and 12624792.

5.3.3 Level C. Marking shall be in accordance with drawings 9340646 and 9340647.

5.4 Unitization.

5.4.1 Level A. The packages shall be unitized in accordance with drawing 19-48-4116/80M.

5.4.2 Level B. The packages shall be unitized in accordance with drawing 19-48-4116/80M.

5.4.3 Level C. The packages in 5.1.3 shall be unitized in accordance with drawing 9347035.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

5.5 Shipping. When warheads from more than one lot are shipped at the same time, each lot shall be kept separate and the division between lots clearly indicated to prevent the mixing of lots in transit.

6. NOTES

6.1 Intended use. The components covered by this plan are intended for use on the M257 Flare Warhead for the 2.75 Inch rocket.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. When specified in the Contract Data Requirement List, DD Form 1423, submit equipment designs as necessary to Commander, AMCCOM, ATTN: AMSMC-QAF-I(D), Dover, NJ 07801-5001.

6.4 Objective evidence.

6.4.1 General. Records of contractor quality control and inspections which can be verified. When test data (see 6.5) is required, the data shall be submitted in accordance with DI-R-1724, DI-T-3718 specified on DD form 1423 incorporated in the contract.

6.4.2 Source control and specification control drawings. Certificate of conformance from the supplier certifying that the item complies with drawing requirements.

6.4.3 Material. Certificate of conformance certifying that material complies with drawing and quality assurance plan requirements.

6.4.4 Protective finish. The contractor shall supply test data for all tests specified in the specifications required on the drawing.

6.5 Subject term (key word) listing.

Military specification
Warhead
Fuze
Pyrotechnics (flare)
Rocket (Hydra 70)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

6.6 Definition of packaging and packing levels.

6.6.1 Level A. A full military protection for unrestricted (OCONUS) shipment and storage.

6.6.2 Level B. Limited military protection for limited (OCONUS) shipment and storage.

6.6.3 Level C. For interplant (CONUS) shipment and very limited storage.

6.6.4 Additional information. For further detailed information concerning packaging and packing levels, consult AR-700-15.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1340-A668)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-W-63377	WARHEAD, ILLUMINATING, M257, W/M442 FUZE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:26Z
Check the source to verify that this is the current version before use.