INCH-POUND

MIL-C-60111C
AMENDMENT 3
16 April 1993
SUPERSEDING
AMENDMENT 2
1 June 1991

MILITARY SPECIFICATION

CARTRIDGE, 5.56MM, TRACER, M196

This Amendment forms a part of Military Specification MIL-C-60111C, dated 15 October 1976, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.1, Delete in its entirety and substitute the following:

"1.1 This specification covers Cartridge, 5.56mm, Tracer, M196 for use in the M16 and M16A1 Rifles and the M231 Port Firing Weapon."

PAGE 2

2.1, Delete:

"10534605 - Packing and Marking, Cartridges, 5.56mm, Cartons; Bandoleers; Box, Ammunition, M2A1; Box, Wirebound"

Substitute:

"12551963 - Packing and Marking for Box Wirebound for Cartridge 5.56mm"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:10Z
Check the source to verify that this is the current version before use.

2.1, Delete the following:

"10535858 - Packing and Marking, Cartridges, 5.56mm; Cartons; Box, Ammunition, M2A1; Box, Wirebound

10542258 - Packing and Marking, Cartridges, 5.56mm; 10Rd. Clips; Cartons; Bandoleers; Box, Ammunition, M2A1; Box, Wirebound

11735709 - Packing and Marking, Cartridges, 5.56mm; 10Rd. Clips; Cartons; Bandoleer M8; Box,Ammunition, M2A1; Box, Wirebound"

PAGE 4

3.12, Delete in its entirety and substitute the following:

"3.12 Function and casualty. The cartridge shall function without casualty at ambient temperature and under the conditions specified in 3.11 when fired in the M16 or M16A1 Rifles and the M231 Port Firing Weapon."

3.14, Delete in its entirety and substitute the following:

"3.14 Fouling. The fouling accumulated in the weapon during the firing of 1000 sample cartridges shall not cause failure of the weapon to function when fired in the M16 or M16A1 Rifles and the M231 Port Firing Weapon."

Add the following paragraph:

"3.15.3 Bullet tip identification. Each cartridge shall be marked on the bullet tip with the appropriate color of paint in accordance with the applicable drawing(s). Prior to linking, clipping or insertion into cartons, cartridges missing up to 10% of the required bullet tip identification shall be acceptable. Following any necessary handling or orientation and after linking or clipping or prior to insertion into cartons, cartridges missing up to 40% of the required bullet tip identification shall be acceptable."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:10Z
Check the source to verify that this is the current version before use.

4.2.1, Delete in its entirety and substitute the following:

"4.2.1 Initial production sample. At the beginning of regular production, a sample of 5200 cartridges shall be submitted in accordance with contract requirements. In addition, 100 bullets shall be submitted for visual and dimensional examinations. The sample shall be manufactured using the same materials, equipment, processes, and procedures as will be used in regular production. All parts and materials, including packaging and packing, shall be the same as used for regular production and shall be obtained from the same source of supply."

* 4.3.2, Delete in its entirety and substitute the following:

"4.3.2 Examination. 100% examination shall be performed for all critical and special defects. Examination for major and minor defects shall be performed on a class basis in accordance with the classification of defects, Table I, using applicable sampling plans and acceptance criteria of MIL-STD-105. The Acceptable Quality Level (AQL) for the major class shall be 1.50%. Examination shall be visual or gage and weigh or by means of Government approved automated inspection system such as optical, mechanical or electrical. All non-conforming cartridges shall be rejected. If a visual critical defect is found in a sample either just prior to a firing test or after a firing test (and the defect is not due to the firing) the lot shall be rejected. The lot shall be rescreened and resubmitted for visual inspection of critical defects. If a critical defect is found during packing, the portion of the lot that has been packed or is in the process of being packed shall be rejected. In addition the portion of the lot remaining to be packed shall be rejected. The lot shall then be rescreened and resubmitted for visual inspection of critical defects."

Table 1, add the following:

"3. Incomplete or missing tip identification (red) 3/, Minor x"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:10Z
Check the source to verify that this is the current version before use.

* Delete Characteristics 32, 33 and 34 in their entirety and substitute the following:

No.	Defect and Method of Inspection	Critical	Special	Major	Minor	Major or Minor
"32.	No Primer		X 4/			
33.	Cocked Primer		X 4/			
34.	Inverted Primer		X 4/"			

* Delete characteristic 37 in its entirety and substitute the following:

No.	Defect and Method of Inspection	Critical	Special	Major	Minor	Major or Minor
"37.	Insufficient/smeared waterproofing material (primer pocket joint)"			X		

Bottom of Table 1, add the following:

"3/ Reference paragraph 3.15.3

* "4/ Refer to MIL-A-48078, para 6.5.4, for the definition of a special defect"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:10Z
Check the source to verify that this is the current version before use.

4.3.3.1 Table II, Delete in its entirety and substitute the following:

TABLE II

Test	Number of Cartridges: Ambient Temp.	70 ± 2°F	Low Temp. (see 4.4.10.1)	High Temp. (See 4.4.10.2	Requirement Para.
Bullet extraction 1/	25				3.2
Residual stress (mercurous nitrate 1/	50				3.3
Airtightness of base closure seal 2/	--				3.5
Waterproof 3/	50				3.4
Accuracy 4/	90				3.6
Trace 5/	100				3.7
Velocity 6/		20	20	20	3.8 & 3.11
Chamber pressure 6/		20	20	20	3.9 & 3.11
Port pressure 6/		--	--	--	3.10 & 3.11
Function & casualty 7/					
Rifle, M16 or M16A1			360	360	3.12 & 3.11
M231 Port Firing Weapon	360		360	360	3.12 & 3.11
Fouling 8/					
Rifle, M16 or M16A1	1000				3.14
M231 Port Firing Weapon	1000				3.14
Bullet integrity 10/	100				3.13
Hardness					
Head 9/	10				Drawing
Sidewall 4/	10				Drawing

4.4.11, Delete in its entirety and substitute the following:

"4.4.11 Function and casualty. This test shall be conducted in accordance with SCATP-5.56mm and 4.4.10 except that 30-round magazines loaded with 30 rounds each shall be used instead of the stated 20-round magazines. When the M231 Port Firing Weapon is used, 30-round bursts and short bursts (3-5 rounds) shall be fired from alternate magazines. Two M16 or M16A1 Rifles and two M231 Port Firing Weapons shall be used and the following number of cartridges shall be fired in each:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:10Z
Check the source to verify that this is the current version before use.

	First Sample	Second Sample (if required)
Ambient Temperature	180	360
Low Temperature	180	360
High Temperature	180	360"

4.4.12, Delete in its entirety and substitute the following:

"4.4.12 Fouling. The test shall be conducted in accordance with SCATP-5.56 except that 30-round magazines loaded with 30 rounds each shall be used instead of the stated 20-round magazines. When the M231 Port Firing Weapon is used, the semi-automatic mode consists of short (3-5 rounds) bursts."

PAGE 14

5.1, Delete "F10535858, F105342258, F10544605, or F11735709." and replace with "12551963".

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR
Air Force-99

User Activity:
Navy-OS, MC

Preparing activity:
Army-AR

(Project 1305-OE46)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:10Z
Check the source to verify that this is the current version before use.