INCH-POUND

MIL-C-60537 (AR)
AMENDMENT 6
28 October 1992
SUPERSEDING
AMENDMENT 5
30 April 1991

MILITARY SPECIFICATION

CARTRIDGE; GRENADE: 5.56MM, M195

This amendment forms a part of MIL-C-60537 (MU), dated 23 August 1966, is approved for use by the U.S. Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

**PAGE 1**

Title: Delete "XM195" and substitute "M195". Make similar model change wherever "XM195" appears in the specification.

**PAGE 2**

* 2.1, under Publications: Delete "AMSMU-P715-501FA1" in its entirety and substitute the following:

"SCATP-5.56mm - Test Procedures for 5.56mm Cartridges"

3.4: Delete in its entirety and substitute the following:

"3.4 Waterproof. Cartridges shall have a minimum velocity of 140 fps after being submerged under twelve inches (12") of water for 24 hours."

3.5, line 1: Delete "The sample cartridges fired in a horizontal position and" and substitute "The sample cartridges conditioned for a minimum of 4 hours and fired in a horizontal position."



**DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.**

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:42Z
Check the source to verify that this is the current version before use.

**PAGE 3**

3.8: Delete in its entirety.

4.2.1: Delete in its entirety and substitute the following:

"4.2.1 Initial production sample. At the beginning of regular production, a sample shall be submitted in accordance with the contract requirements and shall consist of 550 cartridges. The sample shall be manufactured using the same material, equipment, processes and procedures as will be used for regular production and shall be obtained from the same source of supply."

**PAGE 4**

* 4.3.2: Delete in its entirety and substitute the following:

"4.3.2 Examination. One hundred percent examination shall be performed for all critical and special defects. Examination for major and minor defects shall be performed in accordance with the classification of defects, Table I, using applicable sampling plans and acceptance criteria of MIL-STD-105. Examination shall be visual or by means of a government approved automated inspection system such as optical, mechanical, or electronic. The acceptable quality level (AQL) for the major class shall be .25% and for the minor class the AQL will be 1.50%. All nonconforming cartridges will be rejected. If a visual critical defect is found in a sample either just prior to a firing test or after a firing test (and the defect is not caused by the firing), the lot shall be rejected, rescreened, and resubmitted for visual inspection of critical defects. Likewise, if a visual critical defect is found during packing, that portion of the lot that has been packed, is in the process of being packed, or is remaining to be packed will be rejected, rescreened, resubmitted for visual inspection of critical defects. Screening of lots containing special defects will be conducted in accordance with Note 2, Table I and Table III. Both critical and special defects will be subject to the preparation of a detailed failure analysis report which will be made out and submitted directly to the Government Engineering Center at ARDEC, Picatinny Arsenal, NJ, 07806-5000, ATTN: SMCAR-CCL-S, and to the local Government Product Assurance Office/Government Quality Assurance Representative."



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:42Z
Check the source to verify that this is the current version before use.

**PAGES 4 and 5**

* 4.3.2.1, under Table I: Add a column for "Special" between "Critical" and "Major". Delete characteristic 32, 33, and 34 in their entirety and substitute the following:

"

| No. | Defect and Method of Inspection | Critical | Special | Major | Minor |
|---|---|---|---|---|---|
| 32 | No primer[2/] | | X | | |
| 33 | Cocked primer[2/] | | X | | |
| 34 | Inverted primer[2/] | | X | | |

"

Add the following note at the bottom of Table I:

"[2/] All cartridges exhibiting special defects will be immediately removed from the lot being inspected and disposed of after having been subject to proper failure analysis. The lot will then be rescreened prior to being presented for acceptance. Special defects are defined in paragraph 6.5.4 of MIL-STD-48078."

**PAGE 6**

4.3.3.1, Table II - Under Test: After Function and Casualty delete "5/" and substitute "4".

Delete "Primer Sensitivity 6/, 3.8".

**PAGE 7**

4.3.3.1: Delete footnote "5/" in its entirety.

* 4.3.3.2, Table III: Add the following under defect number 2:

"

| | Defects | First Sample | Cumulative First and Second Sample |
|---|---|---|---|
| f | No primer, cocked primer, inverted primer | 0 | 1 |

"



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:42Z
Check the source to verify that this is the current version before use.

**PAGE 8**

* 4.4.1: Delete "AMSMU-P715-501FA1" and substitute "SCATP-5.56mm".

**PAGE 9**

4.4.2: Delete in its entirety and substitute the following:

"4.4.2 Waterproof. The water in the tank shall be between 65°F and 75°F for the duration of the test. The cartridges shall be submerged upright to a depth of 12" from the top of the cartridge for 24 hours. After 24 hours, the cartridges shall be removed from the water bath and towel dried. The cartridges shall then be fired for velocity in accordance with Appendix A."

4.4.6: Delete in its entirety.

4.4.7: Change paragraph number to 4.4.6.

**APPENDIX A**

* 3.2.3.1: Delete in its entirety.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1330-A372)



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:42Z
Check the source to verify that this is the current version before use.