INCH-POUND

MIL-C-70734 (AR)
AMENDMENT 2
05 July 1993
SUPERSEDING
AMENDMENT 1
09 September 1991

MILITARY SPECIFICATION

CONTAINER, AMMUNITION, METAL PA113, FOR CANISTER, VOLCANO MINE M87/M88

This Amendment forms a part of Military Specification MIL-C-70734 (AR), dated 6 October 1987, and is approved for use by the US Army, Armament, Munitions and Chemical Command and is available for use by all the Departments and Agencies of the Department of Defense.

PAGE 1

* 1.1, last line: Delete "M87/M88 VOLCANO" and substitute "M87/M88/M89 VOLCANO".

PAGE 2

* 2.1.2: Delete drawing 9390404 in its entirety and substitute the following:

"9390404 - Canister, Ammo, Metal, PA113, for Canisters Mine, M87; Practice, M88; Training, M89".

PAGE 3

3.3.1, Tensile strength: Delete drawing number "12630901" and substitute "9386828".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

PAGE 6

Table I. First article inspection, Page 1 of 2:

Cover assembly: "Delete "9378170" and substitute "9386824".

Body: Delete "12630901" and substitute "9386828".

PAGE 7

Table I. First article inspection, Page 2 of 2:

Gasket: Delete "9378178" and substitute "12910349".

PAGE 12

4.4.2.4, Shaft: Delete paragraph in its entirety and substitute new 4.4.2.4 included.

PAGE 13

4.4.2.5, Washer: Delete next higher assembly "9378170" and substitute "9386824".

PAGE 14

4.4.2.6, Retainer, washer: Delete next higher assembly "9378170" and substitute "9386824".

PAGE 15

4.4.2.7, Cover: Delete Drawing number "9378182" and substitute "9386821".

Delete next higher assembly "9378181" and substitute "9386822".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70734 (AR)
AMENDMENT 2

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Shaft	1 OF 1	9344037
			NEXT HIGHER ASSEMBLY: 9386824-2

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Length of hexagon segment of shaft	0.40%	3.2	Gage
102	Large diameter (two places)	0.40%	3.2	Gage
103	Small diameter (two places)	0.40%	3.2	Gage
104	Total length of large diameters and hexagon segments	0.40%	3.2	Gage
105	Small diameter segment not tangent to large diameter segment and side of hexagon segment	0.40%	3.2	Gage
106	Length of large diameter segment	0.40%	3.2	Gage
Minor				
201	Length of small diameter segment (two places)	0.65%	3.2	Gage
202	Poor workmanship	0.65%	3.7	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

PAGE 16

4.4.2.8, Gasket: Delete paragraph in its entirety and substitute new 4.4.2.8 included.

PAGE 17

4.4.2.9, Cover weldment: Delete Drawing number "9378181" and substitute "9386822".

Delete next higher assembly "9378170" and substitute "9386824".

Delete Major Defect 101 and 102 in their entirety.

PAGE 18

4.4.2.10, Cover assembly: Delete Drawing number "9378170" and substitute "9386824".

Major defect 103": Delete in its entirety and substitute the following:

"103 Air pressure 100% 3.2 4.5.7.3".

PAGE 19

4.4.2.11, Rim: Delete Drawing number "9375175" and substitute "9386827".

Major defect 103: delete "Inside" and substitute "Outside".

PAGE 20

4.4.2.12, Ring: Delete Drawing number "9378173" and substitute "9382826".

Major defect 103: Delete "Inside" and substitute "Outside".

Delete minor defect 201 in its entirety.

PAGE 21

4.4.2.13, Body: Delete Drawing number "12630901" and substitute "9386828".

PAGE 22

4.4.2.14, Plug, stacking: Delete Drawing number "9344045" and substitute "9386837".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70734 A(R)
AMENDMENT 2

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Gasket	1 OF 1	12910349
			NEXT HIGHER ASSEMBLY: 9386824-2

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material certification		3.2	Certification
102	Hardness test	5	3.2	4.5.6/Gage
103	Inside diameter, maximum	0.40%	3.2	Gage
104	Large width	0.40%	3.2	Gage
105	Middle width	0.40%	3.2	Gage
106	Height of rectangular cross section	0.40%	3.2	Gage
Minor				
201	Poor workmanship	0.65%	3.7	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

PAGE 23

4.4.2.15, Body weldment, prior to painting:

Major defect 101: Delete sample size "10" and subsitute "5".

Major defect 106: Delete "rings" and substitute "rim".

Delete Major defect 104 in its entirety.

Add new Major defect 108:

"108 Air pressure test 100% 3.2 4.5.7.3".

Minor defect 201: Delete sample size "10" and substitute "5".

Minor defect 202: Delete sample size "10" and substitute "5".

Delete Minor defect 203 in its entirety.

PAGE 26

4.4.2.18, Ring: Delete Major 102 and 103 in their entirety.

Major 104: Delete "Inside dimensions" and substitute "Dimension".

Add Minor defect 202 as follows:
"202 Drainage hole missing .65% 3.2 Visual".

PAGE 27

4.4.2.19, Container, ammo, metal, PA113:

Major defect 102: Delete "100%" and substitute ".40%".

PAGE 29

4.5.5, Tensile stress of gasket: Delete paragraph in its entirety.

4.5.7.1, Air pressure of painted container assembly: Delete paragraph in its entirety and substitute new 4.5.7.1 as follows:

"4.5.7.1 Air pressure test of painted container assembly. Subject the container assembly to the internal air pressure test, specified in dwg 9390404 for the test time specified. A container assembly, which exceeds the specified requirement shall be classed defective."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

Add new 4.5.7.3 as follows:

"4.5.7.3 Air pressure test of unpainted cover assembly and unpainted body weldment. Subject the cover assembly and body weldment to the internal air pressure specified in dwg 9390404 for the test time specified. For the cover assembly, apply the pressure when the cover assembly (equipped with a gasket is assembled to a master body weldment (or its equivalent). For the body weldment apply the pressure when the body weldment is assembled to a master cover (or equivalent) and gasket. The master cover and master body weldment shall be provided with satisfactory means for applying and maintaining the specified pressure requirement during the test. A cover assembly or body weldment which exceeds the requirement shall be classed defective.

PAGE 30

* 5.2: Delete in its entirety and substitute the following:

" 5.2 Packing. Packing shall be commercial. Metal ammunition containers shall be prepared in accordance with ASTM-D3951."

* 5.3, line 1: Delete "MIL-STD-1190" and substitute "ASTM-D3951".

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian
Army-AR

Preparing activity
Army-AR

(Project: 8140-A979)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.