INCH-POUND

MIL-DTL-48228B (AR)
w/ AMENDMENT 1
27 November 2017
SUPERSEDING
MIL-DTL-48228B (AR)
20 July 2017

MILITARY SPECIFICATION

BANDOLEERS FOR CARTRIDGES: 40MM AMMUNITION

Reactivated after 20 July 2017 and may be used for new and existing designs and acquisitions

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers two (2) types of Bandoleers for use in 40mm Ammunition: M406 & M386 and M433 accordingly.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 or 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all requirements of documents cited in sections 3 or 4 of this specification, whether or not they are listed.

Comments, suggestions, or questions on this document should be addressed to: Commander, US Army ARDEC, ATTN: RDAR-EIQ-SA, Picatinny Arsenal, New Jersey 07806-5000, or usarmy.picatinny.ardec.list.ardecstdzn-branch@mail.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST online database at https://assist.dla.mil.

AMSC N/A FSC 1310

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

2.2 Government documents.

2.2.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-W-530	Webbing, Textile, Cotton, General Purpose, Natural or in Color

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-1916	DoD Preferred Methods for Acceptance of Product

DEPARTMENT OF DEFENSE COMMERCIAL ITEM DESCRIPTIONS

A-A-59708	Cloth, Cotton, Aftertreated Water-Repellant, Water Repellant, and Mildew Resistant, Mildew Resistant

(Copies of these documents are available online at http://quicksearch.dla.mil or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094)

2.2.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC) DRAWINGS

8835107	Bandoleer for Cartridge 40mm
9278204	Bandoleer for Cartridge, 40mm, M433

(Copies of these drawings may be requested online at usarmy.picatinny.ardec.list.drawing-request-help-desk@mail.mil or from U.S. Army ARDEC, ATTN: RDAR-EIS-PE, Picatinny Arsenal, NJ 07806-5000).

2.3 Order of precedence. Unless otherwise specified in this document or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

3.1 Required inspections.

3.1.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.3.

3.1.2 Conformance. A sample shall be subjected to conformance inspection in accordance with 4.4.

3.2 Material, components and assemblies.

3.2.1 Bandoleer. The Bandoleer shall comply with all the requirements specified in Drawing 8835107 or 9278204 accordingly, its components and its assemblies.

3.2.1.1 Fastener. The fastener shall comply with the closing and opening requirements specified in Drawing 8835107 or 9278204 accordingly.

3.2.1.2 Stitching. Stitching shall be evenly spaced in regular lines and tight with thread endings securely fastened. Tack stitching shall be tight and in a straight line. Ends shall not unravel if pulled.

3.2.1.3 Water repelling and mildew resistance. Material shall conform to the water repellant and mildew resistance requirements as specified in Drawing 8835107 or 9278204 accordingly.

3.3 Workmanship. All parts and assemblies shall be free of tears, rips, burrs, sharp edges, chips, cracks, splits, dirt, rust, corrosion products and other foreign material. All parts shall be assembled without the presence of burn marks, tears, rips, scratches, dirt, grease, rust, corrosion products and other defects and foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat and sharply defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

TABLE I. Requirement/verification cross reference matrix.

Method of verification	Classes of verification
1 - Analysis	A - First article
2 - Demonstration	B - Conformance
3 - Examination	
4 - Test	

Section 3 requirement	Description	Verification methods				Verification class		Section 4 verification method
		1	2	3	4	A	B	
3.1.1	First article			X	X	X		4.3
3.1.2	Conformance			X	X		X	4.4
3.2.1	Bandoleer			X	X	X	X	4.4.2.1
3.2.1.1	Fastener			X	X	X	X	4.5.1
3.2.1.2	Stitching			X	X	X	X	4.5.2
3.2.1.3	Water repelling and mildew resistance			X	X	X	X	4.5.3
3.3	Workmanship			X		X	X	4.3.2, 4.4.2.1, 4.6

4.1 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Conformance inspection (see 4.4).

4.2 Inspection condition. Unless otherwise specified, all inspections shall be performed in accordance with the test conditions specified in 4.5.

4.3 First article inspection. When specified, a sample shall be subjected to first article inspection in accordance with Table III.

4.3.1 First article quantity. When specified, samples shall be submitted for first article inspection in accordance with 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated in Table II.

TABLE II. First article quantity.

Parts description	Drawings	Quantity
Bandoleer for Cartridge, 40MM	8835107	30
Bandoleer for Cartridge, 40MM, M433	9278204	30

4.3.2 Inspections to be performed. The first article inspection shall consist of 100% examination for defects of all drawing requirements including workmanship requirements for the parts and assemblies listed in 4.3.1, and the conduct of all tests specified in Table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

4.3.3 First article rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected.

TABLE III. First article inspection.

Examination or test	No. of sample units	Requirement paragraph	Paragraph reference
Bandoleer for Cartridge 40mm (Drawing 8835107 or 9278204)			
Fastener	30	3.2.1.1	4.5.1
Stitching	30	3.2.1.2	4.5.2
Water repelling and mildew resistance	30	3.2.1.3	4.5.3
Examination for defects	30	3.3, 3.2.1	4.3.2, 4.4.2.1, gage

4.4 Conformance inspection.

4.4.1 Inspection lot formation. Bandoleer lot formation shall be in accordance with MIL-STD-1916, paragraph “Formation and identification of lots and batches”.

4.4.2 Classification of characteristics.

a. Sampling requirements. In addition to the sampling requirements stated herein, Verification Level VII shall be used to verify the 100% screening operation of Critical characteristics. Inspection sampling requirements for Critical, Major, and Minor characteristics are as defined in MIL-STD-1916. Unless otherwise specified, Verification Level IV shall be used for all characteristics defined as Majors and Verification Level II for all Minor characteristics; Critical characteristics shall be addressed in accordance with MIL-STD-1916.

b. Conformance inspection. Conformance inspection shall be performed in accordance with 4.4.2.1. For all conformance inspections the same sample specimen may be used for all non-destructive examinations or tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

Paragraph	Title	Sheet 1 of 1		Drawing number
4.4.2.1	Bandoleer.			8835107 or 9278204
				Next higher assembly
Classification	**Examination or test**	**Conformance criteria**	**Requirement Paragraph**	**Inspection method reference**
Critical	None defined			
Major				
101	Flap does not snap properly over body tab	Level IV	3.2.1	Visual/manual/audible
102	Stitching defective	Level IV	3.2.1.2	4.5.2
103	Any fasteners missing	Level IV	3.2.1.1	Visual
104	Fastener does not work properly 1/	5 1/	3.2.1.1	4.5.1
Minor				
201	Flap does not mate properly with its tab	Level II	3.2.1, 3.3	Visual/manual
202	Rips or tears	Level II	3.3	Visual
203	Color improper	Level II	3.2.1, 3.3	Visual/general match
204	Closing tab on body damaged	Level II	3.3	Visual
205	Evidence of poor workmanship	Level II	3.3	Visual, 4.6

Notes:
1/ If any fastener fails to comply with the requirement specified on the applicable drawings, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

4.5 Methods of inspection.

4.5.1 Pull test of fasteners on tab. This test shall be performed on each fastener of the bandoleer in accordance with the procedure specified on 8835107 or 9278204 accordingly.

4.5.2 Stitching. Stitching shall be visually and manually inspected for evidence of conformance to the requirement specified in 3.2.1.2.

4.5.3 Water repelling and mildew resistance. This test shall be performed in accordance with MIL-W-530 or A-A-59708 on each type of fabric used in the bandoleer. If any sample fails to meet the applicable requirements the quantity represented by the sample shall be rejected.

4.6 Workmanship. Visually inspect all parts and assemblies for workmanship. Evidence of said workmanship defects shall be cause for lot rejection.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DOD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory).

6.1 Intended use. The parts covered by this specification are intended for use with Cartridges: 40mm Ammunition.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification and of all reference documents cited in section 2 and identified for information in section 6.
b. Title, number (w/revision level) and date of all reference documents.
c. Requirements for submission of first article sample.
d. Requirement for submission of conformance inspection sample.
e. Requirement for Certificate of conformance for each lot or shipment of product.
f. Packaging requirements (see 5.1). Reference Packaging Drawings: ASTM D3951 (Standard Practice for Commercial Packaging).
g. Quality Conformance Inspection, if other than specified in section 4 of this specification.
h. Provisions for critical characteristic controls.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

i. Requirement for submission of inspection equipment designs.
j. Applicable National Stock Number (NSN).
k. Serialization requirements, if applicable.
l. Government Furnished Material or Equipment, if applicable.
m. Lists of drawings, publications and specifications, showing applicable revision dates.
n. Critical inspection equipment requirement.

6.3 Submission of inspection equipment design for approval. Submit equipment designs as required to: Commander, U.S. Army, ARDEC, ATTN: RDAR-EIQ-MF, Picatinny Arsenal, NJ 07806-5000. Request letter of submittal should state contractor, contract number, specification number, item nomenclature and classification of defects or test paragraph. Inspection equipment, inspection method and the frequency of inspection should be submitted for approval to ARDEC, ATTN: RDAR-EIQ-MF, Picatinny Arsenal, NJ 07806-5000.

6.3.1 Submission of alternative quality conformance provisions. Unless otherwise specified in the contract, proposed alternative quality conformance provisions should be submitted to: Commander, U.S. Army, ARDEC, ATTN: RDAR-EIQ-MF, Picatinny Arsenal, NJ 07806-5000

6.4 Key word listing.
Mildew resistance

6.5 Revisions/amendments history. The following is a record of changes incorporated into this document:

ECP	Description	Date Approved
R11S2019	Allowing alternate mildew resistance treatments for the M433 Bandoleer. Current production produces bandoleers with the polyester/cotton blended fabric and no mildew treatment. This ECP allows the contractors to choose an alternate treatment that meets the requirements of A-A-59708.	02 May 2011
R17Q2009	The changes to the specification fulfill the requirements of MIL-STD-961 which include administrative updates and the addition of alternate mildew resistance treatments.	Aug 2017

6.6 Changes from previous issues. Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

.

Custodians:
Army - AR

Preparing activity:
Army-AR
(Project 1310-2018-003)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you shall verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.