INCH-POUND

MIL-F-50864B (AR)
AMENDMENT 3
31 July 1993
SUPERSEDING
AMENDMENT 2
27 July 1991

MILITARY SPECIFICATION

FUZE, PIBD, M549, LESS SPITBACK
METAL PARTS AND
LOADING, ASSEMBLING AND PACKAGING

This amendment forms a part of MIL-F-50864B (AR), dated 7 March 1988, and is approved for use by the US Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Add under Military Standards:

"MIL-STD-414 - Sampling procedures and Tables for Inspection by Variables for Percent Defective

MIL-STD-1168 - Ammunition Lot Numbering"

2.1.2, Delete "9349971..." and substitute:

"9349971 - Cartridge, 40mm, Test Vehicle with M549 fuze"

Add, under 2.2:

"ASTM C 208 - Insulating Board (Cellulosic Fiber), Structural and Decorative"

3.3, Delete "Safety spring not engaged in teeth of rotor gear" and substitute "Safety spring not locking rotor and gear assembly".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

PAGE 2 (Cont'd.)

3.4: Delete "... either the air pressure, functioning..." and substitute "... either the functioning...".

PAGE 5

4.3.1, Add:

"Ogive, housing escapement with crimped bottom plate		9287861	50"

Table I, Delete:

"Arming time, minimum	125	3.2	4.5.12"

Substitute:

"Arming time, minimum	125 1/	3.2	4.5.12"

Notes: Add "1/ The one hundred and twenty-five samples shall be tested a total of five times each without failure."

PAGE 10

Table I, Delete:

"Air pressure	125	3.2	4.5.20"

Add:

"Ogive, housing escapement with crimped bottom plate (Dwg. 9287861) Torque test	50	3.2	4.5.20"

Change from "1/2 or 5/8 inch Celotex" to "1/2 or 5/8 inch thick insulating board"

PAGE 12

* 4.4.2.1: Delete Minor 201 in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

PAGE 15

* 4.4.2.4, Major 103: Under No. of Sample Units column, delete "4".

Delete Note 1 in its entirety and substitute "1/ Sampling and rejection shall be in accordance with MIL-C-5541 or MIL-A-8625 as applicable".

PAGE 18

4.4.2.7: Delete "Major 101" in its entirety.

PAGE 20

4.4.2.9: Delete Major 106 from "Diameter across legs" and substitute "Diameter across legs, min".

Delete: Major 106 and substitute:

"106. Leg broken, bent or missing 0.40% 3.2 Visual"

PAGE 27

4.4.2.16: Delete 101 and substitute:

"101. Push test of actuator 125 1/ Acc-1 1/ Rej-2 3.2 4.5.10"

Add: Under Notes:

"1/ For ogive assembly lots of 22,000 or less, use MIL-STD-414. Inspection level II, Single Specification Limit. Variability unknown. Range Method. AQL = .40%. If the calculated value of (X-L)/R is less than "k" or if any individual measurement is less than 400 pounds, the lot shall be rejected."

PAGE 29

4.4.2.18: Delete "Safety spring...sector gear" Critical 4 and substitute:

"Safety spring end not locking rotor and gear assembly 5/"

Delete: Critical 5 in its entirety and substitute:

"5. Drive Screw missing 100% 3.2 AIE/4.5.14"

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:41Z
Check the source to verify that this is the current version before use.

PAGE 32

4.4.2.21: Add:

"CRITICAL

6.	X-ray examination of fuze assembly	100%	3.3	4.5.16.1"

PAGE 33

4.4.2.21: Delete Major 101 in its entirety and substitute:

"101.	Torque Test 5 per shift 2/	0-1	3.2	4.5.20"

Major 102, 103 and 104, Delete "100 1/ 2/" and substitute "100 1/"

Delete Note 2/ in its entirety and substitute the following:

"2/ The 5 samples shall be by assembling ogive, escapement housing and bottom plate only using normal assembly procedure. If any sample fails the drawing requirement, the shift's production represented by the sample shall be rejected."

4.4.2.21, Major 102, No. of Sample Units column, delete "100 1/" and substitute "100 1/ 2/ 4/"

Add under Notes:

"4/ Acceptance is based on requirements of paragraph 3.7 or disassembly of the round and examination of the M59 detonator for functioning in full armed position."

Major 103, delete "1/2 or 5/8 inch Celotex" and substitute "1/2 or 5/8 inch thick insulating board"

Delete: Major 111 in its entirety and substitute:

"111.	Perpendicularity of large outside diameter with crimped surface	0.40%	3.2	Gage"

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

PAGE 32 (Cont'd.)

Add paragraph 4.5.16.1:

"4.5.16.1 X-Ray examination of fuze assembly. The fuze assembly shall be x-rayed using approved automatic test equipment and test techniques (see 6.4). The equipment shall be in accordance with Dwg. 12903079. Inspection shall be conducted in two (2) planes: from the top of the fuze assembly down; and from the side. The side view shall show the setback pin adjacent to the rotor. Observance shall be made for the following critical and major defects:

a. Setback pin not adjacent to the rotor gear.
b. Setback pin not seated in bottom of counterbore of escapement housing.
c. Setback pin missing.
d. Setback spring missing.
e. Safety spring missing.
f. Safety spring end not in contact with root diameter surface or seated within root between first 2 teeth of rotor gear.
g. O-ring missing.
h. Pinion assembly missing.
i. Verge assembly missing.
j. Rotor gear assembly in armed or partially armed position.
k. Drive screw missing or not fully seated.
l. A major defect is defined as any defect not specified as critical above."

PAGE 40

* 4.5.17: Delete in its entirety and substitute the following:

"4.5.17 The fuze assemblies packed in their regular shipping containers shall be tested in accordance with test B1, Section 6.1.2 of MIL-STD-331. The test shall be performed at ambient temperature only. After completion of the test, the fuze assemblies shall be x-rayed as specified in 4.5.16. Observation shall be made for compliance with the requirements specified in 3.4."

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:41Z
Check the source to verify that this is the current version before use.

PAGE 41

4.5.20: Delete in its entirety and substitute the following:

"4.5.20 Torque test. Sample shall be placed in an approved fixture and the torque specified on the applicable drawing shall be applied. Observation shall be made for compliance with the applicable drawing requirement. This test is a destructive test. Parts so tested shall not be returned to the lot."

4.5.21.2: Delete "One-half (1/2) or five-eights (5/8) inch celotex" and substitute "One-half (1/2) or five-eighths (5/8) inch insulating board" and "1/2 or 5/8 inch piece of Celotex." substitute "1/2 or 5/8 inch insulating board per ASTM C 208 or approved equal."

PAGE 42

4.5.22: Delete "1/2 or 5/8 inch piece of Celotex." and substitute "1/2 or 5/8 inch insulating board per ASTM C 208 or approved equal."

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-A788)

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:41Z
Check the source to verify that this is the current version before use.