MILITARY SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES, RECEPTACLE, SOCKET CONTACTS, DECADE INCREMENTS 90, 100, AND 120 CONTACT POSITIONS (.100 INCH SPACING)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the connectors described herein shall consist of this specification and the latest issue of MIL-C-55302.





FIGURE 1. Connector, receptacle .100 (2.54 mm) spacing.

Ⓖ denotes changes


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:47Z
Check the source to verify that this is the current version before use.



WIRE WRAP TERMINAL (TYPE D)


DETAIL B



DETAIL A

FIGURE 1. Connector, receptacle .100 (2.54 mm) spacing - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:47Z
Check the source to verify that this is the current version before use.



CONNECTOR POLARIZATION WITH D SHAPED GUIDE PINS AND SOCKETS. (TYPE Y)

DETAIL C






FIGURE 1. Connector, receptacle .100 (2.54 mm) spacing - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:47Z
Check the source to verify that this is the current version before use.




TYPE F FIXED JACKSCREW

DETAIL D



TYPE S SHORT TURNING SLOTTED JACKSCREW

DETAIL E



TYPE H SHORT TURNING SLOTTED JACKSCREW

DETAIL F

FIGURE 1. Connector, receptacle .100 (2.54 mm) spacing - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:47Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Material: Guide pins, type X guide sockets, jackscrews and jacksockets shall be made of corrosion resisting stainless steel per ASTM-A581 or ASTM-A582 passivated per QQ-P-35 or shall be corrosion resistant copper nickel alloy (61 ±2% copper, 25 ±2% nickel, 2.5% max. other, and the balance zinc) and shall have a brinell hardness of 145 to 175. Type Y guide sockets shall be beryllium copper per QQ-C-550, nickel plated per QQ-N-290, class 2, 50 to 150 microinches.

Plating: The contact plating shall be per MIL-C-55302 or gold per MIL-G-45204, type II, grade C, class 1, over nickel plating per QQ-N-290, class 2, 50 to 150 microinches in the engaging area and (G) gold per MIL-G-45204, type II, grade C, class 00, or type III, grade A, class 00, over nickel plating per QQ-N-290, class 02, 50 to 150 microinches in the termination area.

Contact identification: See figure 1.

Contact engagement and separation forces (No. 22 contacts):
Minimum separation: 0.5 ounce.
Maximum engagement: 12.0 ounces for standard force and 4.0 ounces for low force.
(G) Note: Low force contacts meet the requirements of standard force contacts.

Mating and unmating:
Standard insertion force contacts: The maximum mating force, in pounds, shall be the number of contacts multiplied by 0.56 and the withdrawal force, in pounds, shall be a minimum of 0.08 times the number of contacts and shall not exceed the measured insertion force.

Low insertion force contacts: The maximum mating force, in pounds, shall be the number of contacts multiplied by 0.25 and the withdrawal force, in pounds, shall be a minimum of 0.04 times the number of contacts and shall not exceed the maximum insertion force.

Contact resistance: The average contact resistance of all contacts measured shall not exceed 0.010 ohm, and no individual contact pair shall have a resistance exceeding 0.020 ohm.

Dielectric withstanding voltage:
Sea level: 1,000 volts rms.
High altitude: 300 volts rms.

Current rating: 5.0 amperes maximum per contact.

Polarization: Type X, regular, guide pin and socket, full round (see figure 1). Type Y, adjustable "D" shaped guide pin and/or socket (see MIL-C-55302/57, detail B). *All connectors are supplied in* (G) the -1 polarized position. For other than OEM use, connectors may be repolarized by using M55302/57-01 spanner wrench and M55302/57-02 guide pin and guide socket kit. When guides are removed and reinstalled in another position apply Loctite 83-CV or equivalent to the threads. Ordering connectors in other than the -1 polarized position may be done by the OEM's by placing the desired polarized position in brackets three (3) spaces after the part number on the purchase order. Example M55302/60-A100Y[-32]. Polarization pins and sockets shall be adjusted to any desired position by spanner wrench M55302/57-01. Ordering connectors in the -1 polarized position without Loctite 83-CV or equivalent applied may be done by placing a "-0" in brackets three (3) spaces after the part number on the purchase order. Guide sets, as installed, shall withstand 7 inch ounces backoff torque applied through the guide set mounting nut.

(G) M55302/57-02 kit: Consists of (1) type Y "D" shaped guide socket and one (1) type Y "D" shaped guide pin.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:47Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm	Inches	mm
.001	0.03	.030	0.76	.094	2.39	.172	4.37
.002	0.05	.032	0.81	.100	2.54	.200	5.08
.005	0.13	.035	0.89	.110	2.79	.220	5.59
.006	0.15	.051	1.30	.120	3.05	.225	5.72
.008	0.20	.058	1.47	.125	3.18	.234	5.94
.010	0.25	.075	1.91	.130	3.30	.250	6.35
.025	0.64	.078	1.98	.140	3.56	.335	8.51
.027	0.69	.082	2.08	.150	3.81	.350	8.89
.028	0.71	.086	2.18	.161	4.09	.625	15.88

Number of contacts	Dimensions						
	BSC A	BSC B	*.010 C	*.010 D	REF E	REF F	REF G
90	2.475 (62.87)	2.700 (68.58)	5.650 (143.51)	5.150 (130.81)	2.200 (55.88)	2.100 (53.34)	.400 (10.16)
100	2.725 (69.22)	2.950 (74.93)	6.150 (156.21)	5.650 (143.51)	2.400 (60.96)	2.400 (60.96)	.400 (10.16)
120	3.225 (81.92)	3.450 (87.63)	7.150 ((181.61)	6.650 (168.91)	2.900 (73.66)	2.900 (73.66)	.400 (10.16)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is *.005 (0.13 mm).
4. These connectors mate with connectors specified in MIL-C-55302/59.
5. Numbers indicating the first and last position in each row and every fourth contact position in between shall be marked on the side(s) of the connector. As an option to the above, numbers indicating every fourth cavity may be stamped on the side of the connector, with the exception that the number one contact shall be marked. (G)
6. Termination layout on .025 (0.64 mm) modular grid.
7. Metric equivalents are in parentheses.

FIGURE 1. Connector, receptacle .100 (2.54 mm) spacing - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:47Z
Check the source to verify that this is the current version before use.

Example of part number:

M55302/60	L	A	100	X
Basic number of specification sheet	Type of contacts	Type of terminal (see figure 1)	Number of contacts (see figure 1)	Type of guide pin and/or socket (see figure 1)
	L = Low insertion force contacts - = Standard insertion force contacts	A = solder cup B = dip terminal .140 long C = dip terminal .172 long D = wire wrap E = dip terminal .234 long		Type X = full round Type Y = "D" shaped Type F = fixed jackscrew Type S = .200 slotted turning jackscrew Type H = .200 hex turning jackscrew

Custodians:
Army - CR
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI
Navy - AS, TD
Air Force - 85, 99
DLA - ES

User activities:
Army - AT, AV, ME
Navy - MC, OS
Air Force - 11, 19, 80

Preparing activity:
Army - CR

Agent:
DLA - ES

(Project 5935-3592-6)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:47Z
Check the source to verify that this is the current version before use.