MILITARY SPECIFICATION

GRENADE, GP: M42
BODY ASSEMBLY, TYPE PH, FOR

This amendment forms a part of Military Specification MIL-G-50546B (AR), dated 21 December 1981, and is appoved for use within the US Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 10

4.4.2.3, Critical 1: Delete "4.5.5" from the Paragraph Reference/Inspection Method Column and substitute "4.5.6".

PAGE 17

* 4.4.3.3a, Continuous Sampling: Delete in its entirety and substitute the following:

"a. Continuous Sampling - In order to establish an acceptable heat treatment process, take a group of thirty two (32) grenade bodies for each test from each heat treat furnace at the start of production or after any interruption in the process of one hundred (100) hours or more (a break in production shall be considered to be a period of time where no test samples are taken from material exiting the furnace). The groups of thirty two (32) shall be hardness tested in accordance with 4.5.3 (when in effect) and strength tested in accordance with 4.5.4 and 4.5.5 as applicable. Calculate the standard deviation(s) for each strength test using the formula in 6.6.1. If any individual value falls below the minimum load requirement, the process shall be corrected and additional groups of thirty two (32) grenade bodies taken. If all values are above the minimum load requirement, proceed with production.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:28Z
Check the source to verify that this is the current version before use.

To qualify product during production, a continuous sampling plan shall apply which consists of randomly selecting a body every four (4) minutes for each test from each heat furnace and subjecting them to the tests of paragraph 4.5.4 and 4.5.5. Proceed in this manner until four (4) consecutive groups of four (4) minutes production have been collected into one lot representing sixteen (16) minutes production. The individual mean (x) shall be calculated based on the values of the four test samples for each test. If any individual sample reading falls below the minimum load specified on the drawing or if the mean minus 3.12 times the standard deviation (x - 3.12s) is below the minimum load requirement, then reject that lot and take corrective action. Rejected lots may be reheat treated. A suitable hold area shall be provided at each heat treat furnace.

The standard deviation shall be continually recalculated based on the values of the latest test samples, and individually numbered samples of twenty eight (28) grenade bodies previously tested (initial quantity obtained from above); and use of the formula in 6.6.1. The test statistics then form a running standard deviation based on thirty two (32) samples, including the most recent test samples as the twenty ninth thru thirty second samples and eliminating the first thru fourth samples. This process will continue for each additional group of bodies tested. One continuous data base shall be maintained for each grenade type per furnace."

Control charts shall be maintained as outlined in para. 6.6.2. The contractor shall maintain these charts along with records of corrective action, available for government review, for a minimum of one year."

PAGE 18

* 4.4.4.1, Add new paragraph as follows:

"4.4.4.1 Certification of Nondestructive test personnel. All personnel operating or calibrating non destructive test equipment shall be qualified and certified in accordance with MIL-STD-410."

PAGE 26

5.1, 5.1.1, 5.2, 5.2.1 and 5.3: Delete in their entirety and substitute the following:

"5.1 Level B.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:28Z
Check the source to verify that this is the current version before use.

5.1.1 Preservation, packaging and marking. Grenades shall be packaged, packed and marked in accordance with dwgs. 9206166 and 9206167. Palletization is optional".

PAGE 28

* 6.6.1: Delete the following variable definitions: "x = average value of all individual observations, lbs; n = sample size" and substitute the following: "x = average value of the 4 individual observations, lbs.; n = 4 = sample size."

* 6.6.2: Delete in its entirety and substitute the following:

"6.6.2 x & s control chart procedure. For both the longitudinal and transverse tests maintain x and s charts as follows.

6.6.2.1 Temporary control chart limits and center lines. After 25 subgroups have been plotted, calculate control chart center lines and control limits for the x chart and s chart as follows:

x chart center line = x = average x of 25 subgroups of size n = 4
s chart center line = s = average s of 25 subgroups of size n = 4
x chart upper control limit (UCLx) = x + 1.628s
x chart lower control limit (LCLx) = x - 1.628s
s chart upper control limit (UCLs) = 2.27s
s chart lower control limit (UCLs) = 0

6.6.2.2 Adjusted control chart limits. To monitor the heat treat process through statistical process control proceed as follows:

(a) Maintain the above control charts for the next 75 in control subgroups (a subgroup can be determined to be out of control by the criteria of 6.6.2.3). If an out of control condition arises follow the procedure outlined in 6.6.2.4.

(b) Recalculate x and s using averages of 100 subgroups

(c) Using the new x and s recalculate UCLx, LCLx and UCLs

(d) Rechart the previous data with the new center lines and control limits

(e) Recalculte x, s, UCLx, LCLx and UCLs after removing the out of control subgroups from the calculations

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:28Z
Check the source to verify that this is the current version before use.

(f) Proceed with charting the test results until 250 new in-control subgroups have been accumulated. Each time a subgroup is determined to be out of control follow the procedure outlined in 6.6.2.4.

(g) Calculate x and s (based on 250 subgroups) for comparison purposes and make adjustments to the center lines and control limits based on the following conditions:

(g.1) If x has not decreased and s has not increased then recalculate x, s, UCLx, LCLx and UCLs (based on the new 250 subgroups).

(g.2) If x has increased and s has increased then keep s, and UCLs the same and recalculate x, UCLx and LCLx (based on the previous s value).

(g.3) If x has not increased and s has increased or x has decreased and s has not decreased then keep x, s, UCLx, LCLx and UCLs the same and follow the procedure of 6.6.2.4.

(g.4) If x has decreased and s has decreased then keep x the same and recalculate UCLx, LCLx, s, and UCLs (based on the new 250 subgroups).

(h) Proceed with charting and repeat step (g) for every successive quantity of 250 new in-control subgroups accumulated.

6.6.2.3 Out of control criteria. The contractor shall consider the process out of control if any of the following occur.

(a) Any point falls outside of UCL or LCL
(b) Nine consecutive points are on the same side of a center line.
(c) Six consecutive points are either steadly increasing or decreasing.
(d) Fourteen points in a row are alternating up and down.

6.6.2.4 Reporting action. If any of the criteria of 6.6.2.3 are signaled, the contractor shall record in writing the believed cause of the out of control signal. The contractor shall also record the corrective action taken. If no corrective action is taken, the reason for not taking action shall be recorded. To facilitate investigations into causes of out of control conditions, the contractor shall annotate on the control chart whenever anything noteworthy happened."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:28Z
Check the source to verify that this is the current version before use.

* 6.6.3: Delete in its entirety.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this documents based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian
Army-AR

Preparing activity:
Army-AR

(Project 1320-A266)

Source: https://assist.dla.mil -- Downloaded: 20261O-22T20:28Z
Check the source to verify that this is the current version before use.