INCH-POUND

MIL-PRF-64266/13A
15 October 2013
SUPERSEDING
MIL-PRF-64266/13
9 September 2010


PERFORMANCE SPECIFICATION SHEET

CONNECTORS, FIBER OPTIC, CIRCULAR, PLUG AND RECEPTACLE STYLE, MULTIPLE REMOVABLE GENDERLESS TERMINI, SCREW THREADS, BACKSHELL, SOLID, SINGLE FIBER CABLES, BANDED ADAPTER/CABLE STRAIN RELIEF INTERFACE, ENVIRONMENT RESISTING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring fiber optic connectors described herein shall consist of this specification sheet and MIL-PRF-64266.

SCOPE. The performance requirements specified herein cover a backshell intended for use with a MIL-PRF-64266 or MIL-DTL-38999 connector plug or receptacle in a fiber optic only application. This backshell is intended for the cable harness configuration in which a bundle of single fiber cables (simplex optical cables) are routed through material, such as cable wrap, to the connector plug or receptacle. This backshell is used for interface with the connector plug or receptacle on one end and contains an interface (platform) to secure the cable wrap with a banding strap on the other end. As an alternative, this platform may be used to secure a cable strain relief (such as heat shrink) to the cable entrance end of the backshell. Environmental resistant features include ability to restrict movement, position, and twist of each cable in addition to eliminate or reduce penetration of various environments. This backshell is one of a solid shell configuration. This configuration consists of a solid shell (or body) with coupling nuts on both the ends, gland components and banding adapter/cable strain relief interface components. One coupling nut on the shell mates with the connector, the other both houses the gland and mates with a banding adapter/cable strain relief interface.




Straight Backshell

FIGURE 1. Straight, 45 and 90 degree backshell orientations.


AMSC N/A

FSC 6060

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:20Z
Check the source to verify that this is the current version before use.



45° backshell



90° backshell

FIGURE 1. Straight, 45 and 90 degree backshell orientations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:20Z
Check the source to verify that this is the current version before use.

Shell size	A thread ISO metric	B dia Max		C dia min		D dia max		E dia max	
		inches	mm	inches	mm	inches	mm	inches	mm
11	M15x1.0-6H	1.00	25.4	.31	7.9	.51	13.0	1.38	35.1
13	M18x1.0-6H	1.13	28.7	.38	9.7	.58	14.7	1.38	35.1
15	M22x1.0-6H	1.25	31.8	.50	12.7	.65	16.5	1.38	35.1
17	M25x1.0-6H	1.38	35.1	.50	12.7	.81	20.6	1.56	39.6
19	M28x1.0-6H	1.50	38.1	.63	16.0	.91	23.1	1.56	39.6
21	M31x1.0-6H	1.63	41.4	.69	17.5	1.05	26.7	1.81	46.0
23	M34x1.0-6H	1.75	44.5	.75	19.1	1.18	30.0	1.81	46.0
25	M37x1.0-6H	1.88	47.8	.94	23.9	1.18	30.0	2.12	53.8

Shell size	F Max		G Max		L Max		M Max	
	inches	mm	inches	mm	inches	mm	inches	mm
11	2.0	50.8	3.7	94.0	4.0	101.6	2.5	63.5
13	2.1	53.3	3.7	94.0	4.2	106.7	2.6	66.0
15	2.1	53.3	3.8	96.5	4.2	106.7	2.6	66.0
17	2.2	55.9	3.9	99.1	4.2	106.7	2.6	66.0
19	2.2	55.9	3.9	99.1	4.3	109.2	2.7	68.6
21	2.3	58.4	4.0	101.6	4.3	109.2	2.7	68.6
23	2.4	61.0	4.0	101.6	4.4	111.8	2.8	71.1
25	2.4	61.0	4.0	101.6	4.5	114.3	2.8	71.1

NOTES.
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Dimensions apply to plated/finished part.
4. Backshell internal configuration not shown. The backshell interface dimensions shall be in accordance with figure A-6 of MIL-PRF-64266.
5. See table V herein for relationship of cable entry code to shell size.
6. This interface shall be compatible for use of both a banding strap and heat shrink. Banding strap is one with a .25 inch (6.35 mm) nominal band width and a .375 inch (9.53 mm) maximum buckle (locking mechanism) width. Backshell shall withstand an applied 160 lb (712 N) linear force around the circumference of the backshell at the band interface surface. The force shall be applied by placing a banding strap onto the backshell using a banding tool.

FIGURE 1. Straight, 45 and 90 degree backshell orientations - Continued.

REQUIREMENTS.

Temperature ranges.

Operating:	-67ºF to 329ºF (-55ºC to 165ºC)
Non-operating:	-40ºF to 185ºF (-40ºC to 85ºC)
Storage:	-40ºF to 185ºF (-40ºC to 85ºC)

Dimensions and configurations: See figure 1 herein and MIL-PRF-64266, figure A-6.

Weight: Weight shall not exceed the specified value in table I for the applicable shell size, cable entry angle and material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:20Z
Check the source to verify that this is the current version before use.

TABLE I. Backshell weights.

Shell size	Cable entry angle	Composite		Aluminum		Stainless steel	
		ounce	gram	ounce	gram	ounce	gram
11	straight	1.13	32	1.94	55	5.42	154
	45°,90°	1.30	37	2.39	68	7.18	204
13	straight	1.30	37	2.25	64	6.41	182
	45°,90°	1.44	41	2.57	73	7.36	209
15	straight	1.44	41	2.57	73	7.36	209
	45°,90°	1.62	46	2.89	82	8.17	232
17	straight	1.76	50	3.03	86	8.80	250
	45°,90°	1.94	55	3.70	105	10.07	286
19	straight	1.94	55	3.20	91	9.57	272
	45°,90°	2.08	59	3.70	105	10.70	304
21	straight	2.39	68	4.15	118	11.97	340
	45°,90°	2.71	77	4.96	141	14.22	404
23	straight	2.39	68	4.47	127	12.46	354
	45°,90°	2.89	82	5.10	145	13.41	381
25	straight	2.71	77	4.96	141	14.22	404
	45°,90°	3.20	91	5.60	159	16.30	463

Fabrication procedure. Standard fabrication procedure (for both the terminus placement/termination onto the end of fiber optic cabling and the assembly of the connector and backshell onto the fiber optic cabling) shall be used. Standard fabrication procedure shall be in accordance with NAVAIR 01-1A-505-4/T.O. 1-1A-14-4/TM 1-1500-323-24-4. A copy of this document can be obtained at web site: https://jswag.navair.navy.mil.

Backshell capture mechanism at the cable entry end (for banding strap or strain cable strain relief). A capture adapter/platform, external on and at the cable entry end of the backshell, shall be used to secure either a stainless steel banding strap or a cable strain relief (such as shrink tubing or heat shrink boot) to the backshell.

Cable restraint mechanism. Backshell shall contain means to provide environmentally resisting support for the single fiber cables exiting the termini. Support shall restrict movement during vibration and shock (act as a vibration dampener), restrict position of each cable (act as a positioner to keep each cable separated), and restrict cable twist (act as a anti-rotation mechanism). The term "gland" shall be used in this specification sheet as the generic term for the cable restraint mechanism, piece or resilient member component of the backshell that is used to provide a degree of environmental sealing, restrict the position of each cable, restrict the movement during vibration and shock, and restricts cable twist. The gland may also be referred to as a grommet, resilient bushing or spacer. The gland shall include an anti-rotation feature with a corresponding feature in the backshell. The anti-rotation feature shall position the termini cavities in the gland so that these cavities align with those in the connector insert. Also, the anti-rotation feature shall prevent rotation movement of the gland (i.e., prevent twisting of the cabling) once placed in the backshell.

Requirement for locking mechanism on the backshell coupling nut. The backshell coupling nut shall include a ratchet type locking mechanism (anti-coupling device) to ensure that a backshell mated to a connector maintains full thread engagement (maintains complete coupling). Complete coupling of the mated connector and backshell is achieved by a clockwise rotation of the coupling nut. The anti-coupling mechanism or feature shall be between the backshell coupling nut and the backshell shell only. The locking mechanism shall be sufficient to ensure no backing off of the coupling nut during mechanical shock or vibration.

Wrench flats on composite backshells. Backshell body coupling nuts constructed from composite material shall contain wrench flats or a non-movable hex nut. This wrench flat or hex nut shall be sufficient to permit applying a torque for affixing the backshell to the connector.

Positive stop on gland nut. Backshell body shall contain a positive stop for the gland nut. Once contact (resistance to further tightening) is made, the gland nut shall continue to be tightened until a torque value of 50 ± 10 in-lb is obtained. Two pieces of SAE AMS-DTL-23053/5 heat shrink, a minimum of 2 inches (50.5 mm) in length

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:20Z
Check the source to verify that this is the current version before use.

(before shrinkage), shall be provided with each backshell as part of the PIN (see markings below). One piece of heat shrink shall permit shrinkage directly over the gland nut banding platform and cabling exiting the backshell. The other piece of heat shrink shall permit shrinkage over a banding strap affixing cable wrap or braid to the gland nut banding platform.

Cable diameter range (for each of the single fiber cables in the specified shell size). Cable restraint mechanism and environmental sealing design shall accommodate a single fiber cable with a minimum diameter of .067 inch (1.7 mm) and a maximum diameter of .087 inch (2.2 mm).

Qualification. Qualification shall consist of performing testing specified as listed in table II. Backshells qualified to this specification sheet shall include components for interface with banding strap/cable strain relief.

TABLE II. Qualification inspections (except interoperability).

Cable entry angle	Straight	Straight	45 Degree	90 Degree
Shell size 11/	15	15	15	15
	SM	MM	SM	SM
Fiber size (microns)	TR2	TR2	TR2	TR2
Temperature range	Environmental	Environmental	Environmental	Environmental
Environmental/non-E	/13	/13	/13	/13
Specification sheet				
Test performed 2/, 8/, 9/, 12/				
Group 1 (4 mated pairs)				
Interoperability 6/	X 7/	X 7/	X 7/	X 7/
Visual & Mechanical				
Size	X		X	X
Weight	X		X	X
Identification marking	X	X	X	X
Screw threads	X			
Workmanship	X		X	X
Functional				
Banding strap attachment integrity	X			
Compression fitting engagement integrity				
Backshell mating durability	X			
Optical				
Insertion loss (initial)	X	X	X	X
Return loss (SM only)	X	X		
Group 2 (2 mated pairs)				
Backshell-to-connector mating torque	X			
Cable pull out force (retention)				
External bending moment	X			
Cable seal flexing				
Twist	X			
Impact	X			
Crush	X			
Vibration: Swept sine (TR1)				
Vibration: Random (TR1)				
Vibration: Swept sine (TR2)	X		X	X
Vibration: Random (TR2)	X			
Vibration: Random with temperature (TR2)	X			
Shock: MIL-S-901 10/	X	X		
Shock: Half-sine pulse (TR2)				
Insertion loss verification				
Water pressure				
Modified SO_2/salt spray	X			

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:20Z
Check the source to verify that this is the current version before use.

TABLE II. Qualification inspections (except interoperability) – Continued.

Cable entry angle	Straight	Straight	45 Degree	90 Degree
Shell size 11/	15	15	15	15
Fiber size (microns)	SM	MM	SM	SM
Temperature range	TR2	TR2	TR2	TR2
Environmental/non-E	Environmental	Environmental	Environmental	Environmental
Specification sheet	/13	/13	/13	/13
Test performed 2/, 8/, 9/, 12/				
Group 3 (2 mated pairs)				
Thermal shock (TR1)				
Thermal shock (TR2)	X			
Temperature/humidity cycling	X			
Temperature cycling (TR1)				
Temperature cycling (TR2)	X			
Altitude immersion	X			
Life aging (Temperature life) (TR1)				
Life aging (Temperature life) (TR2)	X			
Freezing water	X			
Insertion loss verification	X 6/			
Sand & dust	X			
Identification marking	X			
Group 4 (2 mated pair + parts) 1/				
Electromagnetic effects (2 mated pair)	X		X	X
Fluid immersion (2 mated pair)	X			
Shell to shell conductivity (initial)	X			
Salt spray (2 mated pair) 4.9.6.10.1 3/	X			
Salt spray (TR2) 4.9.6.10.2				
Shell to shell conductivity	X			
Flammability (1 mated pair) 4/	X			
Fungus resistance (parts) 5/	X			
Ozone exposure (parts) 5/	X			
Insertion loss verification				

1/ Group 1 mated pair are to be used for Groups 2 and 3 tests. Group 4 can be done before Group 1 with separate samples.
2/ TR1 = test as specified for temperature range 1. TR2 = test as specified for temperature range 2.
3/ Two options: a. Use same two mated pair from the fluid immersion test. b. Use separate mated pair (If option b, can use one cable of sufficient length to loop around to the cable entrance of each backshell).
4/ One mated pair from the fluid immersion, salt spray, or Group 2/3 samples after that Group's test completion may be used.
5/ . Parts only; assembly not required.
6/ Interoperability. This testing is done by DLA Land and Maritime-TEB which maintains/retains the interoperability standards. Please note that separate test samples are required for interoperability testing. These test samples will then be retained by DLA Land and Maritime-TEB as interoperability standards.
7/ Interoperability is performed on both single mode and multimode for each shell size.
8/ Specific test practices for physical, mechanical, environmental and material tests, including clarifications and further details, are found in MIL-STD-1678-3.
9/ Specific test practices for the optical performance tests, including clarifications and further details, are found in MIL-STD-1678-2.
10/ Shock test. Standard shock fixture 4A for bulkhead mounting shall be used. Supplement test fixture that shall be used and the mounting that shall be performed are specified in Measurement 3202 of MIL-STD-1678-3.
11/ See qualification by similarity for other shell sizes if shell size 15 is being qualified. Otherwise, use this qualification table for the other shell sizes also.
12/ Full qualification list for the backshell with a straight cable entry angle contains more testing requirements than the 45 or 90º. Only by qualifying the straight backshell first, a further reduced test sequence as listed in the table can be used to qualify the backshell configurations with a 45 and 90º cable entry angle. Otherwise the full qualification listed for the backshell with the straight cable entry angle must be performed for backshell configurations with a 45 and 90º cable entry angle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:20Z
Check the source to verify that this is the current version before use.

Backshell and backshell accessory attachment. Not applicable.

Identification marking. Applicable. Both initial and after environmental testing.

Banding strap attachment integrity. For a backshell containing a rear adapter with a banding platform, no buckling, cracking or other backshell damage (including to plating) shall result from attachment of a banding strap when applied to the conditions of note 6 in figure 1.

Backshell-to-connector mating torque. The backshell threads shall withstand the applied torque to mate (affix) the backshell to the connector that is specified in table III with no damage. The backshell shall be mated to a connector mounted in a suitable fixture to prevent movement of the connector during the test. The torque shall be applied to the backshell at a rate of approximately 10 in-lb per second until the specified applied torque is obtained. This torque shall be applied for a minimum of 1 minute.

TABLE III. Backshell-to-connector mating torque.

Shell size	Mating torque 1/ +/- 5 in-lb (± .55 N-m)			
	Composite		Metal	
	in-lb	N-m	in-lb	N-m
11	50	5.65	100	11.30
13	50	5.65	150	16.95
15	50	5.65	150	16.95
17	50	5.65	150	16.95
19	50	5.65	150	16.95
21	100	11.30	175	19.75
23	100	11.30	175	19.75
25	100	11.30	175	19.75

1/ Increments are rounded to nearest 0.05 N-m for compatibility with a torque wrench.

Cable pull-out force. Not applicable.

Cable seal flexing. Applicable.

Twist. Applicable. A 5 lb weight shall be applied to the entire cable bundle. Perform on a shell size 15 backshell.

Mating durability. Not applicable.

Backshell mating durability. Backshell shall be assembled and completely disassembled for 25 assembly (mating) cycles. Each cycle shall include connector-to-backshell coupling (mating) as part of the backshell assembly. No optical measurements need to be performed during or after this test. A separate piece of cabling may be used for this test. This test may be performed prior to test sample assembly for Group I optical tests.

External bending moment. Applicable. Applied bending moment shall be as specified in table IV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:20Z
Check the source to verify that this is the current version before use.

TABLE IV. Backshell applied bending moment.

Shell size	Minimum applied bending moment 1/					
	Composite		Aluminum		Stainless steel	
	in-lb	N-m	in-lb	N-m	in-lb	N-m
11	25	2.85	125	14.15	125	14.15
13	25	2.85	275	31.10	275	31.10
15	50	5.65	300	33.90	300	33.90
17	50	5.65	300	33.90	300	33.90
19	50	5.65	300	33.90	300	33.90
21	75	8.50	300	33.90	300	33.90
23	75	8.50	300	33.90	300	33.90
25	100	11.30	300	33.90	300	33.90

1/ Increments are rounded to nearest 0.05 N-m for compatibility with a torque wrench.

Impact. Applicable.

Crush. Applicable.

Water pressure. Not applicable.

Banding strap attachment integrity. No buckling, cracking or other backshell damage (including to plating) shall result from attachment of a banding strap when applied to the conditions of note 6 in figure 1.

Freezing water immersion. Applicable.

Sand and dust. Applicable.

Electromagnetic effects. Applicable except for backshell classes D and E material designators. When not tested as part of the initial qualification, the backshell shall be assembled to a MIL-PRF-64266/1 or MIL-PRF-64266/3 receptacle. Electromagnetic effects testing shall be conducted both with and without mating the MIL-PRF-64266/1 or MIL-PRF-64266/3 receptacle to a mating plug connector or dust cover.

Salt spray. Applicable.

Shell-to-shell conductivity. Applicable. Perform both initial and after salt spray. For a backshell mated to a connector plug, the voltage drop of the mated connector plug-to-backshell shall be measured from a point on the rear accessory thread of the connector plug to a point on the backshell 1.0 ± .25 inch from the innermost backshell threads that mate with the backshell gland nut. For a backshell mated to a connector receptacle, the voltage drop of the mated connector receptacle-to-backshell shall be measured from a point on the flange of the connector receptacle adjacent to the mounting hole to a point on the backshell 1.0 ± .25 inch from the innermost backshell threads that mate with the backshell gland nut. When tested as part of the initial qualification, the voltage drop between the connector receptacle and connector plug shall be measured also.

Modified SO_2/salt spray. Applicable.

Altitude immersion. Applicable.

Fluid immersion. Applicable.

Cleaning procedures. Each shipment of backshells shall include recommended cleaning procedures. The following wording or equivalent is recommended "To clean, use lint free wipe dampened with alcohol and blow dry with air."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:20Z
Check the source to verify that this is the current version before use.

Qualification by similarity.

Backshell configurations to test. The below qualification by similarity is valid if MIL-PRF-64266/14 backshells were placed on the connector receptacles and one MIL-PRF-64266/12 backshell and one MIL-PRF-64266/13 backshell was placed on the connector plugs for each two connector mated pair going through group 1, group 2 or group 3, and group 4 tests.

Temperature range. For inspections and tests performed for this qualification by similarity, tests for temperature range 2 shall be performed for those tests done differently dependent upon the temperature range.

Larger shell sizes. This qualification by similarity is applicable when testing larger shell sizes in this specification sheet and the initial shell size 15 is qualified to this specification sheet. If a connector backshell of shell size 15 is qualified to this specification sheet, and a larger connector backshell with similar design, construction, and materials meet the interoperability, visual and mechanical, size, weight, identification marking, workmanship, screw threads, banding strap attachment integrity, backshell mating durability, insertion loss, vibration (swept sine only), shock (MIL-S-901 only), altitude immersion, temperature cycling and electromagnetic effects inspections and tests are performed in the qualification test sequence, then the backshell of the larger shell size inspected is qualified.

Smaller shell sizes. This qualification by similarity is applicable when testing smaller shell sizes in this specification sheet and the initial shell size 15 is qualified to this specification sheet. If a connector backshell of shell size 15 is qualified, and smaller connector backshells with similar design, construction, and materials meet the interoperability, visual and mechanical, size, weight, identification marking, workmanship, screw thread, backshell mating durability, insertion loss, bending moment, mechanical shock and vibration (swept sine only) inspections and tests as performed in the qualification test sequence, then the backshell of the smaller shell size inspected is qualified.

Cable entry angle. If a connector backshell with a straight cable entry angle and specified shell size in this specification sheet is qualified, and connector backshells with 45 degree and 90 degree entry angles in this specification sheet meet the inspections specified in table V, then the connector backshells with 45 degree and 90 degree entry angles for the same shell size are qualified. This qualification by similarity is allowed under the constraint that the same coupling nuts on the shell, same gland components and same banding adapter/cable strain relief interface components are used as is on the backshell with the straight cable entry angle.

Shell sizes in addition to shell sizes 11, 13, 15, and 23. If a connector backshell of shell sizes 11, 13, 15 and 23 in this specification sheet is qualified, and connector backshells of intermediate shell sizes (for use with MIL-DTL-38999 connectors) in this specification sheet meet the visual and mechanical size, weight, identification marking, workmanship, screw thread and backshell mating durability inspections, then the connector backshells of intermediate shell sizes are qualified.


Alternate backshell material. If a connector backshell in this specification sheet made from aluminum is qualified, and connector backshells made from composite or stainless steel in this specification sheet meet the visual and mechanical, size, weight, identification marking, workmanship, screw thread, backshell mating durability, insertion loss, return loss, external bending moment, twist, impact, crush, shock, thermal shock, temperature humidity cycling, temperature cycling, life aging, sand and dust, fluid immersion, shell-to-shell conductivity, modified SO_2/salt spray, vibration (as performed in the qualification test sequence), electromagnetic effects, salt spray, flammability, fungus resistance, and ozone exposure inspections, then the backshells of the alternate material inspected are qualified. If there is a material change of the rear adapter, then banding strap attachment integrity shall be included.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:20Z
Check the source to verify that this is the current version before use.

Alternate plating or plating process. If a connector backshell with one plating or plating process in this specification sheet is qualified, and connector backshells made with an alternate (different type) plating or same type plating using an alternate plating process in this specification sheet meet the plating and plating process specified in 4.7.5.5 of the MIL-PRF-64266 base specification, then the backshells with the alternate plating or plating process, as applicable, inspected are qualified.

Marking.

Part or Identification Number (PIN). Mark on coupling ring of the backshell.



PIN example: M64266/13CAA

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:20Z
Check the source to verify that this is the current version before use.

TABLE V. PIN code designators.

Shell size	Shell size code	Cable entry code 1/	Cable entry angle	Connector type	# of entry cables
11	B	A	Straight	M64266	2
	B	B	45°	M64266	2
	B	C	90°	M64266	2
11	B	L	Straight	M64266	4
	B	M	45°	M64266	4
	B	N	90°	M64266	4
11	B	D	Straight	M38999	2
	B	E	45°	M38999	2
	B	F	90°	M38999	2
13	C	A	Straight	M64266	6
	C	B	45°	M64266	6
	C	C	90°	M64266	6
13	C	D	Straight	M38999	4
	C	E	45°	M38999	4
	C	F	90°	M38999	4
15	D	A	Straight	M64266	10
	D	B	45°	M64266	10
	D	C	90°	M64266	10
15	D	L	Straight	M64266	8
	D	M	45°	M64266	8
	D	N	90°	M64266	8

See notes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:20Z
Check the source to verify that this is the current version before use.

TABLE IV. PIN code designators - Continued.

Shell size	Shell size code	Cable entry code 1/	Cable entry angle	Connector type	# of entry cables
15	D	D	Straight	M38999	5
	D	E	45°	M38999	5
	D	F	90°	M38999	5
17	E	D	Straight	M38999	8
	E	E	45°	M38999	8
	E	F	90°	M38999	8
19	F	D	Straight	M38999	11
	F	E	45°	M38999	11
	F	F	90°	M38999	11
21	G	D	Straight	M38999	16
	G	E	45°	M38999	16
	G	F	90°	M38999	16
23	H	A	Straight	M64266	36
	H	B	45°	M64266	36
	H	C	90°	M64266	36
23	H	D	Straight	M38999	21
	H	E	45°	M38999	21
	H	F	90°	M38999	21
25	J	D	Straight	M38999	37
	J	E	45°	M38999	37
	J	F	90°	M38999	37
25	J	G	Straight	M38999	29
	J	J	45°	M38999	29
	J	K	90°	M38999	29

1/ Cable entry code based on cable entry angle, connector type and number of cavities in the connector insert.

Mating counterpart. Backshell mates with MIL-PRF-64266/1 wall mounting receptacle, MIL-PRF-64266/2 plug, and MIL-PRF-64266/3 jamnut mounting receptacle.

Installation and removal tools: Adjustable or 1.25 inches (31.8 mm) open end wrench, strap wrench, and scissors.

Referenced documents. In addition to MIL-PRF-64266, this specification sheet references the following documents:

MIL-PRF-28876
MIL-S-901
MIL-STD-1678-2
MIL-STD-1678-3
MIL-DTL-38999
MIL-PRF-64266/1
MIL-PRF-64266/2
MIL-PRF-64266/3
MIL-PRF-64266/12
MIL-PRF-64266/14
NAVAIR 01-1A-505-4/T.O. 1-1A-14-4/TM 1-1500-323-24-4
SAE AMS-DTL-23053/5

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:20Z
Check the source to verify that this is the current version before use.

Standardization based on lessons learned. For the older, existing fiber optic, multiple termini connectors; each vendor has a different backshell aramid yarn capture mechanism and assembly process. The logistic support is taxing the system. For instance, at several JFOWG (Joint Fiber Optic Working Group) meetings, the Navy school house reported that training on the MIL-PRF-28876 connector assembly took a significant portion of the time and cost for the fiber optic curriculum. This leads to logistic difficulties in adding new training material and obtaining (paying for) parts needed in this connector assembly. The implementation of this lesson learned is that the backshell configuration and assembly process for any new connector and any new backshell configuration introduced must be standardized to the maximum extent feasible.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue, due to the extent of the changes.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - AS
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 6060-2013-013)

Review activities:
Army - TE
Navy - SH
Air Force - 13, 19, 93, 99
MISC - DI
MISC - MDA

Civil agencies:
GSA – FAS
NASA - NA

NOTE: The activities listed above were interested in this document on the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:20Z
Check the source to verify that this is the current version before use.