INTERIM FEDERAL SPECIFICATION

CASE, FILING, TRANSFER, KNOCKDOWN

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers a knockdown transfer filing case with a detachable cover, to be used as a transfer and storage case.

1.2 Classification.

1.2.1 Type and sizes. The case shall be of one type and of the dimensions stated in table II, as specified (see 3.4 and 6.2).

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

Federal Specification:

PPP-B-636 - Box, Fiberboard.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).
Fed. Test Method Std. No. 191 - Textile Test Method.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specification procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:47Z
Check the source to verify that this is the currentversion before use.

Technical Association of the Pulp and Paper Industry (TAPPI) Test Methods:

T402 os - 49 - Conditioning of Paper and Paperboard.
T410 os - 61 - Basis Weight of Paper and Paperboard.
T411 os - 44 - Thickness and Density of Paper.
T807 su - 66 - Bursting Strength of Paperboard and Liner Board.

(Application for copies should be addressed to the Technical Association of the Pulp and Paper Industry, 360 Lexington Avenue, New York, New York 10017.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Material.

3.1.1 Fiberboard. The solid fiberboard shall be constructed of two plies of liner board and filler material. The fiberboard shall be made from such materials and by such process so as to meet the physical property requirements listed in table I, and tests as specified in 4.4.1.2.

TABLE I. Physical properties

Caliper, inch	0.090 inch (Minimum)
Basis weight, per thousand square feet	340 pounds (Minimum)
Bursting strength	520 pounds per square inch (Minimum)

3.1.2 Wood. The bottom reinforcement shall be manufactured of solid wood. The wood reinforcement shall be not less than four inches wide and 5/16 inch thick. Knots, if any, shall be free of decay, and the outer edge of the knot(s) shall be at least one inch away from the edges facing the center section of the base.

3.1.3 Binding cloth. The binding cloth shall be made of cotton, rayon, nylon or polyester, or a combination thereof (see 4.4.1.1). The cloth shall have not less than 60 yarns per inch in the warp direction and not less than 50 yarns per inch in the filling direction. It shall be plain finished, or shall have a synthetic resinous finish (see 4.4.1.1). The color of the cloth shall approximately match the color of the fiberboard.

3.2 Design. The case shall be designed to assemble easily and quickly. Unassembled, the case shall consist of three separate sections: (a) a wood reinforced bottom, (b) a collapsible side and end section (center section), and (c) a cover. The solid wood boards shall serve as a bottom reinforcement, and as a medium to which the center section of the case can be nailed. When attached, the center section shall rest on the edges of the fiberboard bottom and against the wood reinforcement.

3.3 Construction.

3.3.1 Base. The base shall be manufactured of materials conforming to 3.1, and shall be designed as specified in 3.2. Two wood reinforcements shall be securely fastened to the fiberboard bottom (see 3.1.2). All outside corners of the center section shall be reinforced with binding cloth, and all butted body joints shall be securely hinged together with binding cloth, properly cemented (see 3.1.3). The binding cloth shall extend the full length, and not less than 1/2 inch on each side of the corners and joints. Nail holes shall be punched at the lower edges of the center section to facilitate assembling of the case.

3.3.2 Cover. The cover shall be made of one piece of fiberboard conforming to 3.1.1. The sides of the cover shall extend down over the base approximately one inch. The butted corner joints of the cover shall be held together with appropriate metal staples, and covered with kraft paper tape.

3.3.3 Nails. The nails shall be suited for the intended purpose. The appropriate number of nails shall be packed in an envelope and securely stapled to the wood reinforcement.

3.4 Dimensions. The base inside dimensions shall be as specified in table II. A plus tolerance of 1/2 inch, and a minus tolerance of 1/4 inch will be permitted in height and width dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:47Z
Check the source to verify that this is the current version before use.

TABLE II. Sizes (inside dimension)

	Height 1/	Width	Depth
			Minimum
Letter size (inches)	10-3/4	12-1/4	21
Legal size (inches)	10-3/4	15-1/4	21

1/ The height dimension shall be measured starting from the top of the wood reinforcement to the upper edge of the center section.

3.5 Identification marking. Unless otherwise specified, each case shall be permanently and legibly marked with the name or trademark of the manufacturer.

3.6 Workmanship. The cases shall be free from defects and imperfections which affect appearance or may impair the serviceability. The binding cloth, and the paper tape shall be neatly cemented to present a smooth and uniform appearance.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Inspection and testing of materials. In accordance with 4.1, the supplier is responsible for insuring that materials are manufactured, examined, and tested in accordance with this specification or referenced subsidiary specifications, standards and other documents.

4.1.2 Evidence of compliance. In lieu of using his own facilities, the contractor may submit a report of analysis of component materials from a laboratory acceptable to the Government, whether an independent test facility or laboratory of raw material supplier, as evidence of compliance with the specification requirements. The report of analysis shall include, in addition to the actual test data, the manufacturer's name, the name and address of the testing laboratory, date of test(s), and quantity of material represented by the test report. When reports of analysis are submitted, the Government reserves the right to check test to determine the validity of the analysis.

4.2 Sampling.

4.2.1 Size of lot. All cases of the same size presented for inspection at one time shall be considered a lot for purposes of examination and test.

4.2.2 Sampling for inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise specified.

4.2.3 Sampling for visual and dimensional examination. Random sample of cases shall be taken from each lot in accordance with MIL-STD-105. A sample unit shall be one case. The cases shall be examined for defects listed in table III. The Inspection Level shall be S-3, and the Acceptable Quality Level (AQL) shall be 4.0 percent defective.

4.2.4 Sampling for preparation for delivery examination. Sampling shipping containers shall be taken from each lot in accordance with MIL-STD-105. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. The lot size shall be the number of shipping containers in the inspection lot fully prepared for delivery. Defects of closure listed in table IV shall be examined on shipping containers fully prepared for delivery. The inspection level shall be S-2, and the AQL shall be 2.5 defects per hundred units.

4.2.5 Sampling for material tests. One knockdown transfer filing case shall be taken at random from each lot. One strip of binding cloth shall be detached from the corners, and one strip from the butted body joints from the center section and tested as specified in 4.4.1.1. The fiberboard of the same case shall be utilized to perform the physical property tests of the fiberboard, as specified in 4.4.1.2.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:47Z
Check the source to verify that this is the currentversion before use.

4.3 Examination.

4.3.1 Visual and dimensional examination. Samples taken in accordance with 4.2.3 shall be examined for defects listed in table III. Any case having one or more defects shall be rejected. If the number of defective units in the sample exceeds the acceptance number for that sample, the entire lot represented by the sample shall be rejected.

TABLE III. Classification of defects

Examine	Defects
Material	Wood does not conform to the requirements specified in 3.1.2. Binding cloth does not approximately match the color of the fiberboard (see 3.1.3).
Design	Design not in accordance with 3.2.
Construction	Bottom of base not reinforced as specified (see 3.3.1). Wood not securely attached to fiberboard (see 3.3.1). Corners of center section not reinforced as specified (see 3.3.1). Butted body joints not hinged together as specified (see 3.3.1). Cover not made of one piece of fiber (see 3.3.2). Butted corner joints of cover not held together with metal staples and covered with kraft paper tape (see 3.3.2).
Dimension	Dimension not as specified (see 3.4 and table II).
Identification marking	Identification marking missing, incomplete or illegible (see 3.5).
Workmanship	Not in accordance with 3.6.

4.3.2 Examination of preparation for delivery. Samples selected in accordance with 4.2.4 shall be examined for defects listed in table IV, to determine that packing, and marking requirements of section 5 of this specification are complied with. Any shipping container having one or more defects shall be rejected. If the number of defective cases exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

TABLE IV. Classification of preparation for delivery defects

Examine	Defects
Marking (exterior and interior)	Omitted; incorrect; illegible; or improper size, location, sequence or method of application.
Materials	Any component missing or not as specified. Any component damaged, affecting serviceability.
Workmanship	Inadequate application of components, such as, incomplete closure of container flaps, loose strapping, improper taping, inadequate stapling. Bulging or distortion of containers.
Contents	Number of bundle and container is more or less than required.
Weight	Weight exceeds requirements.

4.4 Test.

4.4.1 Test for materials. Samples obtained in accordance with 4.2.5 shall be subjected to the following tests. Failure to pass the tests shall be considered cause for rejection of the lot, as not meeting the material requirements of this specification.

4.4.1.1 Binding cloth test. The sample binding cloth shall be subjected to the test cited in table V to insure yarn per inch requirements stated in 3.1.3. Two determinations shall be made on each strip of cloth. In addition, the supplier shall submit a certificate of compliance stating that the binding cloth has been manufactured of yarn(s) as specified in 3.1.3.

TABLE V. Physical properties testing (Cloth)

Physical properties	Fed. Test Method Std. No. 191
Yarn per inch in woven fabric	Test Method No. 5050

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:47Z
Check the source to verify that this is the current version before use.

4.4.1.2 Fiberboard test. The fiberboard of the sample case shall be tested in accordance with the applicable TAPPI Test Methods listed in table VI, to assure compliance with the requirements listed in table I. All samples shall be conditioned and tested under uniform atmospheric conditions as specified in TAPPI Test Method T402 os - 49.

TABLE VI. Physical properties testing (Paper)

Physical properties	TAPPI Test Methods
Conditioning of paper and paperboard.	T402 os - 49
Basis weight of paper and paperboard.	T410 os - 61
Thickness and density of paper.	T411 os - 44
Bursting strength of paperboard and linerboard.	T807 su - 66

5. PREPARATION FOR DELIVERY

5.1 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A. Knocked-down filing cases in quantities as specified (see 6.2) shall be packed in a box conforming to PPP-B-636, class weather-resistant. The box shall be closed in accordance with the appendix to the box specification.

5.1.2 Level B. Six knocked-down filing cases shall be packed in a box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to the box specification.

5.1.3 Level C. Knocked-down filing cases shall be packed to insure delivery at destination at the lowest rates, in containers complying with the rules and regulations applicable to the mode of transportation.

5.2 Marking.

5.2.1 Civil agencies. In addition to markings required by the contract or order, the shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.2.2 Military agencies. In addition to markings required by the contract or order, the shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The knockdown transfer filing cases are intended to be used for the transfer or storage of inactive records, documents, letters, file cards, and other types of office papers.

6.2 Ordering data. The purchaser should select the preferred option permitted herein and include the following information in procurement documents.

(a) Title, number, and date of this specification.
(b) Size of case (see 3.4).
(c) Level of packing required (see 5.1).
(d) Marking for shipment required (see 5.2).

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:47Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:47Z
Check the source to verify that this is the current version before use.

GENERAL SERVICES ADMINISTRATION - FEDERAL SUPPLY SERVICE

SPECIFICATION COMMENT SHEET

BUDGET BUREAU NO. 29-R0175

INSTRUCTIONS

This form provides a way for users of this specification to inform the originator of problems encountered in its use. It is not to be used to request changes to accommodate proprietary features. All comments will be considered and appreciated, but please do not expect a reply. To comment: detach, complete, fold, staple, and mail.

NOTE: Comments on this form do not constitute or imply authorization to waive any part of the document or serve to amend contractual requirements.

1. SPECIFICATION

LLL-C-001491(GSA-FSS) Case, Filing, Transfer, Knockdown

2. CONTRACT NO. *(If any)*	3. QUANTITY ON CONTRACT *(Optional)*	4. DOLLAR VALUE *(Optional)*

5. GENERAL NATURE OF PROBLEM *(e.g., inspection difficulties, manufacturers unable to meet tolerances, containers collapse under normal warehousing conditions, etc.)*

6. SPECIFIC REQUIREMENTS AFFECTED *(Include paragraph number and lines of wording)*

7. SPECIFIC PROBLEMS *(e.g. tests in 4.2.2 will not assure that the battery will last required time; temperature ranges in table 2 do not conform to commercially available items.)*

8. RECOMMENDATIONS

9. NAME OF MANUFACTURER, ASSOCIATION, GOVT., AGENCY, ETC.	10. ADDRESS *(Number, Street, City, State and Zip Code)*

11. NAME AND TITLE OF SUBMITTER

12. DATE

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:47Z
Check the source to verify that this is the current version before use.

FOLD

GENERAL SERVICES ADMINISTRATION

OFFICIAL BUSINESS



POSTAGE & FEES PAID
GENERAL SERVICES ADMINISTRATION

General Services Administration
Federal Supply Service (FMSO)
Washington, D. C. 20406

FOLD

GSA FORM FED 69 2200

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:47Z
Check the source to verify that this is the current version before use.