FEDERAL SPECIFICATION

PLUGS AND FLANGES
(FOR DRUM CLOSURES)

This amendment, which forms a part of Federal Specification PPP-P-420B, dated August 15, 1972, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 3

Paragraph 3.2, line 2: Delete "(4.3.2.1)" and substitute "(4.3.1)".

Paragraphs 3.2.1.1 and 3.2.1.2: Delete.

PAGE 4

Paragraphs:

3.2.3, line 2: After "neck" add "and gasket".

3.2.5, line 4: Delete "retaining ring" and substitute "plastic closure".

3.2.5.1, line 5: Delete "curved" and substitute "curled".

3.3.1, line 4: Delete "0.750-inch" and substitute "3/4-inch".

3.3.1.1, line 3: Delete "4.2.3.1" and substitute "4.3.1".

PAGE 5

Paragraph 3.3.4:
Line 3: Delete "0.093" and substitute "0.078".
Line 6: Delete "1-5/16 ± 1/64" and substitute "2-5/16 ± 1/64".

Paragraph 3.3.5:
Line 2: Delete "31/64" and substitute "1-31/64".
Line 3: Delete "0.093 inch" and substitute "not less than 0.078 inch thick".

Paragraph 3.4: Delete and substitute:

3.4 When there is a conflict between this specification and the Department of Transportation (DOT) container specifications for certain hazardous materials described in 49 CFR, the DOT plug and flange requirement of authorization by the Bureau of Explosives for those specific commodities shall supersede the requirements of this specification.

PAGE 6

Paragraphs 3.4.1 and 3.4.2: Delete.

Paragraph 4.2.2.1, line 2: Delete "table I" and substitute "table III".
TABLE I:
Delete "I" and substitute "III".
Line 11: Delete "Hole".

PAGE 7

TABLE I (Con't):
Delete "I" and substitute "III".
Line 7: Delete "or II".
Line 9: Delete "seals" and substitute "diaphrams".
Line 12: Delete "II" and substitute "I".

Paragraph 4.2.2.2 after "specified" add "for types and classes in 3.2 through 3.2.3".

FSC 8110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.