MIL-B-0023137C(MU)
13 July 1973
USED IN LIEU OF
MIL-B-23137B
2 December 1970
(See Section 6)

MILITARY SPECIFICATION

BOMB, INCENDIARY, TH3, 4-POUND, M126;

COMPONENTS FOR

This limited coordination Military specification has been prepared by Edgewood Arsenal based upon currently available technical information, but it has not been approved for promulgation as a coordinated revision of Military Specification MIL-B-23137B. It is subject to modification. However, pending its promulgation as a coordination Military specification, it may be used in procurement.

1. SCOPE

1.1 This specification covers the components for a 4-pound incendiary bomb.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures, and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-1168	-	Lot Numbering of Ammunition.

DRAWINGS

US ARMY MUNITIONS COMMAND

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:40Z
Check the source to verify that this is the current version before use.

EDGEWOOD ARSENAL

D14-5-3018 - Bomb, Incendiary, 4 Pound, TH3, M126.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies of these ratings, rules and regulations should be addressed to Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606).

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing D14-5-3018 or on the subsidiary drawings shall conform to the specifications thereon, or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components shall conform to the specifications and drawings listed on Drawing D14-5-3018 and subsidiary drawings.

3.2 Assembly. The components of the bomb shall be assembled in accordance with the applicable drawings listed on Drawing D14-5-3018.

3.3 Preproduction. Prior to the start of regular production, a pre-production lot of like components shall be produced in accordance with this specification for examination and test (see 4.3).

3.4 Workmanship. All components shall be free of all foreign matter (oil, grease, etc.) and damage such as dents, cracks, and deformation which could affect their intended use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:40Z
Check the source to verify that this is the current version before use.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction inspection.

4.3.1 Lot. A preproduction lot of 500 like components shall be manufactured using the same methods, materials, equipment, and processes as will be used during regular production.

4.3.2 Inspection procedure.

4.3.2.1 For examination. Three hundred like components shall be taken at random from the preproduction lot and examined for conformance with the applicable drawings, specifications, and classification of defects. The AQL's do not apply.

4.3.2.2 Acceptance/rejection criteria. The preproduction sample when examined, must meet the requirements of this specification to be acceptable. The supplier shall obtain written approval from the contracting officer prior to proceeding with regular production.

4.4 Quality conformance inspection.

4.4.1 Lotting. Each lot shall be identified and controlled in accordance with MIL-STD-1168. Contained in anyone interfix number of bombs, no more than one interfix number of components produced in one week by one manufacturer is permitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:40Z
Check the source to verify that this is the current version before use.

4.4.2 Sampling for examination. Sampling shall be conducted in accordance with MIL-STD-105.

4.4.3 Inspection procedure.

4.4.3.1 For examination. Sample components shall be examined in accordance with the classification of defects and MIL-STD-105.

4.4.3.2 Classification of defects.

(a) Nose-body assembly (C14-5-1178).

Categories		Defects
Critical:		None defined
Major:		AQL 1.5 percent defective
	101	Nose and body misalignment excessive
	102	Length incorrect
	103	Large counterbore diameter incorrect
	104	Large counterbore depth incorrect
	105	Plunger hole diameter or location incorrect
	106	Plunger hole counterbore diameter or depth incorrect
	107	Screw holes diameter or countersink incorrect
	108	Screw holes location incorrect
	109	Eccentricity inside dia excessive
	110	Vent holes dimensions or location incorrect
	111	Distance across flats at tail end incorrect
	112	Marking missing, illegible, or incorrect
	113	Body diameter (inside) incorrect
	114	Length of small hexagon incorrect
	115	Wall thickness at safety plunger hole incorrect
	116	Workmanship (3.5)
	117	Loose nose and body
	118	Tail seam clearance slot incorrect or mislocated
	119	Presence of burrs around drilled and counterbored holes
	120	Chamfer on small hex missing
	121	Chamfer on vent holes missing
	122	Nose body assembly fails to pass through "1.930 gauge for 6"

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:40Z
Check the source to verify that this is the current version before use.

*Inspection to be by an established industrial practice acceptable to the Government or Edgewood Arsenal Standard.

Minor:	AQL 4.0 percent defective	
201		Misalignment of small hexagon with large hexagon excessive
202		Distance across flats of large hexagon incorrect

(b) Plug, vent-hole (Dwg A14-5-459).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Diameter incorrect
102	Workmanship (see 3.5)
Minor:	AQL 2.5 percent defective
*201	Thickness incorrect

(c) Plunger assembly (Dwg A14-5-122).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Component missing, or incorrectly assembled
102	Sleeve outside diameter incorrect (Dwg A14-5-76)
103	Flange outside diameter incorrect (Dwg A14-5-122)
104	Flange thickness incorrect
105	Sleeve length (0.47) incorrect (Dwg A14-5-76)
*106	Machine finish incorrect
107	Safety plunger overall length incorrect (Dwg A14-5-121)
108	Bead diameter incorrect
109	Workmanship (see 3.5)

*Inspect prior to assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:40Z
Check the source to verify that this is the current version before use.

4.4.3.2 Classification of defects (continued).

(c) Plunger assembly (Dwg A14-5-122)(continued).

Categories	Defects
Minor:	AQL 2.5 percent defective
*201	Protective finish missing or incorrect

*Inspect prior to assembly.

(d) Holder, primer (Dwg B14-5-116).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Outside diameter incorrect
102	Thickness at periphery incorrect
103	Primer cavity diameter incorrect
*104	Porosity
105	Workmanship (see 3.5)
Minor:	AQL 2.5 percent defective
201	Overall thickness incorrect

*Inspection to be by an established industrial practice acceptable to the Government or Edgewood Arsenal Standard.

(e) Holder and firing pin-assembly (Dwg B14-5-119).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Component missing, or incorrectly assembled
102	Riveting incorrect (visual)
*103	Machine finish incorrect
*104	Burrs
*105	Point length and profile incorrect (Dwg B14-5-118)

Source: https://assist.dla.mil Downloaded: 2026-10-19T15:40Z
Check the source to verify that this is the current version before use.

4.4.3.2 Classification of defects (continued).

(e) Holder and firing pin-assembly (Dwg B14-5-119)(continued).

Categories		Defects
Major:		
*106		Retaining flange hole diameter incorrect (Dwg B14-5-114)
107		Eccentricity bore with outside diameter excessive
108		Safety plunger hole diameter or location incorrect
109		Outside diameter incorrect
110		Workmanship (see 3.5)
Minor:	AQL 2.5 percent defective	
*201		Chamfer missing
*202		Protective finish missing or incorrect
203		Overall length incorrect
204		Vent groove missing
205		Large end length incorrect (Dwg B14-5-114)

*To be performed on component parts prior to assembly.

(f) Preparation for delivery (section 5).

Categories		Defects
Critical:		None defined
Major:	AQL 4.0 percent defective	
101		Containers damaged
102		Marking missing, or incorrect
Minor:	AQL 10.0 percent defective	
201		Marking illegible

5. PREPARATION FOR DELIVERY

5.1 Packaging, level C. The bomb components shall be preserved and packaged to provide adequate protection against damage from the supply source to the first using activity for immediate use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:40Z
Check the source to verify that this is the current version before use.

5.2 Packing, level C. A uniform number of components, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at first destination for immediate use. Containers shall comply with Uniform Freight Classification Rules or regulation of other carriers applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages and shipping containers shall be marked in accordance with MIL-STD-129.

5.4 Palletization. The nose body assemblies, packed in suitable containers, shall be palletized to facilitate handling. Pallets and palletized loads shall be in compliance with applicable transportation rules and regulations. Loaded pallet weights shall not exceed the weight limitations of the respective type pallet utilized, with a limit of 2000 pounds gross weight for any type pallets, and a minimum quantity of 400 items per pallet. The pallet shall be loaded and the contents secured thereon in a manner that will insure the security of the load under routine shipping conditions.

6. NOTES

6.1 Ordering data. Procurement documents should specify the title, number, and date of this specification.

6.2 Supersession data. This used in Lieu of military specification supersedes Interim Amendment 1(MU) dated 19 May 1971.

Custodians:

Army - MU

Preparing activity:

Army - MU(EA)

Project No. 1325-A331

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:40Z
Check the source to verify that this is the current version before use.