MIL-B-23137B
2 December 1970
SUPERSEDING
MIL-B-23137A
26 July 1968

MILITARY SPECIFICATION

BOMB, INCENDIARY, TH3, 4-POUND, M126;

COMPONENTS FOR

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the components for a 4-pound incendiary bomb.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures, and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-1168	-	Lot Numbering of Ammunition.

DRAWINGS

US ARMY MUNITIONS COMMAND

EDGEWOOD ARSENAL

D[illegible]14-5-3018 - Bomb, Incendiary, 4 Pound, TH3, M126.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:40Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies of these ratings, rules and regulations should be addressed to Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606).

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL14-5-3018 or on the subsidiary drawings shall conform to the specifications thereon, or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components shall conform to the specifications and drawings listed on Drawing DL14-5-3018 and subsidiary drawings.

3.2 Assembly. The components of the bomb shall be assembled in accordance with the applicable drawings listed on Drawing DL14-5-3018.

3.3 Functioning. The holder and firing pin assembly (Drawing B14-5-119) shall function as follows:

(a) Five-foot drop. The assembly shall not function when tested as specified in 4.4.4.1.

(b) Forty-foot drop. The assembly shall function when tested as specified in 4.4.4.2.

3.4 Preproduction. Prior to the start of regular production, a pre-production lot of like components shall be produced in accordance with this specification for examination and test (see 4.3).

3.5 Workmanship. All components shall be free of all foreign matter (oil, grease, etc.) and damage such as dents, cracks, and deformation which could affect their intended use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:40Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction inspection.

4.3.1 Lot. A preproduction lot of 500 like components shall be manufactured using the same methods, materials, equipment, and processes as will be used during regular production.

4.3.2 Inspection procedure.

4.3.2.1 For examination. Three hundred like components shall be taken at random from the preproduction lot and examined for conformance with the applicable drawings and specifications.

4.3.2.2 For destructive tests. Primer holder and firing pin assemblies shall be taken at random from the preproduction sample and tested as follows:

(a) Forty for 5-foot drop. (see 4.4.4.1.)
(b) Forty for 40-foot drop. (see 4.4.4.2.)

4.3.2.3 Acceptance/rejection criteria. The preproduction lot when examined, must meet the requirements of this specification to be acceptable. The supplier shall obtain written approval from the contracting officer prior to proceeding with regular production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:40Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Lotting. Each lot shall be identified and controlled in accordance with MIL-STD-1168. Contained in anyone interfix number of bombs, no more than one interfix number of components produced in one week by one manufacturer is permitted.

4.4.2 Sampling.

4.4.2.1 For examination. Sampling shall be conducted in accordance with MIL-STD-105.

4.4.2.2 For destructive tests.

(a) Five-foot drop. Forty primer holders and firing pin assemblies, 20 for first sample and 20 for second sample, shall be taken at random from each production lot.

(b) Forty-foot drop. Forty primer holders and firing pin assemblies, 20 for first sample and 20 for second sample, shall be taken at random from each production lot.

4.4.3 Inspection procedure.

4.4.3.1 For examination. Sample components shall be examined in accordance with the classification of defects and MIL-STD-105.

4.4.3.2 For destructive tests. Sample primer holders and firing pin assemblies shall be tested in accordance with 4.4.4.1, 4.4.4.2, 4.4.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:40Z
Check the source to verify that this is the current version before use.

4.4.3.3 Classification of defects.

(a) Nose-body assembly (Dwg C14-5-124 or C14-5-1178).

Categories		Defects
Critical:		None defined
Major:	AQL	1.5 percent defective
101		Nose and body misalignment excessive
102		Length incorrect
103		Large counterbore diameter incorrect
104		Large counterbore depth incorrect
105		Plunger hole diameter or location incorrect
106		Plunger hole counterbore diameter or depth incorrect
107		Screw holes diameter or countersink incorrect
108		Screw holes location incorrect
109		Eccentricity inside dia excessive
*110		Blooming, porosity, or cracks
111		Vent holes dimensions or location incorrect
112		Distance across flats at tail end incorrect
113		Marking missing, illegible, or incorrect
114		Body diameter (inside) incorrect
115		Length of small hexagon incorrect
116		Wall thickness at safety plunger hole incorrect
117		Workmanship (3.5)
118		Loose nose and body
119		Tail seam clearance slot incorrect or mislocated
120		Presence of burrs around drilled and counterbored holes
121		Chamfer on small hex missing
122		Chamfer on vent holes missing
123		Nose body assembly fails to pass through "1.930 gauge for 6"

*Inspection to be by an established industrial practice acceptable to the Government or Edgewood Arsenal Standard.

Minor:	AQL	4.0 percent defective
201		Misalignment of small hexagon with large hexagon excessive
202		Distance across flats of large hexagon incorrect

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:40Z
Check the source to verify that this is the current version before use.

4.4.3.3 Classification of defects (continued).

(b) Plug, vent-hole (Dwg A14-5-459).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Diameter incorrect
102	Workmanship (see 3.5)
Minor:	AQL 2.5 percent defective
*201	Thickness incorrect

(c) Plunger assembly (Dwg A14-5-122).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Component missing, or incorrectly assembled
102	Sleeve outside diameter incorrect (Dwg A14-5-76)
103	Flange outside diameter incorrect (Dwg A14-5-122)
104	Flange thickness incorrect
105	Sleeve length (0.47) incorrect (Dwg A14-5-76)
*106	Machine finish incorrect
107	Safety plunger overall length incorrect (Dwg A14-5-121)
108	Bead diameter incorrect
109	Workmanship (see 3.5)

*Inspect prior to assembly.

Minor:	AQL 2.5 percent defective
*201	Protective finish missing or incorrect

*Inspect prior to assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:40Z
Check the source to verify that this is the current version before use.

4.4.3.3 Classification of defects (continued).

(d) Holder, primer (Dwg B14-5-116).

Categories		Defects
Critical:		None defined
Major:	AQL 1.0 percent defective	
101		Outside diameter incorrect
102		Thickness at periphery incorrect
103		Primer cavity diameter incorrect
*104		Porosity
105		Workmanship (see 3.5)
Minor:	AQL 2.5 percent defective	
201		Overall thickness incorrect

*Inspection to be by an established industrial practice acceptable to the Government or Edgewood Arsenal Standard.

(e) Holder and firing pin-assembly (Dwg B14-5-119).

Categories		Defects
Critical:		None defined
Major:	AQL 1.0 percent defective	
101		Component missing, or incorrectly assembled
102		Riveting incorrect (visual)
*103		Machine finish incorrect
*104		Burrs
*105		Point length and profile incorrect (Dwg B14-5-118)
*106		Retaining flange hole diameter incorrect (Dwg B14-5-114)
107		Eccentricity bore with outside diameter excessive
108		Safety plunger hole diameter or location incorrect
109		Outside diameter incorrect
110		Workmanship (see 3.5)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:40Z
Check the source to verify that this is the current version before use.

(e) Holder and firing pin-assembly (Dwg B14-5-119) (continued).

Categories		Defects
Minor:	AQL 2.5 percent defective	
*201		Chamfer missing
*202		Protective finish missing or incorrect
203		Overall length incorrect
204		Vent groove missing
205		Large end length incorrect (Dwg B14-5-114)

*To be performed on component parts prior to assembly.

(f) Preparation for delivery (section 5).

Categories		Defects
Critical:		None defined
Major:	AQL 4.0 percent defective	
101		Containers damaged
102		Marking missing, or incorrect
Minor:	AQL 10.0 percent defective	
201		Marking illegible

4.4.4 Tests.

4.4.4.1 Five-foot drop. The primer holder and firing pin assembly, fitted to the bomb body, minus thermate, first fire mixture, and fin (see Drawing D14-5-3018) shall be dropped nose-down through a 2-inch standard metal pipe from a minimum height of 5 feet onto a level 1/2-inch thick (nominal) steel plate, 4 to 6 inches square, imbedded in a concrete block at least 12 by 12 by 12 inches, and placed on a level concrete surface.

4.4.4.2 Forty-foot drop. The primer holder and firing pin assembly shall be dropped nose-down from a maximum height of 40 feet, using the same techniques and equipment as specified in 4.4.4.1.

4.4.5 Acceptance/rejection criteria. Acceptance/rejection criteria for destructive testing of primer holder and firing pin assemblies shall be as set forth in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:40Z
Check the source to verify that this is the current version before use.

Table I. Acceptance/rejection criteria

Test	1st sample	Failures	Action	1st sample plus 2nd sample	Failures	Action
5-foot drop test	20	0	Accept	40	1	Accept
		1	Test 2nd sample		2 or more	Reject
		2 or more	Reject			
40-foot drop test	20	0	Accept	40	1	Accept
		1	Test 2nd sample		2 or more	Reject
		2 or more	Reject			

5. PREPARATION FOR DELIVERY

5.1 Packaging, level C. The bomb components shall be preserved and packaged to provide adequate protection against damage from the supply source to the first using activity for immediate use.

5.2 Packing, level C. A uniform number of components, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at first destination for immediate use. Containers shall comply with Uniform Freight Classification Rules or regulation of other carriers applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data. Procurement documents should specify the title, number, and date of this specification.

Custodians:

Army - MU
Air Force - 70

Review activity:

Air Force - 70

Preparing activity:

Army MU(EA)

Project No. 1325-0149

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:40Z
Check the source to verify that this is the current version before use.