MIL-D-23119F
AMENDMENT 2
15 December 1986
SUPERSEDING
INTERIM AMENDMENT 1(ME)
31 July 1985

MILITARY SPECIFICATION

DRUMS, FABRIC, COLLAPSIBLE, LIQUID FUEL, CYLINDRICAL,

500-GALLON CAPACITY

This amendment forms a part of MIL-D-23119F, dated 6 May 1985, and is approved for use within the USA Belvoir Research, Development, and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1, under SPECIFICATIONS, FEDERAL, add:

"PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner."

Under SPECIFICATIONS, MILITARY, add:

"MIL-L-10547 - Liner, Case, and Sheet. Overwrap, Water Vaporproof or Waterproof, Flexible."

PAGE 5

* 3.5.2, line 2, delete: "20 mg/100 ml" and substitute "60 mg/100 ml".

PAGE 14

4.6.1.3, delete defect No. 126 and substitute the following:

"126. Box closure and strapping not as specified for level A and B."

5.2.1, delete in its entirety and substitute the following:

AMSC N/A FSC 8110

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:35Z
Check the source to verify that this is the current version before use.

"5.2.1 Level A. Each complete drum, preserved as specified in 5.1, shall be individually packed in a close-fitting box conforming to PPP-B-621, class 2, style 2 or 2-1/2, type 3 load. Each box shall be equipped with a caseliner conforming to MIL-L-10547, type IV, grades E or F. When skids and reinforcement battens are required, the battens shall be placed on the box exterior and the skids shall be placed on the outside of the box bottom, in alignment with each side reinforcement batten. Box assembly, closure and strapping shall be as specified in the appendix to the box specification except that the strapping shall be flat, the finish B and that a dado shall be incorporated into the bottom face of each skid, full length at the center line, so that strapping, normally positioned adjacent to the skids, shall completely encompass the reinforcement battens and the skids. Alternatively, when specified (see 6.2), the shipping container may be a close-fitting box conforming to PPP-B-601, overseas type, style A or B, with caseliner as specified herein and with the boxlid secured to the box body with formed spring clips/fasteners and strapping in lieu of nailing and strapping."

PAGE 15

5.2.2, delete in its entirety and substitute the following:

"5.2.2 Level B. Each complete drum, preserved as specified in 5.1, shall be packed as specified in 5.2.1 for level A except that boxes shall be domestic type; or each complete drum, preserved as specified in 5.2.1, shall be packed in a close-fitting box conforming to PPP-B-640, class 2, style A, B, C, or D. Strapping for level B packing shall be finish A."

6.2, add the following new option:

"g. When alternate PPP-B-601, style A or B box with special closure is required for level A."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ME
Navy - SA
Air Force - 69

Preparing activity:
Army - ME

Project 8110-0284

Review activities:
Army - AT
DLA - GS

User activities:
Army - GL
Navy - MC, YD
Air Force - 99

Source: https://assist.dla.mil -- Downloaded: 202640-19T15:35Z
Check the source to verify that this is the currentversion before use.