MILITARY SPECIFICATION

Gyroscope Indicator System, Vertical

This Amendment forms a part of Military Specification MIL-G-23081C(AS) dated 2 October 1972 and has been approved by the Naval Air Systems Command, Department of the Navy.

Page 2, Under Specifications Military: Add

MIL-L-81846	Lubricating Oil, Instrument, Ball, Bearing, High Flash Point.
MIL-G-81935	Grease, Instrument, Ultra Clean.

Page 4, Delete Naval Air Systems Command

AS-2844	Lubricant, Instrument Ball Bearing, High Flash Point.

Page 8, Paragraph 3.3.10 Primary Input Power Requirements - Subparagraph (1). Third Line. Delete "55 VA Starting"; Substitute: "65 VA Starting".

Page 9, Paragraph 3.3.15 Lubrication - Delete Paragraph. Substitute "The gimbal bearings shall be lubricated with oil MIL-L-81846. The spin rotor bearings shall be lubricated with grease MIL-G-81322 or MIL-G-81937 with particle size not exceeding 25 microns for two percent and 5 microns for 98 percent of volume. Spin rotors shall have porous separators impregnated with oil MIL-L-81846 or Mobil oil 743A.

Page 9, Paragraph 3.3.13 Insulation Resistance - Add "This test shall be conducted only one time on any one gyroscope on Individual Tests".

Page 9, Paragraph 3.3.16 Barrier Coated Bearings - Add "Each unit shall be identified by a red background decal with black letters as follows: "Contains Barrier Coated Bearings per MIL-STD1334".

Page 10, Paragraph 3.4.1.7 Uncoordinated Turns - Last Line Delete "20", Substitute "2 degrees".

Page 13, Figure 3, Delete.

Page 19, Paragraph 3.5.3 Attitude Indicator - Add "The power failure warning flag shall operate satisfactorily when installed in parallel with indicators incorporating an AC flag motor".

Page 34, Reliability Acceptance Phase - Second Sentence-Delete "150". Substitute "120". Fourth Sentence Add "In the compilation". Seventh Sentence: Delete "100". Substitute "80". Eight Sentence: Delete "IV". Substitute "II".

FSC 6610

Project No. 6610-N075

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:31Z
Check the source to verify that this is the current version before use.