MIL-T-23080(OS)
AMENDMENT -6
20 February 1970
Superseding
AMENDMENT -5
8December 1969

MILITARY SPECIFICATION

TEST SET, DC POWER SUPPLY, MARK 366 MOD 1

This amendment forms a part of Military Specification MIL-T-23080(OS) of 3 May 1963 and has been approved by the Naval Ordnance Systems Command, Department of the Navy

By this change, MIL-T-23080(Wep) is changed to MIL-T-23080(OS).

Wherever it appears in specification delete "Bureau of Naval Weapons" and substitute "Naval Ordnance Systems Command"; also delete "BUORD".

Wherever it appears in specification delete "acceptance tests" and substitute "quality conformance tests".

Page 1, paragraph 1.1D: Delete "200 milliamperes" and substitute "25 milliamperes".

Page 1, paragraph 2.1: Delete "PPP-B-575", "PPP-B-645", and associated titles.

Page 1: Under "FEDERAL" add "PPP-B-576 Boxes, Wood, Cleated, Veneer, Paper-Overlaid."

Page 2: Delete "MIL-B-10377" and associated title.

Page 2, paragraph 2.1: Delete title after MIL-E-22403 and substitute: "Environmental Requirements and Tests (For Torpedo Mark 45 Mods 0, 1, and 2 components and Assemblies)"

Page 2, paragraph 2.2: Delete "and all supplements thereto."

Page 4, paragraph 3.1.8. Delete and substitute:
"3.1.8 Threads. Unless otherwise specified, all threads shall be in accordance with National Bureau of Standards Handbook H28. The class or fit for threads shall be as specified on the applicable drawings."

FSC 1045

Source: https://assist.dla.mil -- Downloaded: 202610-19T15:30Z
Check the source to verify that this is the current version before use.

Page 4, paragraph 3.3.2: In line 2 delete "120 volts a.c. plus or minus 10 percent" and substitute "121 volts plus or minus 11 volts ac".

Page 4, paragraph 3.3.4.2, line 2: Delete "6.0 plus or minus 0.5 ohm" and substitute "4.5 plus or minus 0.5 ohm".

Page 5, paragraph 3.3.4.4: Delete "breaker shall trip within 3 seconds maximum after being placed in its ON position" and substitute "breaker shall trip within 6 seconds maximum for the first activation and 3 seconds maximum for succeeding activations after being placed in its ON position."

Page 5, paragraph 3.3.6: In lines 3 and 4 delete "120 volts plus or minus 10 percent" and substitute "121 volts plus or minus 11 volts".

Page 7, paragraph 3.3.6.3.3, line 3: Delete "0 to 400 volts" and substitute "0 to 320 volts".

Page 8. Delete TABLE I and substitute:

"TABLE I
CIRCUIT CONTINUITIES

From	To	Maximum Resistance in Ohms
A - J16	B - J12	0.1
	K - J14	0.1
	L - J14	0.1
	M - J14	0.1
	N - J14	0.1
A - J16	P - J14	0.1
	R - J14	0.1
B - J16	A - J12	*(a) 0.18
	C - J14	*(b) 0.18
	D - J14	*(b) 0.18
	E - J14	*(b) 0.1
	F - J14	*(b) 0.1
	H - J14	*(b) 0.1
	J - J14	*(b) 0.1
A - J11	TP4	0.1
B - J11	TP3	0.1
A - J13	TP6	0.1
A - J15	TP2	*(c) 0.1
B - J15	TP1	*(c) 0.1

Source: https://assist.dla.mil -- Downloaded: 202610-19T15:30Z
Check the source to verify that this is the current version before use.

*(a) - Resistance measured with circuit breaker CB3 and switch S1 ON. With CB3 or S1 OFF, the resistance shall be greater than 10 x 10^6 ohms.

*(b) - Resistance measured with circuit breaker CB2 and switch S1 ON. With CB2 or S1 OFF, the resistance shall be greater than 10 x 10^6 ohms.

*(c) - Resistance measured with circuit breaker CB1 ON. With CB1 OFF, the resistance shall be greater than 10 x 10^6 ohms."

Page 11, paragraph 4.3.3: In line 2 delete "with an accuracy of 1/2 percent" and substitute "with an accuracy of 0.1 percent."

Page 13. Add the following new paragraph:
"4.3.28 Resistance of 4.5 plus or minus 0.5 ohms and capable of dissipating 200 watts."

Page 15. Delete paragraphs 4.4.4.4.1, 4.4.4.4.2, 4.4.4.4.3, and 4.4.4.4.4.

Page 15, paragraph 4.4.4.5.2: Delete "circuit breaker trips in 3 seconds maximum" and substitute "circuit breaker trips in 6 seconds maximum for the first activation and 3 seconds maximum for succeeding activations."

Page 16, paragraph 4.4.4.6: In lines 2 and 3 delete "at 108 plus 2 minus 0 volts a.c." and substitute "at 110 plus 2 minus 0 volts ac".

Page 16, paragraph 4.4.4.7: In line 3 delete "at 108 plus 2 minus 0 volts a.c." and substitute "at 110 plus 2 minus 0 volts ac".

Page 17, paragraph 4.4.4.7.5.1: Delete "150, 220, 245, 270, 320, and 400 volts dc" and substitute "150, 220, 245, 270, and 320 volts dc."

Page 18, paragraph 4.4.4.9. Delete and substitute:
"4.4.4.9 Remove all test equipment and cables from the test set and place all switches and circuit breakers in their ON position. Connect all test points and all connector pins together with a common jumper wire. With the high potential tester 4.3.24 connected between the jumper and the panel of the test set, verify that there is no puncturing or breakdown of insulation between any component or connection in the test set and the test set panel when a potential of 1000 volts dc plus or minus 10 percent is applied as specified in 3.3.7. See NAVORD OD 12301 for acceptance procedures."

Page 20, Figure 1 (c): Change "4.3.8" (connected to J14C) to "4.3.28."

Page 25, paragraph 6.1: Delete "Torpedo Mark 45 Mod 0 or Mod 1" and substitute "Torpedo Mark 45 Mods 0, 1, or 2,".

Source: https://assist.dla.mil -- Downloaded: 202610-19T15:30Z
Check the source to verify that this is the current version before use.

Page 26, TABLE II: Delete "PPP-B-575", "PPP-B-645", associated titles, and dimensions; delete "MIL-B-10377" and substitute "PPP-B-576".

Page 27: Delete "NOTICE" paragraph.

Preparing Activity
Navy - OS
Project No. 1045-N006

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:30Z
Check the source to verify that this is the current version before use.