MIL-F-40047B(IH)
31 March 1969
Superseding
MIL-F-40047A(QMC)
30 June 1961

MILITARY SPECIFICATION

FLAG, SIGNAL, RED, VEHICLE, DANGER

1. SCOPE

1.1 This specification covers a red danger flag.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue on effect on the date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS
FEDERAL
V-T-276 - Thread, Cotton
CCC-C-446 - Cloth, Muslin, Cotton
PPP-B-601 - Boxes, Wood, Cleated Plywood
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner
PPP-B-636 - Box, Fiberboard
PPP-B-676 - Boxes, Set-Up, Paperboard
MILITARY
MIL-G-16491 - Grommets, Metallic
STANDARDS
FEDERAL
Fed. Std. No. 191 - Textile, Test Methods
Fed. Std. No. 751 - Stitches, Seams and Stitchings
MILITARY
MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

(Copies of specifications, standards and drawings required by the contractor in connection with a specific procurement should be obtained from the procuring activity or as directed by the contracting officer.)

/FSC 8345/

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

2.2 Other publications.- The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

COLOR ASSOCIATION OF THE UNITED STATES, INCORPORATED
Standard Color Card of America, 9th Edition

Department of Defense, Standard Color Card of Official Standardized Shades of Sewing Threads

(Application for copies of the color cards should be addressed to the Color Association of the United States, Inc., 200 Madison Ave., New York, NY 10016.)

3. REQUIREMENTS

3.1 Guide sample.- When required, guide samples of the flag may be obtained from the contracting officer and shall be furnished for information and guidance only. Where variation appears between the guide sample and the specification, the specification shall govern.

3.2 First article.- When required (see 6.2), before production is commenced a sample of the finished item shall be submitted to the contracting officer or his authorized representative for inspection as specified in 4.2. The approval of the first article authorizes the commencement of production but does not relieve the contractor of responsibility for compliance with all applicable provisions of this specification. The first article shall be manufactured by the contractor in the same facilities to be used for the manufacturing of the production items.

3.3 Materials.- Material shall conform to the referenced specifications and to the requirements specified herein.

3.3.1 Cloth, muslin, cotton.- The cotton muslin cloth shall conform to class 3 of CCC-C-446, except only the fastness to weathering shall be required. The cloth shall be dyed scarlet to match Cable No. 70080 (see 2.2).

3.3.2 Thread, cotton.- The thread for stitching shall be cotton conforming to type IA3, ticket No. 50, 3 ply of V-T-276. The thread shall be dyed scarlet to match CA 66040 of the DOD Standard Color Card for Sewing Threads. The thread shall show good fastness to weathering when tested as specified in V-T-276.

3.3.3 Grommets.- The metallic grommets shall conform to type I, class 1, size 1 of MIL-G-16491.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

3.4 Construction.-

3.4.1 Hems.- The four sides of the flag shall be hemmed with a 1-3/4 inches, plus or minus 1/8 inch wide hem having a 3/8 inch turned edge and stitching 1/16 inch from inside the turned edge.

3.4.2 Stitches and stitching.- The stitches and stitchings shall conform to stitch type 301 and stitching type EFb-1 of Fed. Std. No. 751 with 10 to 14 stitches per inch. Thread breaks in stitching shall be backstitched not less than 1 inch at each break. Stitching shall be backstitched not less than 1/2 inch at the ends, except where ends are turned under in a hem or held down by other stitching. Thread tension shall be maintained so that there will be no loose stitching and that the lock will be embedded in the materials sewed. All thread ends shall be trimmed.

3.4.3 Size.- The finished flag shall measure 18 inches long by 18 inches wide, with a tolerance of plus or minus 1/2 inch.

3.4.4 Setting of grommets.- The grommets specified in 3.3.3. shall be placed at each corner of the flag. The center of the grommet shall be 7/8 inch plus or minus 1/8 inch from each outside edge. The grommets shall be securely clinched without cutting the fabric.

3.5 Workmanship.- The finished flags shall conform to the quality and grade of product established by this specification. Occurance of defect shall not exceed the applicable acceptance quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Inspection responsibility.- Unless otherwise specified in the contract or order, the supplier is responsible for the performance of all the inspection requirements specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless otherwise dissapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification when deemed necessary to assure supplies and services conform to the prescribed requirements.

4.2 First article inspection.- When a first article is required, the sample shall be inspected for all provisions of this specification applicable to end item examination and testing.

4.3 Inspection for acceptance.- The inspection shall be in accordance with MIL-STD-105 except where otherwise indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

4.3.1 Testing of components.- In addition to the quality assurance provisions of the subsidiary specifications and drawings, testing shall be performed on the dyed cloth, cotton, print to determine fastness to weathering in accordance with test method 5671 of Fed. Std. No. 191. The inspection level (sample size) shall be S-1 and the acceptable quality level (AQL) shall be 6.5 defects per hundred units. Requirements shall be applicable to the sample unit.

4.3.2 *Inspection of the end item*.-

4.3.2.1 Examination of end item.- The flag shall be examined to determine conformance with the requirements of this specification. Defects found during this examination shall be classified in accordance with 4.3.2.2 and 4.3.2.3. The sample unit shall be one completely finished flag.

4.3.2.2 Examination for visual characteristics.- The sample unit for this examination shall be one flag.

Examine	Defect	Classification	
		Major	Minor
Fabric	Holes or any weakening defects, such as smashes, multiple floats or loose and weakening slubs expected to develop into a hole.....	x	-
	Needle chews.....	x	-
	Any scissors or knife cut, tear, mend or burn...	x	-
	Shade bar, affecting appearance.....	-	x
	NOTE: Slight defects of shade bars, slubs and needle holes (not chews) not expected to weaken the fabric and not affecting appearance or serviceability shall not be classified as defects.		
Cleanness	Spots or stains of an obvious permanent nature..	x	-
	Removable spots or stains clearly noticeable....	-	x
	Thread ends not trimmed throughout.....	-	x
Seams and stitching	Ends of all stitching not backstitched at least 1/2 inch, (except where ends are turned under or held down by other stitching).....	-	x
	Thread breaks not backstitched at least 1 inch..	-	x
	Gage of stitching irregular, i.e., unevenly gaged or various stitching not uniform, affecting appearance.....	-	x
	Open seams or hems 1/2 inch or more.....	-	x
	Open seams on hems less than 1/2 inch at two or more places.....	-	x

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification	
		Major	Minor
	NOTE: One or more broken or two or more continuous skipped or runoff stitches constitutes an open seam. Thread breaks not backstitched shall be classified as open seams.		
	Any raw edge	x	-
	Hem on four sides of flag less than 1-5/8 inch or more than 1-7/8 inch	-	x
	Wrong seam type	-	x
	Wrong stitch type	-	x
	Loose tension resulting in loosely exposed bobbin or top thread	x	-
	Tight tension (stitches break when normal strain is applied to the stitching)	x	-
	NOTE: Puckering is evidence of tight tension. When puckering is evident, the inspector shall test stitching by exerting normal pull in the lengthwise direction of the stitching.		
	One or more stitches per inch less than specified	-	x
	Three or more stitches per inch less than specified	x	-
	One or more stitches in excess of maximum specified	-	x
Grommets	One or more missing	x	-
	Insecurely clinched, broken, cracked or otherwise defective, affecting function	x	-
	Any (4 required) clinched too tight cutting surrounding fabric	x	-
	Rough or sharp edges	-	x
	Not brass	-	x
	Not positioned as specified	x	-

4.3.2.3 Dimensional examination.- The sample unit shall be one flag. Any measurement beyond applicable tolerances shall be classified as a defect.

4.3.2.4 Inspection levels and acceptable quality levels.- The inspection levels and acceptable quality levels (AQL's) expressed in defect per hundred units, shall be as follows:

	Inspection level	AQL Major	AQL Total
For defects applicable to 4.3.2.2	II	2.5	6.5
For defects applicable to 4.3.2.3	S-3	(one class)	2.5

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

4.3.3 Examination of preparation for delivery requirements.- An examination shall be made to determine that packaging, packing and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

Examine	Defect
Marking (exterior and interior)	Omitted, incorrect, illegible, of improper size, sequence, location or method of application.
Materials	Any component missing.
	Any component damaged, affecting serviceability.
Workmanship	Inadequate application of components, such as incomplete closure of case liners, container flaps, improper taping, loose strapping, inadequate stapling.
	Bulging or distortion of containers.
Content	Number in container is more or less than required.

5. PREPARATION FOR DELIVERY

5.1 Packaging.- Packaging shall be level A or C, as specified (see 6.2).

5.1.1 Level A.-

5.1.1.1 Unit package.- Each flag shall be folded into an approximately 9 inch square. Ten folded flags shall be neatly stacked and inserted in a snug-fitting, transparent, polyethylene bag. The polyethylene film shall be not less than 0.0015 inch thick. All seams and closures shall be affected by heat sealing and all excess air within the bag shall be expelled before sealing.

5.1.1.2 Intermediate packaging.- Five units packaged (50 flags) shall be packaged in a set-up, paperboard box conforming to type I, variety 2, class A, style 4 of PPP-B-676. Box closure shall be in accordance with the appendix of the container specification.

5.1.2 Level C.- Flags shall be packaged to afford adequate protection against deterioration and damage during shipment from the supply source to the first receiving station. The supplier may use his standard practice when it meets these requirements.

5.2 Packing.- Packing shall be level A, B or C, as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

5.2.1 Level A.- Flags packaged as specified in 5.1, shall be packed in a shipping container conforming to overseas type, style A, B, I or J of PPP-B-601 or class 2, style 4 of PPP-B-621. Closure shall be in accordance with the appendix of the container specification.

5.2.2 Level B.- Ten intermediate packages (500 flags) packaged as specified in 5.1 shall be packed in a shipping container conforming to type SF, class weather-resistant, grades V3s or W5s of PPP-B-636. Closure shall be in accordance with the appendix of the container specification.

5.2.3 Level C.- Flags packaged as specified in 5.1, shall be packed in a manner to assure carrier acceptance and safe delivery at destination at the lowest transportation rates for such supplies. Containers shall be in accordance with the rules and regulations of carriers applicable to the mode of transportation.

5.3 Marking.- In addition to any special marking required by the contract or order, unit packages, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES.

6.1 Intended use.- Flags covered by this specification are intended to be used on vehicles transporting explosives or other hazardous cargo.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) When a first article is required.
(c) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

Custodian:
Army - IH
Review Activity:
Other - DP
User Activity:
Army - SM
Navy - MC

Project No. 8345-0069

Preparing Activity:

The Institute of Heraldry,
United States Army

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

MIL-F-40047B(IH) Flag, Signal Red, Vehicle, Danger

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
THE INSTITUTE OF HERALDRY, U.S. ARMY
CAMERON STATION
ALEXANDRIA, VA. 22314

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

COMMANDING OFFICER
THE INSTITUTE OF HERALDRY, U.S. ARMY
ATTN: AGAH-T
CAMERON STATION
ALEXANDRIA, VA. 22314

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.