NOT MEASUREMENT SENSITIVE

MIL-F-40047C
12 May 1992
SUPERSEDING
MIL-F-40047B(IH)
31 March 1969

MILITARY SPECIFICATION

FLAG, SIGNAL, RED, VEHICLE, DANGER

This specification is approved for use by all Departments and Agencies of the Department of Defense

1. SCOPE

1.1 Scope. This specification covers the general requirements of a red danger flag.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

NN-P-71 - Pallets, Material Handling, Wood Stringer Construction, 2-Way and 4-Way (Partial)
V-T-285 - Thread, Polyester
CCC-C-430 - Cloth, Sheeting, Cotton and Polyester and Cotton
PPP-B-636 - Box, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in preparing this document should be addressed to: Director, The Institute of Heraldry, U.S. Army, Cameron Station, Alexandria, VA 22304-5050 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:04Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-15011 - Pallet, Material Handling, Wood Post Construction 4 Way entry
MIL-G-16491 - Grommet, Metallic

STANDARDS

FEDERAL

FED-STD-191 - Textile, Test Methods
FED-STD-751 - Stitches, Seams and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads

(Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from: Standardization Document Order Desk, Building 4D, Section D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

COMMERCIAL ITEM DESCRIPTIONS

A-A-50155 - Cloth, Muslin, Cotton
A-A-52094 - Thread, Cotton

(Copies of specifications, standards, drawings and specification sheets required by the contractors in connection with specific procurement functions should be obtained from the procuring activities or as directed by the contracting officer.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

THE COLOR ASSOCIATION OF THE UNITED STATES, INC.

United States Army Color Card, The Official Colors for Branches, Agencies, etc.

DOD Standard Color Card of Official Standardized Shades for Heraldic Yarns, 1974.

(Application for copies of the color cards should be addressed to the Color Association of the United States, 343 Lexington Avenue, New York, NY 10016.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:04Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM-D-3951 - Standard Practice for Commercial Packaging (DOD adopted)

(Application for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Nongovernment standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other information services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (See 6.3).

3.2 Material. Materials shall conform to the referenced specifications and the requirements specified herein.

3.2.1 Cloth, muslin, cotton. The cotton muslin shall conform to Type I, II or III, of A-A-50155 or Type II, Class 2, Style B of CCC-C-430. The cloth shall be dyed scarlet to match Cable No. 65006 of the Standard Color Reference of America, United States Army Color Card and shall have good fastness to weathering when tested as specified in 4.3.1.

3.2.2 Thread, cotton. The thread for stitching shall be cotton conforming to Type 1, Ticket No. 50, 3 ply of A-A-52094. The thread shall be dyed scarlet to match Cable No. HL 67111 of the DOD Standard Color Card of Official Standardized shades for Heraldic Yarns. The thread shall show good fastness to weathering when tested as specified in A-A-52094.

3.2.3 Thread, Spun Polyester. Use of spun polyester thread Type 1 Class 1, 3 ply, Letter size B of V-T-285, matching Scarlet HL 67111 of the DOD Standard Color Card of Official Standardized Shades for Heraldic Yarns is authorized as an optional thread for stitching.

3.2.4 Grommets. The metallic grommets shall conform to Type I, Class 1, Trade size 1 of MIL-G-16491 {See MS20230 (ASG)}.

3.3 Construction.

3.3.1 Hems. The four sides of the flag shall be hemmed with 1-3/4 inches ± 1/8 inch (4.45 cm ± 0.32 cm) wide hem having a 3/8 inch (0.95 cm) turned edge and stitching 1/16 inch (0.16 cm) from inside the turned edge. The flag shall be constructed from a single piece of material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:04Z
Check the source to verify that this is the current version before use.

3.3.2 Stitches and stitching. The stitches and stitching shall conform to stitch type 301 and stitching type EFb-1 of FED-STD-751 with 10 to 14 stitches per inch. Thread breaks in stitching shall be backstitched not less than 1 inch (2.54 cm) at each break. Stitching shall be backstitched not less than 1/2 inch (1.27 cm) at the ends, except where ends are turned under in a hem or held down by other stitching. Thread tension shall be maintained so there will be no loose stitching and the lock will be embedded in the materials sewed. All threads shall be trimmed.

3.3.3 Size. The finished flag shall measure 18 inches (45.72 cm) long by 18 inches (45.72 cm) wide, with a tolerance of plus or minus 1/2 inch (1.27 cm).

3.3.4 Setting of grommet. The grommets specified in 3.2.4 shall be placed at each corner of the flag. The center of the grommet shall be 7/8 inch ± 1/8 inch (2.22 cm ± 0.32 cm) from each outside edge. The grommets shall be securely clinched without cutting the fabric.

3.4 Workmanship. The finished flags shall be clean, well made and shall meet the acceptable quality levels established by this specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspections set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 First article inspection. When a first article is required, inspection and testing shall be made on a completely finished item for all provisions of this specification applicable to the end product examination and tests (see 6.4).

4.3 Inspection for acceptance. The inspection shall be in accordance with MIL-STD-105 except where otherwise indicated.

4.3.1 Testing of components. In addition to the quality assurance provisions of the subsidiary specifications and drawings, testing shall be performed on the dyed cotton muslin to determine fastness to weathering in accordance with test method 5671

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:04Z
Check the source to verify that this is the current version before use.

of FED-STD-191. The inspection level shall be S-1 and the acceptable quality level (AQL) shall be 6.5 defects per hundred units. Requirements shall be applicable to the sample unit.

4.3.2 Inspection of the end item.

4.3.2.1 Examination of end item. The flag shall be examined to determine conformance with the requirements of this specification. Defects found during this examination shall be classified in accordance with 4.3.2.2 and 4.3.2.3. The sample unit shall be one completely finished flag.

4.3.2.2. Examination for visual characteristics. The sample for this examination shall be one flag.

EXAMINE	DEFECT	CLASSIFICATION Major	Minor
Fabric	Holes or any weakening defects, such as smashes, multiple floats or loose and weakening slubs expected to develop into a hole.....	x	-
	Needle chews.....	x	-
	Any scissors or knife cut, tear, mend or burn.....	x	-
	Shade bar, affecting appearance.....	-	x
	NOTE: Slight defects of shade bars, slubs, and needle holes (not chews) not expected to weaken the fabric and not affecting appearance or serviceability shall not be classified as defects.		
Cleanliness	Spots or stains of an obvious permanent nature.....	x	-
	Removable spots or stains clearly noticeable.....	-	x
	Thread ends not trimmed throughout.....	-	x
Seams and stitching	Ends of all stitching not backstitched at least 1/2 inch (1.27 cm) (except where ends are turned under or held down by other stitching).....	-	x
	Thread breaks not backstitched at least 1 inch (2.54 cm).....	-	x
	Gage of stitching irregular; i.e., unevenly gaged or various stitching not uniform in appearance.....	-	x
	Open seams or hems 1/2 inch (1.27 cm) or more.....	-	x
	Open seams or hems less than 1/2 inch (1.27 cm) at two or more places.....	-	x
	NOTE: One or more broken or two or more continuous skipped or runoff stitches constitutes an open seam. Thread breaks not backstitched shall be classified as open seams.		
	Any raw edge.....	x	-
	Hem on four sides of flag less than 1-5/8 inch (4.13 cm) or more than 1-7/8 inch (4.77 cm).....	-	x
	Wrong seam type.....	-	x
	Wrong stitch type.....	-	x

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:04Z
Check the source to verify that this is the current version before use.

EXAMINE	DEFECT	CLASSIFICATION Major	Minor
	Loose tension resulting in loosely exposed bobbin or top thread.....	x	-
	Tight tension (stitches break when normal strain is applied to the stitching).....	x	-
	NOTE: Puckering is evidence of tight tension. When puckering is evident, the inspector shall test stitching by exerting normal pull in the lengthwise direction of the stitching.		
	One or more stitches per inch less than specified....	-	x
	Three or more stitches per inch less than specified..	x	-
	One or more stitches in excess of maximum specified..	-	x
Grommets	One or more missing.....	x	-
	Insecurely clinched, broken, cracked or otherwise defective, affecting function.....	x	-
	Any (4 required) clinched too tight cutting surrounding fabric.....	x	-
	Rough or sharp edges.....	-	x
	Not brass.....	-	x
	Not positioned as specified.....	x	-

4.3.2.3 Dimensional examination. The sample unit shall be one flag. Any dimension which is not within the specified tolerances shall be classified as a defect.

4.3.2.4 Inspection levels and acceptable quality levels. The inspection levels and acceptable quality levels (AQL's) expressed in defects per hundred units shall be as follows:

	Inspection Level	AQL Major	AQL Total
For defects applicable to 4.3.2.2	II	2.5	6.5
For defects applicable to 4.3.2.3	S-3	(one class)	2.5

4.3.3 Examination of preparation for delivery requirements. An examination shall be made to determine that packaging, packing and marking requirements are complied with. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery, with the exception that it need not be sealed. Defects of closure listed below shall be examined on a shipping container fully prepared for delivery. The lot size shall be the number of containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:04Z
Check the source to verify that this is the current version before use.

EXAMINE	DEFECT
Markings, exterior and interior	Missing, incorrect, illegible or improper size, location sequence or method of application.
Materials	Component missing, damaged or otherwise defective, affecting serviceability.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, inadequate stapling. Bulging or distortion of containers.
Content	Number in container is more or less than required.
Weight	Net weight exceeds the requirements.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Unit packaging. Each flag shall be folded into an approximately 9 inch (22.86 cm) square. Ten folded flags shall then be neatly stacked and placed in a snug fitted transparent polyethylene bag. The polyethylene film shall be not less than 0.0015 inch (0.0381 cm) thick. All seams and closures shall be affected by heat sealing and excess air within the bag shall be expelled before sealing.

5.1.2 Commercial. Flag shall be preserved and packaged in accordance with the applicable requirements of ASTM-D-3951.

5.2 Packing. Packing shall be level B or commercial as specified (see 6.2).

5.2.1 Level B. Fifty unit packages (500 flags) packaged as specified in 5.1.1 shall be packed in a snug-fitting shipping container conforming to Style RSC, Type CF or SF, class weather-resistant, variety SW, grades V3S or W5S of PPP-B-636. Closure shall be in accordance with the appendix of the container specification; however, method III or VI may be permitted.

5.2.2 Commercial. Flags packaged a specified in 5.1.1 shall be packed in accordance with the applicable requirements of ASTM-D-3951.

5.3 Palletization. Unitized loads, commensurate with the level of packing specified in the contract or order, shall be palletized on a 4-way entry pallet in accordance with load type 1A of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means C, K and L or O or P. Pallet pattern shall be in accordance with the appendix of MIL-STD-147. The pallet shall be 4-way, type I, Class 1, Style 1, Size A, Wood Group I, II, III or IV of MIL-P-15011, or, 4-way, Type IV, V or VIII, Class 1, Style A, Size 2, Wood Group I, II, III or IV, Grade A of NN-P-71. Interlocking of loads shall be effected by

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:04Z
Check the source to verify that this is the current version before use.

reversing the pattern of each course. If the container is of a size which does not conform to any of the patterns specified in MIL-STD-147, the pallet pattern used shall be approved by the contracting officer.

5.4 Marking. In addition to any special markings required by the contract or purchase order, unit packages, intermediate boxes, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. Flags covered by this specification are intended to be used on vehicles transporting explosives or other hazardous cargo.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1).

c. When first article is required (See 3.1).

d. Selection of application levels of packaging and packing (See 5.1 and 5.2).

6.3 First article. When first article inspection is required, the contracting officer should provide specific article test results and disposition of first articles. The invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or tests, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.4 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army - IH
Navy - NU

Review activities:
DLA - CT

User activity:
Navy - MC

Preparing activity:
Army - IH

(Project No. 8345-0197)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:04Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-F-40047C	020525

3. DOCUMENT TITLE
FLAG, SIGNAL, RED, VEHICLE, DANGER

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON
The Institute of Heraldry	(703) 274-6636	284-6636
c. ADDRESS (Include Zip Code) Bldg 15, Technical & Production Division Cameron Station Alexandria, VA 22304-5050	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-03-27 15:23:47 Z
Check the source to verify that this is the current version before use.