MIL-F-0040048B

3 June 1977

Used IN LIEU OF

MIL-F-40048A

28 March 1962

MILITARY SPECIFICATION

FLAGSTAFFS AND INSIGNIA, FLAGSTAFF HEADS

GENERAL SPECIFICATION FOR

This interim specification has been developed by the Institute of Heraldry, US Army, based on currently available technical information and is recommended for use by the Defense Personnel Support Center until a coordinated specification can be approved.

1. SCOPE

1.1 Scope.- This specification covers wood and metal flagstaffs, and flagstaff heads.

1.2 Classification.- Flagstaffs and flagstaff heads shall be of the following types, components, sizes, classes and style as specified. (See 6.2 and 6.3.)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: Director, The Institute of Heraldry, US Army, Cameron Station, Alexandria, VA 22314, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8345

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

Type I - Presidential Flagstaff

Component A - Staff with upper and lower ferrule and male and female coupling mounted

Component B - Flagstaff head, eagle

Type III - Army 9 ft. 6 inch jointed flagstaff (colors)

Component A - Staff with lower ferrule and coupling mounted

Component B - Flagstaff head spear

Type IV - Army 8 ft. jointed Flagstaff (Guidons)

Component A - Staff with lower ferrule and coupling mounted

Component B - Flagstaff head spear

Type V - Army Markers and Marking pennant flagstaff

Type VI - Navy Battalion flagstaff

Component A - Staff with base and male and female ferrules mounted

Component B - Flagstaff head, Battleaxe

Type VIII - Navy Boat Flagstaff

Component A - Staff with truck (adapter) mounted

Size - 4 ft 6 inch

Size - 5 ft

Size - 5 ft 6 inch

Size - 6 ft

Size - 6 ft 6 inch

Size - 7 ft

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

Size - 7 ft 6 inch

Size - 8 ft

Size - 8 ft 6 inch

Size - 9 ft

Size - 9 ft 6 inch

Size - 10 ft

Component B - Flagstaff head, Navy

Style 1 - Spread eagle

Style 2 - Halberd

Style 3 - Ball

Style 4 - Star

Type IX - Automobile flagstaff

Size 1 - President's

Size 2 - Official's

Type X - Wooden minesweeping flagstaff

Size 1 - Type S.G. and "O" type, Size 5 Floats

Size 2 - Position Buoy

Size 3 - Type 3 Dan Buoy

Type XI - Metal Minesweeping flagstaff

Class 1 - Carbon steel for Size 1 and 4 "O" type floats

Class 2 - Corrosion-Resisting steel, nonmagnetic, for size 0, 1 and 4 "O" Type floats

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-B-613	-Brass, Leaded and Nonleaded; Flat Products, (Plate, Bar, Sheet and Strip.)
QQ-B-626	-Brass, Leaded and Nonleaded; Rod, Shape, Forgings and Flat Products with Finished Edges (Bars, and Strips.)
QQ-C-320	-Chromium Plating (Electrodeposited.)
QQ-C-390	-Copper Alloy Castings, (Including Cast Bar.)
QQ-P-416	-Plating, Cadmium (Electrodeposited.)
QQ-S-633	-Steel Bars, Carbon, Cold Finished and Hot Rolled, (General Purpose.)
QQ-S-698	-Steel, Sheet and Strip, Low Carbon
QQ-T-830	-Tube, Steel, Carbon, Mechanical, Round; Seamless and Welded.
TT-E-489	-Enamel; Alkyd Gloss (for Exterior and Interior Surfaces.)
TT-L-31	-Lacquer, Cellulose Nitrate, Gloss.
TT-P-59	-Paint; Ready-Mixed, International Orange.
TT-P-636	-Primer Coating, Synthetic, Wood and Ferrous Metal.

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:05Z
Check the source to verify that this is the current version before use.

TT-V-119 -Varnish, Spar, Phenolic-Resin.

TT-V-121 -Varnish, Spar, Water-Resisting.

UU-P-268 -Paper, Kraft, Wrapping.

MMM-A-100 -Adhesive, Animal-Glue.

MMM-A-125 -Adhesive, Casein-Type, Water-And Mold-Resistant.

MMM-A-193 -Adhesive, Vinyl Acetate, Resin Emulsion.

PPP-B-566 -Boxes, Folding, Paperboard.

PPP-B-636 -Box, Shipping Fiberboard.

PPP-B-676 -Box, Set-Up.

PPP-P-291 -Paperboard, Wrapping, Cushioning.

PPP-T-45 -Tape, Gummed Paper.

MILITARY

MIL-A-22397 - Adhesive, Phenol and Resorcinol Resin Base (For Marine Services.)

MIL-D-3943 - Decorations General Specification for.

MIL-I-17214 - Indicator, Permeability, Low-mu (Go-no-go)

STANDARDS

FEDERAL

FED-STD-151 - Metals, Test Methods

FED-STD-595 - Colors

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by attributes

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:05Z
Check the source to verify that this is the current version before use.

MIL-STD-129 - Marking for Shipment and Storage

MIL-STD-1363 - Measurement of Wood Moisture Content

DRAWINGS

THE INSTITUTE OF HERALDRY

B-7-1	Flagstaff Head Eagle
B-7-2	Flagstaff Head Spread Eagle
B-7-3	Flagstaff Head Halberd (Navy)
B-7-4	Flagstaff Head Ball (Navy)
B-7-5	Flagstaff Head Spear, Army, Male section
B-7-6	Ferrule, Flagstaff, Army and Flagstaff Head, Spear Female section
B-7-7	Flagstaff Head, Star (Navy)
B-7-8	Flagstaff Head Battleaxe (Navy)
B-7-9	Truck Flagstaff Head (Navy)
B-7-10	Flagstaffs, Army, Details and Assembled views
B-7-11	Flagstaff, Automobile, Metal, Assembly and Details
B-7-12	Flagstaff, Battalion, Navy, Assembly and Details
B-7-13	Flagstaff, Minesweeping, wooden
B-7-14	Flagstaff, Metal, Floats
B-7-15	Flagstaff Boat (Navy)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

B-7-17 Flagstaff Head, Acorn (wooden)

B-7-19 Flagstaff, Presidential, Details and Assembled Views

B-7-20 Ferrules, Upper and Lower, Presidential Flagstaff

B-7-21 Couplings, Male and Female, Presidential Flagstaff

(Copies of specifications, standards, and drawings required by the contractor in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3 REQUIREMENTS:

3.1 *Standard sample.*- Unless otherwise specified, (see 6.2), a standard sample and/or production plate shall be furnished. When a production plate is furnished, the standard sample shall be used for color and finish only. When no production plate is furnished, the standard samples shall be used as a model in addition to establishing the color and finish.

3.2 First article.- Unless otherwise specified, (see 6.2), before production is commenced, a sample of the finished item covered by this specification shall be submitted or made available to the contracting officer or his authorized representative for inspection and tests as specified in 4.2. The approval of the first article does not relieve the contractor of responsibility for compliance with all applicable provisions of this specification. The first article shall be manufactured by the contractor in the same facilities to be used for the manufacture of the production items.

3.3 Material: Materials shall conform to the referenced specification and the requirements specified herein.

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:05Z
Check the source to verify that this is the current version before use.

3.3.1 Brass.-

3.3.1.1 Castings.- Brass for castings shall conform to the chemical composition of Alloys Nos. A3 or A4 of QQ-C-390 for brass finished end items and Alloys A3, B2 or B5 of QQ-C-390 for Chrome or Gold plated end items.

3.3.1.2 Forgings.- Brass for forgings shall conform to composition 21, half hard of QQ-B-626.

3.3.1.3 Machined parts.- The brass used for machine parts shall conform to chemical composition 1 or 2 of specifications "QQ-B-613 or QQ-B-626."

3.3.2 Wood. All wood used for flagstaffs and acorns shall have a moisture content of 8 to 12 percent at the time of milling when tested in accordance with 4.4.1. The slope of the grain shall not exceed 1 inch in 12 inches when tested in accordance with 4.4.2. The wood shall be free from checks, splits, crook, and torn or raised grain or any other defect which may affect appearance and serviceability. One tight knot not to exceed 1/2 inch at largest dimension and not more than one per staff will be permitted. The species of wood for the various types of flagstaffs shall be as follows:

(a) Type I, Birch, Maple, Beech, Ash.

(b) Types III, IV, V, VI, VIII and Type X, Sizes 1 and 2, Oak, Birch, Beech, Hickory, Ash, Pecan.

(c) Type X, size 3, Red spruce or Sitka spruce.

3.3.3 Gold. Gold for plating shall be 24 Karat.

3.3.4 Primer. Primer shall conform to TT-P-636.

3.3.5 Enamel. Enamel shall conform to class A or B of TT-E-489. The color shall be black and shall match color number 17038 of Standard No. 595, except that the following characteristics shall not apply: saponifiable matter

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

water percent; coarse particles and skins; viscosity; drying time; storage stability; dilution stability; bruising properties and odor.

3.3.6 Glue.

3.3.6.1 Nonwaterproff glue. Glue for nonwaterproof service shall conform to one of the following at the option of the manufacturer:

(a) Type I or II of MMM-A-100, except that the following characteristics shall not apply: Viscosity; foam; odor; and keeping quality.

(b) Type I or II of MMM-A-125, except that the following characteristics shall not apply: Working lie; setting properties.

(c) MMM-A-193, except that the following characteristics shall not apply: Viscosity; stability.

3.3.6.2 Waterproof glue. Glue for marine service shall conform to grade A or B of MIL-A-22397, except that the following characteristics shall not apply: Liquid working life; cleanability; adhesive spread; storage life.

3.3.7 Varnish.

3.3.7.1 Shore service varnish. Varnish for on-shore service shall conform to TT-V-121, except that the following characteristics shall not apply: Set to touch; dry hard free from tack; viscosity; flash point; skinning; odor.

3.3.7.2 Varnish for marine service. Varnish for marine service shall conform to TT-V-119, except that the following characteristics shall not apply: Viscosity; flash point; drying time; compatibility with zinc oxide pigment; skinning; baking properties; gas proofness; draft - proofness; odor.

3.3.8 Steel.-

3.3.8.1 Steel bar stock.- Bar stock steel shall conform to condition HR or CR, C1010-1020 of QQ-S-633.

Source: https://assist.dla.mil -- Downloaded: 202640-21T19:05Z
Check the source to verify that this is the currenversion before use.

3.3.8.2 Steel sheet and strip.- Sheet and strip steel shall conform to hot rolled or cold rolled commercial quality of QQ-S-698 any temper.

3.3.9 Steel tubing.

3.3.9.1 Steel tubing, carbon. Carbon steel tubing shall be welded or seamless, killed or semikilled, HR or CD, MT-1010-1020 of QQ-T-830.

3.3.9.2 Steel tubing, corrosion-resistant . Corrosion-resistant steel tubing shall be type 304, No. 2 B finish, commercial grade.

3.3.10 Orange paint. Orange paint for marine services shall conform to TT-P-59.

3.3.11 Lacquer.- Lacquer shall be clear and shall conform to TT-L-31.

3.4 Construction.- Flagstaff, flagstaff heads, trucks, ferrules, and couplings shall be constructed in accordance with the applicable drawings and the requirements specified herein. Unless otherwise specified herein, staffs shall be made from the types of hardwood specified in 3.3.2. The wood portions shall be turned and sanded smooth. After fabrication, there shall be no warp, bow or croole exceeding 1/32 inch per foot. When screw holes are required for mounting couplings, ferrules, trucks or flagstaff heads, the holes shall be drilled to the proper size and screws shall not be driven by hammer.

3.4.1 Type I.-

3.4.1.1 Component A. Staffs shall be constructed in accordance with drawings B-7-19, B-7-20, and B-7-21. The upper and lower ferrules, coupling and mounting screws shall be made from brass specified in 3.3.1 and shall have a polished gold plated finish. The wood portions of the staff shall have a hand rubbed enamel finish (see 3.5.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

3.4.1.2 Component B.- The flagstaff head shall be molded from brass specified in 3.3.1. The design of the eagle shall be controlled by the Government furnished production plate. The eagle shall be cast in two pieces. The legs shall be forced fit into the body and the pieces shall be joined by means of a screw passing through the tail feather and into the ball. The eagle shall have a polished gold plated finish. When the eagle is procured as a separate item, the stud shall be furnished with the eagle.

3.4.2 Types III & IV.

3.4.2.1 Component A.- Staff shall be constructed in accordance with drawings, B-7-6 and B-7-10. The ferrule and coupling shall be fabricated from brass specified in 3.3.1 and shall have a chrome plated finish. Screws used for mounting shall be nickel plated. Prior to assembly, the staff shall be given 2 coats of varnish in accordance with 3.5.3.

3.4.2.2 Component B.- The spearhead shall be constructed from brass specified in 3.3.1 in accordance with drawings B-7-5 and B-7-6 and shall have a chrome plated finish. When the spearhead is procured separately, mounting screw specified in 3.4.2.1 shall be furnished with the spearhead.

3.4.3 Type V. The staff shall be constructed in accordance with drawings B-7-10 and B-7-17. The ferrule and coupling shall be fabricated from brass specified in 3.3.1 and shall be chrome plated. The acorn shall be fabricated

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:05Z
Check the source to verify that this is the current version before use.

from wood specified in 3.3.2. The acorn shall be free from defects and tumbled or sanded smooth. The acorn shall be secured to the staff by means of glue specified in 3.3.6.1. The glue shall be applied in accordance with manufacturers recommendations. Prior to mounting of the ferrule and coupling; the staff shall be varnished in accordance with 3.5.3. Mounting screws shall be made from brass and shall be nickel plated.

3.4.4 Type VI.-

3.4.4.1 Component A.- Staffs shall be constructed in accordance with drawing B-7-12. The base and ferrule shall be fabricated from brass specified in 3.3.1 and shall have a brightly polished lacquered finish. Prior to mounting of the base and ferrules, the wood portion of the staff shall be varnished in accordance with 3.5.3. Mounting screws and rivets shall be fabricated from commercial brass and shall be finished to match the ferrule.

3.4.4.2 Component B.- Flagstaff head (Battleaxe) shall be constructed from brass specified in 3.3.1 in accordance with Drawing B-7-8 and shall have a brightly polished lacquered finish. When the flagstaff head is ordered as a separate item, the mounting screws shall be furnished with the flagstaff head.

3.4.5 Type VIII.-

3.4.5.1 Component A.- Staff shall be constructed in accordance with Drawing B-7-15. The size required shall be as specified (see 6.2). The truck (adapter) shall be fabricated from brass specified in 3.3.1 and shall have a polished lacquered finish. The bottom of the staff shall be adapted to suit the insign

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

or jack socket as specified (see 6.2). Prior to mounting the adapter (Truck), the wood positions of the flagstaff shall be varnished in accordance with 3.5.3. The rivet and screws shall be made from commercial brass and shall be finished to match the adapter.

3.4.5.2 Component B.- Flagstaff heads shall be fabricated from brass specified in 3.3.1 and shall have a polished lacquered finish. The style flagstaff head desired shall be as specified (see 6.2). When the flagstaff head is procured as a separate item, the screws shall be furnished with the flagstaff head.

3.4.5.2.1 Style 1.- The spread eagle shall be fabricated in accordance with Drawing 8-7-2. When the eagle is cast in two pieces, the pieces shall be jointed by brazing or hard soldering. The whole surface of contact shall be affected.

3.4.5.2.2 Style 2.- The flagstaff head (halberd) shall be fabricated in accordance with Drawing B-7-3.

3.4.5.2.3 Style 3.- The flagstaff head (Ball) shall be fabricated in accordance with Drawing B-7-4.

3.4.5.2.4 Style 4.- The flagstaff head (Star) shall be fabricated in accordance with Drawing B-7-7.

3.4.6 Type IX.- Automobile flagstaff shall be fabricated in accordance with Drawing B-7-11. All metal components shall have corners rounded and all burrs removed. The staff and acorn shall be fabricated from brass in 3.3.1 and shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

have a bright chrome plated finish. The bumper clamp, clamp bolt, nut and bumper bolt shall be made from steel specified in 3.3.8 and shall have a cadmium plated finish. The lock washer and screws shall be commercial grade cadmium plated.

3.4.7 Type X flagstaff.- The Type X flagstaffs shall be fabricated in accordance with Drawing B-7-13.

3.4.7.1 Size 1 and 2 staffs.- The size 1 and size 2 staffs shall be given 3 coats of varnish specified in 3.3.7.2 and applied as specified in 3.5.3. Before application of suceeding coats of varnish, the prior coat shall be throughly dried and lightly sanded.

3.4.7.2 Size 3 staff.- The size 3 staff shall be fabricated by gluing six equilateral triangle shape strips of hardwood together with glue specified in 3.3.6.2. The glue shall be applied as recommended by the manufacturer. After lamination process is completed, the staff shall be machined smooth and given two coats of paint specified in 3.3.10. Prior to application of the second coat, the first coat shall be throughly dried and lightly sanded. When tested as specified in 4.4.6, the staff shall not break.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

3.4.8 Type XI flagstaffs.-

3.4.8.1 Class 1.- The Type XI, class 1 flagstaffs shall be fabricated from carbon steel specified in 3.3.9.1 in accordance with Drawing 8-7-14. The staff shall be free from burrs and sharp edges. The staff shall have both the inside and outside surfaces coated with a commercial zinc chromate primer and two coats of commercial quick drying white alkyd type outside paint shall then be applied to the outside surfaces. Each coat shall be thoroughly dried before the succeeding coat is applied.

3.4.8.2 Class 2.- The Type XI, class 2 flagstaffs shall be fabricated from corrosion-resisting steel specified in 3.3.9.2 in accordance with Drawing B-7-14. When tested as specified in 4.4.8, the magnetic permeability level after fabrication shall not exceed 2.0. The staff shall have the letters "NM" stenciled in orange colored paint specified in 3.3.10. The letters shall be 1/2 inch high and shall be centered between the two 1/4 inch diameter holes located at the top of the staff.

3.5 Finishing.- Metal components shall be finished as specified in the applicable construction paragraph and in accordance with the requirement specified herein. All brass components which are not plated shall be coated with lacquer in accordance with 3.5.2.

3.5.1 Plating.- Prior to plating, the surface to be plated shall be cleaned of all matter which would affect the plating.

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:05Z
Check the source to verify that this is the current version before use.

3.5.1.1 Gold plating.- Gold plating shall be accomplished using gold specified in 3.3.3. The use of white metal as an underplating shall not be permitted. When tested as specified in 4.4.3., no visible chemical reaction such as evolution of gases shall appear. Gold plated items may be lacquered at the option of the manufacturer.

3.5.1.2 Cadmium plating.- When cadmium plating is required, the plating shall be in accordance with class 1, Type 1 of QQ-P-416.

3.5.1.3 Chromium plating.- When required, chromium plating shall be in accordance with class 1, Type 1 of QQ-C-320.

3.5.2 Lacquering.- Lacquering shall be accomplished using lacquer specified in 3.3.11. The dry lacquer film shall be continuous, level, adherent and free from lint, dust or other inclusions. When tested as specified in 4.4.9.1, there shall be no change in appearance of the lacquered surface except for a slight yellowing of the highlights and not more than two spots, each less than 1/16 inch largest dimension. When tested as specified in 4.4.7.2, the tissue paper shall not adhere to the lacquered surface.

3.5.3 Varnishing.- Varnishing shall be accomplished using varnishes specified in 3.3.7. The Types III, IV, V and VI staff shall use shore service varnish specified in 3.3.7.1. The Type VIII and Type X, sizes 1 and 2 flagstaff shall use marine service varnish specified in 3.3.7.2. Unless otherwise specified, two coats of varnish shall be applied. Each coat shall be thoroughly dried

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:05Z
Check the source to verify that this is the current version before use.

and the staff lightly sanded before the succeeding coat is applied. When tested as specified in 4.4.4.4, The tissue paper shall not stick to the staff. When tested as specified in 4.4.5, no ink shall remain on the staff.

3.5.4 Enameling.- When enameling is required, the enamel shall be as specified in 3.3.5. Prior to enameling, the surface to be enameled shall be coated with primer specified in 3.3.4 and thoroughly dried and lightly sanded. The drying and sanding process shall be repeated for each succeeding enamel coat. After the final coat of enamel is applied, the staff shall be given a hand rubbed finish. Enamel shall be applied so that there is no runs or areas of rough or missing film.

3.6 Workmanship.- Flagstaffs or flagstaff components shall be clean, well made, and meet the acceptable quality established by this specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 Inspection responsibility.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to the prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

4.2 First article inspection.- Inspection and testing of the first article shall be made on a completely finished flagstaff or component for all provisions applicable to the end product examination and tests.

4.3 Sampling for inspection and acceptance.- Sampling for inspection and acceptance shall be in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

4.3.1 Inspection of components.-

4.3.1.1 Testing of components.- In addition to the quality assurance provisions of the subsidiary specifications and standards, inspection shall be performed on components and materials listed in Table II for test characteristics shown. The inspection level shall be S-1.

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:05Z
Check the source to verify that this is the current version before use.

TABLE II Component testing.-

Component and lot expressed in terms of	Characteristic	Rqm't paragraph	Test method	Rqm't applicable to: Individual unit	Rqm't applicable to: Lot average	#determinations per sample unit	Results reported as	Sample unit
Wood (100 board feet)	species	3.3.2	Visual	x		1	Pass or fail	1 board
	Moisture Content	3.3.2	4.4.1	x		3	Average of 3 determinations to nearest 0.1%	1 component prior to milling
	Slope of grain	3.3.2	4.4.2	x		1	Pass or fail	1 component prior to milling
Steel Tubing Corrosion Resisting steel (100 lbs)	Chemical Composition	3.3.9	Method 111 or 112*		x	2 each element	To the nearest 0.01% each element	4 oz Composite

* FED-STD-151

4.3.1.2 Certification of compliance.- Components and materials listed herein may be accepted on the basis of a contractor's certification of compliance for the requirements indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

Components	Characteristics	Reqm't Ref.
Gold for plating	Karat	3.3.3
Zinc chromatic primer	Material Identification	3.4.8.1
White alkyd outside paint	Material Identification	3.4.8.1
Glue application	As recommended by glue manufacturer	3.4
screws	Material Identification and type of plating	3.4.1.1, 3.4.1.2, and 3.4.1.3
Screws and rivets	Material Identification	3.4.4.1 and 3.4.5.1
Lock washers and screws	Material Identification	3.4.6
Solder	Material Identification	3.4.5.2

4.3.2 Inprocess inspection.- Inspection shall be made at any point or during any phase of the manufacturing process to determine whether operations and assemblies are accomplished as specified. Inprocess inspection shall be conducted to see if accomplishment of the following is in accordance with the specification requirements:

Requirement, operation or assembly	Requirement paragraph
Sizes of screw holes	3.4
Driving of screws	3.4
Application of primer	3.4.8.1 and 3.5.4
Sanding first or first and second coat of enamel as applicable	3.5.4
Varnishing	3.5.3
Lacquering	3.5.2
Finish	3.5
Painting	3.4.8.1

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:05Z
Check the source to verify that this is the current version before use.

4.3.2.1 Intermediate examination. The defects found during examination shall be classified in accordance with the defects classification below. The lots shall be inspected in accordance with 4.3.2.1.1. The sample unit for these examinations shall be one partially fabricated typeI, type X, size 3 and type XI, class 1, flagstaff of each size, after fabrication, but prior to the assembly of hardware and the application of primer or finish coatings.

Examine	Defect	Classification	
		Major	Minor
Quality of wood.....	Not species specified	x	
	Decay or rot	x	
	Fracture, split, break or splinter	x	
	Shake, check, pitch pocket, torn, raised or loose grain ..	x	
	Any loose or unsound knot or hole (except specified hole) .	x	
	Tight knot more than 1/2 inch in largest dimension	x	
	More than one tight knot 1/2 inch or less in largest dimension, per flagstaff or section of staff		x

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
	Wane, larvae channel or other imperfection		x
	Any nonpermissable defect filled in with plastic wood or other filler material		x
Construction and workmanship	Type X, size 3 staff not laminated of six equilateral triangular shaped segments	x	
	Laminated staff contains open glue joint 1/16 inch or more in depth or 3 inches or more in length	x	
	Laminated staff contains open joint less than 1/16 inch in depth or less than 3 inches in length	x	
	Any segmented pieced, i.e., is not the full length of flagstaff	x	
	Segments of type X, size 3 staff are not in alignment, e.g., edge protrudes		x
	Not sanded smooth where required	x	
Quality of metal ...	Crack, tear, split or hole (except specified hole)	x	
	Pipe, burnt spot or incomplete penetration of weld (in welded tubing)		x
	Welded tubing has more than one weld (the longitudinal weld necessary for manufacture)		x
	Crushed or bent out of shape .	x	
	Burr, sliver, rough edge or shape edge		x

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:05Z
Check the source to verify that this is the current version before use.

4.3.2.1.1 Inspection levels and AQL's. The inspection levels and acceptable quality level (AQL) expressed in defects per hundred units shall be as follows:

		AQL	
	Inspection level	Major	Total
For defects applicable to 4.3.2.1	II	1.5	6.5

4.3.3 End item examination. The defects found during examination shall be classified in accordance with 4.3.3.1 and 4.3.3.2. The lots shall be inspected in accordance with 4.3.3.3. The sample unit for these examinations shall be one flagstaff, or flagstaff head of each type, class size, or styles, as applicable.

4.3.3.1. Examination of flagstaffs, flagstaff heads, coupling, trucks, and ferrules for visual characteristics.

		Classification	
Examine	Defect	Major	Minor
Finish of wooden components.....	Not finished or finish is not as specified, e.g., type I flagstaff does not have hand rubbed finish ...	x	
	Not close match to specified color ..		x
	Finish is not smooth and uniform, e.g., contains run, sag, drip, drop or area of no film or thin film		x

Source: https://assist.dla.mil -- Downloaded: 20261-21T19:05Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification: Major	Classification: Minor
	Finish is not adherent, e.g., is blistered, peeling or flaking		x
	Stained or discolored		x
	Foreign matter imbedded		x
	Gouge, scratch, scuff, chipout, machine mark or other impairment	x	
	Wet or tacky		x
Finish of metal components	Not finished	x	
	Type of finish is not as specified, e.g., is not gold, cadmium, nickel or chrome plated when specified	x	
	Plating is cut through or is not continuous	x	
	Plating is not smooth and fine-grained		x
	Plating is not adherent, e.g., is blistered, flaking or peeling	x	
	Pit, nodule, stain or indication of of burning		x
	Excessive edge build up		x

Source: https://assist.dla.mil -- Downloaded: 20261O-21T19:05Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification: Major	Classification: Minor
	Finish is not as specified, e.g., is not bright, or mirror-like when specified	x	
	Not lacquered, when specified	x	
	Lacquer is not clear and transparent, e.g., is cloudy		x
	Lacquer coating is not smooth and continuous, e.g., has break in film, contains lump, run, drop or sag ...		x
	Lacquer coating is not adherent, e.g., is blistered, peeling or flaking ..		x
	Foreign matter included		x
	Tarnished, stained, spotted or discolored		x
	Gauge, scratch, scuff, machine mark, pit crack, or other impairment seriously affecting appearance and serviceability	x	
	Gauge, scratch, scuff, machine mark, pit crack, or ther impairment affecting appearance or seviceability but not seriously		x

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification: Major	Classification: Minor
Quality of wood...	Not specified species	x	
	Decay or rot	x	
	Fracture, split, break or splinter .	x	
	Shake, pitch pocket, check, torn, raised or loose grain		x
	Loose or unsound knot or hole (except specified hole)	x	
	Tight, sound knot more than 1/2 inch in largest dimension		x
	More than one tight, sound knot, 1/2 inch or less in largest dimension, per flagstaff or section of staff .		x
	Warped more than 1/32 inch per foot of length	x	
	Wane, larvae channel or other imperfection		x
	Any nonpermissible defect filled in with plastic wood or other filler material		x
Quality of metal components	Any characteristic not in accordance with the specified design		x

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification: Major	Classification: Minor
	Eagle if not a close match to the standard or approved sample	x	
	Not fabricated of the specified material	x	
	Any component broken, fractured, cracked or split	x	
	Any component malformed, bent out of shape, miscast or is otherwise impaired, e.g., collar or band is out of round		x
	Hole (except specified hole)	x	
	Tubing (where specified) is crushed or bent out of shape		x
	Burr, sliver, rough edge or sharp edge		x
	Evidence of blowhole, porosity or shrinkage defect in casting	x	
	Edge not square or rounded as required		x
Construction and workmanship	Any operation omitted or not properly		

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:05Z
Check the source to verify that this is the currentversion before use.

Examine	Defect	Classification Major	Minor
	performed		x
	Any component misplaced, loose or not in proper alignment		x
	Staff is not tapered when required, or taper is not as specified		x
	Type X, Size 3 staff not laminated of six equilateral triangular shaped segments	x	
	Glue joint (in laminated staff) open 1/16 inch or more in depth or 3 inches or more in length	x	
	Any segment pieced, i.e., is not full length of flagstaff		x
	Segments of type X, size 3 staff are not in alignment, e.g., edge protrudes		x
	Thread on metal component is stripped or damaged		x
	Components cannot be connected or joined as specified or assembly is difficult		

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:05Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification: Major	Classification: Minor
	to acomplish	x	
	Any component (including rivet, screw, bolt or stud) missing	x	
	Any rivet, screw, bolt, stud or washer is not specified type or size		x
	Rivet not peened, e.g., can be removed by hand	x	
	Rivet is partially peened, e.g., cannot be removed by hand		x
	End of rivet is sharp or ragged		x
	Solder or brazing missing (where required	x	
	Soldered or brazed joint is not continuous, e.g., parts are not completely joined		x
	Metal damaged or deformed in soldering or brazing material		x
	Flux or excess solder not removed ...		x
	Coupling not forced fit to staff	x	
Marking (Type XI, class 2 flagstaff).....	Not marked or marking is illegible, incorrect, not specified type, size, color or is not in specified location		

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

4.3.3.2 Examination of flagstaff or flagstaff components for defects in dimensions.- Any dimension that is not within the specified tolerances shall be classified a defect.

4.3.3.3 Inspection levels and AQL's. The inspection levels and acceptable quality levels (AQL's) expressed in defects per hundred units, shall be as follows:

	Inspection level	AQL Major	AQL Total
For defects applicable to 4.3.3.1			
a) Flagstaff assembled.....	II	2.5	10.0
b) Staffs only (when procured as a separate item).....	II	1.5	6.5
c) Flagstaff heads (when procured as a separate item).....	II	1.5	6.5

For defects applicable to 4.3.3.2 S-3 (one class) 2.5

4.3.3.4 End item testing.- Testing of completely fabricated flagstaff or flagstaff component shall be performed in accordance with Table III for the characteristics shown therein. The sample unit shall be one completely fabricated staff or component as applicable. The inspection level shall be S-1. The acceptable quality level (AQL) shall be 6.5 defects per hundred units. Determinations are applicable to the individual unit.

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:05Z
Check the source to verify that this is the current version before use.

Table III - End item testing

Characteristics	Reqm't Para.	Test Method	# Determinations per Sample Unit	Results reported as
Acid test for Gold plating	3.5.1.1	4.4.3	3	Pass or fail
Test for chrome plating thickness	3.5.1.3	QQ-C-320	2	To nearest 0.00000 1 inch
Adhesion			1	Pass or fail
Test for Cadmium plating:	3.5.1.2	QQ-P-416		
Thickness			2	To nearest 0.00000 1 inch
Adhesion			1	Pass or fail
Test for Lacquering	3.5 and 3.5.2			

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:05Z
Check the source to verify that this is the currentversion before use.

Characteristics	Reqm't Para.	Test Method	# Determinations per Sample Unit	Results reported as
Liver of sulfur		4.4.7.1	1	Pass or fail
Tackiness test		4.4.7.2	1	Pass or fail
Test for Varnishing	3.5.3			
Tackiness test		4.4.4	1	Pass or fail
Coverage test		4.4.5	1	Pass or fail
Breaking load test	3.4.7.2	4.4.6	1	Pass or fail
Magnetic permeability test	3.4.8.2	4.4.8	1	Pass or fail

4.3.4 Examination of preparation for delivery requirements.- An examination shall be made to determine that applicable packaging, packing and marking requirements are complied with. Defects shall be scored in accordance with the lsit below. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. Defects of closure listed below shall be examined on shipping containers fully prepared for

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the acceptables quality level (AQL) shall be 4.0 defects per hundred units.

Examine	Defect
Marking (exterior and interior)	Omitted, incorrect, illegible, of improper size, location, sequence or method of application.
Materials	Any component missing. Any component damaged.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, inadequate stapling.
Weight or content (exterior and interior)	Bulging or distortion of containers. Number of intermediate packages is more or less than required; net weight exceeds requirements.

4.4 Tests.

4.4.1 Moisture content of wood.- Moisture content of wood shall be determined in accordance with MIL-STD-1363.

4.4.2 Slope of wood grain. The slope of wood grain may be determined by combining the grain direction of two adjacent faces of a square or rectangular piece. When one of these faces is straight grained, the true slope of grain is shown on the other face. When there is a slope on both faces, the true or

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

combined slope is greater than the slope on either face. Slope of grain is shown on edge grained faces by the summerwood bands, and on flat grained faces by resin-ducts, by the direction in which a free flowing ink or dye spreads or by the course taken by a narrow strip lifted by a knife point and torn out. Direction of fiber may also be measured by the Teco Slope of Grain Detector supplied by the Timber Engineering Company, Inc., Washington, D.C.

4.4.3 Acid test for gold plating.- The test acid shall be applied as follows: Place a drop of test acid (each drop shall be not less than 1/16 inch in diameter) on three different spots on the gold plated surface allowing the drops to remain for not less than 2 minutes, during which time the surface of the insignia shall be inspected to determine compliance with the requirements specified in 3.5.1.1. The test acid applied at room temperature shall consist of a solution containing 50 percent by volume of CP nitric acid (specific gravity 1.42) and an equal volume of distilled water. If the test insignia has been lacquered, the lacquer must be removed prior to testing.

4.4.4 Test for varnish tackiness.- A piece of tissue paper shall be wrapped around the varnished flagstaff and grasped tightly for 60 seconds. The tissue shall then be removed and the staff examined to determine compliance with 3.5.3.

4.4.5 Test for varnish coverage.- Water soluble writing fluid shall be applied to the varnished piece by pen or other means. After allowing the ink to stand for 3 minutes, the staff shall be wiped with a damp cloth and the staff examined to determine compliance with 3.5.3.

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:05Z
Check the source to verify that this is the current version before use.

4.4.6 Breaking load test.- The staff shall be supported at one end in the fashion of a cantilever beam. A full test load of 40 pounds shall be applied to the staff at the point of support and gradually moved out to a point 106 inches plus or minus 1/4 inches from the forward support point. The staff shall then be examined to determine compliance with 3.4.7.2.

4.4.7 Lacquer tests.-

4.4.7.1 Liver of sulfur test.- Lacquered items shall be immersed in a 2 percent by weight CP liver of sulfur (sulfated potash) water solution, at a temperature of 100 degrees F., plus or minus 10 degrees F., for a period of 3 minutes. The item shall then be removed and rinsed in warm, then cold, then hot water. The item shall be wiped gently with an absorbent cellulose material or whirled to remove residual moisture and shall be air dried at room temperature (60 to 80 degrees F.) for 1 hour. The item shall then be inspected to determine compliance with the requirements specified in 3.5.2.

4.4.7.2 Tackiness test.- At room temperature (60 to 80 degrees F.) press a piece of tissue paper against the lacquered surface for 15 seconds, using any pressure capable of being exerted between thumb and two fingers, after which, the pressure shall be released and the item inspected to determine compliance with the requirements specified in 3.5.2.

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:05Z
Check the source to verify that this is the currentversion before use.

4.4.8 Magnetic permeability test.- Magnetic permeability shall be determined in accordance with MIL-I-17214. The results shall be compared to the requirements of 3.4.8.2.

5. PREPARATION FOR DELIVERY

5.1 Packaging - Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Types I, III, and IV.

5.1.1.1.1 Component A.- All staffs shall be disjointed. Metal parts shall be wrapped with not less than two thicknesses of antitarnish tissue paper and over wrapped with cushioning paperboard conforming to type I, class 1 of PPP-P-291. The paperboard shall be secured with 2 inch minimum width gummed paper tape conforming to type III of PPP-T-45. The staff section shall then be completely enclosed in a sheet of 50-pound minimum basis weight kraft paper conforming to grade B of UU-P-268. The wrap shall be secured with gummed paper tape specified above.

5.1.1.1.2 Component B.- Flagstaff heads shall be wrapped with not less than two sheets of antitarnish tissue paper and over wrapped with cushioning paper conforming to type I, class 1 of PPP-P-291. The paperboard shall be secured with tape specified in 5.1.1.1.1.

5.1.1.2 Type V.- Staff shall be disjointed. Metal parts shall be wrapped with no less than two thickness of antitarnish tissue paper and overwrapped with cushioning paperboard as specified in 5.1.1.1.1.

5.1.1.3 Type VI.

5.1.1.3.1 Component A.- Metal parts and staff shall be packaged as specified in 5.1.1.1.1.

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:05Z
Check the source to verify that this is the current version before use.

5.1.1.3.2 Component B.- Flagstaff heads shall be packaged as specified in 5.1.1.1.2.

5.1.1.4 Type VIII.-

5.1.1.4.1 Component A.- Metal parts and staff shall be packaged as specified in 5.1.1.1.1.

5.1.1.4.2 Component B.- Flagstaff heads shall be packaged as specified in 5.1.1.1.2.

5.1.1.5 Type XI.- Each staff and acorn shall be completely wrapped in not less than two thickness of antitarnish tissue paper and completely enclosed in a sheet of 50 pound minimum basis weight kraft paper conforming to grade B of UU-P-268. The wrap shall be secured with 2 inch minimum width gummed paper tape conforming to type III of PPP-T-45. The bumper clamp assembly, bumper bolt nuts, bumper bolt and lock washers shall be placed together in an end opening drawstring-type bag made from unbleached cotton sheeting cloth.

5.1.1.6 Type X and XI.- Flagstaffs shall be completely enclosed in a sheet of 50 pound minimum basis weight kraft paper conforming to grade B of UU-P-268. The wrap shall be secured with 2 inch minimum width gummed paper tape conforming to type III of PPP-T-45.

5.1.2 Level C.- Flagstaffs with or without flagstaff head or flagstaff heads shall be packaged in accordance with the manufacturer's commercial practice.

5.2 Packing.- Packing shall be level A, B or C as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

5.2.1 Level A.- Flagstaff with flagstaff heads, flagstaff without flagstaff head or flagstaff heads of one type, component, size, style, or class, packaged as specified in 5.1.1, shall be packed in a snug fitting shipping container conforming to class weather resistant, V3c or V3s of PPP-B-636. Closure shall be in accordance with the appendix of the container specification. The weight of contents of each container shall not exceed the size and weight limitation of the container specification.

5.2.2 Level B.- Flagstaff with flagstaff heads, flagstaff without flagstaff head or flagstaff heads of one type, component, size, style or class packaged as specified in 5.1.1 shall be packed in a snug fitting shipping container conforming to class Domestic, Grade 275 of PPP-B-636.

5.2.3 Level C.- Items packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rates for such supplies. Containers shall be in accordance with rules and regulations of carriers applicable to the mode of transportation.

5.3 Marking.- In addition to any special marking required by the contract or order, unit packages, interior packages and shipping containers shall be marked in accordance with MIL-STD-129, except unit package marking may be printed on the reverse of the mounting card provided the printing is continuous and legible through the bag.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

6 NOTES.

6.1 Intended use.- Flagstaff covered by this specification are intended to be used by various offices and units to display, national, organizational, individual or identification flags used within the Department of Defense.

6.2 Ordering Data: Procurement documents should specify the following:

a. Title number and date of this specification.

b. Type, compoent, size, style, and class required (see 1.2, 3.4.5.1 and 3.4.5.2).

c. When a standard sample will not be furnished (see 3.1).

d. When a first article is not required (see 3.2).

e. Type of bottom required for Type VIII flagstaff (see 3.4.5.1).

f. Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.3 Deletion Data.- Type II flagstaff specified in MIL-F-40048A, dated 28 March 1962, has been deleted. Flagstaff bands covered by MIL-F-40048A, dated 28 March 1962, has been deleted from this specification and will be included in MIL-D-3943.

6.4 Type VIII flagstaff heads.-

Style 1- Spread eagle is used by officials whose official salute is 19 or more guns.

Style 2- Halberd is used by flag officer ranks or equal.

Style 3- Ball is used by Naval Captain rank or equal.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

Style 4- Staff is used by commander rank or equal.

Adopter is used for all other grades.

Custodian:

Army - IH

PREPARING ACTIVITY:

The Institute of Heraldry

United States Army

Project No. 8345-A138

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:05Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
THE INSTITUTE OF HERALDRY, US ARMY
CAMERON STATION
ALEXANDRIA, VA 22314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD 314



DIRECTOR
THE INSTITUTE OF HERALDRY, US ARMY
CAMERON STATION
ALEXANDRIA, VA 22314

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:05Z
Check the source to verify that this is the current version before use.