MIL-P-40023D

9 September 1969
SUPERSEDING
MIL-P-40023C
2 March 1967

MILITARY SPECIFICATION

PAPER, TELETYPEWRITER, CONTINUOUS FLATFOLD

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope.- This specification covers continuous flat-folded teletypewriter paper, single and multi-copy.

1.2 Classification.- Teletypewriter paper shall be of the following types, classes, styles, compositions and fastenings, as specified (see 6.2):

Type I - Single copy.

Style A - Perforated horizontally every 11 inches.
Style B - Perforated horizontally every 5-1/2 inches.

Type II - Multi-copy.

Class 1 - White.
Class 2 - Strip color coded sequence.
Class 3 - Solid color sequence.

Style A - Perforated horizontally every 11 inches.
Style B - Perforated horizontally every 5-1/2 inches.

Composition 1 - Auto-copy (carbonless).
Composition 2 - Carbon-interleaved.

Fastening 1 - Glued.
Fastening 2 - Crimped.
Fastening 3 - Sewed.
Fastening 4 - Locked.
Fastening 5 - Stapled.

FSC 7530

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-B-636 - Box, Fiberboard.
PPP-F-320 - Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-147 - Palletized and Containerized Unit Load 40" x 48" Pallet Skids, Runners, or Pallet-Type Base.

(Copies of specifications, standards and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.- The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC.

National Motor Freight Classification

(Application for copies should be addressed to American Trucking Associations, ATTN: Tariff Order Section, 1616 P Street, N.W., Washington, D.C. 20036).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 202, Union Station, 516 W. Jackson Blvd., Chicago, Illinois 60606.)

TECHNICAL ASSOCIATION OF THE PULP AND PAPER INDUSTRY (TAPPI)

PUBLICATIONS

T 401 m-60 - Fiber Analysis of Paper and Paperboard.
T 402 m-49 - Conditioning Paper and Paperboard for Testing.
T 410 os-68 - Weight per Unit Area (Basis Weight or Substance) of Paper and Paperboard.
T 411 os-68 - Thickness (Caliper) of Paper and Paperboard.
T 414 ts-65 - Internal Tearing Resistance of Paper.

(Application for copies should be addressed to the Technical Association of the Pulp and Paper Industry, 360 Lexington Avenue, New York 10017.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Materials.-

3.1.1 Composition 1 (auto-copy).- The auto-copy paper shall be made from 100 percent bleached chemical wood pulp, with the exception that "trace" amounts of other fibers shall be allowed.

3.1.1.1 Treatment.- The auto-copy paper shall be coated or treated in such a manner that when characters are typed or written on the first sheet of a collated set of teletypewriter forms, the characters shall be legibly reproduced on each underlying sheet in the set without the use of interleaved carbon paper. The first sheet of each set shall accept the ink from the teletypewriter ribbon quickly without smearing or blurring of the printed characters. When specified (see 6.2), the top sheet of a form set shall be treated in such a manner that the image of the characters typed using a ribbonless teletypewriter are reproduced on the first as well as all subsequent sheets in a form set.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.

3.1.1.2 Color of image.- The color of the image made by auto-copy paper shall be blue or black at the suppliers option, unless otherwise specified in the contract or purchase order.

3.1.1.3 Physical properties.- The auto-copy paper shall conform to the physical characteristics specified in table I when tested as specified in 4.2.3.

TABLE I.- Physical properties of auto-copy paper

	Minimum	Maximum
Basis weight, pounds (17 x 22 - 500)	9.5	18.0
Thickness, inch	0.0019	0.0042
Tearing resistance, grams, each direction	13	---

3.1.2 Composition 2 (carbon-interleaved).- Teletypewriter paper for carbon interleaved forms shall be made from bleached chemical wood fibers and additives necessary to meet the requirements of this specification. The paper shall be free from groundwood pulp, except for trace amounts.

3.1.2.1 Physical properties.- The paper for carbon interleaved forms shall conform to the physical characteristics in table II when tested as specified in 4.2.3.

TABLE II.- Physical characteristics of carbon interleaved paper

Basis weight (17 x 22 - 500)		Thickness		Tearing resistance	
Minimum Pounds	Maximum Pounds	Minimum Inch	Maximum Inch	Machine Direction, grams	Cross Direction, grams
9.5	10.5	0.0017	0.0024	16	18
10.5	12.5	0.0019	0.0028	20	24
14.3	20	0.0026	0.0031	26	31

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.

3.1.3 Carbon paper.- The carbon paper used in the carbon interleaved forms shall be black and of a quality suitable for one time use. Carbon paper shall consist of tissue paper coated on one side with a suitable form of carbon and other materials necessary to give clear, legible copies on all under sheets of the teletypewriter paper. The carbon paper shall be continuous and shall cover at least the entire writing area and shall extend into the margin enough to allow a glue line, when required.

3.1.4 Color and cleanliness.- The color and cleanliness of the paper shall conform to the standard comparison sample furnished with the contract or order (see 6.3). The paper furnished by the supplier shall also conform to the requirement of this specification in all other respects.

3.1.5 Writing quality.- Paper shall permit the writing of clear cut characters with no tendency to feather or spread when tested as specified in 4.2.3.

3.2 Construction.-

3.2.1 Type I.- Type I forms (single) shall consist of one part. The forms shall be furnished in the strip lengths and sizes specified in 3.2.2.1 for type II forms and shall have marginal punching and perforations and horizontal and vertical tearlines as specified in 3.2.2.3, 3.2.2.4, 3.2.2.4.1, and 3.2.2.4.2.

3.2.1.1 Composition.- Type I forms shall be composed of 14.3 to 20 pound basis weight paper conforming to 3.1.2.1 or when specified (see 6.2) auto-copy paper conforming to 3.1.1.3 capable of being printed by a ribbonless teletypewriter.

3.2.2 Type II.- Type II forms (multi-copy) shall consist of two or more parts, as specified (see 6.2), fastened in the left margin by the methods specified in 3.2.2.5, assembled in a continuous strip and flat folded at the tearline. The paper used in type II forms shall be auto-copy paper (composition 1) conforming to 3.1.1.3 or carbon interleaved paper (composition 2) conforming to 3.1.2.1, as specified. For carbon interleaved forms, the teletypewriter paper shall be 9.5 to 10.5 pound basis weight paper for all parts except at the option of the supplier, 10.5 to 12.5 pound basis weight paper may be used for the first and/or last sheet. The carbon interleaved forms shall be interleaved with continuous carbon paper conforming to 3.1.3. Carbons for each set, as applicable, when specified (see 6.2), shall be provided with a tongue cut or other suitable extraction feature.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.

3.2.2.1 Strip length and size.- Style A forms shall be furnished as one continuous strip to produce 500 forms, 8-1/2 ± 1/16 inches in width and 11 ± 1/32 inches in length, folded one form set per fold. Style B forms shall be furnished as one continuous strip to produce 1,000 forms, 8-1/2 ± 1/16 inches in width and 5-1/2 ± 1/32 inches in length, folded two form sets per fold. The length of the forms shall be measured between two horizontal perforations, and the width shall be measured across the entire form, printing area plus margins. Glue fastened forms, when specified, may be furnished with the first and last forms 8-1/2 ± 1/16 inches in width and the inner parts not less than 3/16 inch in width less than the first and last parts.

3.2.2.2 Classes.- Type II forms shall be furnished in the following classes, as specified (see 6.2): Class 1 forms shall be all white, class 2 forms shall be strip color coded sequence and class 3 forms shall be solid color coded sequence. Class 2 strip color coded sequence shall consist of white parts printed with a solid color strip, approximately 1/2 inch wide in the left and right hand margins and running up to 1/2 inch from top and bottom or full length of each part, the color sequence shall be the same as for class 3. Class 3 shall consist of solid color forms in the following color sequence from the top: blue, green, yellow, pink, goldenrod, white, or as specified (see 6.2).

3.2.2.3 Marginal punching.- The forms teletypewriter paper shall be punched in the left and right margins with holes 5/32 ± 1/64 inch in diameter, spaced 1/2 ± 1/64 inch center to center and positioned with the left marginal holes parallel to and spaced 1/4 ± 1/32 inch from the left edge of the form to the center of the hole. The corresponding right marginal holes shall be 8 ± 1/64 inches, center to center, from the left marginal holes and parallel thereto. Carbons, when required, shall be punched in the left margin, or left and right margins, with holes 5/32 to 7/32 inch in diameter, positioned as specified for the form and holes centered with the corresponding holes in the form. Alternatively, punching of carbon paper may be omitted when carbon paper does not extend to the left edge or left and right edges of the forms. When this construction is used, the carbon paper shall be affixed to the preceding sheet by a narrow glue strip or glue spot within the margin. All holes shall be punched clean so that no discs remain in either the carbon or form sheets, except when sheets are fastened by an interlocking device caused by incompletely punched holes.

3.2.2.4 Tearline perforations.- Cut and uncut portions of tearline perforations shall be uniformly accurate in length and spacing to insure proper and efficient tearing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.

3.2.2.4.1 Horizontal tearline.- All forms (teletypewriter paper) and carbons, when specified, shall be perforated every 11 or 5-1/2 inches as specified (see 6.2), across the width. Perforations shall be positioned 1/4 ± 1/32 inch above the center of the top marginal aligning holes within the form. Perforations shall be accurately and consecutively positioned perpendicular to a straight line projected through the centers of the left aligning holes and across the width of the form. Carbon paper may be perforated independently of the forms provided that these perforations coincide with those in the forms.

3.2.2.4.2 Vertical tearline.- When specified (see 6.2), all forms (teletypewriter paper) and carbons shall have vertical perforations located 1/2 ± 1/32 inch from and parallel to the left edge, except that when specified (see 6.2) the tearline shall be located 5/8 ± 1/32 inch from the left edge.

3.2.2.5 Fastening.- The method of joining, such as stapling, sewing, gluing, crimping, locking or bump fastening shall be as specified in the contract or order and shall conform to the requirements in the appropriate subparagraph (see 6.2).

3.2.2.5.1 Stapling.- When forms are stapled, wire staples shall be clinched in the left margin of the forms, centered between margin aligning holes and parallel to the horizontal perforations. Clinched staples shall be not less than 1/4 inch nor more than 7/16 inch in length. Staples shall be crimped in such a manner that they do not catch on succeeding forms or staples or cause bulges. Crimped prongs shall be flat against the paper. There shall be at least two staples in each style A form and at least one staple in each style B form.

3.2.2.5.2 Sewing.- When sewed, the stitches shall be continuous for the full form length and shall be centered between the aligning holes and the vertical perforations. Locked stitches shall be used to preclude raveling and the thread shall be cut at the perforation between sets.

3.2.2.5.3 Gluing.- When glue is used, it shall not extend beyond the vertical perforations into the message space. Glue application may be as a continuous line or spots of adhesive applied not more than 5 inches apart. Glue lines or spots shall show fiber separation when tested as specified in 4.2.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.

3.2.2.5.4 Crimping.- Crimping shall be positioned between aligning holes and shall not fall on the horizontal tearline nor extend beyond the vertical perforations into the message space. Crimping shall not fail when tested as specified in 4.2.3. The carbon paper shall extend a minimum of 1/8 inch beyond the typing area.

3.2.2.5.5 Locking.- When fastening is accomplished by incomplete punching of marginal holes, the location and frequency of such punching shall not interfere with proper operation as specified in 4.2.3. The incompletely punched holes shall be hinged at the top.

3.2.2.5.6 Bump fastening.- When bump fastening is used there shall be at least two bump fasteners in style A forms and one bump fastener in style B forms. The bump fasteners shall be in the left aligning margin.

3.2.2.6 Form markings.-

3.2.2.6.1 Corner lines (first part, style A only).- Unless otherwise specified, a line 1/2 + 1/8, - 1/16 inch long shall be printed or perforated horizontally, beginning 1 ± 1/8 inch from the left edge of the form and 1 ± 1/8 inch from the top of the form. A vertical line 1/2 ± 1/8, - 1/16 inch long perpendicular to the horizontal line shall be perforated or printed 1 ± 1/8 inch from the top of the form and 1 ± 1/8 inch from the left side of the form. These lines shall make a "corner" which shall appear in the upper lefthand corner of the first part of style A form.

3.2.2.6.2 Warning signal.- When specified (see 6.2), a red warning signal, in the form of a printed line, not less than 1/4 inch wide shall be applied to the left edge of the form in the machine direction for a distance of 25 ± 1 feet from the end of each continuous strip of forms to warn the operator of approaching end of the set. The red signal shall be placed on the outer sheet only.

3.3 Performance.- Teletypewriter forms shall produce clear, legible copies on all parts when tested as specified in 4.2.3, and shall feed through the teletypewriter machine without jamming or interrupting operation due to assembly or construction of the forms.

3.4 Workmanship.- The teletypewriter forms shall be free from tears, cuts or punctures (except as specified). Forms shall not contain any sharp folds (except as specified), crimped corners, waves or wrinkles. Edges shall be clean cut.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Inspection.- Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.2.1 Inspection of materials and components.- In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended or qualified in this specification or applicable purchase documents.

4.2.2 Inspection of the end item.-

4.2.2.1 Examination of the end item.- The end item shall be examined for the defects set forth in the applicable subparagraphs at the inspection levels and acceptable quality levels (AQL's) set forth in 4.2.2.1.6. Random samples shall be drawn from each lot of the teletypewriter forms for examination of visual, construction, workmanship, dimensional, count, preparation for delivery and palletization defects. The lot size for purposes of determining the sample size in accordance with MIL-STD-105 shall be expressed in units of shipping containers of one type, class, style, composition and fastening for examination in 4.2.2.1.1 through 4.2.2.1.4 inclusive, and in units of palletized unit loads for examination in 4.2.2.1.5.

4.2.2.1.1 Examination of the end item for visual defects.- The sample unit for this examination shall be three continuous sets of forms and no more than one sample unit shall be examined from a shipping container. Both sides of all sheets and carbons shall be examined. The same defect shall be scored only once per sample unit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.

Examine	Defect
Appearance	
Paper	Color and cleanliness does not compare favorably with the comparison sample.
Carbon paper, when applicable	Not tissue paper. Not black. Not coated on one side only. Coating not uniform. Any coating material on back of the sheet or sheets. Not continuous; does not cover the entire writing area and extend into the margin as required.
Color of image (auto-copy only)	Not blue or black, as required.
Construction	
Assembly of forms	Not type, class, style or composition specified. Color sequence of forms not as required or specified, or not all white. Carbons not properly interleaved, when specified. Carbons not punched or glued, as applicable. Carbons not provided with an extraction feature when specified.
Punched holes in right and left aligning margins (forms and when applicable, carbons)	Any hole missing. Left side holes not within alignment tolerances with right side holes. Not punched cleanly, any disc in hole, except when used as a locking device. Holes not round. Holes in paper and carbon do not align (when applicable). Tear between edge of sheet and hole. Tear between holes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.

Examine	Defect
Perforations	
Horizontal	Missing or not perforated entire width of sheets and carbons. Not perpendicular to center line of left margin aligning holes. Do not allow easy separation of forms. Sheets or carbons separated at perforations. Wavy. Not uniform; not aligned through set.
Vertical	Missing or not perforated along entire length of sheets and carbons. Not parallel to center line of left margin aligning holes. Do not allow easy separation of margins from form. Not on left side only. Sheets or carbons separated at perforations. Wavy. Not uniform; not aligned through set.
Fastening	
Stapling (when applicable)	Not method specified. Missing. Not between aligning holes. Not one or two staples per set, as applicable. Prongs not clinched flat along the paper; rounded; staples catch on the forms or other staples on succeeding form sets. Not parallel to horizontal perforations. Causes bulges in forms.
Sewing (when applicable)	Missing; not continuously sewn full length of form. Not stitched through all parts. Not lock-type stitch. Thread not cut at the perforations between sets. Not centered between marginal holes and vertical perforation. Runs into marginal holes or vertical perforations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.

Examine	Defect
Fastening (cont'd)	
Gluing (when applicable)	Glued areas missing, separate easily with no fiber separation. Glue spots, if used, more than five inches apart. Extends beyond vertical perforations. Runs into marginal holes. Not on left side only.
Crimping (when applicable)	Missing. Not between aligning holes. Causes bulges in forms. Extends into writing area.
Bump fastening (when applicable)	Less than two bump fasteners in style A forms or one bump fastener in style B forms. Not in left aligning margin.
Corner lines (when specified)	Missing from first part. Does not consist of a vertical and horizontal line meeting to produce a "corner". Not in upper left side of form. Lines not parallel or perpendicular, as applicable, to form edges. Included on carbons or any part other than first part.
Warning signal (when applicable)	Missing. Not on outer sheet.
Workmanship	Any tear, cut or puncture. Ragged, uneven or crushed edge. Any sharp fold not at a horizontal perforation. Any crimped corner or side. Any wrinkle or wave.

4.2.2.1.2 Examination of the end item for dimensional defects.- The sample unit for this examination shall be one set of forms. Not more than one sample unit shall be taken from a shipping container and each part of the set shall be examined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.

Examine	Defect
Width of form, except glued forms (including alignment strips on both sides)	Varies from specified size by more than ± 1/16 inch.
Glued forms	
Width of first and last forms (including alignment strips on both sides)	Varies from specified size by more than ± 1/16 inch.
Width of any inner parts	Less than 3/16 inch in from edge of first or last part.
Distance between horizontal perforations	Varies by more than ± 1/32 inch from specified length.
Width of carbon paper (when applicable)	Does not cover entire printing area.
Vertical perforation from left trimmed edge of form	More than 17/32 inch. Less than 15/32 inch.
Diameter of holes in paper sheets	More than 11/64 inch. Less than 9/64 inch.
Diameter of holes in carbons (when applicable)	More than 7/32 inch. Less than 5/32 inch.
Distance, center to center of holes in paper and carbon (when applicable)	More than 33/64 inch. Less than 31/64.
Position of holes	
From edge of sheet to center of holes, both sides	More than 9/32 inch. Less than 7/32 inch.
Top holes, from horizontal perforations, both sides	More than 17/32 inch below horizontal perforation. Less than 15/32 inch below horizontal perforation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.

Examine	Defect
Position of holes (cont'd)	
Bottom holes, from horizontal perforations, both sides	More than 17/32 inch above horizontal perforation. Less than 15/32 inch above horizontal perforation.
Lateral distance between holes	More than 8-1/64 inches. Less than 7-63/64 inches.
Joining	
Staples	
Length of clinched staple	More than 7/16 inch. Less than 1/4 inch.
Corner marking lines (when applicable, see 3.2.2.6.1)	
Length of horizontal and vertical lines	More than 5/8 inch. Less than 7/16 inch.
Distance from horizontal tear-line to horizontal line and top of vertical line	More than 1-1/8 inches. Less than 7/8 inch.
Distance from left edge of form to vertical line and left end of horizontal line	More than 1-1/8 inches. Less than 7/8 inch.
Warning signal (when specified)	
Length	More than 26 feet. Less than 24 feet.
Width	Less than 1/4 inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.

4.2.2.1.3 Examination for average count.- The sample unit for this examination shall be the contents of one shipping container. The average number of sets per container, of all containers examined, shall be not less than specified or indicated, and the average number of forms in a continuous strip shall be not less than specified when one strip is counted from each container examined.

4.2.2.1.4 Examination of preparation for delivery.- An examination shall be made to determine that packing and marking requirements comply with the requirements of Section 5 of this specification. The sample unit shall be one shipping container, fully prepared for delivery except that it shall not be palletized or sealed. Shipping containers fully prepared for delivery that have not been palletized shall be examined for closure defects.

Examine	Defects
Markings (exterior and interior)	Incorrect; incomplete; illegible; omitted; of improper size, location, sequence or method of application (see 5.2).
Materials	Any nonconforming component; component missing, damaged or otherwise defective.
Workmanship	Inadequate application of components, such as: incomplete closure, container flaps, loose or inadequate sealing, strapping or stapling. Bulged or distorted container. Not packing level specified.

4.2.2.1.5 Examination for palletization.- An examination shall be made to determine that palletization complies with the requirements of Section 5 of this specification. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully prepared for delivery.

Examine	Defects
Finished dimension	Length, width, or height exceeds specified maximum requirement.
Palletization	Not as specified. Container pattern not as specified. Load not bonded with required straps as specified. Exceeds maximum load limits.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.

4.2.2.1.6 Inspection levels and acceptable quality levels (AQL's) for examination.- The inspection levels, for determining the sample size and the acceptable quality levels (AQL's) expressed as defects per 100 units shall be as follows:

Examination paragraph	Inspection level	AQL
4.2.2.1.1	III	1.5
4.2.2.1.2	S-3	2.5
4.2.2.1.3	S-2	N.A.
4.2.2.1.4	S-1	2.5
4.2.2.1.5	S-1	6.5

4.2.3 Testing of the end item.- The end item shall be tested for the applicable characteristics in Table III. The lot size, for purposes of determining the sample size, shall be expressed in units of shipping containers of teletypewriter paper of one type, class, style, composition and fastening. The sample unit shall be five complete sets of forms in one continuous strip for style A and ten complete sets of forms in one continuous strip for style B, as applicable, for all tests except performance. The sample unit for the performance tests shall be 500 complete sets of style A or B, as applicable. The sample size shall be drawn at inspection level S-1 of MIL-STD-105. All specimens shall be conditioned in accordance with TAPPI method T 402 m-49 prior to testing. Test reports shall include all values upon which results are based. There shall be no failure to meet the composite, sample unit or lot average requirements. A composite shall consist of equal portions taken from all sample units and combined in a single sample. The marginal aligning strips shall be removed for all tests except the performance and glue tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS FOR TESTING OF THE END ITEM

TABLE III

CHARACTERISTIC	Specification Reference		Requirements Applicable To		Number Determinations Per Sample / Per Unit	Results Reported As		Inspect Level	AQL
	Requirement	Test Method	Individ Unit	Lot Aver		Pass or Fail 1/	Numerically to Nearest		
Paper									
Stock									
Auto-copy	3.1.1	T401m-60*			Average of 2 on composite		5 percent		
Carbon interleaved	3.1.2	T401m-60*			Average of 2 on composite		5 percent		
Basis weight									
Auto-copy	Table I	T410os-68*		X	1		0.1 pound		
Carbon interleaved	Table II	T410os-68*		X	1		0.1 pound		
Thickness									
Auto-copy	Table I	T411os-68*		X	20 (4 per sheet)		0.0001 inch		
Carbon interleaved	Table II	T411os-68*		X	20 (4 per sheet)		0.0001 inch		
Tearing resistance									
Auto-copy (each direction)	Table I	T414ts-65*		X	10 (5 in each direction)		gram		
Carbon interleaved									
Machine direction	Table II	T414ts-65*		X	5		gram		
Cross direction	Table II	T414ts-65*		X	5		gram		
Writing quality	3.1.5	4.3.1	X		1	X			
Performance test									
Machine feed	3.4	4.3.2	X		1	X			
Registration	3.4	4.3.2	X		1	X			
Glue	3.2.2.5.3	4.3.3	X		1	X			

1/ If failure is indicated report description of failure.

AMXRE Form 598
8 February 1965

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.

4.3 Test procedures.-

4.3.1 Writing quality.- Characters shall be written on each part of a set with a 1 percent aqueous solution of Acid Red 1, Color Index Number 18050 or Acid Green 3, Color Index Number 42085 (see 6.4).

4.3.2 Performance.-

4.3.2.1 Apparatus.- Teletypewriter forms shall be tested for satisfactory operation and accuracy of registration using a teletypewriter set AN/FGC No. 20, 21 or 21X equipped with sprocket feed capable of accepting flatfold type of paper.

4.3.2.2 Procedure.- Run 500 sets of forms through the teletypewriter specified in 4.3.2.1 at normal operating speed and print five lines of characters or symbols on the first and last set of forms.

4.3.2.3 Machine feed.- Report as a failure any jamming or interruption of operation caused by poor assembly or construction of the forms.

4.3.2.4 Registration and legibility.- Examine all parts in the first and last sets for accuracy of registration. The sample unit shall be considered to have failed if any part of either set shows incomplete or illegible registration of the characters or symbols printed as specified in 4.3.2.2.

4.3.3 Gluing.- The glued areas shall show fiber separation when slowly separated by hand.

5. PREPARATION FOR DELIVERY

5.1 Packing.- Packing shall be level A, B or C as specified (see 6.2).

5.1.1 Level A.- Teletypewriter paper of one type, class, style, composition, and fastening only, as specified in 3.2.1 and 3.2.2, with one form set per fold for style A and two form sets per fold for style B, shall be packed in the quantities as specified in table IV in a snug-fitting fiberboard shipping container conforming to grade V2s, style RSC of PPP-B-636. Each shipping container shall be provided with a full length and width fiberboard top and bottom pad. Each shipping container shall be closed, waterproofed with tape and reinforced in accordance with the appendix of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.

TABLE IV.- Packing

	Quantity of form sets per shipping container
Type I	
Style A	4000
Style B	8000
Type II	
Style A	500
Style B	1000

5.1.2 Level B.- Teletypewriter paper of one type, class, style, composition and fastening only, as specified in 3.2.1 and 3.2.2, with one form set per fold for style A and two form sets per fold for style B, shall be packed in the quantities as specified in table IV in a snug-fitting fiberboard shipping container conforming to type CF, (variety SW) or type SF, class domestic, grade 200, style RSC of PPP-B-636. Each shipping container shall be provided with a full length and width fiberboard top and bottom pad. Each shipping container shall be closed in accordance with method II of the appendix of PPP-B-636.

5.1.2.1 When specified (see 6.2), the shipping container shall be a grade V3c or V3s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix thereto. The shipping container material may also be grade V4s of PPP-F-320.

5.1.3 Level C.- Teletypewriter paper of one type, class, style, composition and fastening only, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Rules, as applicable.

5.2 Palletization.- Unless otherwise specified (see 6.2), teletypewriter paper packed as specified shall be palletized in accordance with Load Type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall be approved by the contracting officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.

5.3 Marking.- In addition to any special marking required by the contract or order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.- Teletypewriter paper covered by this specification is intended for use in teletypewriter machines equipped with a sprocket feed mechanism. It is not intended for use in machines of the friction feed type.

6.2 Ordering data.- Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number and date of this specification.
(b) Type, class, style, composition and number of parts required (see 1.2 and 3.2.2).
(c) When paper for ribbonless teletypewriter is required (see 3.1.1.1).
(d) Color combination required, all white, strip color or solid color sequenced (see 3.2.2.2).
(e) When extraction feature is required (see 3.2.2).
(f) Method of fastening (see 3.2.2.5).
(g) Corner lines if desired (see 3.2.2.6.2).
(h) Warning signal if desired (see 3.2.2.6.2).
(i) Selection of applicable level of packing (see 5.1).
(j) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.1.2.1).
(k) When palletization is not required (see 5.2).

6.3 Comparison sample.- For comparison sample, address inquiry to the procuring agency issuing the invitation for bid.

6.4 Acid Red 1, Color Index Number 18050 may be obtained from Textile Aniline and Chemical Company. Acid Green 3, Color Index Number 42085 may be obtained from the following: Sandoz, Incorporated; National Aniline Division of Allied Chemical Corporation; Geigy Chemical Corporation; or American Cyanamid Company (see 4.3.1).

6.5 All types of auto-copy paper are covered by this specification including pigment transfer, chemical transfer or self-contained chemical, which may be used with ribbonless teletypewriter.

6.6 Carbon interleaved forms should not be procured in quantities larger than will be used in one year since prolonged storage may have a detrimental effect on the carbon.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL

Air Force - 84

Review activities:

Army - GL

Air Force - 84

User activities:

Navy - MC, SA

Preparing activity:

Army - GL

Project No. 7530-0119

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. Army Natick Laboratories
Natick, Massachusetts 01760

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding General
U. S. Army Natick Laboratories
ATTN: AMXRES-EQS
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

Paper, Teletypewriter, Continuous Flatfold MIL-P-40023D

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:01Z
Check the source to verify that this is the current version before use.