This document has been approved for public release and sale; its distribution is unlimited.

MIL-D-16191F(NAVY)
3 August 1970
SUPERSEDING
MIL-D-16191E
15 March 1962
(See 6.3)

MILITARY SPECIFICATION

DETECTORS, EXPOLOSIVE VAPOR

All interested Commands of the Department of the Navy concurred in the use of this specification.

1. SCOPE

1.1 Scope. This specification covers equipment for detecting explosive vapors or gases associated with fuel oils and gasoline, and operating an alarm when the concentration exceeds a predetermined value.

1.2 Classification. The detectors shall be designated in the following form as specified (see 6.1):

IC/	U	3	N	6	A1
Basic indicator (see 1.2.1)	Type of supervision (see 1.2.2)	Number of sampling points supervised (see 1.2.3)	Atmosphere to be analyzed (see 1.2.4)	Frequency of power supply (see 1.2.5)	Manufacturer, modification, and similar data (see 1.2.6)

1.2.1 Basic indicator. The basic indicator for Naval Interior Communication equipment is IC/.

1.2.2 Type of supervision. The type of supervision is indicated as follows:

S - Scanning type (see 3.3.8.1).
U - Unit type (see 3.3.8.2).
M - Manual type (see 3.3.8.3).

1.2.3 Number of sampling points supervised. The number of sampling points supervised is indicated by a number.

1.2.4 Atmosphere to be analyzed. Whether the equipment is to operate in an atmosphere composed largely of nitrogen or of nitrogen and carbon dioxide is indicated by a letter as follows:

N - Nitrogen (see 3.2.2(a)).
C - Carbon dioxide (CO_2) and nitrogen (see 3.2.2(b)).

1.2.5 Frequency of power supply. The frequency of the power supply (see 3.2.1) is indicated as follows:

4 - 400 cycles, alternating current (a.c.).
6 - 60 cycles, a.c.

1.2.6 Manufacturer, modification, and similar data. The name of the manufacturer, modifications of original design, and similar data are denoted by a dash and a letter or a letter and a number to be assigned by the procuring activity when drawings are approved.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:22Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of the specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods of.
MIL-S-901 - Shock Tests, H.I.(High Impact); Shipboard Machinery, Equipment and Systems, Requirements for.
MIL-I-983 - Interior Communication Equipment, Naval Shipboard; Basic Design Requirements For.
MIL-M-15071 - Manuals, Technical: Equipments and Systems - Content Requirements For.
MIL-A-15303 - Audible Signals: Alarms, Bells, Buzzers, Horns and Sirens - Shipboard.
MIL-M-17059 - Motors, Alternating-Current, Fractional HP (Shipboard Use).
MIL-M-17060 - Motors, 60 cycle Alternating-Current, Integral HP (Shipboard Use).

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE
Uniform Freight Classification Rules.

(Application for copies should be addressed to Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

3. REQUIREMENTS

3.1 Sample for first article inspection. A sample explosive vapor detector shall be provided for performance of the inspection specified in 4.3 (see 6.4).

3.2 General features.

3.2.1 The explosive vapor detectors shall be in accordance with the following paragraphs of MIL-I-983 in addition to the requirements specified hereinafter. When a requirement of MIL-I-983 conflicts with a requirement of this specification, the requirement of this specification shall govern.

General requirements
Materials, general
Fungus-inert materials
Flammable materials
Toxic materials
Wood
Aluminum
Magnesium
Ferrous alloys
Plastics
Lubricants and lubrication
Painting
Protection against corrosion (salt spray test required)
Bolts, machine screws, studs and nuts
Gaskets
Dials and pointers
Dial sizes
Locking devices
Washers
Ball bearings
Parts - electrical - general
Electron tubes
Electron tube or capacitor sockets

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:22Z
Check the source to verify that this is the current version before use.

Capacitors
Variable resistors
Transformers and Inductors
Relays
Electrical tapes
Batteries
Dial illumination lamps
Switches
Enclosures - general
Enclosure - accessibility
Enclosure - degree of (dripproof) (see 3.3.1)
Enclosure - mounting (bulkhead) (see 3.3.1)
Stiffening grooves
Through bolting
Ventilation
Size (for surface ships)
Threaded devices
Rounded corners and edges
Internal subassembly protection
Drilled and tapped holes
Structural welding
Temperature and humidity (extreme temperature for exposed location)
Shock, vibration and inclination (vital vibration test required) (see 3.2.5 and 3.5)
Primary power supply circuits
Power supply tolerances (normal power supply 115 volts, 60 or 400 cycles as specified) (see 1.2.5)
Safety (personnel hazard)
Ground potential and grounding
Soldering
Electrical parts mounting
Internal subassembly connection (test cable required)
Electrical connectors
Terminal boards and terminals
Wiring
Dielectric strength and insulation resistance clearances
Airborne noise
Drawings - general
Drawings - preliminary
Drawings - working
Schematic diagrams
Wiring diagram
Assembly drawings
Drawings - manufacturing
Interchangeability and standardization
Manuals (see 3.6)
Repair parts (see 3.7 and 6.1)
Designation and marking
Workmanship and general examination

3.2.2 Operation. The detector shall be capable of safely, quickly, and accurately detecting explosive gases or vapors associated with fuel oils and gasoline, and operating an alarm when the concentration exceeds a predetermined value. The detector shall be sensitive in detecting small quantities of pentane and similar hydrocarbon vapors, and shall give a reliable indication of the concentration, in percent, of the lower explosive limit (on a scale graduated from 0 to 50) of pentane or similar hydrocarbon vapors based on use in an inert gas atmosphere made up of one of the following compositions as specified (see 1.2.4 and 6.1):

(a) Ninety-seven percent inert gas (96 percent nitrogen and 1 percent argon and 3 percent oxygen) (maximum) with the possibility that the oxygen content may be reduced to a minimum of 1/2 percent, all mixed with air to a 43-percent inertness (approximately 9 percent oxygen) at slightly higher than atmospheric pressure.
(b) Eighty-six percent nitrogen, 2 to 3 percent oxygen, remainder CO_2 all mixed with air to a 43-percent inertness (approximately 9 percent oxygen) at slightly higher than atmospheric pressure.

The detector shall operate an alarm when the explosive vapor concentration reaches 20 percent of the lower explosive limit within an accuracy of plus or minus 10 percent (that is, plus or minus two percentage points). Where explosive vapor detectors employ the use of a

Source: https://assist.dla.mil -- Downloaded: 202640-18T08:22Z
Check the source to verify that this is the current version before use.

platinum filament as a catalytic reagent, a surplus of oxygen shall be added in the sample atmosphere to maintain the optimum catalytic activity of the platinum filament. The gas sample shall be diluted with air in some chosen fixed ratio to assure an adequate supply of oxygen in the filament chamber for burning all combustibles that might be present in the gas sample. This shall be accomplished by withdrawing the gas sample to be analyzed from the cofferdam space or other enclosure under test, through the dilution mechanism, where it is diluted with air at the chosen fixed ratio, through the filament chamber, where it is analyzed, and finally through some adequate exhaust system.

3.2.3 Tetraethyl lead. The accuracy of the detector shall not be impaired by burning the filament for a period of 15 minutes while sampling an atmosphere representing less than half scale of combustible gases or vapors containing tetraethyl lead.

3.2.4 Endurance. The detector shall be capable of continuous operation for not less than 10,000 hours without change in accuracy, drift, and zero adjustment. The detector shall conform to the initial accuracy, drift and zero adjustment requirements of 3.3.6 following the endurance test of 4.6.2.

3.2.5 Units. The detector shall consist of an indicator and sampling lines as specified (see 6.1). It shall be so designed that the accuracy of the indications will not be affected by inclinations or by operation in any ambient temperature specified (see 3.2.1).

3.3 Indicator.

3.3.1 Enclosure. The indicator enclosure shall be of dripproof construction designed for bulkhead mounting. Dimensions shall not exceed 24 inches high by 12 inches wide by 12 inches deep, and weight shall not exceed 200 pounds for an indicator supervising a single sampling point.

3.3.2 Indicating instruments and controls. The necessary indicating instruments and controls shall be conveniently arranged on the front of the enclosure. The arrangement of the controls shall be such that all normal operating adjustments may be made without opening the enclosing case.

3.3.3 Units of each circuit shall be grouped and identified as to location of the associated sampling line.

3.3.4 Conveniently accessible terminals shall be provided for connection of the power supply, sampling lines, and audible signal.

3.3.5 An "On-Off" power supply switch of ample capacity shall be provided, together with a white "power-on" indicator light.

3.3.6 The initial accuracy of the indicator at 25°C. shall be such that the actual percentage of pentane, by volume, present in less-than-explosive mixtures will be correctly indicated by the instruments within the limits of plus or minus 0.25 percent. After 150 hours of service from a single set of sampling lines, the indicator shall show no drift greater than the scale equivalent of 0.25 percent pentane, after proper zero adjustment, from the initial calibration of the instrument. It shall not be necessary to adjust the indicator to zero oftener than once during a 10-day period in order to maintain the accuracy requirements.

3.3.7 Alarm unit. The alarm unit shall indicate when the concentration of explosive vapor has reached or exceeded 20 percent of the lower explosive limit. The alarm unit shall consist of an audible signal and a visual signal.

3.3.7.1 Audible signal. The audible signal shall be a type IC/B1S4, 60-cycle, or type IC/B1F4, 400-cycle bell conforming to MIL-A-15303 (not supplied by the contractor). Provisions shall be made for connection to the bell. Means shall be provided to silence the bell manually even when the concentration of explosive vapor is above the alarm point setting.

3.3.7.2 Visual signal. The visual signal shall consist of a lamp type indicator with a red lens located on the indicator. This light shall remain energized as long as an excessive concentration of explosive vapor exists at any positive element.

Source: https://assist.dla.mil -- Downloaded: 20261O-18T08:22Z
Check the source to verify that this is the current version before use.

3.3.8 Supervision. The sampling points associated with an indicator shall be supervised by the "Scanning", or "Unit" type of indicator as specified (see 1.2.2 and 6.1). The features of these indicators shall be as specified hereinafter.

3.3.8.1 Scanning (type S). The scanning indicator shall be provided with an automatic means of scanning each sampling point at an interval not to exceed 15 minutes, and indicating by lamp type indicator or other means approved by the procuring activity. The sampling line shall be connected to the indicating meter at the time. Only one alarm unit (see 3.3.7) is required to indicate excessive concentration at any sampling location. The audible alarm shall continue to sound until manually reset. In addition to the red alarm light, a drop-type annunciator, or other indication approved by the procuring activity shall be provided to indicate which sampling point has reached or exceeded the concentration for which the alarm is set.

3.3.8.2 Unit (type U). The unit indicator shall provide a separate analyzing circuit and an indicating meter for each sensitive element. Only one alarm unit (see 3.3.7) is required to indicate excessive concentration at any sensitive element.

3.3.8.3 Manual (type M). The manual indicator shall be provided with a manually-operated selector for connecting the sampling line to the indicating meter. Only one alarm unit (see 3.3.7) is required to indicate excessive concentration at any sampling point.

3.3.9 Amplifiers. Amplifiers, if used, shall be of the magnetic type unless otherwise specifically approved by the procuring activity.

3.4 Sampling lines. The sampling lines shall be designed to sample the gas or vapor mixture continuously at distances up to 100 feet from the indicator without manual operation by operating personnel. This may be accomplished by a circulating pump driven by a motor conforming to MIL-M-17059 or MIL-M-17060. Necessary flame arresters or filters, or both, shall be provided. The useful life of a set of sampling lines shall be not less than 10,000 hours. (The useful life of the sampling lines shall be considered as terminated when the usual operation adjustments do not result in a correct zero adjustment.)

3.5 Shock. The detector shall withstand the grade A, class I, type A test for lightweight equipment in accordance with MIL-S-901.

3.6 Manuals, technical. Type II manuals in accordance with MIL-M-15071 shall be furnished in quantities as specified (see 6.1).

3.7 Repair parts. Repair parts included in the maintenance parts kit shall be as follows:

(a) Sufficient sampling line pairs to provide for 10,000 hours operation of the indicator.
(b) Sufficient filters, flame arresters, and similar items, if used, to provide for 10,000 hours operation of the indicator.
(c) Four brushes for each motor used.
(d) Electron tubes - 100 percent.
(e) Relays - 1 each type.
(f) Switches - 1 of each type.
(g) Condensers, resistors, potentiometers - 2 of each type.
(h) Electron tube sockets - 1 of each type.
(i) Motors - 1 complete motor of each type.
(j) Pumps - 1 complete pump assembly.

3.7.1 Prior to packaging for shipment, the repair parts shall be tested for fit, dimensions, function, operation, and interchangeability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:22Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

(a) First article inspection.
(b) Quality conformance inspection.

4.2.1 The attention of the manufacturer is invited to the applicable paragraphs of MIL-I-983 for information concerning tests.

4.3 First article inspection. First article inspection shall be conducted on one sample of the explosive vapor detector equipment. Tests shown in table I shall be performed in the order listed.

Table I - First article inspection.

Examination or test	Requirement paragraph	Test reference
General examination	3.2.1	MIL-I-983
Operation	3.3.6 and 3.3.7	4.6.1
Supply line voltage and frequency variation	3.2.1	MIL-I-983
Airborne noise	3.2.1	MIL-I-983
Salt spray	3.2.1	MIL-I-983
Temperature (extreme temperature for exposed locations) and humidity	3.2.1	MIL-I-983
Inclination	3.2.1	MIL-I-983
Dielectric strength	3.2.1	MIL-I-983
Insulation resistance	3.2.1	MIL-I-983
Endurance	3.2.4	4.6.2
Enclosure	3.2.1, 3.3.1	MIL-I-983
Vibration (vital)	3.2.1	MIL-I-983
Shock	3.2.1	MIL-I-983

4.3.1 The result of each test shall be compared with the requirements of this specification. In the event of failure to conform to this specification, the contractor shall correct the cause of failure in the first article sample and on future production units.

4.4 Quality conformance inspection. Quality conformance inspection shall consist of the following group A, B, and C examination and tests performed, in general, in the order listed:

Table II - Quality conformance inspection.

Examination or test	Requirement paragraph	Test reference
Group A examination and tests		
General examination	3.2.1	MIL-I-983
Dielectric strength	3.2.1	MIL-I-983
Insulation resistance	3.2.1	MIL-I-983
Operation	3.2.2, 3.2.3, 3.3.6, 3.3.7	4.6.1
Group B tests		
Supply line voltage and frequency variation	3.2.1	MIL-I-983
Airborne noise	3.2.1	MIL-I-983
Group C tests		
Salt spray	3.2.1	MIL-I-983
Temperature and humidity	3.2.1	MIL-I-983
Inclination	3.2.1	MIL-I-983
Endurance	3.2.4	4.6.2
Enclosure	3.2.1	MIL-I-983
Vibration (vital)	3.2.1	MIL-I-983
Shock	3.2.1	MIL-I-983

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:22Z
Check the source to verify that this is the current version before use.

4.5 Sampling for quality conformance inspection.

4.5.1 Inspection lot. All equipments of the same type designation presented for quality conformance inspection at one time shall be considered a lot. The lot may include the entire contract quantity or it may be the production of any convenient time period.

4.5.2 Sampling for group A examination and tests. A sample of equipments shall be selected from each inspection lot in accordance with table III. Samples shall be subjected to each of the group A examination and tests specified in 4.4. The results of each test shall be compared with the requirements of this specification. Failure to conform to this specification for any examination or test shall be counted as a defect, and the equipment shall be rejected. If the number of such nonconforming equipments in any sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

Table III - Sampling for group A examination and tests AQL (approx.) = 1.5 percent defective.

Number of equipments in inspection lot	Number of equipments in sample	Number of equipments nonconforming on any group A examination or test	
		Acceptance number	Rejection number
7 and under	All	-	-
8 to 15	7	0	1
16 to 40	15	0	1
41 to 110	25	1	2
111 to 300	35	1	2
301 to 500	50	2	3
501 and over	75	3	4

4.5.3 Sampling for group B tests. A sample of equipments shall be selected from each inspection lot in accordance with table IV. Samples shall be subjected to each of the group B tests specified in 4.4. The results of each test shall be compared with the requirements of this specification. Failure to conform to this specification for any group B test shall be counted as a defect, and the equipment shall be rejected. If the number of such nonconforming equipments in any sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

Table IV - Sampling for group B tests.

Number of equipments in inspection lot	Number of equipments in sample	Number of equipments nonconforming on any group B test	
		Acceptance number	Rejection number
3 and under	All	-	-
4 to 15	3	0	1
16 to 40	5	0	1
41 to 110	7	0	1
111 to 300	10	0	1
301 to 500	15	1	2
501 and over	25	2	3

4.5.4 Sampling for group C tests. When required by the procuring activity (see 6.1), and where required by design or material changes in the equipment, one sample equipment shall be subjected to each of the group C tests specified in 4.4. The results of each test shall be compared with the requirements of this specification. In the event of failure to conform to this specification for any group C test, the contractor shall correct the cause of failure on future production units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:22Z
Check the source to verify that this is the current version before use.

4.6 Test procedures.

4.6.1 Operating test. The operating test shall consist of those tests necessary to determine compliance with 3.2.2, 3.2.3, 3.3.6, and 3.3.7.

4.6.2 Endurance. The detector shall be operated continuously for a period of 10,000 hours to determine conformance with 3.2.4.

4.7 Inspection of preparation for delivery. Sample packages and packs shall be selected in accordance with MIL-P-116 and inspected to determine conformance with section 5 of this specification.

5. PREPARATION FOR DELIVERY

(The preparation for delivery requirements specified herein apply only for direct Government procurements. For the extent of applicability of the preparation for delivery requirements of referenced documents listed in section 2, see 6.2.)

5.1 Domestic shipment and early installation.

5.1.1 Preservation and packaging. Preservation and packaging, which may be the supplier's commercial practice, shall be sufficient to afford adequate protection against corrosion, deterioration, and physical damage during shipment from the supply source to the using activity and until early installation.

5.1.2 Packing. Packing shall be accomplished in a manner which will insure acceptance by common carrier at the lowest rate and will afford protection against physical or mechanical damage during direct shipment from the supply source to the using activity for early installation. The shipping containers or method of packing shall conform to the Uniform Freight Classification Rules or other carrier regulations as applicable to the mode of transportation, and may conform to the supplier's commercial practice when such meets these requirements.

5.1.3 Marking. Shipment marking information shall be provided on interior packages and exterior shipping containers in accordance with the contractor's commercial practice. The information shall include Federal stock number or manufacturer's number, contractor's name, and destination.

5.2 Domestic shipment and storage or overseas shipment. The requirements and levels of preservation, packaging, packing, and marking for shipment shall be specified by the procuring activity (see 6.1).

(5.2.1 The following provides various levels for protection during domestic shipment and storage or overseas shipment, which may be required when procurement is made.

5.2.1.1 Preservation and packaging, packing, and marking. Equipment shall be preserved and packaged level A or C; packed level A, B, or C as specified (see 6.1) and marked in accordance with MIL-E-17555, except that fiberboard boxes shall not exceed the weight limitations of the applicable box specification.)

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Complete type designation (see 1.2).
(c) Inventory control points for repair parts (see 3.2.1).
(d) Quantity of manuals required (see 3.6).
(e) Whether group C tests are required (see 4.5.4).
(f) Level of preservation and packaging and level of packing required if other than as specified in 5.1 (see 5.2).

6.2 Sub-contracted material and parts. The preparation for delivery requirements of referenced documents listed in Section 2 do not apply when material and parts are procured by the supplier for incorporation into the equipment and lose their separate identity when the equipment is shipped.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:22Z
Check the source to verify that this is the current version before use.

6.3 CHANGES FROM PREVIOUS ISSUE. THE OUTSIDE MARGINS OF THIS DOCUMENT HAVE BEEN MARKED "#" TO INDICATE WHERE CHANGES (DELETIONS, ADDITIONS, ETC.) FROM THE PREVIOUS ISSUE HAVE BEEN MADE. THIS HAS BEEN DONE AS A CONVENIENCE ONLY AND THE GOVERNMENT ASSUMES NO LIABILITY WHATSOEVER FOR ANY INACCURACIES IN THESE NOTATIONS. BIDDERS AND CONTRACTORS ARE CAUTIONED TO EVALUATE THE REQUIREMENTS OF THIS DOCUMENT BASED ON THE ENTIRE CONTENT AS WRITTEN IRRESPECTIVE OF THE MARGINAL NOTATIONS AND RELATIONSHIP TO THE LAST PREVIOUS ISSUE.

6.4 First article. Invitation for bids should provide that the Government reserves the right to waive requirement for first article inspection as to those bidders offering a product which has been previously procured or tested by the Government, and that bidders offering such products who wish to rely on such production or test must furnish evidence with the bid that prior Government approval is presently appropriate for the pending procurement.

Navy interest:
Review - OS
User - CG

Army interest:
None

Air Force interest:
None

Preparing activity:
Navy - SH
(Project 6665-N261)

Source: https://assist.dla.mil -- Downloaded: 202640-18T08:22Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:22Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)* | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE 0101-807-2000

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:22Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
Naval Ship Engineering Center
Center Building
Prince George's Center
Hyattsville, Maryland 20782

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
NAVY DEPARTMENT

Commander, Naval Ship Engineering Center
DOD Standardization Program & Documents Branch
Center Building
Prince George's Center
Hyattsville, Maryland 20782

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:22Z
Check the source to verify that this is the current version before use.