MIL-B-43965A
25 June 1982
SUPERSEDING
MIL-B-43965
31 March 1977

MILITARY SPECIFICATION

BAG, WET WEATHER CLOTHING: (PARKA AND TROUSERS)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers the requirements for one type of carrying bag (see 6.1).

2. APPLICABLE DOCUMENTS

* 2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

V-T-295	-	Thread, Nylon
UU-P-268	-	Paper, Kraft, Wrapping
DDD-L-20	-	Label: for Clothing, Equipage, and Tentage (General Use)
PPP-B-636	-	Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Laboratories, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8465

Source: https://assist.dla.mil -- Downloaded: 20261O-21T23:13Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-T-8363	-	Tape and Webbing, Textile, Woven, Nylon
MIL-F-10884	-	Fasteners, Snap
MIL-F-21840	-	Fastener Tapes, Hook and Pile, Synthetic
MIL-C-23926	-	Cloth, Coated and Laminated, Polychloroprene on Nylon, and Tape, Polychloroprene, Unsupported

STANDARDS

FEDERAL

FED-STD-751	-	Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Loads
MIL-STD-1188	-	Commercial Packaging of Supplies and Equipment

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 Materials.

3.1.1 Laminated cloth. The cloth used in the fabrication of the bag shall conform to type II of MIL-C-23926, except that the color of the base cloth before laminating shall be Olive Green 106 and the color of the coating used to bind the two layers of base cloth shall be Olive Green 207.

* 3.1.2 Thread. The thread shall conform to type I, class B, size B of V-T-295. The thread shall be dyed Olive Drab S-1, C.A. 66022, and shall have good colorfastness to laundering and good colorfastness to light after 20 hours exposure.

3.1.3 Webbing. The webbing shall conform to type III of MIL-T-8363 and shall be Olive Green 106.

* 3.1.4 Fastener tape. The fastener tape shall be 1 inch wide, and shall conform to type II, class 1 of MIL-F-21840. The color of the tape shall be either Black 3230 or OG 106.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:13Z
Check the source to verify that this is the current version before use.

3.1.5 Fastener, snap. The snap fastener shall conform to style 4, finish 2 of MIL-F-10884.

3.1.6 Label. The label shall conform to type IV, class 5 of DDD-L-20.

3.2 Construction.

3.2.1 Patterns. Standard patterns will be furnished by the Government, and provide the proper allowance for all seams. Standard patterns shall not be altered in any manner and are to be used only as a guide for cutting the contractor's working patterns.

3.2.2 Manufacturing operations. The bag shall be manufactured by and with the use of all operations specified in table I. The contractor is not required to follow the exact sequence of operations.

3.2.3 List of pattern parts. The component parts for the bag shall be cut from the material and in the number of parts as specified below:

Material	Item	Nomenclature	Cut parts
Cloth, laminated	1	Back	1
Cloth, laminated	2	Front	1
Cloth, laminated	3	Top flap No. 1	1
Cloth, laminated	4	Top flap No. 2	1

* 3.2.4 Stitching, machine. All stitching shall conform to type 301 of FED-STD-751 with 8 to 10 stitches per inch.

* 3.2.4.1 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched 1 inch minimum except where ends are turned under in a hem or held down by other stitching. Thread tension shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread, or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be embedded in the materials sewn.

* 3.2.4.1.1 Repairs of stitching.

a. When thread breaks or bobbin run-outs occur during stitching, the stitching shall be repaired by restarting the stitching a minimum of 1/2 inch back of the end of the stitching. 1/

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:13Z
Check the source to verify that this is the current version before use.

b. Thread breaks, or two or more consecutive skipped or run-off stitches noted during inspection of the item (in process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area, continue over the defective area and continue a minimum of 1 inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repair, the ends of the stitching are not required to be backstitched.

3.2.4.2 Thread ends. All thread ends shall be trimmed to a length of not more than 1/4 inch.

3.2.4.3 Fusing of ends of nylon webbing. The ends of the nylon webbing shall be fused in such a manner as to prevent sharp edges from forming. The apparatus used to fuse the webbing ends shall be capable of providing sufficient heat to fuse the cut ends of the webbing yarns together.

* 3.2.4.4 Setting of the metallic snap fastener. A hole shall be prepunched through the material before inserting the stud eyelet tube or the socket eyelet tube. The hole shall be smaller than the outside diameter of the applicable eyelet tube so that the tube must be forced through the hole. Prepunched holes shall not be accomplished by using stud eyelet tube or socket eyelet tube. Fastener components shall be securely clinched without cutting the adjacent materials and no more than three splits shall occur in the button or eyelet barrels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:13Z
Check the source to verify that this is the current version before use.

TABLE I

NO.	MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
1.	Cutting.						
	a. Cut the bag in strict accordance with patterns furnished. Patterns show directional lines, shape, and notches for proper assembly of all parts.						
	b. Cut two pieces of the webbing specified in 3.1.3, each 5-3/4 ± 1/8 inch in length. Fuse each end of the webbing to prevent ravelling.						
	c. Cut two pieces of hook fastener tape and pile fastener tape specified in 3.1.4, each 2 ± 1/8 inch long.						
2.	Make bag.						
	a. Hem the front piece of the carrying bag along the top edge with one row of stitching 1/8 inch from the raw edge of the 1/2 inch turn under.	301	EFa-1	8-10 1/	B	B	
	b. Join the front of the bag to the back using a single row of stitching 3/8 inch from the raw edges.	301	LSq-2(a)	8-10	B	B	
	c. Turn and raise stitch with a single row of stitching 1/4 inch from the folded edge.	301	LSq-2(b)	8-10	B	B	
	d. Continue the raise stitch onto the end flaps and form the stitching for the flap hem.	301	EFa-1	8-10	B	B	
	e. Stitch hook and pile fastener tapes to pouch at locations shown on pattern. Stitching shall be 1/4 inch from the edges on all sides.	301	LSbj-1	8-10	B	B	

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:13Z
Check the source to verify that this is the current version before use.

NO.	TABLE I (cont'd) MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
2.	Make bag. (cont'd)						
	f. Locate label under front flap. The label shall be centered under the hook fastener tape with the top edge of the stamped label adjacent to the bottom edge of the hook fastener tape.						
	g. Turn under 3/8 inch, and hem both sides of each end flap.	301	EFa-1	8-10	B	B	
	h. Join the end flaps to the bag. The ends of the flaps shall be even with the raw edge of the front piece hem turn under. The continuous stitching shall form a box that is the full width of the strap and 1/8 inch wide.	301	LSa-2	8-10	B	B	
	i. Fold the end of the webbing belt straps under 1-1/8 inch and stitch with one row of stitching 1/16 inch from the edges in a box pattern.	301	EFa-1	8-10	B	B	
	j. Install one snap fastener button through the folded end of each webbing belt strap. The button shall be positioned so that the opening symbol (dot) on the button shall be towards the bottom of the bag. The center of the button shall be 3/4 inch from the folded edge and equidistant from the sides.						
	k. Stitch the opposite ends of the webbing to the back of the pouch at the marks on the pattern with one row of stitching in a box pattern 3/4 by 3/8 inch. Fold the webbing downward covering the box stitching.	301	EFa-1	8-10	B	B	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:13Z
Check the source to verify that this is the current version before use.

NO.	TABLE I (cont'd) MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
2.	Make bag. (cont'd) 1. Install the three-way locking snap fastener studs at the pattern marks on the back of the bag. The studs shall be reinforced on the backside with a 1 inch diameter patch of coated cloth (self material). 3. Clean bag. a. Trim all thread ends to 1/4 inch maximum. Remove loose thread. b. Remove all spots and stains.						

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:13Z
Check the source to verify that this is the current version before use.

3.3 Dimensions. The finished measurements of the bag shall be 2-1/8 ± 1/8 inch for the width of the bottom and 9-1/4 ± 1/8 inch for the side. The finished measurement of the carrying bag shall be taken as follows: The measurement of the bottom of the bag shall be taken from corner to corner. The measurement of the side shall be taken, with the bag in a flattened position, from folded edge to folded edge.

* 3.4 Workmanship. The finished bag shall conform to the quality of product established by this document. The occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.2 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

* 4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

* 4.2.2 End item examination. The end item shall be examined in accordance with 4.2.2.1 and 4.2.2.2. The lot size shall be expressed in units of one bag. The sample unit shall be one bag.

* 4.2.2.1 Visual examination. The end item shall be examined for the defects listed below. The inspection level shall be II and the acceptable quality level (AQL) shall be 2.5 major and 6.5 total (major and minor combined) defects per hundred units.

Examine	Defect	Classification Major	Minor
Cleanness	Any permanent spot or stain	X	
	Any removable spot or stain		X
	Thread ends not trimmed to 1/4 inch maximum		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:13Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Component and assembly	Any defective part		X
	Any part omitted	X	
	Any required operation omitted or improperly performed	X	
Labels	Marking missing, incorrect, or illegible		X
	Location of marking not as specified		X
Laminated cloth	Any cut, hole, or tear	X	
	Any delamination	X	
	Any crease or wrinkle		X
	Color not as specified	X	
Workmanship	Needle chews	X	
	Any mend, cut, or hole less than 3/16 inch in length or diameter in hem area		X
Seams and stitching	Seams badly twisted, pleated, or puckered	X	
	Ends of stitching, if not caught in other stitching, not backstitched as specified		X
	Stitching less than 1/16 inch from edge but not resulting in damage to material		X
	Stitching less than 1/16 inch from edge but resulting damage to material	X	
	Any open seam	X	
	Any raw edge		X
	One stitch per inch less than minimum specified		X
	Two stitches per inch less than minimum specified	X	
	Wrong seam type		X
	Wrong stitch type		X
	One stitch per inch over maximum specified		X
	Two or more stitches per inch over maximum specified	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:13Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Thread breaks, skipped stitches, or runoffs	Not overstitched as specified		X
NOTE:	Thread breaks or two or more consecutive skipped or runoff stitches not overstitched shall be classified as open seams.		
Snap fastener	Eyelet or button of snap fastener improperly clinched or having rough or sharp edges	X	
	Roll of clinched eyelet fastener assembly contains more than two scores (splits)		X
	Eyelet or button of snap fastener reversed, i.e., place opposite to side indicated on pattern	X	
	Dot on button of belt straps not pointed toward bottom of bag	X	
Fastener tape	Not positioned as shown on pattern		X

* 4.2.2.2 Dimensional examination. The end item shall be examined for conformance to the dimensions specified in 3.3. Any measurement deviating from the specified dimension shall be classified as a defect. The inspection level shall be S-3 and the AQL shall be 4.0 defects per hundred units.

* 4.2.3 Packaging inspection. An examination shall be made to determine that the preservation, packing, and marking comply with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packaged except that it shall not be palletized and need not be closed. Examination of closure defects listed below shall be made on shipping containers fully packaged. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-1 and the AQL shall be 2.5 defects per hundred units.

Examine	Defect
Markings (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:13Z
Check the source to verify that this is the current version before use.

Examine	Defect
Workmanship	Inadequate application of components, such as: incomplete closure of container flap, loose strapping, improper taping, or inadequate stapling. Bulged or distorted container.
Content	Number of bags per bundle is more or less than specified. 1/ Number of bags per container is more or less than specified.

1/ For this defect, two bundles from each shipping container in the sample shall be examined.

* 4.2.4 Palletization examination. An examination shall be made to determine that palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the end item inspection lot. The inspection level shall be S-1 and the AQL shall be 6.5 defects per hundred units.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

5. PACKAGING

* 5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

* 5.1.1 Level A. Each bag, with outside fasteners closed, shall have the bottom portion folded partially over the front so the bag measures approximately 9-1/2 by 7-1/2 inches. Ten bags, alternately reversed top to bottom, shall be evenly stacked to form a neat bundle measuring approximately 9-1/2 by 7-1/2 by 3-3/4 inches. The bundle shall be securely cross-tied with cotton tape or twine.

* 5.1.2 Commercial. Each bag shall be preserved in accordance with MIL-STD-1188.

* 5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:13Z
Check the source to verify that this is the current version before use.

* 5.2.1 Level A packing. Two hundred and forty bags, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each fiberboard container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Level A bundles shall be packed flat, three in length, two in width, and four in depth within a shipping container. Inside dimensions of each shipping container shall approximate 23 inches in length, 19-1/2 inches in width and 15 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each fiberboard container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced in accordance with the appendix of PPP-B-636, except the inspection shall be in accordance with 4.2.3.

* 5.2.2 Level B packing. Two hundred and forty bags, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each fiberboard container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Level A bundles shall be packed flat, three in length, two in width, and four in depth within a shipping container. Inside dimensions of each shipping container shall approximate 23 inches in length, 19-1/2 inches in width and 15 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636 except the inspection shall be in accordance with 4.2.3.

* 5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.2.3.

* 5.2.3 Commercial packing. Covers, preserved as specified in 5.1, shall be packed in accordance with MIL-STD-1188.

* 5.3 Palletization. When specified (see 6.2), bags, packed as specified in 5.2, shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by contracting officer.

* 5.4 Marking. In addition to any special marking required by the contract, unit packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or MIL-STD-1188, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:13Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The bag is intended as a container for the wet weather parka and trousers.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
c. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
d. When palletization is required (see 5.3).

6.3 Changes from previous issue. The margins of this document are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Air Force - 99

Review activity:

DLA - CT

User activity:

Air Force - 45

Preparing activity:

Army - GL

Project No. 8465-0790

☆ U.S. GOVERNMENT PRINTING OFFICE: 1982—505-022/3453

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:13Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development
Command
ATTN: DRDNA-ES
Natick, MA 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:13Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-B-43965A Bag, Wet Weather Clothing: (Parka And Trousers)

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1426 1 OCT 76 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:13Z
Check the source to verify that this is the current version before use.