MILITARY SPECIFICATION

CAMERA, COPYING, LITHOGRAPHIC, VERTICAL

This specification is approved for use by the Natick Research and Development Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a commercial, lithographic copying camera, for 14 x 18 inch (356 x 457 mm) film size.

1.2 Classification. The camera covered by this specification shall have contact screens of the following classes and grades as specified (see 6.2).

Class 1 - Gray screen (positive or negative)
Class 2 - Magneta screen (positive or negative)

Grade A - 65 ruling lines per inch (2.6 ruling lines per mm)
Grade B - 85 ruling lines per inch (3.4 ruling lines per mm)
Grade C - 100 ruling lines per inch (6 ruling lines per mm)

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

CC-M-1807 - Motors, Alternating Current, Fractional and Integral Horsepower (500 Horsepower and Smaller)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Command, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 3610

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-G-174	-	Glass, Optical
MIL-C-675	-	Coating of Glass Optical Elements (Anti-Reflection)
MIL-C-3615	-	Cameras, Copying Lithographic, Packaging Of

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-150	-	Photographic Lenses
MIL-STD-461	-	Electromagnetic Interference Characteristics, Requirements For Equipment
MIL-STD-462	-	Electromagnetic Interference Characteristics, Measurement Of

(Copies of specifications and standards required by contractors in connection with specific procurement functions, should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

Std. No. 70 - The National Electrical Code

(Application for copies should be addressed to the National Fire Protection Association, 60 Batterymarch Street, Boston, MA 02110.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups, and using Federal agencies.)

3. REQUIREMENTS

3.1 Standard product. The cameras furnished under this specification shall be of the manufacturers current standard product except for changes necessary to comply with the requirements of this specification.

3.2 NFPA and certification. Wiring of the camera shall conform to NFPA Standard No. 70. Acceptable evidence of meeting the requirements of NFPA Standard No. 70 shall be written certification by the manufacturer that the cameras are wired to conform to NFPA Standard No. 70.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

3.3 Materials. Materials not definitely specified shall be of the quality normally used by the manufacturer for the specified equipment, provided the completed item complies with all provisions of this specification (see 6.3).

3.4 Design and construction. The camera shall be a vertical precision type. The design and construction of the cameras shall provide positive locking of all movable components. The cameras shall be of a vertical design with a removable copyboard. The movement of components controlling the operation, focusing, and adjustment of the camera shall be positive with uniform resistance, and freedom from lost motion. Controls shall be located within reach of the operator and in such a manner as not to interfere with the operation of the camera. All glass-air surfaces shall have a reflection reduction coating conforming to MIL-C-675. The lens shall be calibrated and have a matching cap and be capable of being mounted on the lens plate and attached to the lensholder. The optical glass for the camera lens shall conform to class 1 or 2, grade A plate or slab of MIL-G-174. The camera back shall accommodate up to 14 x 18 inch (356 x 457 mm) sheet film and 14-1/2 x 18-1/2 inch (368 x 470 mm) contact screen. Class 1 shall have a gray screen (positive or negative) and class 2 shall have magneta screen (positive or negative). Grade A shall have 65 ruling lines per inch (2.6 ruling lines per mm), grade B 85 ruling lines per inch (3.4 ruling lines per mm), and grade C 100 ruling lines per inch (6 ruling lines per mm). The overall dimensions of the camera shall not be greater than 24 inches deep, 60 inches wide, and 52 inches high (610 mm deep, 1524 mm wide, and 1321 mm high). The weight of the camera shall not exceed 290 pounds (131.5 kg). The range of reproduction shall not be less than a reduction of 33-1/3 percent and an enlargement of 300 percent. The camera frame shall be constructed from 2-1/2 inch (63.5 mm) square steel tubing integral with a U shape base. The iris diaphgram shall have a manual control for correlation of the "f" values of the lens to provide an equivalent transmission of light at various rates of enlargement and reductions. The diaphgram control shall be marked f/8, f/11, f/16, f/22, f/32 and f/64. The camera vacuum back shall be equipped with a motor driven vacuum pump and tubing. The motor driven vacuum pump shall be furnished complete with base, switches, controls, fittings, vibration mounts and connecting hose. The motor and pump shall be mounted and aligned as a unit. A switch mounted on the camera back shall be provided for control of the motor. The electrical components shall operate on 110 volt, 60 hertz, single phase current. The cords extending to the copyboard shall be rubber covered with helical coils, or be provided with automatic takeups. Terminal boxes shall be provided for all color coded wires, and identifying switches and controls by name and part number, shall be mounted on a terminal box. The vacuum motors shall conform to CC-M-1807, continuous duty, 1/10 horsepower (746 W), when specified (see 6.2), motors shall be fungus proofed in accordance with applicable requirements of CC-M-1807.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

3.4.1 Copyboard assembly. The copyboard assembly for the camera shall accommodate up to 18 x 24 inch (457 x 610 mm) copy material. The copyboard shall be maintained in parallel alignment with the camera focal plane when the board is in the horizontal position. Graduated centerlines shall be permanently marked on the copyboard to provide a guide for centering the copy. The copyboard shall have its center coincident with the optical axis of the lens. The copyboard assembly shall be mounted to the camera back and be positioned by manually operated hand cranks. The copyboard assembly shall be mounted on roller bearings or roller bushings on the track of the back assembly. A mechanical means shall be provided for applying vacuum to the areas required for applicable copy material sizes. The vacuum copyboard shall hold copy material smoothly with no visual distortion of the surfaces. The copyboard shall be maintained in parallel alignment in all positions (see 4.3.1).

3.4.2 Lens holder assembly. The lens holder assembly shall consist of a movable holder, lens, manual iris diaphgram control, and shutter with electric timer. The holder shall maintain the lens in parallel alignment in all positions (see 4.3.1).

3.4.3 Camera back assembly. The camera back assembly shall include a vacuum back and frosted viewing glass, separately mounted to permit the vacuum back and glass to be alternately brought into the focal plane of the camera. The back assembly shall be attached to the vertical frame assembly and be in parallel alignment in all positions (see 4.3.1).

3.4.4 Lamps. Each lamp shall be quartz iodide. The lamps when operated shall provide uniform illumination readings (within $\pm$ 15 percent of each other) of the copyboard, with no blistering or discoloration of the reflectors (see 4.3.2).

3.4.5 Lamp carriers. The lamp carriers shall be capable of being adjusted and locked in position. The lamp carriers shall operate without binding (see 4.3.2).

3.4.6 Lens. The radial distortion of the lens shall not vary more than .05 mm at a ratio of 1:1 reproduction, throughout an angular field of 0 to 23 degrees for the following lens characteristics: focal length (equivalent) 8.3 inch (210 mm); minimum and maximum relative apertures, f/64 and f/8 respectively; field of view, 42-46 degrees full angle; and apochromatic color correction (see 4.3.3).

3.4.7 Bellows assembly. A bellows assembly shall connect the lens holder assembly to the camera back assembly. The complete bellows assembly shall be readily removable for ease of maintenance and periodic calibration of the camera.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

The bellows shall provide the necessary extension and retraction to obtain reproduction without image obstruction in any position. The bellows shall be fabricated of molded rubber or impregnated rubberized materials, and shall be an accordian type with all corners reinforced. The bellows frame shall fit properly to lensholder and vacuum back. The bellows shall permit adjustment movements with no damage, and shall be light-tight (see 4.3.4).

3.4.8 Vacuum back. The vacuum back shall be hinged to pivot about a vertical or horizontal axis. The vacuum surface shall be black, neutral, or of low-light reflecting color and have small perforations or slots for holding film and contact screens by vacuum. A mechanical means shall be provided for applying vacuum to the areas required for applicable film and screen sizes. The vacuum back shall hold 0.003 thru 0.007-inch (.076 thru .178 mm) thick film smoothly, emulsion side up, with no visual distortion of the surface (see 4.3.5).

3.4.9 Glass, frosted viewing. The frosted viewing glass shall be housed in a metal frame and be removable from the viewing position when the glass is not in use. One surface of the glass shall be uniformly fine grained obtained by an acid or mechanical process. The glass shall be capable of resolving not less than 20 lines per millimeter in a projected image and also the glass shall have permanent markings that shall be coincident with markings on copyboard, when tested as specified in 4.3.6. The permanent markings shall also permit visual orientation and positioning of the image in relation to the film position on the vacuum back. Orientation markings shall consist of a clear, ungrained glass of 1-inch (25.4 mm) square or circle at the center and diagonals radiating to the corners of the glass. The edges of the glass shall be ground square.

3.4.10 Focusing controls. Controls for focusing shall include magnifying indicators and two metal hairline focusing tapes with permanent markings that shall be legible and related to the lens. The focus measuring tapes shall measure distances of lens to copy and lens to film to obtain the reproduction ratio required. Hand controls for movement of the lensholder and copyboard for focusing shall be located on the front of the camera back assembly. A direct reading scaling system using focusing tapes for copyboard and lensholder in direct reading percentages of original size shall be provided. With the lensholder copyboard set for a 1 to 1 reproduction ratio the camera shall take a sharp picture of the test grid or two test scales that shall have a reproduction accuracy within 1/64 inch (.4 mm) in the vertical and horizontal directions throughout the entire field of view (see 4.3.7).

3.5 Electromagnetic compatibility. When specified (see 6.2), the camera shall be designed and equipped for electromagnetic compatibility in accordance with class IIB of MIL-STD-461 (see 4.4).

3.6 Contract data requirements. The contract data requirements shall be as specified (see 6.2 and 6.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

3.7 Threaded fasteners. Threaded fasteners shall conform to the commercial practice of the manufacturer.

3.8 Lubrication. Oil fittings, grease cups, or other means of lubrication shall be provided for lubricating all parts subject to wear. Parts that must not be lubricated, such as graphited vanes in the vacuum pump and the lens iris diaphragm, shall be marked with a "DO NOT LUBRICATE" warning.

3.9 Finish. The cameras shall be given the finish normally used by the manufacturer on this type of equipment.

3.10 Marking. Marking for identification shall be in accordance with the manufacturers commercial practice and shall include manufacturers name, date of manufacture, model number and electrical characteristics.

3.11 Instruction plates. Instruction plates conforming to commercial practice shall indicate procedures for operation and servicing the camera, including warnings and cautions.

3.12 Workmanship. The camera shall be free from burrs, slivers or sharp edges, dents, fractures, breakage, and misalignment of parts. The camera lens and viewing glass surfaces shall be free of scratches and stains. The camera finish shall be free of blisters, peel, chipped areas or areas of no film. The camera finish shall be free from smudges, poor touch up, scale, scratches, over-spray, sag, emprint or embedded foreign matter. Threaded fasteners shall not be broken, stripped, fractured or loose. Rivets shall be driven to completely fill the holes, with full size heads neatly finished and in full contact with the surface of the riveted members.

3.12.1 Welding. The surface of parts to be welded shall be free from oxide, scale, paint, grease and other foreign matter. Welds shall be sound, continuous, smooth, and free from porosity, cracks, incomplete fusion, and deformation of material. All scale and deposits shall be removed from the finished welds.

3.12.2 Electrical wiring. Wiring shall not be cut, abraded, or have excessive insulation stripped, and shall be properly and tightly joined at terminals. Wiring shall have adequate slack to provide relief strain.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

4.2 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.2.2 End item inspection. The inspection lot shall be all complete cameras offered for inspection at one time. The sample unit shall be one complete camera.

4.2.2.1 Visual examination. The cameras shall be examined for the defects in table I. The inspection level shall be II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Minor
Finish	Not finished where required	X	
	Not manufacturers commercial finish		X
	Blistered, peeled, chipped or area of no film		X
	Poor touch up, orange peel, color separation, smudge, scale, scratched, stained, overspray, sag, imprint or foreign matter imbedded		X
Design and construction and workmanship, general	Any component or part missing or not specified type or size	X	
	Any part dented, fractured, broken or misaligned	X	
	Sharp burr, sliver or sharp edge	X	
	Locking of moving components not positive	X	
	Movement of operating components for focusing and adjustment not positive with uniform resistance and free from lost motion	X	
	Controls not within reach of operator, or interfere with operation of camera	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Screen	Not color specified	X	
	Not number of ruling lines specified	X	
Copyboard	Not framed in metal, scratched, cracked, centerlines missing, not permanently marked	X	
	No visual distortion of copy material surface	X	
Lamp carriers	Do not operate as specified	X	
Lens and lensholder	Lens not as specified	X	
	Lens not free from scratches or stains; cap, reflection coating, or calibration missing	X	
Iris diaphragm	Not graduated as specified or graduations not legible	X	
Bellows assembly	Material not as specified, cracked or worn, corners not reinforced	X	
	Improper bellows frame fit to lensholder or camera vacuum back	X	
Camera back assembly	Frosted viewing glass, markings not as specified, missing or not legible, or vacuum system cannot be brought into focal plane of camera	X	
Focusing controls, including aids	Missing or not as specified	X	
Electrical components	Not as specified	X	
Lubrication fittings	Missing	X	
Welding	Missing, incomplete, burn holes, fractured, or not fused	X	
	Slag inclusion, undercut, not smooth and uniform, or deposit of scale and flux not removed	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Threaded fasteners	Broken, stripped, fractured or not tight	X	
Lubrication fittings (where applicable)	Missing	X	
	Not accessible for servicing	X	
Rivets (when required)	Broken, not peened or insufficiently peened or loose	X	
Marking for identification, and instruction plates	Missing, incomplete, not legible		X
Electrical wiring	Wiring cut, abraded, or not properly installed or joined	X	
	Adequate slack not provided for wiring to relieve strain		X

4.2.2.2 Dimensional examination. The cameras shall be examined for compliance with dimensions and weight specified. Any dimension or weight not within this specification tolerance shall be a defect. The inspection level shall be S-2 with an AQL of 4.0 defects expressed in terms of defects per hundred units.

4.2.2.3 End item testing. Each camera shall be as specified in 4.3 thru 4.3.8. Failure of any test shall be cause for rejection of the item. When applicable, the test specified in 4.4 shall be performed on one representative production unit. Failure of the test shall be cause for rejection of the lot.

4.2.2.4 Code compliance. Certification of compliance with NFPA requirements shall be made available to the Government representative.

4.2.3 Inspection of preparation for delivery. Preservation-packaging, packing and marking shall be inspected in accordance with the quality assurance provisions in MIL-C-3615.

4.3 Tests. Tests shall be conducted at an ambient temperature of between 68 to 75°F (20 to 24°C) and at 45 to 60 percent relative humidity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

4.3.1 Parallelism test. The parallelism test of copyboard, lensholder and camera back assemblies shall be made by means of a telescoping trammel rod with dial indicator (calibrated in 0.001-inch (.025 mm) increments) attached at one end. Parallelism of the planes of these components shall be checked at reproduction ratios of 33-1/3, 25, and 20 percent reduction and 300 percent enlargement. Any nonconformance with the parallel alignment in all positions between copyboard, lensholder, and camera back requirements 3.4.1, 3.4.2 and 3.4.3 shall constitute failure of this test.

4.3.2 Lamp illumination and carrier tests. A sheet of white paper equal in size to the copyboard and equally subdivided into 25 rectangles shall be placed on the copyboard. The lamp carriers shall be positioned as far as possible away from the copyboard. The lamps shall be turned "on" and adjusted to obtain maximum illumination coverage of the copyboard and lamp carriers locked. All other lights shall be turned "off". Light meter readings at the center of each of the 25 rectangles shall be taken and the reflecting surfaces of each of the lamps shall then be examined. Any nonconformance with the lamp illumination, lamp reflector blistering and discoloration requirements (see 3.4.5) or lamp carrier locking requirements (see 3.4.4) shall constitute failure of this test.

4.3.3 Lens test. The lens shall be tested in accordance with test methods in MIL-STD-150 except for the apochromatic characteristic. A certified certificate from the lens manufacturer stating that the lens is an apochromatic lens is acceptable. Any nonconformance with the lens characteristic requirements of 3.4.6 shall constitute failure of this test.

4.3.4 Light-tightness test. The camera shall be set up with a darkroom. The lens shutter shall be "closed" and the lensholder assembly shall be moved forward toward the copyboard until the bellows extends to 1/2 its maximum limit. With copyboard illumination lamps directed toward the lensholder and bellows and turned on, all room lights "off", and a 5-minute allowance for eyes to become accustomed to darkness, the bellows shall be extended and retracted to its maximum limit for a minimum of 5 cycles. The bellows at its maximum extension limit shall then be examined for light-tightness and bellows damage and sag. Any nonconformance with the light-tight requirements of 3.4.7 shall constitute failure of this test.

4.3.5 Camera vacuum back test. The vacuum back shall be tested for film adherence with 6 films, ranging in sizes from 0.003 to 0.007-inch (.076 to .178 mm) thick and ranging in sizes from 4 by 5 inches (102 by 127 mm) to 14 x 18 inch (356 x 457 mm) film size. Each film size shall be tested separately. A light shall then be moved about the film surface to check distortion. Any nonconformance with the visual distortion of film surfaces of 3.4.8 shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

4.3.6 Glass frosted viewing test. The frosted viewing glass shall be tested for resolution of lines per millimeter and the coincidence of glass and copyboard markings. Any nonconformance with the line resolution and coincidence of glass and copyboard marking requirements of 3.4.9 shall constitute failure of this test.

4.3.7 Focusing test. A rectalinear reproduction test grid equal in area size to the copyboard or two 18 inch (457 mm) long calibrated test scales centrally located at right angles to each other shall be placed on the copyboard. The .250 inch (6 mm) grid squares and scale graduations shall have a tolerance of ± .005 inch (.127 mm). The lensholder and copyboard shall be set for a 1 to 1 reproduction ratio and the lens for operation at f/22. The copyboard lamps shall be placed 2 feet (610 mm) from the center of the copyboard at an angle of 45 degrees and the light source shall be set for 3200 kelvin. With the shutter control on "manual" all room lighting shall be turned "off" and the lamps turned "on". The picture of the reproduction test grid or scales shall be photographed for determination of picture sharpness and accuracy of reproduction. Any nonconformance with the reproduction accuracy requirements of 3.4.10 shall constitute failure of this test.

4.4 Electromagnetic compatibility test. When electromagnetic compatibility is required, the first article or initial production unit as applicable, shall be tested by the contractor in accordance with test methods CE03 and RE02 of MIL-STD-462. The Government reserves the right to witness tests performed by the contractor or an independent testing agency. The contractor shall furnish the contracting officer written certification that the Interference Control Plan, the EMI/EMC Test Plan and the Electromagnetic Test Report and the requirements meet MIL-STD-461 (see 3.5).

4.5 Inspection of packaging. An inspection shall be made to determine that preservation-packaging, packing and marking as specified in section 5 is in conformance with MIL-C-3615.

5. PACKAGING

5.1 Preservation-packaging, packing and marking. Preservation-packaging, packing and marking for level A, B, or C shall be in accordance with MIL-C-3615 (see 6.2).

6. NOTES

6.1 Intended use. The camera covered by this specfication is intended for use in the precision production of line and half tone negatives for the lithographic process, when mounted in Editorial-Photo Mechanical Shelter of the Special Warfare, Printing Plant (Lightweight).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Class and grade of camera contact screen required (see 1.2).
(c) When fungus proofing of the motor is required (see 3.4).
(d) When electromagnetic compatability is required (see 3.5).
(e) Contract data requirements (see 3.6 and 6.2.1).
(f) Selection of applicable levels of preservation-packaging and packing (see 5.1).

6.2.1 Contract data requirement. Any data items to be delivered under any contract covered by this specification shall be specifically called for in contract in accordance with applicable regulation of the procurement agency (see 3.6 and 6.2).

6.3 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.3).

6.4 Metric equivalents. Metric equivalents, indicated in parentheses throughout this document, are based on practices, conversion factors, and symbols specified in ASTM E 380 Standard for Metric Practice, and are for information only. In each instance, the value in US customary units shall be controlling.

Custodian:

Army - GL

Review activity:

DLA - GS

Preparing activity:

Army - GL

Project No. 3610-0283

☆U.S. GOVERNMENT PRINTING OFFICE: 1978 — 703-122/768

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-43973(GL) - Camera, Copying, Lithographic, Vertical

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK RESEARCH and DEVELOPMENT COMMAND
NATICK, MASSACHUSETTS 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
DRXNM-TD G

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD-314

U.S. MAIL

Commander
US Army Natick Research and Development Command
ATTN: DRXNM-TD G
Natick, MA 01760

NATICK OP 1 JUL 77
FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.