INCH-POUND
MIL-DTL-44001C
29 Apr 2025
SUPERSEDING
MIL-C-44001B
30 Mar 1990

DETAIL SPECIFICATION

COVER, HELMET, CHEMICAL PROTECTIVE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type and size of chemical protective helmet cover.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3, 4, or 5 of this standard. This section does not include documents cited in other sections of this standard or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, 4, or 5 of this standard, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

Comments, suggestions, or questions on this document should be emailed to trpsptctstandardiz@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 8415

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:20Z
Check the source to verify that this is the current version before use.

FEDERAL SPECIFICATIONS

JJ-W-155 - Webbing, Textile, (Cotton, Elastic)

COMMERCIAL ITEM DESCRIPTIONS

A-A-50199 - Thread, Polyester Core, Cotton or Polyester-Covered
A-A-59991 - Thread and Twine, Mildew Resistant or Water Repellent Treated

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-C-51251 - Cloth, Coated: CBR Protective

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-129 - Marking for Shipment and Storage

(Copies of these documents are available online at https://quicksearch.dla.mil.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

AMERICAN SOCIETY FOR QUALITY (ASQ)

ASQ/ANSI Z1.4 - Sampling Procedures And Tables For Inspection By Attributes

(Copies of this document are available online at https://asq.org)

ASTM INTERNATIONAL

ASTM D6193 - Standard Practice for Stitches and Seams

(Copies of these documents are available online at https://www.astm.org)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3), in accordance with 4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:20Z
Check the source to verify that this is the current version before use.

3.2 Samples. Guide samples, when furnished, are solely for guidance and information to the contractor (see 6.4). Variations from the specification may appear in the sample, in which case the specification shall govern.

3.3 Recycled, recovered, environmentally preferable, or biobased materials. Recycled, recovered, environmentally preferable, or biobased materials should be used to the maximum extent possible, provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs.

3.3.1 Cloth, coated, CBR protective. The coated nylon (ripstop) butyl cloth for the body piece shall conform to MIL-C-51251, with the exception of the decontamination procedure requirement (para 4.4.3.8) and the bias bow requirement (para 4.4.3.10). The color shall approximate Camouflage Green 483.

3.3.2 Webbing, elastic, cotton. The cotton elastic webbing shall conform to type II, class 2, unbleached, 7/16 inch wide of JJ-W-155 except that the requirement for accelerated aging shall not apply and the initial tension shall not exceed 2.30 pounds.

3.3.3 Thread. The thread for all stitching shall be polyester-covered, cotton-covered or rayon-covered, ticket number 50, 2 or 3 ply, conforming to A-A-50199. The color shall approximate the shade of the basic material (see 3.3.1). The thread shall be water repellent treated in accordance with type II, class 3 of A-A-59991.

3.4 Design. The cover is made from a single piece of coated cloth with elastic webbing inserted within a hem which is sewn around the periphery of the cover.

3.5 Cut parts.

3.5.1 Body piece. Cut body piece 25 (± 1/2) inches in diameter.

3.5.2 Webbing, elastic. Cut elastic webbing 26 (± 1/4) inches long.

3.6 Construction. Overlap ends of elastic webbing 3/4 (± 1/2) inch and box stitch together with a 3/8- by 1/2-inch pattern centered on the overlap. As an alternate, secure ends with a 1/8-inch wide, 28 stitch 1/2-inch long bartack centered on overlap and perpendicular to length of the elastic. Bartacking shall be free from the thread breaks and loose stitching. With the heavy coated side of the body piece facing down, double fold the edge back with the first fold 3/8 ± (1/16) inch and the second fold 3/4 (+1/8, –1/16) inch. Position the elastic webbing within the formed hem and stitch around entire periphery with stitching located 1/16 to 1/8-inch from the inner folded edge. During the stitching operation, the elastic webbing shall be stretched so that puckers caused by take-up of the elastic are not sewn into the seam. The elastic shall be enclosed within the hem with no twists and shall not be caught in the stitching.

3.6.1 Stitches, seams, and stitching. All stitching shall be 8–10 stitches per inch using stitch type 301 of ASTM D6193.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:20Z
Check the source to verify that this is the current version before use.

3.6.1.1 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched 1/2-inch minimum. Thread tension shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread, or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be embedded in the materials sewn.

3.6.1.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-offs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 1 inch behind the end of the stitching. When making the above repairs the ends of the stitching are not required to be backstitched.
b. Threads breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch before the defective area and continue a minimum of 1 inch beyond the defective area onto the existing stitching (except on box stitching substitute 1/2 inch for 1 inch). Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner. When making the above repairs the ends of the stitching are not required to be backstitched.

3.6.1.2 Use of automated apparel equipment. Automated apparel equipment may be used to perform any of the operations specified in 3.6, providing that the seam and stitch type are as specified, and the finished component conforms to the required configuration. When a government furnished shaper pattern is forwarded, the component shall conform to that pattern.

3.6.1.3 Thread ends. All thread ends shall be trimmed to a length of not more than 1/4-inch.

3.6.2 Identification Marking. Each helmet cover shall be permanently and legibly marked on the top inside (lightly coated side of cloth) surface of the cover in bold-faced gothic capital letters of not less than 1/4-inch in height with black indelible marking ink with the following legend:

STOCK NUMBERS: 8415-00-000-0000 (Example)
NOMENCLATURE: Cover, Helmet, Chemical Protective (Example)
SPECIFICATION NUMBER: MIL-C-44001 (Example)
CONTRACT NUMBER: SPE1C1-00-C-0000 (Example)
CONTRACTOR'S NUMBER:
DATE OF MANUFACTURE (CURE DATE) (MONTH AND YEAR): 02/06 (Example).

3.6.3 Repairs. Repairs such as mends, darns, or patches are not permitted on the cover.

3.6.4 Replacement of defective components. During the spreading, cutting, and manufacturing process, components of the cover having material defects or damages that are classified as defects in 4.4.3 shall be removed from production and replaced with non-defective and properly matched components.

3.7 Workmanship. The cover shall conform to the quality of product established by this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:20Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.1.3 Certificates of compliance. Where certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with ASQ/ANSI Z1.4.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:20Z
Check the source to verify that this is the current version before use.

4.4.2 In-process inspection. In-process inspection shall be performed on the elastic webbing to assure that the cut length and joining operation are in accordance with specified requirements. Whenever nonconformance is noted, corrections shall be made to the items affected and lot in-process. Parts which cannot be corrected shall be removed from production. The Government reserves the right to exclude from consideration for acceptance, any material or service for which in-process inspection has indicated nonconformance.

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of helmet covers. The sample unit shall be one helmet cover.

TABLE I
End item visual defects

Examine	Defect	Classification	
		Major	Minor
Cloth, coated	Cut, tear or hole	101	
	Abrasion mark or scratch which extends through the coating to a point where base yarn or fabric weave can be seen	102	
	Uncoated area	103	
	Pit, blister, tunnel, or delamination of coating	104	
	Lump or imbedded foreign matter which protrudes so as to be readily abraded from material or easily removed	105	
	Crease or wrinkle which when flattened by pulling manually results in delamination of coating from base fabric	106	
Seams and stitching:			
Open seams	Up to 1/2-inch inclusive		201
	More than 1/2-inch	107	
NOTE: A seam shall be classified as an open seam when one or more stitches joining a seam are broken, or when two or more consecutive skipped or runoff stitches occur.			
Stitch type	Incorrect stitch type	108	
Seam type	Hem not double folded	109	
Stitch tension	Loose tension, resulting in a loose top or bobbin thread		202
	Excessively tight tension, resulting in puckering of material		203
Stitches per inch	One stitch less than minimum specified		204
	Two or more stitches less than minimum specified	110	
	One or more stitches in excess of maximum specified		205
Stitching ends	Not secured as specified		206

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:20Z
Check the source to verify that this is the current version before use.

Thread breaks, skipped stitches, or runoffs	Thread breaks or two or more consecutive skipped or runoff stitches over-stitched less than 1 inch in each direction beyond the defective stitching area		207
NOTE: Thread break or two or more consecutive skipped or runoff stitches not overstitched shall be classified as open seam.			
Component and assembly	Elastic webbing omitted	111	
	Elastic webbing caught in stitching	112	
	Any unauthorized repair	113	
	Heavy coated side of cloth not on outside of cover (hem is on inside surface)	114	
Cleanness	Spot, stain, or streak more than 1-inch in combined directions which cannot be readily removed with naphtha or water		208
	Thread ends not trimmed as specified		209
Identification label	Omitted, incorrect, illegible, or not as specified		210

4.4.4 End item dimensional examination. The end items shall be examined for conformance to the hem widths and stitch margin requirements specified in 3.6. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of helmet covers. The sample unit shall be one helmet cover.

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged.

Examine	**Defect**
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application including frequency of shipping tags on unit packs
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping or inadequate stapling
	Bulged or distorted container
Content	Number per container or unit pack is more or less than required

4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged.

Examine	**Defect**
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:20Z
Check the source to verify that this is the current version before use.

	Interlocking of loads not as specified
	Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of material is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Department or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The cover provides chemical protection for the Ground Troops – Parachutists Helmet.

6.2 Acquisition requirements. Acquisition documents must specify the following:
a. Title, number, and date of this specification.
b. The specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When first article is required (see 3.1, 4.3, and 6.3).
d. Packaging requirements (see 5.1).

6.3 First article. When a first article is required, it will be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Sample. For access to samples, address the contracting activity issuing the invitation for bids or request for proposal.

6.5 Subject term (key word) listing.
Protection
Clothing, special purpose
Parachutist's

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:20Z
Check the source to verify that this is the current version before use.

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army – GL
Navy – NU
Air Force – 11

Preparing Activity:
DLA – CT
Project 8415-2025-002

Review activities:
Army – MD
Navy – MC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of this information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:20Z
Check the source to verify that this is the current version before use.