MIL-D-43969
17 August 1977
SUPERSEDING
MIL-D-0040631E(GL)
In Part
19 April 1974
(See 6.3)

MILITARY SPECIFICATION

DISPENSERS, BREAD, SELF-LEVELING, DROP-IN

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE.

1.1 Scope. This specification covers self-leveling, sliced bread dispensers for counter drop-in installation.

1.2 Classification. The bread dispensers shall be of the following styles, as specified (see 6.2):

Style 2 - Two dispenser unit
Style 3 - Three dispenser unit
Style 4 - Four dispenser unit

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Command, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7320

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

QQ-W-423	-	Wire, Steel, Corrosion-Resisting
PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	-	Boxes, Shipping, Fiberboard

MILITARY

MIL-P-116	-	Preservation-Packaging, Methods of

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage

(Copies of specifications, standards and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 167	-	Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

NATIONAL SANITATION FOUNDATION (NSF)

Standard No. 2 - Food Service Equipment.

Listing of Food Service Equipment.

(Application for copies should be addressed to the National Sanitation Foundation, NSF Building, Ann Arbor, MI 48105.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Standard product. The bread dispensers shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product with any added features needed to comply with the requirements of this specification. Modifications to add features shall not incorporate different parts unless such parts are used on other current commercial models. Standard or modified commercial products furnished in accordance with this specification shall be identifiable by all regular manufacturer's commercial service organizations servicing the brand involved. Service organizations shall be capable of providing complete parts and repair services on models furnished to the Government consistent with their normal commercial practices.

3.2 Codes and standards. The bread dispensers covered by this specification shall conform to the applicable requirements of NSF Standard No. 2.

3.2.1 Compliance. Prior to commencing production, the contractor shall submit to the contracting officer or his authorized representative satisfactory evidence that the bread dispensers he proposes to furnish under this specification meet the applicable requirements of NSF Standard No. 2.

3.2.1.1 NSF. Acceptable evidence of meeting the requirements of NSF shall be:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" and display of the NSF seal on the finished dispensers, or

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

(2) A certification for the rack issued by NSF under their special one-time contract evaluation/certification service, or

(3) A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the dispensers are being procured, indicating that the dispensers have been tested and conform to the applicable requirements of NSF Standard No. 2.

3.3 Materials and components. Materials and components shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer in his standard commercial dispensers provided the completed item complies with all provisions of this specification.

3.3.1 Stainless steel.

3.3.1.1 Sheet and strip. Stainless steel sheet and strip shall conform to type 302 or 304 of ASTM-A 167.

3.3.1.2 Wire. Corrosion-resisting steel wire shall conform to form 1, composition 302 or 304, condition B of QQ-W-423.

3.4 Construction and design. The bread dispenser shall be of the completely enclosed design with supporting flange(s) for counter drop-in installation. The bread dispenser shall be furnished in style 2, 3 or 4 dispenser units as specified having a common drop edge. Each dispenser tube shall have a capacity of 1-1/2 loaves of sliced pullman bread. The dispensing mechanism of each dispensing tube shall maintain the load of bread at the correct dispensing level without binding when tested as specified in 4.4.1.

3.4.1 Bread dispensing tubes. The bread dispensers shall be completely enclosed, fabricated of stainless steel specified in 3.3.1.1, furnished with removable crumb tray, top supporting flange, and hinged cover. The inside dimensions of dispensing tubes shall be not less than 5-1/2 inches (139.7 mm) by 5-1/2 inches (139.7 mm) by 25 inches (635 mm) deep with a usable depth of not less than 20 inches (508 mm) measured from the top of the supporting flange to the top of the leveling mechanism when fully depressed. A separate hinged cover shall be provided on each dispensing tube.

3.4.1.1 Self-leveling mechanism. Each dispensing tube shall have a spring actuated self-leveling mechanism. The self-leveling mechanism shall consist of a spring, a top plate and adjusting device hardware. The springs shall be fabricated of stainless steel wire specified in 3.3.1.2, or a commercial grade chromium vanadium steel in accordance with the manufacturers standard practice. The top plate of the self-leveling mechanism shall be adjustable without removing the mechanism from the dispenser. The hardware, and top plate shall be fabricated of stainless steel. The self-leveling mechanism shall be removable through the top of the dispensing table for cleaning.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

3.5 Finish. The finish shall comply with the applicable provision of NSF Standard No. 2.

3.6 Marking for identification. Each dispenser shall be permanently and legibly marked with the manufacturer's name, trade name, or trademark of such known character as to be identifiable with said manufacturer. Marking shall be applied in accordance with MIL-STD-130.

3.7 Workmanship. The finished dispensers shall be complete and clean, and free of fabrication marks, scratches, dents, breaks, sharp edges, sharp corners, deformities, burrs, slivers, or visible evidence of rust.

3.7.1 Rivets. Rivets, when used, shall be tight and the rivet heads and peened ends shall be round and concentric and shall be in full contact with the joined metal surfaces. There shall be no empty rivet holes.

3.7.2 Welds. Welds shall be clean, continuous, sound, free of flux, pits, buildups, undercuts, and shall be ground so as to blend with adjacent surfaces. Spot welds when used shall be sound and free of discoloration, splatter and burn throughs.

3.7.3 Threaded fasteners. Threaded fasteners shall be drawn tight. Lockwashers shall be used on all nuts and bolts. There shall be no crossed or stripped threads.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, standards, and drawings unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.2.3 End item inspection. The lot shall consist of all bread dispensers of one style offered for inspection at one time. The sample unit shall be a completely fabricated bread dispenser.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

4.2.3.1 Visual examination. The bread dispenser shall be examined for defects in table I. The inspection level shall be II with an AQL of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examine	Defect	Major	Minor
Standard product	Item not in accordance with manufacturers standard product except for changes necessary to comply with specification requirements	X	
Finish	Not as specified	X	
	Rough or sharp edges, burr(s) slivers, or scratches	X	
Construction and workmanship general	Component missing	X	
	Any burr, sliver, sharp edge, rough die, tool, gouge, trim or grind marks	X	
	Not fabricated of material specified	X	
	Component split, cracked, or showing delamination	X	
	Any component fractured, buckled, bent, dented, punctured or malformed	X	
	Any component misplaced or not in alignment	X	
Fastening devices	Missing, cracked or stripped	X	
	One bolt, nut, screw or washer missing		X
	Two or more bolts, nuts, screws or washer missing	X	
	Fastener loose		X
	Rivet holes not accurately punched	X	
	Rivet not peened properly		X
Welding	Not free from rust scale, paint, grease and other foreign matter	X	
	Scale and flux deposits not removed		X
	Weld not smooth and free of cracks, burnholes, undercuts or incomplete fusion	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defect	Major	Minor
Design and construction	Not completely enclosed	X	
	Supporting flange not furnished	X	
	Crumb tray not removable	X	
	Cover not hinged	X	
	Dispensing mechanism not self-leveling	X	
	Self-leveling mechanism not removable through top of dispensing tube	X	
Identification marking	Missing, incomplete, illegible		X

4.2.3.2 Dimensional examination. Examination shall be made of the end item to determine compliance with the dimensional requirements of this specification. Any dimension that is not within the specified requirements shall be classified a defect. The inspection level shall be S-2 with an AQL of 6.5 defects, expressed in terms of defects per hundred units.

4.2.3.3 End item testing. One bread dispenser of the lot shall be tested as specified in 4.4.1. Any nonconformance shall be cause for rejection of the lot.

4.2.4 Packaging inspection. An examination shall be made to determine whether the preservation-packaging, packing and marking complies with the section 5 requirements. Defects shall be listed in table II. The sample unit shall be one shipping container fully prepared for delivery, except that it need not be closed. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

TABLE II. Inspection of packaging

Examine	Defect
Marking (exterior and interior)	Omitted, incorrect, illegible, of improper size, location, sequence or method of application.
Materials	Any component missing, damaged or not as specified.
Workmanship	Contents of interior packages not immobilized as specified. Bulged or distorted containers.
Content	Number of packages per shipping container is more or less than required.

4.2.4.1 Inspection of interior boxes and shipping containers. When interior boxes and shipping containers are required to comply with PPP-B-601, PPP-B-621 or PPP-B-636, inspection for defects in the closure and strapping (when applicable) shall be in accordance with appendix of the applicable box specification.

4.3 Certificate examination. Certificates of compliance, certified test reports, approval labels or listing marks for codes and standards, as applicable that are submitted as proof of compliance with the specification requirements shall be examined and validated.

4.4 Test method.

4.4.1 Operational test. Each dispensing tube of the bread dispenser shall be fully loaded with 1-1/2 loaves of sliced pullman bread. The dispensing mechanisms shall then be adjusted without removing from the dispensing tube to expose three bread slices at the dispensing level. Two bread slices shall be removed at a time until the full load of each dispensing tube is dispensed while observing to determine compliance with 3.4. Any nonconformance shall constitute failure of this test.

5. PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A. Each dispenser shall be preserved-packaged in accordance with method III of MIL-P-116. The dispensers shall be packaged in a snug-fitting fiberboard box conforming to style RSC, grade V3c of PPP-B-636. The contents of each box shall be cushioned, blocked and braced within the box to prevent movement while in transit. Each box shall be securely closed in accordance with method IV as specified in the appendix of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

5.1.2 Level C. Each dispenser shall be preserved-packaged to afford adequate protection against physical damage during shipment from the contractor to the first receiving activity. The package shall be the same as that normally used by the contractor for retail distribution.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Level A packing. Six style 2, four style 3 or three style 4 dispensers, preserved-packaged as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to overseas type, style A or B, grade A or B, type 2 load of PPP-B-601 or class 2, style 2 or 4, grade A or B, type 2 load of PPP-B-621. Each shipping container shall be closed and strapped in accordance with the appendix of the applicable container specification.

5.2.2 Level B packing. Six style 2, four style 3 or three style 4 dispensers, preserved-packaged as specified in 5.1, shall be packed as specified in 5.2.1 except the PPP-B-601 container shall be domestic type and the PPP-B-621 container shall be class 1.

5.2.3 Level C packing. Dispensers, preserved-packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that normally used by the contractor for retail distribution. Containers shall comply with the Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The dispensers covered by this specification are intended for use in the dispensing of sliced bread in serving lines.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Style required (see 1.2).
(c) Selection of applicable levels of preservation-packaging and packing (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

6.2.1 Contract data requirements. Any data items to be delivered under any contract for items covered by this specification should be specifically called for in the contract in accordance with the applicable regulations of the procuring activity.

6.3 Supersession data. This specification includes the requirements of the type V, design E, styles 2, 3 and 4 of MIL-D-0040631E(GL).

Custodians:

Army - GL
Navy - YD

User activity:

Navy - SA

Preparing activity:

Army - GL

Project No. 7320-0623

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-D-43969 - Dispensers, Bread, Self-Leveling, Drop-In

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

FORM 1426
1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK RESEARCH and DEVELOPMENT COMMAND
NATICK, MASSACHUSETTS 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
DRXNM-TD G

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD-314

U.S. MAIL

Commander
US Army Natick Research and Development Command
ATTN: DRXNM-TD G
Natick, MA 01760

NATICK OP 1 JUL 77
FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:14Z
Check the source to verify that this is the current version before use.