MIL-F-43997A(GL)
30 September 1986
SUPERSEDING
MIL-F-43997(GL)
19 June 1979

MILITARY SPECIFICATION

FIELD PACK, TRAINING

This specification is approved for use by the Natick Research, Development and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers one type and size training field pack.

2. APPLICABLE DOCUMENTS

2.1 Government documents

2.1.1 Government documents The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

L-P-378	-	Plastic Sheet and Strip, Tin Gauge, Polyolefin
V-T-285	-	Thread, Polyester
UU-P-121	-	Paper, Bond and Writing; White and Colored
A-A-203	-	Paper, Kraft, Untreated
DDD-L-20	-	Label: For Clothing, Equipage, and Tentage (General Use)
PPP-B-636	-	Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to : U.S. Army Natick Research, Development and Engineering Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of the document or by letter.

AMSC N/A FSC 8465

DISTRIBUTION STATEMENT A. Approved for public release; distribution unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:19Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-B-543	-	Buckles, Tongueless and Web Strap
MIL-R-3390	-	Rings, Dee
MIL-W-4088	-	Webbing, Textile, Woven Nylon
MIL-T-5038	-	Tape, Textile and Webbing, Textile, Reinforcing, Nylon
MIL-C-7219	-	Cloth, Duck, Nylon
MIL-H-9890	-	Hardware, Individual Load Carrying Equipment: and Hardware, Miscellaneous
MIL-E-20652/1-		Eyelets, Metallic, Rolled Flange Type; and Eyelet Washer
MIL-F-21840	-	Fastener Tapes, Hook and Pile, Synthetic
MIL-W-27265	-	Webbing, Textile, Woven Nylon Impregnated
MIL-L-35078L	-	Loads, Unit, Preparation of Semiperishable Subsistance Items; Clothing, Personal Equipment and Equipage; General Specification For
MIL-W-43668	-	Webbing, Textile, Bulked Nylon
MIL-C-43906	-	Cloth, Coated, Nylon, Polyurethane Double Coated

STANDARDS

FEDERAL

FED-STD-751	-	Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Loads
MIL-STD-731	-	Quality of Wood Members for Containers and Pallets.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

2-3-265	-	Field Pack, Training Assembly
2-3-266	-	Field Pack, Training Details "A"
2-3-267	-	Field Pack, Training Details "B"
2-3-268	-	Field Pack, Training Sections

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:19Z
Check the source to verify that this is the current version before use.

documents which are DOD adopted shall be those listed in the issues of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Guide samples. Samples when furnished are solely for guidance and information (see 6.3). Variations from the document may appear in the samples, in which case the document shall govern.

3.1.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.5).

3.2 Materials (see 6.6).

3.2.1 Cloth, duck, nylon. The nylon duck cloth shall be dyed Olive Green 106 and shall conform to type III, class 3 of MIL-C-7219, except the requirement for water resistance after dry cleaning shall not apply. The dimensional stability shrinkage requirement shall be 3.5 maximum and the air permeability requirement shall be 4.0 maximum.

3.2.2 Cloth, coated, nylon, polyurethane double coated. The coated cloth for the throat shall conform to type 1 of MIL-C-43906.

3.2.3 Webbing, nylon.

3.2.3.1 Webbing, 2-1/4 inch width. The 2-1/4 inch webbing shall be dyed Olive Drab 7 and shall conform to type VIIIc of MIL-W-4088.

3.2.3.1.1 Treatment. The type VIIIc webbing shall be resin impregnated conforming to class R treatment of MIL-W-27265.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:19Z
Check the source to verify that this is the current version before use.

3.2.3.2 Webbing, 1 inch width. The 1 inch nylon webbing shall be dyed Olive Drab 7 and shall conform to type III of MIL-W-43668.

3.2.3.3 Webbing, 3/4 inch width. The 3/4 inch nylon webbing shall be dyed Olive Drab 7 and shall conform to type IV of MIL-W-43668 or type Ia of MIL-W-4080.

3.2.4 Tape, nylon. The nylon tape shall be dyed Olive Drab 7 and shall conform to type III, 1 inch width of MIL-T-5038.

3.2.5 Thread, polyester. The polyester thread shall conform to type I, class 1, sub-class B of V-T-285. Sizes shall be as follows:

For all stitching except overedging, bartacking, and binding	Size F
For overedging, bartacking, and binding	Size E

3.2.5.1 Color. The thread shall be dyed Olive Drab S-1 (C.A. 66022) and shall show good fastness to weathering.

3.2.6 Film, polyethylene, unsupported, flexible. The film shall conform to the requirements for 0.0060 inch thick film; type I; class 1; grade A, B, or C; finish 1 of L-P-378 except that the film thickness shall be 0.020 inch. The water vapor transmission, impact resistance, slip, and heat seal strength tests are not required.

3.2.7 Keeper with slide. The keeper with slide shall conform to type X of MIL-H-9890.

3.2.8 Buckle, non-slip. The buckle shall conform to type V, class 3, 1 inch of MIL-B-543.

3.2.9 Eyelet, aluminum. The aluminum eyelet shall conform to dash number ABE131 of MIL-E-20652/1.

3.2.10 Fastener tape, hook and pile, nylon. The nylon tape fasteners shall be 1 inch wide, OG 106 conforming to type II, class 1 of MIL-F-21840.

3.2.11 Dee rings. The dee rings shall conform to class 1, configuration A, 25/32 inch by 3/8 inch of MIL-R-3390.

3.3 Construction. The construction shall conform in all respects to the drawings listed in 2.1 and as specified herein.

3.3.1 Stitches, seams and stitching. All seams and stitchings, except bartacking, shall conform to FED-STD-751 as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:19Z
Check the source to verify that this is the current version before use.

For all stitching except overedge stitching and binding.	Stitch type 301 or 401, 8 to 10 stitches per inch.
For stitching the binding.	Stitch type 301, 8 to 10 stitches per inch.
For overedge stitching, (single operation optional) 3/16 to 1/4 inch gage.	Stitch type 503 or 504, 8 to 10 stitches per inch.

For closing seams and overedge stitching (simultaneous operation optional), type 301 or 401 in combination with 503, 504, or 602, with 8 to 10 stitches per inch may be used. All edges of closing seams on the nylon duck including the dart in the flap shall be overedged stitched together.

3.3.1.1 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched 1/2 inch minimum except when caught in other stitching or turned under in a hem. Thread tensions shall be maintained so that there will be no loose stitching resulting in puckering of the materials sewn. The lock shall be embedded in the materials sewn.

3.3.1.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 1 inch back of the end of the stitching. 1/

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area (1/2 inch on box, box-x and W-W stitching) and continue a minimum of 1 inch beyond the defective area on to the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

3.3.1.2 Types 401 stitching. Thread tension shall be maintained so that there will be no loose stitching. Both ends of all seams or stitching produced with 401 stitch type, when not turned under in a hem or held down by other stitching, shall have a 1/2 to 3/4 inch chain extending beyond each end. The looper (underthread) shall be hidden between the cover and lining assembly. All repairs shall be in accordance with 3.4.1.1.1a and 3.4.1.1.1b. Repairs may be made using 301 stitch type.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:19Z
Check the source to verify that this is the current version before use.

3.3.1.3 Types 503, 504, and 602 stitching. Thread tension shall be maintained so that there will be no loose stitching. All repairs shall be in accordance with 3.4.1.1.1a and 3.4.1.1.1b, except substitute 3/4 inch for 1 inch wherever 1 inch appears.

NOTE: The above should be included in all documents which require the use of 401 stitching in the table of manufacturing operations or on drawings.

3.3.1.4 Bartacking. Unless otherwise specified, bartacks shall be 3/4 ± 1/16 inch in length, and 1/8 ± 1/32 inch wide, and shall contain 42 stitches. Bartacking shall be free from thread breaks and loose stitching.

3.3.1.5 Automatic stitching. Automatic machines may be used to perform any of the stitch patterns provided the requirements of stitch pattern, stitches per inch, and size and type of thread are met; and at least three or more tying, over-lapping, or back stitches are used to secure the ends of the stitching.

3.3.1.6 Thread ends. All thread ends that are visible on the finished item shall be trimmed to 1/4 inch maximum length.

3.3.1.7 Lubrication of thread. There shall be no lubrication of the thread by any means, prior to or during sewing (see 4.4.1.1).

3.3.2 Setting of eyelets. A holes shall be prepunched before inserting the eyelets. The hole shall be smaller than the outside diameter of the eyelet barrel so that the barrel must be forced through the hole. The eyelet shall be securely clinched without splitting in a manner that will prevent detachment from or cutting of the adjacent material. Unless otherwise specified, the washer may be on either side of components on which installed.

3.3.2.1 Eyelets, aluminum. The aluminum eyelets specified in 3.2.9 shall be installed using score setting dies conforming to J. C. Rhodes part number 1-KW-1KL and 101Y-Klom, or Stimpson Co. Part Number A 2744-7 or equal (see 6.4). The eyelet shall be securely set in a manner that will prevent detachment from or cutting of, the surrounding material. The clinched portion of the eyelet shall be on the inside of the assembly. Prior to use of the "or equal" item, the contractor shall submit the item to the contracting officer with supporting data for approval.

3.3.3 Fusing of ends of nylon cord, webbing and tape. All ends of nylon cord, webbing and tape shall be fused. The apparatus used to fuse the cord, webbing and tape ends shall be capable of providing sufficient heat to provide a smooth edge and with the cut ends of the cord, webbing and tape yarns all fused together. Fusing of the cord, webbing and tape ends shall be accomplished prior to being assembled for stitching.

3.3.4 Location marks. Location marks shall not be drilled. Printed markings shall not be more than 1/32 inch in width.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:19Z
Check the source to verify that this is the current version before use.

3.3.5 Finishing of throat. One pleat, up to 1/2 inch wide, will be allowed for "take-up" of excess material when attaching the throat.

3.3.6 Instruction sheet. A paper instruction sheet, to be furnished by the contractor, shall be placed in each field pack (see 5.1.1). The paper sheet shall be approximately 8 by 14 inches and shall conform to type IV of UU-P-121. The information on the instruction sheet shall be printed in black characters 1/16 inch minimum height and shall be as follows:

ASSEMBLY INSTRUCTIONS FOR

INDIVIDUAL LIGHTWEIGHT LOAD-CARRYING EQUIPMENT

(Pack on Belt)

1. Adjust Individual Equipment Belt. Adjust belt around waist, loose enough that it does not constrict the clothing, by engaging hooks at each end in center row of eyelets. Move a keeper next to each hook to prevent unfastening and move other keeper against buckle component at each end to keep in position.

2. Attach Field Pack to Belt. Lay belt out flat, inside up, on back of Field Pack, with male belt fastener to your right. Attach Field Pack by attaching clips so that the center of belt matches center of pack. Make sure that tip of sliding bar engages hole in bottom of clip in all instances.

3. Attach Suspenders to Field Pack and Belt. Attach back suspender straps to pack by engaging hooks on straps onto "D" rings of pack's two web tabs. Attach front suspender straps to belt by engaging hook of left strap into eyelet on left side of belt nearest buckle, and hook of right strap into eyelet on right side of belt nearest buckle. Be sure that closure of snap hooks are shut.

4. Adjust Front and Back Suspender Straps. Put on assembled equipment and adjust front suspender straps so belt is properly located at waist. Remove equipment and adjust length of each back suspender strap so belt hangs evenly in front and back.

5. Attach Intrenching Tool Carrier to Belt. Attach on left side close to pack, by means of two attaching clips on back of intrenching tool carrier.

6. Attach Canteen Cover to Belt. Attach on right side close to pack, by means of two attaching clips on back of canteen cover.

7. Attach Small Arms Ammunition Cases to Belt. Attach one on left side next to intrenching tool carrier and one on right side next to canteen cover, by means of two attaching clips on back of each case. Attach supporting strap of each case to the metal "D" ring on each suspender strap. Adjust length of each supporting strap so it has same amount of strain as suspender strap next to it.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:19Z
Check the source to verify that this is the current version before use.

8. Attach First Aid Packet or Lensatic Compass Case. Attach to belt on right side next to ammunition case if space is available. If not, attach to left side of right ammunition case.

9. Attach Hand Grenades to Small Arms Ammunition Cases. Attach hand grenade to side of ammunition case at rearmost position so that grenade is well protected. Grenades should be carried in the front position only when carrying more than two grenades has been authorized. Slide handle of grenade into loop formed at end of webbing, securing the attaching clips to case. Place web securing strap around top of grenade and fasten snap fastener.

3.3.7 Marking. The identification marking shall be applied in the location shown on Drawing 2-3-267 and shall conform to type IV, class 5 of DDD-L-20. The letters "US" shall be applied in the size characters and in the location indicated on Drawing 2-3-267 and shall conform to type IV, class 9 of DDD-L-20. Fastness of class 9 marking shall be as specified for class 5 marking.

3.3.8 Repairs. Except as otherwise specified herein, repairs such as mends, darns or patches are not allowed to be made to the field pack.

3.3.9 Replacement of defective components. During the spreading, cutting and manufacturing process, components having material defects or damages that are classified as defects in 4.4.3 shall be removed from production and replaced with non-defective and properly matched components.

3.4 Workmanship. The field pack shall conform to the quality of product established by this document and the occurrence of defects shall not exceed the applicable acceptable quality levels (AQLs).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirement in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:19Z
Check the source to verify that this is the current version before use.

material, either indicted or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.1.3 Certificate of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1.1), it shall be examined for the defects specified in 4.4.3 and 4.4.4. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.1.1 Certification. The contractor shall furnish a certificate of compliance for the requirement specified in 3.3.1.6.

4.4.2 In-process inspection. Inspection of sub-assemblies shall be made to ascertain that construction details which cannot be examined in the finished product are in accordance with specified requirements. The Government reserves the right to exclude from consideration for acceptance, any material or service for which in-process inspection has indicted nonconformance.

4.4.3 End item visual examination. The end item shall be examined for the defects listed in table I. The lot size shall be expressed in units of field packs. The sample unit shall be one completely fabricated field pack. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0 for major defects and 15.0 for total (major and minor combined) defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:19Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Cloth, nylon	Any hole, cut, tear, or smash	X	
	Any abrasion mark, open place, broken or missing yarn, or multiple floats, clearly visible at normal inspection distance (approximately 3 feet)		X
Cloth, coated nylon	Coating defects, such as abrasions, blisters, cuts, holes, or uncoated areas	X	
Webbing or tape	Any hole, cut, tear, or frayed edge	X	
	Edges scalloped, not firmly and tightly woven		X
	Cut ends of webbing not fused as specified		X
Fastener tape, hook and pile	Any cut, or tear	X	
	Hooks flattened affecting closure	X	
Hardware	Broken or malformed, failing to serve intended purpose; corroded area, burr or sharp edge	X	
	Finish omitted or not as specified:		
	- on brass or aluminum components		X
	- on steel components	X	
	Area of partial or no finish		X
	Any required component improperly installed causing failure to serve intended purpose	X	
	Not assembled as specified	X	
	Size or type not as specified	X	
Eyelets, aluminum	Insecurely clinched	X	
	Clinched excessively tight cutting fabric	X	
	Not installed with a scored setting	X	
	Clinched portion on outside of pack		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:19Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (contd')

Examine	Defect	Classification Major	Classification Minor
Open seam	1/2 inch or less		X
	More than 1/2 inch	X	
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken, or when two or more consecutive skipped or run-off stitches occur. On double stitched seams, a seam shall be considered open when either one or both sides of the seam are open.		
Raw edge (or edge required to be finished)	More than 1/2 inch when securely caught in stitching		X
	NOTE: Raw edge not securely caught in stitching shall be classified as an open seam.		
Run-off (see open seam)			
Seam and stitch type	Wrong seam or stitch type	X	
Stitch tension	Loose, resulting in loose top or bobbin thread		X
	Excessively tight, resulting in puckering of material		X
Stitches per inch	One stitch less than minimum specified		X
	Two or more stitches less than minimum specified	X	
	One or more stitches in excess of maximum specified		X
	NOTE: Variation in the number of stitches per inch caused by the operator speeding up the machine and pulling the material in order to sew over heavy seams or in turning corners, shall be classified as follows: (a) Within the minor defect classification no defect (b) Within the major defect classification minor defect		

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:19Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Bartacks	Any omitted	X	
	Stitching loose, incomplete or broken	X	
Stitching ends (not held down by other stitching or turned under in an hem)	Not secured as specified		X
Thread breaks, skipped stitches or runoffs	Not overstitched as specified		X
NOTE:	Thread breaks or two or more consecutive skipped or run-off stitches not overstitched shall be classified as open seam.		
Row of stitching	Any row missing except on box-x and W-W stitching	X	
	On box-x and W-W stitching:		
	- one row omitted		X
	- two or more rows omitted	X	
Components and assembly	Any component or required operation omitted (unless otherwise classified herein)	X	
	Any component misplaced or not assembled as specified (unless classified herein)	X	
	Mend, darn or patch	X	
	Needle chew	X	
	Ends of securing straps not cut on a bias		X
	Any unauthorized repair	X	
Binding	Loosely applied but not exposing raw edge of material		X
	Loosely applied exposing raw edge of material	X	
Throat	Hemming of throat not as specified		X
	Pleat (when required for excess material)		
	- More than 1/2 inch wide		X
	- more than one pleat		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:19Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Cleanness	Grease or oil stains clearly noticeable; thread ends not trimmed to 1/4 inch maximum length		X
Location marking	Drilled		X
	Inked marking more than 1/32 inch wide		X
Markings: "US" and identification	Omitted, incorrect, illegible, or misplaced		X
Instruction sheet	Omitted, illegible or incorrect		X

4.4.4 End item dimensional examination. The end item shall be examined for conformance to the overall width, depth and height dimensions specified on Drawing 2-3-265. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of field packs. The sample unit shall be one complete field pack. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

4.4.5 Packaging inspection. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Inadequate application of components, such as: incomplete closure of container flap, loose strapping or inadequate stapling.
	Bulged or distorted container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:19Z
Check the source to verify that this is the current version before use.

Examine	Defect
Content	Number of bundles per shipping container is more or less than required. Number of intermediate containers is more or less than specified. Number of packs per intermediate container is more or less than specified. 1/

1/ For this defect one intermediate container shall be examined.

4.4.6 Palletization examination. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the inspection lot. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. Each field pack, with the instruction sheet (see 3.3.6) placed inside, shall be laid out flat with keepers closed, waterproof throat in place, gussets tucked inside, and the flap folded over in a closed position. The securing straps shall be placed under the flap. Five packs shall be neatly stacked one on top of another, alternately reversed handle to bottom, with flaps facing downward. The top pack shall be inverted so that the flap faces upward. The stacked packs shall be securely cross-tied with cotton tape or twine to form a bundle.

5.1.2 Commercial. The field packs shall be preserved in accordance with ASTM D 3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:19Z
Check the source to verify that this is the current version before use.

Defect Class is usually about four percent. For

5.2 Packing. Packing shall be level A, B or Commercial as specified (See 6.2).

5.2.1 Level A packing. Forty field packs, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Field packs, preserved as specified in 5.1.1, shall be packed flat, two in length, one in width and four in depth within a shipping container. Inside dimensions of each shipping container shall approximate 24-1/2 inches in length, 14 inches in width, and 14 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to A-A-203. Each shipping container shall be closed in accordance with method III, water-proofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads."

5.2.2 Level B packing. Forty field packs, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to class domestic, variety DW, grade 275 of PPP-B-636. Field packs, preserved as specified in 5.1.1, shall be packed flat, two in length, one in width and four in depth within a shipping container. Inside dimensions of each shipping container shall approximate 24-3/4 inches in length, 14 inches in width, and 14 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to A-A-203. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except the inspection shall be in accordance with 4.4.5.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

5.2.3 Commercial packing. Field packs, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2) (Field Packs Training), packed as specified in 5.2.2 and 5.2.3, shall be palletized in accordance with load type Ia of MIL-STD-147. Pallet type shall be type 1 (4-way entry), type IV or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:19Z
Check the source to verify that this is the current version before use.

groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be number 3 in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course.

5.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The field pack is to be carried on the soldier's back, secured by suspenders and belt. It is designed to carry essential items, such as food, toilet articles, etc., as a part of the training load.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1.1, 4.3, and 6.5).
d. Selection of the applicable level of preservation and packing (see 5.1 and 5.2).
e. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
f. When palletization is required (see 5.3).
g. Types and class of unit load required (see 5.2.1).

6.3 Samples. For access to samples, address the contracting activity issuing the invitation for bids.

6.4 Source of supply. Source of supply for the score setting eyelet die are, J.C. Rhodes and Company, Box B-962, New Bedford, MA 02745 or Stimpson Co., Inc., Bayport, NY 11075.

6.5 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

6.6 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.2).

6.7 Subject term (key word) listing.

Field pack
Training

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:19Z
Check the source to verify that this is the current version before use.

6.8 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:

Army - GL

Review activities:

Army - MD
DLA - CT

Preparing activity:

Army - GL

Project No. 8465-A917

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:19Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US ARMY NATICK RESEARCH
and DEVELOPMENT CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research
and Development Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:19Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-F-43997A(GL)	Field PAck, Training

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 20 Nov 84

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:19Z
Check the source to verify that this is the current version before use.