MILITARY SPECIFICATION SHEET

ELECTRON TUBE, POWER

TYPE 577W

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

DESCRIPTION: Diode, half-wave rectifier, high-vacuum

See figure 1

Mounting position: Any

Weight: 5-ounces (141.8 grams) nominal

ABOSLUTE RATINGS:

Parameter:	Ef	epx	Ib	Ib
Unit:	Vac	kv	a	mAdc
Maximum:	5.25	25.0	1.5	300
Minimum:	4.75	---	---	---
TEST CONDITIONS:	5.0	25.0	---	---

GENERAL:

Qualification - Required

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:23Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	NOTES	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS		UNIT
							MIN	MAX	
	Quality conformance inspection, part 1								
1301	Filament current	-		0.65	II	If	9.5	11.0	Aac
1231	Peak emission	-	eb = 3,000 v(max)	0.65	II	is	3.0	---	a
1353	Operation of rectifiers	-	t = 300 seconds (min); ib = 1.5a; Ib = 300 mAdc	0.65	II	---	---	---	---
	Quality conformance inspection, part 2								
1031	Low-frequency vibration	-	No voltages applied; t = 120 seconds	---	---	---	---	---	---
1041	Shock	-	Hammer angle = 25°	---	---	---	---	---	---
---	Shock end point:								
1353	Operation of rectifiers	-		---	---	---	---	---	---
1256	Electrode current (anode)	-	Eb = 250 Vdc; t = 30 seconds	---	---	Ib	500	---	mAdc
	Quality conformance inspection, part 3								
---	Life test	-	Group C; Operation of rectifiers; t = 750 hours	---	---	---	---	---	---
---	Life-test end points:								
1231	Peak emission	-		---	---	is	2.5	---	a
---	Failure to rectify	-		---	---	---	---	---	
1031	Variable-frequency vibration	1	No voltages applied	---	---	---	---	---	---

NOTE:

Ⓒ 1. This test shall be performed during the initial production and once each succeeding 12-calendar months in which there is production. A regular double sampling plan shall be used, with the first sample of three tubes with an acceptance number of zero, and a second sample of three tubes with a combined acceptance number of two. In the event of failure, the test will be made as a part of quality conformance inspection (QCI), part 2, code level D, with an AQL of 6.5. The regular "12-calendar month" double sampling plan shall be reinstated after three consecutive samples have been accepted.

Custodians:
Army - EL
Navy - EC
Air Force - 85

Review activities:
Air Force -17, 80
DSA - ES


User activities:
Army - MU
Navy - AS, OS, MC, CG, SH
Air Force - 11

Preparing activity:
Navy - EC

Agent:
DSA - ES

(Project 5960-2955)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:23Z
Check the source to verify that this is the current version before use.



Ltr	Dimensions in inches with metric equivalents (mm) in parentheses	
	Minimum	Maximum
Quality conformance inspection, part 2		
A	7.00 (177.80)	7.50 (190.50)
B		2.062 (52.37)
D	.844 (21.44)	.906 (23.01)
(C) Quality conformance inspection, part 3 (see note)		
E	Base: A4-81	
G	.355 (9.02)	.365 (9.27)
Reference dimension		
F	.375 (9.53)	

PIN CONNECTIONS	
Pin No.	Element
1	nc
2	f
3	f
4	nc
cap	a

NOTE:
Dimensions shall be checked during the initial production and once each succeeding 12-calendar months in which there is production. A regular double sampling plan shall be used, with the first sample of three tubes with an acceptance number of zero, and a second sample of three tubes with a combined acceptance number of two. In the event of failure, the test will be made as a part of quality conformance inspection, part 2, code level D, with an AQL of 6.5. The regular "12-calendar month" double sampling plan shall be reinstated after three consecutive samples have been accepted.

FIGURE 1. Outline drawing of electron tube type 577W.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:23Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:23Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D. C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT
DOD 316

OFFICIAL BUSINESS

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:23Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

S/N-0102-014-1801 C-25254

Source: https://assist.dla.mil -- Downloaded: 202610-15T14:23Z
Check the source to verify that this is the current version before use.