INCH-POUND

MIL-PRF-1/1260H
19 July 1999
SUPERSEDING
MIL-E-1/1260G
11 November 1975

PERFORMANCE SPECIFICATION SHEET

ELECTRON TUBE, THYRATRON
TYPES 7190 AND 7191

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the electron tube described herein shall consist of this document and the latest issue of MIL-PRF-1.

DESCRIPTION: Triode, hydrogen.
See figures 1 and 2.
Mounting position: Any.
Weight: 0.5 ounce (14.2 grams) nominal.

ABSOLUTE RATINGS:

Parameter:	Ef	epy	epx	Ebb	Ecc	egx	egy	ib	Ip
Unit:	V	kv	kv	V dc	V dc	v	v	a	A ac
Maximum:	1/	1.2 2/	1.0 3/	---	---	200	400	20	1.0
Minimum:	---	---	---	300	---	---	175 4/	---	---
Test conditions:	6.3	1.2	---	---	0	---	130	---	---

ABSOLUTE RATINGS:

Parameter:	Ib	tj	tk	$\frac{dik}{dt}$	Pb	Ehk	prr	TA	Barometric pressure, reduced
Unit:	mA dc	ns	sec	$\frac{a}{\mu s}$	---	V	---	°C	mmHg
Maximum:	50	5 5/	---	400	0.1×10^{9}	+25	6/	+125	---
Minimum:	---	---	30	---	---	-100	---	-60	20
Test conditions:	---	---	30	---	---	---	5,000	---	---

See footnotes at end of table I.

GENERAL:

Qualification: Required.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:20Z
Check the source to verify that this is the current version before use.

TABLE I. Testing and inspection.

Inspection	Method	Notes	Conditions	Acceptance level	Inspection level or code	Symbol	Limits		Unit
							Min	Max	
Conformance inspection, part 1									
Direct current holdoff	---	9/	egy = 0; Rp = Rg = 1,000 ohms; tk = 30	0.65	II	Ebb	1,600	---	V dc
Grid short and continuity	---	10/	Ecc = +200 V dc; Rg/Ic = 5 mA dc (max); epy = 0	0.65	II	---	---	---	---
Short and discontinuity detection	1201	---		0.40	II	---	---	---	---
Heater current	3241	---		0.65	II	If	1.5	2.0	A
Instantaneous starting	3267	7/ 12/ 19/	epy = 1,000 v	0.65	II	---	---	---	---
DC anode voltage for conduction	3247	13/		0.65	II	Ebb	---	100	V dc
Operation (1)	3246	7/ 14/ 19/	epy = 1.4 kv (min); ib = 20a (min)	0.65	II	egy	---	130	v
Voltage drop	3204	7/ 15/	tp = 1.0 µs ± 10 percent; prr = 2,000	0.65	II	etd	---	90	v
Conformance inspection, part 2									
Sweep-frequency vibration (1)	1031	8/ 11/	t = 4 minutes; Ebb = 1,600 V; egy = 0; Rp = Rg = 1,000 ohms; Ehk = -100 V	---	---	---	---	---	---
Sweep-frequency vibration end points:	---								
Operation (1)	3246	---		---	---	egy	---	130	v
Time jitter	3261	---	epy = 500 v (max)	---	---	tj	---	4.0	ns
Shock	1041	---	Ef = 6.3 V; no voltages applied; 720 G at 1 ms	---	---	---	---	---	---
Shock end points:	---								
Operation (1)	3246	7/		---	---	egy	---	130	v
Time jitter	3261	7/	epy = 500 v (max)	---	---	tj	---	5.0	ns
Heater current	3241	---	Ef = 7.5 V	---	---	If	1.6	2.2	A

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:20Z
Check the source to verify that this is the current version before use.

TABLE I. Testing and inspection - Continued.

Inspection	Method	Notes	Conditions	Acceptance level	Inspection level or code	Symbol	Limits Min	Limits Max	Unit
Conformance inspection, part 2 - Continued									
Heater-cathode leakage	1336	---	Ehk = -100 V dc Ehk = +50 V dc	---	---	Ihk	---	100	µA dc
Anode delay time	3256	---	Operation (1); t = 120	---	---	tad	---	0.6	µs
Anode delay time drift	3256	16/	Anode delay time	---	---	Δtad	---	0.15	µs
Time jitter	3261	7/	epy = 500 v (max); egy = 175 v	---	---	tj	---	4.0	ns
Conformance inspection, part 3									
Life test	---	7/ 17/	Group C; epy = 1,200 v; egy = 140 v; ib = 20a; prr = adjust for Ip = 1.0 A ac; t = 500 hours	---	---	---	---	---	---
Group C, establishment of prerelease eligibility	---	---		---	---	---	---	---	---
Life-test end points:	---								
Operation (1)	3246	---		---	---	egy	---	140	v
Anode delay time drift	3256	---	egy = 140 v	---	---	Δtad	---	0.2	µs
Time jitter	3261	---	egy = 175 v	---	---	tj	---	5.0	ns
Voltage drop	3204	---		---	---	etd	---	130	v
Heater-cycling life	1506	18/	Ef = 7.0 V; Ehk = -100 V dc; Ec = Ebb = 0	---	10 tubes	---	---	---	---
Heater-cycling life-test end points:	---	---							
Heater-cathode leakage	1336	---	Ehk = +50 V dc Ehk = -100 V dc	---	---	Ihk	---	125	µA
Barometric pressure, reduced (type 7191)	1002	20/	Pressure = 20 ± 5 mmHg; Ebb = 1,400 V; egy = 0; Rp = Rg = 1,000 ohms; Ehk = -100 V	---	---	---	---	---	---
Sweep-frequency vibration (2)	1031	7/ 8/ 20/	t = 120 minutes in 3 planes; 40 min/plane	---	---	---	---	---	---
Vibration fatigue	1031	20/	No voltages applied	---	---	---	---	---	---
Operation at elevated ambient temperature	3246	7/ 20/	TA = +125°C; t = 300 (min)	---	---	egy	---	130	v

See footnotes at top of next page.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:20Z
Check the source to verify that this is the current version before use.

TABLE I. Testing and inspection - Continued.

1/ It is recommended that a heater voltage, as determined from figure 3, be utilized whenever Ip is less than 0.75 A ac. The heater voltage must be held within ± 5 percent of the values shown on figure 3.

2/ For cold-starting applications, where anode voltage is applied instantaneously, the power-supply filter design shall be such that the maximum permissible epy is 1,000 v and cannot be attained in less than 0.04 second. It is recommended that the driver pulse be applied prior to the application of anode voltage.

3/ In pulsed operation, the peak inverse voltage shall not exceed 500 v during the first 25 µs after the pulse.

4/ The value shown is valid only for the following pulse shape: Time of rise = 0.5 µs maximum, grid pulse duration = 2.0 µs minimum. Impedance of drive circuit = 1,000-ohms maximum.

5/ The rated time jitter of 5 ns is applicable only at peak forward anode voltages in excess of 500 v epy, and with a driver pulse in excess of 250 v egy. At values of epy less than 500 v or egy less than 250 v, the time jitter maximum is 10 ns.

6/ Under reduced ratings, operating frequencies up to 50 kHz are feasible.

7/ The circuit constants shall be chosen so that at epy = 1.2 kv under resonant charging conditions: dik/dt = 400a/µs minimum, ib = 20a, tp = 0.50 µs ± 10 percent, prr = 5,000 and Rg1 = 10,000 to 30,000 ohms. The grid pulse characteristics shall be tp = 2.0 µs maximum, tr = 0.5 µs, and driver impedance = 1,000 ohms minimum.

8/ Heater-cathode shorts for 100,000 ohms or less, having a duration of 100 µs or more, are cause for rejection.

9/ Inability to hold off dc anode voltage, when tapped with a cork hammer using 3-inch strokes constitutes a failure.

10/ Monitor grid-cathode voltage to indicate short or open when tube is tapped with a cork hammer using 3-inch strokes. Indication of short or open is cause for rejection.

11/ Failure to hold off dc anode voltage during the vibration period shall constitute a failure.

12/ The tube shall operate satisfactorily on pushbutton starting within three attempts when anode voltage is applied in such a manner as to rise from 0 to 1,000 v within 0.03 second (the filter design shall be such that at least 500 v is reached within 0.015 second). Any tube failing to start within three attempts shall be considered a failure.

13/ No voltages shall be applied to the grid or anode of the tube under test for at least 10 minutes prior to performing this test.

14/ The tube shall operate continuously for 5 minutes without evidence of continuous conduction, anode heating, or loss of control.

15/ Using a calibrated oscilloscope, adjust epy for a peak cathode current of 20 amperes. Measure the voltage drop between anode and cathode from the zero reference line to the center of the tube drop porch (see figure 4).

16/ During the interval between 2 minutes and 7 minutes of the tad test, the anode delay time drift relative to the tad value observed on the anode delay time test, shall not exceed the value specified herein.


17/ Life test shall be operated with the tube in a horizontal position. Operation shall consist of 12 minutes of operation (heater, trigger, and anode voltage) and 12 minutes off. The application of anode voltage may be delayed a maximum of 60 seconds after the application of heater voltage. Only anode operating time shall be considered test time. The average life of the sample shall be not less than 90 percent of the duration of the test.

18/ No defects are allowed.

19/ This test is to be the first test performed at the conclusion of the holding period.

20/ This test shall be performed during the initial production and once each succeeding 12-calendar months in which there is production. A regular double sampling plan shall be used, with the first sample of three tubes with an acceptance number of zero, and a second sample of three tubes with a combined acceptance number of one. In the event of failure, the test will be made as a part of conformance inspection, part 2, code level D, with an acceptance level of 6.5. The regular "12-calendar month" double sampling plan shall be reinstated after three consecutive samples have been accepted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:20Z
Check the source to verify that this is the current version before use.



Pin connections	
1	Grid
2	Cathode
3	Heater
4	Heater
5	Cathode
6	Anode
7	Cathode


Ltr	Dimensions			
	Inches		Millimeters	
	Min	Max	Min	Max
Conformance inspection, part 2				
A	.804	.844	20.42	21.44
C	---	2.125	---	53.98
E	---	1.875	---	47.63
Conformance inspection, part 3 (see note 4)				
K	Base: E7-1			

NOTES:

1. Anode terminal material shall be nickel.
2. Pins must be gold plated, if made of tungsten.
3. This dimension lies in a plane passing through the centerline of the tube and pin 6.
4. Dimensions shall be checked during the initial production and once each succeeding 12-calendar months in which there in production. A regular double sampling plan shall be used, with the first sample of three tubes with an acceptance number of zero, and a second sample of three tubes with a combined acceptance number of one. In the event of failure, the test will be made as a part of conformance inspection, part 2, code level D, with an acceptance level of 6.5. the regular "12-calendar months" double sampling plan shall be reinstated after three consecutive samples have been accepted.

FIGURE 1. Outline drawing of electron tube type 7190.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:20Z
Check the source to verify that this is the current version before use.



Pin connections	
1	Grid
2	Cathode
3	Heater
4	Heater
5	Cathode
6	No connection (do not use No. 6 pin socket terminal as tie point)
7	Cathode

Ltr	Dimensions			
	Inches		Millimeters	
	Min	Max	Min	Max
Conformance inspection, part 2				
A	.804	.844	20.42	21.44
C	---	2.478	---	62.94
D	---	2.228	---	56.54
Conformance inspection, part 3 (see note 4)				
B	.115	.135	2.92	3.43
E	---	1.593	---	40.46
F	.090	.110	2.29	2.79
G	.087	.101	2.21	2.57
H	.037	.047	0.94	1.19
J	.070	.090	1.78	2.29
K	Base: E7-1			
M	.075	.175	1.91	4.45
N	.210	.230	5.33	.5.84

NOTES:
1. Anode terminal material shall be nickel.
2. Pins must be gold plated, if made of tungsten.
3. This dimension lies in a plane passing through the centerline of the tube and pin 6.
4. Dimensions shall be checked during the initial production and once each succeeding 2-calendar months in which there in production. A regular double sampling plan shall be used, with the first sample of three tubes with an acceptance number of zero, and a second sample of three tubes with a combined acceptance number of one. In the event of failure, the test will be made as a part of conformance inspection, part 2, code level D, with an acceptance level of 6.5. The regular "12-calendar months" double sampling plan shall be reinstated after three consecutive samples have been accepted.

FIGURE 2. Outline drawing of electron tube type 7191.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:20Z
Check the source to verify that this is the current version before use.




FIGURE 3. Recommended cathode heater voltage, electron tube types 7190 and 7191.




FIGURE 4. Tube drop porch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:20Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AR
Navy - AS, CG, MC, OS, SH
Air Force - 99

Preparing activity:
DLA - CC

(Project 5960-3539)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:20Z
Check the source to verify that this is the current version before use.