[INCH-POUND]
A-A-59492
19 AUGUST 1999
SUPERSEDING
MIL-T-40632B
7 AUGUST 1994

COMMERCIAL ITEM DESCRIPTION
FOR TRUCK, FORKLIFT, DIESEL ENGINE DRIVEN, 120 INCH LIFT HEIGHT, DS SAFETY RATED, PNEUMATIC RUBBER TIRES, ROUGH TERRAIN, FOR SHIPBOARD USE

The General Services Administration has authorized the use of this Commercial Item Description as a replacement for MIL-T-40632 which is canceled for all federal agencies.

1. SCOPE.

1.1 This commercial item description (CID) covers the requirements for pneumatic-tired, diesel engine driven, "DS" safety rated, rough terrain forklift trucks for use on board marine (shipboard) vessels.

1.2 Intended Use. Each type of truck described herein is intended to be used aboard marine vessels for the purpose of stacking, unstacking, and transporting palletized loads, some of which may consist of ordnance.

2. CLASSIFICATION.

The trucks shall be of the following classifications:

TYPE I: 6,000 pound capacity at 24 inch load center.
TYPE II: 10,000 pound capacity at 24 inch load center.

3. SALIENT CHARACTERISTICS.

3.1 Configuration. In addition to the other requirements stated in this CID, each truck must meet the characteristics listed in Table 1.

Beneficial comments (recommendations, additions, deletions) and any other pertinent data which may be of use in improving this document should be addressed to: Department of the Navy, Naval Inventory Control Point, Code 1041, 5450 Carlisle Pike, P.O. Box 2020 , Mechanicsburg, PA 17055-0788.

AMSC N/A FSC 3930

DISTRIBUTION STATEMENT A. Approved for public release; distribution unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

Table 1.

CHARACTERISTIC	TYPE I	TYPE II
Lifting Capacity	6,000	10,000
Load Center	24"	24"
Lift Height	120"	120"
Length with forks Maximum	268"	268"
Width Max.	90"	90"
Height without ROPS/FOPS Max.	96"	96"
Underclearance Min.	14"	14"
Weight Max.	26,000 #	30,000 #
Fork length Max.	48"	48"
Fork width Max.	6"	6"
Fork thickness Max.	2"	2"
Max. truck speed with rated load	10 mph	10 mph
Fork tilt Forward	30 degrees	30 degrees
Fork tilt rearward	25 degrees	25 degrees
Fork spacing	15" - 84"	15" - 84"

3.2. Design. The truck shall be pneumatic tired, diesel engine driven, DS safety rated, 4-wheel drive, rigid frame with 4-wheel and rear wheel steering, or articulated frame. The truck shall be designed to traverse shipboard ramps and to move cargo on weather and hangar decks onboard marine vessels. The truck shall be designed for the lifting capacity at the specified load center and to the specified full lift height without the use of outriggers or stabilizers. The lifting capacity for articulated frame steer shall be determined at full articulation of the frame. No adjustments or deration to the lifting capacity will be permitted for lift height, side shifters or any other factor specified herein. Truck shall be designed to permit selection

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

and operation of travel, lift, steering, tilt, and side shift separately, simultaneously or combinations thereof.

3.3 Safety. Trucks shall conform to the applicable requirements of UL 558 (Type DS), ANSI B56.6, and OSHA Standards in effect at the time of issue of the solicitation. The truck shall bear the UL stamp of approval for "DS" safety rated trucks.

3.4 Engine. The engine shall be diesel powered, capable of operating on the following fuels: Navy Distillate (F-76) conforming to MIL-F-16884, JP-5 (F-44) conforming to MIL-DTL-5624, and JP-8 (F-34) conforming to MIL-DTL-83133. The engine shall meet all U.S. Environmental Protection Agency regulations and U.S. Federal Laws in act at the time of manufacture.

3.5 Fan. The cooling system fan shall discharge air away from the operator. Provisions shall be made for the protection of the fan during fording operations. Such provisions may include a manual disconnect or a guard around the fan. Fan disconnect shall not affect coolant circulation within the engine. When fan disengagement is used for fording, it shall be manually controlled within reach of the seated operator. Means shall be furnished to notify the operator that the fan is disengaged.

3.6 Exhaust System. The engine exhaust system shall be designed to prevent entry of rain into the exhaust system and to prevent accumulation of water and condensed vapors. Exhaust gases shall be discharged vertically above the operator's compartment or at the rear or side rear of the truck within the plan outline of the truck. Exhaust gases shall not be discharged in a path that would interfere with the operator or by-standers.

3.7 Cold weather system aids. The truck shall be equipped with cold weather system aids to meet the environmental requirements specified herein. Fluid priming systems are not permitted.

3.8 Transmission. The truck shall be equipped with 4-wheel drive. The transmission shall allow for shifting under full engine power through all successive forward and reverse transmission gear ratios. The transmission shall be protected from damage when the operator moves or attempts to move the directional control lever to the opposite direction while the forklift is in motion.

3.9 Front and rear axles. Components of the front and rear axles shall be interchangeable with relation to the differentials, hub assemblies, bearings, and seals. Sway cylinders may be provided

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

on the front axle for the oscillation of the truck. One axle of the truck shall incorporate a differential action lock. With this lock, neither wheel of the axle shall spin out due to loss of traction. Differential locks shall not subject the axle or differential to damage when the truck is driven on improved surfaces.

3.10 Clutch disconnect/Inching. The transmission shall be provided with a clutch disconnect or inching control. The disconnect/inching control shall disengage the transmission and apply the service brakes while allowing the engine to be operated throughout the entire speed range. The disconnect/inching control shall permit full lifting, lowering and tilting specified herein with rated load without truck movement while the disconnect/inching control is engaged and the transmission is in either the forward or reverse positions.

3.11 Hydraulic System. The hydraulic system shall consist of all hydraulic components necessary for operation of the forklift and steering system but shall not include the brake system and power train components. The truck shall be equipped with a fail-safe hydraulic system. In the event of engine or hydraulic system failure or hydraulic fluid loss, a raised load of rated capacity shall not be lowered until the system is manually overridden by the operator. Pressure hose and return lines conforming to SAE J517 100R7 and 100R8 are not acceptable. All hydraulic hoses shall be routed and secured for maximum protection and shall not be exposed where they can be inadvertently damaged through normal usage. The hydraulic system shall include a signal mechanism or contamination indicator to indicate when filter maintenance or replacement is required.

3.12 Forklift mechanism and carriage assembly. The forklift mechanism shall be hydraulically operated and shall be either a boom-type lever arm and carriage assembly or a loader type linkage and carriage assembly. Neither type of mechanism shall allow the rated load to be extended past a reach point which will decrease the lifting capacity of the truck.

3.13 Tilt mechanism. The lift mechanism shall include a means for tilting the forks upward and downward of the horizontal to the degree specified herein. The forks shall remain tilted without movement during engine or hydraulic system failure. The forks shall tilt fully upward and downward at all lift heights above 24 inches from the ground. The fork tilt angle shall remain constant throughout the entire lift range without manual adjustment by the operator.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

3.14 Carriage. The carriage shall provide a vertical support for the load to rest against when tilted to the rear. When the carriage is sideshifted to the maximum travel in either direction, the carriage shall not extend beyond the outside edge of either front tire. The carriage shall be positioned on the lift mechanism so that a centered load, wider than the truck and the carriage, will not interfere with the front tires or any other portion of the truck when operated as specified herein.

3.15 Load backrest. A removable load backrest fastened to the top of the carriage shall be provided. The load backrest shall be the same width as the carriage and shall extend from the top of the carriage to a height of 48 inches plus or minus 1/4 inch above the load carrying surface of the forks.

3.16 Fork Positioner/Sideshift. A hydraulically powered fork positioner and sideshifter shall be provided.

3.17 Forks. Forks shall be attached to the carriage in a manner which prevents lateral movements of the forks, except when fork positioner is activated by the operator. Fork dimensions shall be as specified herein.

3.18 Handtool box. A hand-tool box shall be provided. The tool box shall be secured to the truck in a protected location.

3.19 Electrical system. The truck shall have a 24 volt electrical system. All electrical circuitry, controls, instrumentation, and components shall be protected in order to prevent any type of moisture or water damage.

3.20 Lights. The truck shall be provided with not less than two headlights and two floodlamps for forward illumination and two floodlamps for rearward illumination. Floodlamps shall be horizontally and vertically adjustable. Each floodlamp shall be furnished with three sets of lenses. Color of lenses shall be clear, red and yellow. Red and yellow lenses shall be stored in a pocket located on the back of the operator's seat. The truck shall be provided with two rear mounted combination stop light and tail light.

3.21 Blackout lighting. The truck shall be provided with two blackout headlights and two blackout combination stoplight and taillights.

3.22 Slave receptacle. Truck shall be furnished with one 24 volt slave receptacle conforming to MS-75058 which will permit

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

charging of the truck battery(ies) and slave starting the engine from an external power source. The slave receptacle shall be accessible to personnel when standing on the ground.

3.23 Fluid Service Access. All fluid levels must be accessible without removal of panels. This includes both provisions for the checking and topping off of fluid levels. There shall be no leakage of any fluid while the vehicle is positioned in any stability or slope configuration. All fluid reservoirs exceeding 15 quarts shall be fitted with sampling valves, excluding fuel, coolant and hydraulic reservoirs. The valves shall be accessible without removal of panels.

3.24 Controls. All controls shall be clearly marked. Plastic control knobs, buttons, switches, etc. are not permitted. All load motion controls shall be of the self centering type.

3.25 Blackout lighting control. One switch conforming to MIL-PRF-11021 shall be provided to control the front headlights, blackout headlights, stop light, tail light, blackout stoplight and taillights, and instrument panel lights.

3.26 Starter switch/Engine-run control. A key-less starter switch/engine run-control shall be furnished which shall have not less than two positions, "on" and "off". The switch shall control operation of all electrical system components, except the horn. The diesel engine operation shall be terminated when the engine control is positioned to "off". Switch shall not engage starter when engine is running or when transmission is in any other gear than neutral.

3.27 Braking and declutch/inching controls. A separate declutch/inching pedal and brake pedal (two pedals) or a combination braking and declutch/inching pedal (one pedal) may be used. When a combination braking and declutch/inching pedal (one pedal) is utilized, a switch shall be provided to permit selection between braking only or a combination of braking and declutch/inching.

3.28 Instruments. The instrument, gauges, and warning lights furnished on the manufacturer's standard commercial models shall be furnished. A time totalizing hour meter shall be furnished. When an air or air-over-hydraulic brake system is furnished, an air pressure gauge shall be provided. Gauges shall have internal lighting which shall be controlled by a single on-off switch.

3.29 Identification plates. The truck, including each component

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

which must be removed for transportation purposes, shall be equipped with identification plates conforming to A-A-50271, Composition C.

3.29.1 Identification marking plate. The identifying data to be applied to the identification plates shall be in accordance with ASME B56.6 in addition to the following: contract number, gross vehicle weight, USN registration number, delivery date, technical manual national stock number, shipping weight, cube dimension, name or stamp of government inspector, and HI-Shock test date, manufacturer's name and address, and date shipped.

3.29.2 Instruction, warning and caution plates. Each truck shall be equipped with instruction, warning, and caution plates, prominently located and describing any special or important procedure to be followed in operating, lifting, and servicing of the truck or its components.

3.29.3 Shipping data plate. Shipping data plate shall indicate the silhouette of the forklift in transport position showing the center of gravity and the location and capacity of the lifting and tiedown attachments. Wheel loading information may be included on shipping data plate.

3.29.4 Wheel loading plate. Each truck shall be equipped with a wheel loading plate. As a minimum the plate shall have the following information:

Wheel loading (no load on forks)
Front wheels (each wheel) pounds
Rear wheels (each wheel) pounds

Wheel loading (rated load on forks)
Front wheels (each wheel at maximum sideshift) pounds
Rear wheels (each wheel at maximum sideshift) pounds

3.29.5 Safety rating plate. Each truck shall be equipped with a safety designation plate. As a minimum, the plate shall indicate the truck manufacturer's name, truck model number, safety designation (Type DS), Underwriter's Laboratory's registration number assigned to the inspected truck, and date of inspection.

3.29.6 Slave receptacle plate. The voltage potential of the slave receptacle shall be identified on a plate furnished adjacent to the receptacle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

3.29.7 Lubrication Tag. The truck shall be equipped with a lubricant/fluid list installed in a visible location to indicate which lubricant/fluid has been used in each component or system. The lubricants/fluids shall be listed by their commercial designation and their military equivalent, if applicable.

3.30 Vehicle marking. Each truck shall be marked as specified herein. All markings shall be painted in black enamel block letters and numbers.

3.30.1 Safe Working Load. Safe working load (capacity) of the truck shall be three inches high located on each side and rear of truck. Example: SWL 6000 lbs.

3.30.2 Registration number. Assigned USN registration number for each truck shall be 3 inches high located on each side and on rear of truck. Example: USN 18-12345

3.30.3 Tire pressure. The tire pressures for each tire shall be 1 inch high located on each side of the truck above the applicable tire. Example: TP 25 PSI

3.30.4 Safety rating. Markers indicating the DS safety designation of truck shall be applied on each side of the truck. These markers shall be in accordance with UL 558.

3.30.5 Supplementary markings. Supplementary marking and load handling symbols as specified in ASME MH11.3 are required.

3.30.6 Slinging and tiedowns. Slinging and tiedown markings shall be in accordance with MIL-STD-209.

3.30.7 Safety warning. Safety warning information shall be two inches high located as follows:

3.30.7.1 Title: WARNING, NO CLEARANCE FOR A PERSON STANDING IN THIS AREA. Near the articulated frame steering hinge on both sides of truck.

3.30.7.2 Title: No smoking. Inside personnel cab. When cab is not furnished, on the forklift mechanism.

3.30.7.3 Title: No riders. Inside personnel cab. When cab is not furnished, on the forklift mechanism.

3.30.8 Fuel type marking. Fuel type shall be 1 inch high near fuel tank filler. The fuel cap shall be painted green.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

3.30.9 Shipboard marking. The truck shall be identified with the words "SHIPBOARD USE APPROVED", 1-1/2 inch high located on each side of truck.

3.30.10 Structural testing marking. The truck which successfully passes the weight test specified herein shall be identified with the following, located on each side of truck using 1/4" high (minimum) letters:

STRUCTURALLY TESTED
date
BY (manufacturer)

3.30.11 Paint marking. Each side of the truck shall be marked as follows using 1/4" high (minimum) letters: "Painted with lead/chromate free paint by manufacturer (name), month, and year".

3.30.12 Non-asbestos brakes. Following statement shall be painted on truck using 1/4" high (minimum) letters: "Non-asbestos brake linings used. Replacement brakes shall be non-asbestos"

3.30.13 Truck weight. The truck's weight, without load, shall be painted on each side of the truck using 2" high (minimum) letters.
Example: Truck weight - 11,000 pounds

3.31 Treatment and painting. All truck surfaces shall be thoroughly cleaned, treated or painted to prevent rusting or failure. Painting of the truck shall be in accordance with the manufacturer's standard commercial practice. Paint (primer and finish coats) shall be lead and chromate free. The finish color shall be yellow. Color 13538 of FED-STD-595 may be used for guidance.

3.32 Performance.

3.32.1 Truck stability. The truck's longitudinal and lateral stability shall be as specified herein:

(a) Axle weight distribution. The truck rear axle weight without rated load and with the heel of the forks positioned 24 inches above the ground shall be a minimum of 52% of the curb weight. The truck rear axle weight with rated load and with the heel of the forks positioned 24 inches above the ground shall be a minimum of 20% of the curb weight. Curb weight is defined as the weight of the truck including the operator and the maximum capacity of fluids, lubricants, and diesel fuel.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

(b) Dynamic stability. The truck with rated load shall be capable of decelerating from the maximum speed in the forward direction to a full stop without any truck tire leaving the ground and the load slipping on the forks.

(c) Lift system stability. The truck shall be capable of lowering the rated load at maximum lowering speed and abruptly terminating the descent 24 inches above the ground without any tire leaving the ground.

3.32.2 Slope operation. The truck shall negotiate slopes as follows:

(a). Slope ascension. The truck with rated load shall be capable of ascending and descending a 100 foot, 45% (24 degrees) minimum slope in low gear when the lateral axis of the truck is parallel to the slope for a total of 20 consecutive passes. One pass is defined as one ascent and one descent.

(b). Lateral slope (static). The truck with rated load shall maintain 4-wheel ground contact on a 30% (17 degrees) minimum side slope when the lateral axis of the truck is parallel to the truck axles without any tire leaving the ground.

(c). Lateral slope (dynamic). The truck without rated load shall operate and maintain 4-wheel ground contact on a 30% (17 degrees) minimum lateral slope in low gear when the lateral axis of the truck is parallel to the truck axles without any tire leaving the ground.

3.32.3 Noise Limits. The noise level of the truck (excluding horns) shall not exceed the following:

(a). Operator's station. 85 decibels (dB)(A) maximum at the operator's station during normal operating procedures of the truck.

(b). Exterior of truck. 85 dB(A) maximum at 24.5 feet from the side of the truck during normal operation of the truck.

3.32.4 Electromagnetic Interference. The truck shall conform to the radiation and susceptibility EMI requirements of MIL-STD-461D.

3.32.5 High Impact (HI) Shock Requirements. The truck shall be designed to withstand Type A HI shock as a Grade A Item in accordance with MIL-S-901.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

3.32.6 Reliability. The truck shall be capable of operating for 500 hours without the need for unscheduled maintenance.

3.32.7 Maintainability. Provisions shall be made for timely servicing of the trucks. All components associated with routine and preventive maintenance shall be readily accessible. No tools shall be necessary to gain access to fluid level inspection points. All routine and preventive maintenance actions shall be accomplished with the use of common automotive tools.

3.32.8 Fork reach: Fork reach shall be 36 inches maximum measured from the front edge of front tires with forks level and positioned 24 inches above ground level to the heel of forks. When forks are retracted, forks shall be 15 inches maximum measured from front edge of front tires with forks level and positioned at ground level to the vertical face of the forks. Forks shall be capable of 6 inch minimum reach below ground level measured from ground level to the horizontal face of the forks, with and without rated load and normal operating tire pressure.

3.32.9 Fork sideshift. A hydraulically powered sideshift mechanism shall be provided. Sideshift mechanism shall operate forks to either side of center while carrying rated load a minimum of one half the truck width minus 18 inches.

3.32.10 Lifting speed. The speed of lifting the rated load from ground level to the maximum fork height shall be 40 feet per minute minimum.

3.32.11 Lowering speed. Speed of lowering of forks without rated load shall be not less than 60 feet per minute and not more than 80 feet per minute with rated load over the entire distance from maximum fork height to ground level.

3.32.12 Hydraulic drift. The truck lift assembly shall be capable of holding the rated load at the maximum lift height for not less than ten minutes with not more than one inch of vertical drift and not more than one degree of rotational drift from the vertical.

3.32.13 Overload. The truck shall be capable of sustaining 300 percent overload (18,000 pounds for size A, and 30,000 pounds for size B) for a minimum of ten minutes. (Front axle support and rear axle tie downs are permissible.)

3.32.14 Service brakes. The truck shall be equipped with four wheel service brakes and a parking brake. Service brake system

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

shall be independent of the hydraulic system and power train. A dual (split) redundant hydraulic or air system shall be provided to independently activate the front and rear brakes to prevent complete brake failure in the event of failure in either circuit. The brake system shall be equipped with a visual or audible warning indicator which shall be energized due to a loss of hydraulic or air pressure in either brake circuit. The service brakes shall function with either a dead or stalled engine. The service brake system shall be equipped with a control which permits the wheel brakes to remain activated after the operator force has been removed from the foot brake pedal. A brake pedal force of not more than 100 pounds and not less than 50 pounds shall stop the truck with and without the rated load as specified herein. Brake linings, shoes, or pads shall contain no asbestos.

(a) Service brakes shall stop the truck within the specified limits when tested in accordance to ASME B56.6.

(b) Service brakes shall stop the truck within a distance of 10 feet maximum when the truck is travelling down a 45% (24 degrees) at a speed of 5 mph minimum in the reverse direction.

(c) Service brakes shall restrain the truck on a 45% (24 degrees) minimum slope immediately after the service wheel brakes have been immersed in water for a period of ten minutes minimum.

(d) Service brakes shall stop the truck within a distance of 5 feet maximum when the truck is travelling at a speed of 5 mph minimum and with a dead engine.

3.32.15 Parking brake. A mechanical parking brake shall be provided. The parking brake shall be capable of retaining the truck on a 45% (24 degrees) longitudinal slope with rated load positioned in the carry position for 2 minutes minimum without permitting any tire movement. The maximum force required to activate the parking brake shall be 100 pounds.

3.32.16 Resistance to saline atmosphere. The truck shall be designed to withstand the corrosive effects of saline atmosphere without any formation of rust, loss or deterioration of performance, evidence of harmful corrosion, loss of mobility of parts and a inability to disassemble parts for service or repair when tested as specified herein. Also, operation of all components within the electrical system shall remain operative.

3.32.17 Slinging and tiedown attachments. Slinging and tiedown provisions shall be provided which permit the truck to be lifted

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

in its normal travel position and to be fastened to the floor or deck of a transportation medium. Each lifting and tiedown provision shall be capable of withstanding the loads indicated in MIL-STD-209. The truck tiedowns shall also meet the requirements of a Grade A item in Type A HI (high-impact) shock specified in MIL-S-901.

3.32.18 Wheel and Tires. Wheels shall be in accordance with the Tire and Rim Association Yearbook and shall be of uniform size. All tires on the truck shall be new, unused, and of uniform size with the same rated size and construction and shall be listed in the Tire and Rim Association Yearbook. Truck tire loadings with rated load shall not exceed the tire load limits indicated in the Year Book of the Tire and Rim Association at rated tire ply rating, inflation pressure and the truck's maximum speed as specified herein. The tire compound(s) shall be suitable for operation on non-slip compounds on the ship's decks. Hydroinflated tires are not acceptable. The front tire pressure shall be determined at gross vehicle weight (with rated load on the forks) and the rear axle tire pressure at curb weight (no load on the forks). The front and rear tires, when inflated to 20 psig maximum, shall show no evidence of failure, deterioration or separations from the wheels when truck is operated with rated load over soft terrain or in sea water at a minimum speed of 2 mph for a period of 30 minutes. Soft terrain is defined as noncompacted sand, snow or mud.

3.32.19 Deck loading. The truck individual wheel loading with rated load and forks at maximum sideshift position and fully extended shall not exceed 250 psi. The minimum dimension measured across the bearing area of each individual tire shall be 6 inches minimum under the wheel loading specified herein.

3.32.20 Weighing device. Type I truck shall be equipped with an analog (dial) weighing device to measure the amount of weight on the forks. The weighing device shall be capable of measuring a minimum weight of 100 pounds and a maximum weight equal to the rated capacity of the truck plus 300 pounds in 50 pound increments. The weighing device shall be capable of withstanding the pressure caused by placing 150% of the truck rated load on the forks without sustaining damage.

3.32.21 Curb-clearance diameter. Truck curb to curb turning diameter as defined in SAE J695 shall be 30 feet.

3.32.22 Steering. The truck shall be equipped with a power steering system which permits operation of truck at all speeds as

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

specified herein. The system shall provide four wheel cramp and two wheel rear wheel steer for rigid frame trucks or articulated frame steering. For trucks equipped with articulated steering, provisions shall be provided for the point of articulation to be pinned for towing and shipping. Warning signs shall be placed at the point of articulation. The steering system for both rigid and articulated frames must be operable with a dead engine. In the event of power steering failure or engine failure, and without rated load, steering shall be operable with a force not to exceed 50 pounds.

3.32.23 Pintle hook. A rear mounted pintle hook shall be provided which conforms to A-A-52550. The pintle hook shall be located on the vertical center-line of the forklift between 31 inches and 37 inches above ground level. The pintle hook and mounting shall be capable of a longitudinal pull of 34,000 pounds and a lateral pull of 17,000 pounds without deformation.

3.32.24 Roll Over Protective Structure and falling objects protective structure(ROPS/FOPS). The truck shall be equipped with a complete ROPS and FOPS conforming to the requirements for loaders indicated in SAE J154, SAE J231, J1040, and SAE J1042. Installation and removal of the ROPS/FOPS shall be accomplished without requiring cutting or welding. The ROPS/FOPS shall be free from sharp edges at any point where a sling can come in contact during lifting operations.

3.32.25 Frame or fork oscillation. The truck rotational motion of the frame and body assembly or the fork assembly about the pivot point with rated load shall be not less than 10 degrees clockwise and 10 degrees counterclockwise relative to a longitudinal vertical plane through the center of the truck.

3.32.26 Hydraulic fittings. When permanently attached type hose fittings are utilized, a replacement hose assembly fitted with reusable type fittings shall be capable of replacing the original hose assembly without any alterations to the hose, hose routing and the truck.

3.32.27 Weight testing. Each truck shall be capable of sustaining 150 percent of the rated load minimum for a minimum of ten minutes without damage to the truck in the operational mode.

3.32.28 Operating Temperatures. The engine shall start within 5 minutes and the truck shall operate as specified herein within 15 minutes after engine start in any ambient temperature in the range of 0 degrees Fahrenheit to +120 degrees Fahrenheit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

3.32.29 Rain. The truck shall start within 5 minutes and operate as follows when exposed to a minimum 4 inch per hour rainfall:

(a). Without malfunction of any electrical component, gage or instrument.

(b). Without leakage of water in the air-intake filter in excess of 8 percent of the fluid capacity of the sediment chamber.

(c). Without leakage of water into the torque converter oil chamber, engine crankcase sump, transmission, transfer case, instruments, gages or fuel tank.

3.32.30 Fording Conditions. There shall be no evidence of water damage to, or water leaking into water resistant housings, water resistant jackets and closed tanks of the engine, transmission, torque converter, fuel system, brakes and hydraulic system or any evidence of water damage or corrosion of any truck part which affects operation of the truck and its ability to meet all of the performance requirements specified herein. The truck fording depth shall be 60 inches minimum. The truck engine shall be capable of being started at full fording depth.

3.32.31 Back-up alarm. Truck shall be provided with a back-up alarm. When transmission is placed in reverse, alarm shall produce an audible warning which can be heard within a minimum 15 foot radius of the rear of the truck when the engine is operating within its normal speed range.

4. REGULATORY REQUIREMENTS.

4.1 Recovered materials. The manufacturer is encouraged to use recovered materials to the maximum extent practical, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR). However, used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the forklift truck.

5. QUALITY ASSURANCE PROVISIONS.

5.1 Product Conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, quality assurance practices, and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

5.2 Warranty. Unless otherwise specified in the contract of purchase order, the manufacturer's standard commercial warranty shall apply.

6. PACKAGING.

6.1 Preservation, packing, and marking. Preservation, packing, and marking shall be in accordance with the manufacturer's standard commercial practice unless otherwise specified in the contract or purchase order.

7. NOTES.

(Information in this section is for guidance only. This section contains information of general or explanatory nature, which is helpful, but not necessary.)

7.1 Source of documents.

7.1.1. Federal and Military Specifications and Standards are available from the DODSSP, Standardization Documents Order Desk, Bldg 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

MIL-S-901 - Shock Tests, H.I.(High Impact)Shipboard, Machinery, Equipment and Systems; Requirements For

MIL-F-16884 - Fuel, Naval Distillate

MIL-PRF-11021- Switch, Vehicular Lights, 24 Volt DC

MIL-DTL-5624 - Turbine Fuel, Aviation Grades JP-4, JP-5, and JP-5/JP-8 ST
MIL-DTL-83133- Turbine Fuels, Aviation, Kerosene Types, NATO F-34(JP-8) and NATO F-35.
FED-STD-595 - Colors

MIL-STD-209 - Slinging and Tiedown Provisions For Lifting and Tying Down Military Equipment
MIL-STD-461 - Requirements for the control of Electromagnetic Interference Emissions and Susceptibility
MS-75058 - Connector, Receptacle, Electrical Slave, 2 Contact, 24 Volt, Waterproof
A-A-50271 - Plate Identification

A-A-52550 - Pintle Assembly, Towing Manual Release 18,000, 40,000, and 100,000 lbs capacity

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

7.1.2 OSHA documents are available from Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)
29 CFR, Chapter XVII, Part 1910
Occupational Safety and Health Standards

7.1.3 ASME documents are available from American Society of Mechanical Engineers, United Engineering Center, 345 East 47th Street, New York, N.Y. 10017.

ASME B56.6 - Safety Standard for Rough Terrain Forklift Trucks.

ASME B56.11.3 - Load Handling Symbols for Powered Industrial Trucks.

7.1.4 SAE documents are available from the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, Pennsylvania 15096.

SOCIETY OF AUTOMOTIVE ENGINEERS HANDBOOK (SAE Handbook)

SAE J154 - Operator Space Envelope Dimensions for Off-Road Machines
SAE J231 - Minimum Performance Criteria For Falling Object Protective Structure
SAE J517 - Hydraulic Hose

SAE J695 - Turning Ability and Off Road Tracking - Motor Vehicles
SAE J1040 - Performance Criteria for Rollover Protective Structures (ROPS)for Construction, Earthmoving, Forest and Mining Machines
SAE J1042 - Operator Protection for General-Purpose Industrial Machines

7.1.5 Tire and Rim Association documents are available from the Tire and Rim Association, Inc., 175 Montrose West Avenue, Suite 150, Copley, Ohio 44321.

Year Book.

7.1.6 UL documents are available from Underwriter's Laboratories Inc., 333 Pfingsten Road, Northbrook, Illinois 60062.

UL 558 - Internal Combustion Engine Powered Industrial Trucks

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

7.2 Ordering Data. Acquisition documents should specify the following:

a. Title, number, and date of this CID.
b. Classification of truck required, see Paragraph 2.

7.3 Supersession data. This CID replaces Military Specification MIL-T-40632B dated 7 August 1994.

Custodian:
Navy -SA
Air Force - 99

Preparing Activity:
Navy - SA

Reviewer:
Air Force - 84

(Project No. 3930-0016)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7, and send to preparing activity.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1. DOCUMENT NUMBER** A-A-59492	**2. DOCUMENT DATE (YYYYMMDD)** 19990819

3. DOCUMENT TITLE **TRUCK, FORKLIFT, DIESEL ENGINE DRIVEN, 120 INCH LIFT HEIGHT, DS SAFETY RATED, PNEUMATIC RUBBER TIRES, ROUGH TERRAIN, FOR SHIPBOARD USE**

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON *(if applicable)*	**7.DATE SUBMITTED** (YYYYMMDD)

8. PREPARING ACTIVITY

a. NAME NAVAL INVENTORY CONTROL POINT CODE 1041	b. TELEPHONE *Include Area Code)* (1) Commercial (717) 605-4025 (2) AUTOVON 430-4025
c. ADDRESS *(Include Zip Code)* 5450 CARLISLE PIKE, P.O. BOX 2020 MECHANICSBURG, PA 17055-0788	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman road, Suite 2533, Ft. Belvoir, VA 22060-2533 Telephone (703) 767-6888 AUTOVON 427-6888

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.