MILITARY STANDARD

AUTOMATED ENGINEERING

DOCUMENT PREPARATION SYSTEM

MICROWAVE/WAVEGUIDE COMPONENTS

TO ALL HOLDERS 0F MIL-STD-35-75(MI):

1. THE FOLLOWING PAGES OF MIL-STD-35-75(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED:

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
Cover	31 December 1974	(REPRINTED WITHOUT CHANGE)	
ii	30 July 1976	ii	31 December 1974
iii	30 July 1976	iii and iv	31 December 1974
vii	30 July 1976	vii	31 December 1974
Vlll	30 July 1976	Vlll	31 December 1974
ix	30 July 1976		31 December 1974
	31 December 1974	(REPRINTED WITHOUT CHANGE)	
1-1	30 July 1976	l-1	31 December 1974
1-2	30 July 1976	1-2	31 December 1974
1-3	30 July 1976	1-3 and 1-4	31 December 1974
2-1	30 July 1976	2-1	31 December 1974
2-2	30 July 1976	2-2	31 December 1974
5-3	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-4	30 July 1976	5-4	31 December 1974
5-5	30 July 1976	5-5	31 December 1974
5-6	30 July 1976	5-6	31 December 1974
5-11	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-12	30 July 1976	5-12	31 December 1974
5-13	30 July 1976	5-13	31 December 1974
5-14	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-19	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-20	30 July 1976	5-20	31 December 1974
5-21	30 July 1976	5-21	31 December 1974
5-22	30 July 1976	5-22	31 December 1974
5-23	30 July 1976	5-23	23 May 1975
5-24	30 July 1976	5-24	31 December 1974
5-39	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-40	30 July 1976	5-40	31 December 1974
5-41	30 July 1976	5-41	31 December 1974
5-42	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-47	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-48	30 July 1976	5-48	31 December 1974
5-49	30 July 1976	5-49	31 December 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
5-50	30 July 7976	5-50	31 December 1974
5-53	30 July 1976	5-53	31 December 1974
5-54	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-59	30 July 1976	5-59	31 December 1974
5-60	30 July 1976	5-60	23 May 1975
5-69	30 July 1976	5-69	31 December 1974
5-70	30 July 1976	5-70	31 December 1974
5-75	30 July 1976	5-75	31 December 1974
5-76	30 July 1976	5-76	31 December 1974
5-77	30 July 1976	5-77	31 December 1974
5-78	30 July 1976	5-78	23 May 1975
5-79	30 July 1976	5-79	31 December 1974
5-80	30 July 1976	5-80	31 December 1974
5-83	30 July 1976	5-83	23 May 1975
5-84	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-85	30 July 1976	5-85	31 December 1974
5-86	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-87	30 July 1976	5-87	31 December 1974
5-88	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-89	30 July 1976	5-89	31 December 1974
5-90	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-91	30 July 1976	5-91	31 December 1974
5-92	30 July 1976	5-92	31 December 1974
5-95	30 July 1976	5-95	31 December 1974
5-96	30 July 1976	5-96	31 December 1974
5-103	30 July 1976	5-103	31 December 1974
5-104	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-105	30 July 1976	5-105	31 December 1974
5-106	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-107	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-108	30 July 1976	5-108	31 December 1974
5-109	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-110	30 July 1976	5-110	31 December 1974
5-111	30 July 1976	5-111	31 December 1974
5-112	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-113	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-114	30 July 1976	5-114	31 December 1974
5-115	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-116	30 July 1976	5-116	31 December 1974
5-117	30 July 1976	5-117	31 December 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
5-118	30 July 1976	5-118	31 December 1974.
5-121	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-122	30 July 1976	5-122	23 May 1975
5-123	30 July 1976	5-123	31 December 1974
5-124	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-125	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-126	30 July 1976	5-126	31 December 1974
5-131	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-132	30 July 1976	5-132	23 May 1975
5-133	30 July 1976	5-133	23 May 1975
5-134	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-135	30 July 1976	5-135	31 December 1974
5-136	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-137	31 December 1974	(REPRINTED WITHOUT CHANGE)	
5-138	30 July 1976	5-138	23 May 1975
6-1	30 July 1976	6-1 and 6-2	31 December 1974

2. THE FOLLOWING PAGES HAVE BEEN ADDED:

NEW PAGE	DATE
8-7	30 July 1976

3. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF-CONTENTS.

4. Holders of MIL-STD-35-75(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages . is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army - MI

Review activities:
Army - AT
Army -AV
Army - EL
Army - ME
Army - MR
Army - SG
Army - WC

User activity:
Army - MU

Preparing activity:
Army - MI

(Project EDS-A182)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

MILITARY STANDARD

AUTOMATED ENGINEERING DOCUMENT PREPARATION SYSTEM

MICROWAVE/WAVEGUIDE COMPONENTS

Reprinted without change.

FSC-EDS

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF THE ARMY
U. S. ARMY MATERIEL
DEVELOPMENT AND READINESS COMMAND
ALEXANDRIA, VA. 22333

Automated Engineering
Document Preparation System,
Microwave/Waveguide Components

MIL-STD-35-75(MI)

1. This Military Standard is approved by the U.S. Army Materiel Development and Readiness Comnand, Department of the Army, and is approved for use by all its activities. All other milltary activities are required to employ this Standard where suitable.

2. Recommended corrections, additions or deletions should be addressed to Commander, U.S. Army Missile Conmnand, ATTN: DRSMI-RCS, Redstone Arsenal, Alabama 35809.

Supersedes page ii of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

FOREWORD

1. The purpose of MIL-STD-35-75(MI) is to facilitate the preparation of Military Specification, Exceptions for Microwave/Wageguide components.

2. In order to properly utilize this document, it is necessary to have a complete and thorough understanding of the basic MIL-STD-35.

3. It is important that the procedure described in the basic document (MIL-STD-35C) and subsequent revisions be followed explicitly in order for the computer to produce a document suitable for competitive procurement. Information which is standard for all dash-numbered parts has been included in the basic document at the issuance of MIL-STD-35C. This information is not repeated in each dash-numbered part.

Supersedes pages iii and iv of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS (CONT)

SECTION	TITLE	INSTR PAGE	SRL PAGE
5.12	Design Characteristics (Directional Couplers)	5-17	5-72
5.12.1	Directional Type	5-17	5-72
5.12.2	Connectors	5-17	5-72
5.12.3	Transmission Line	5-18	5-72
5.12.4	Power Coupling	5-18	5-73
5.12.5	Power Rating	5-18	5-73
5.12.6	Isolation	5-18	5-73
5.12.7	Frequency Sensitivity	5-19	5-73
5.12.8	Tracking	5-19	5-73
5.12.9	Amplitude Equality	5-19	5-73
5.12.10	Phase Equality	5-19	5-74
5.12.11	Mounting Method	5-19	5-74
5.13	Design Characteristics (Switches)	5-20	5-74
5.13.1	Actuation	5-20	5-74
5.13.2	Coupling	5-20	5-75
5.13.3	Switch Type	5-20	5-75
5.13.4	Mounting Patterns	5-21	5-75
5.13.5	Return Mechanism Type	5-21	5-75
5.13.6	Interlock Circuitry	5-21	5-75
5.13.7	Receptacle Pressure	5-21	5-76
5.13.8	Holding Current	5-21	5-76

Supersedes page vii of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS (CONT)

SECTION	TABLE	INSTR PAGE	SRL PAGE
5.14	Altitude	5-21	5-76
5.15	Attenuation (Fixed and Variable Attenuators)	5-22	5-77
5.16	Deleted		
5.17	Attenuation Stability (Fixed Attenuators)	5-24	5-80
5.18	Connector Wear Resistance (Fixed Attenuators)	5-25	5-81
5.19	Coupling Factor (Couplers)	5-25	5-81
5.20	Coupling Variation (Couplers)	5-25	5-82
5.21	Dial-Calibration (Variable Attenuators)	5-26	5-83
5.22	Dielectric Withstanding Voltage (Reduced Barometric Pressure)	5-26	5-84
5.23	Dielectric Withstanding Voltage (Sea Level)	5-28	5-86
5.24	Effective Directivity (Couplers)	5-29	5-88
5.25	Endurance (Switches)	5-30	5-89
5.26	Frequency Sensitivity (Variable Attenuators)	5-30	5-90
5.27	Fungus	5-31	5-91
5.28	Gage (Adapters)	5-31	5-92
5.29	Heat Aging (Switches)	5-33	5-94
5.30	High Temperature	5-34	5-95

Supersedes paqe viii of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS (CONT)

SECTION	TITLE	INSTR PAGE	SRL PAGE
5.31	Humidity	5-35	5-96
5.32	Insertion Loss	5-36	5-99
5.33	Insulation Resistance	5-37	5-100
5.34	Isolation (Switches)	5-38	5-102
5.35	Low Temperature	5-39	5-102
5.36	Moisture Resistance’	5-40	5-104
5.37	Operating Voltage (Switches)	5-41	5-106
5.38	Peak Power (Fixed and Variable Attenuators)	5-42	5-107
5.39	Power Dissipation (Couplers)	5-43	5-108
5.40	Power Handling Capacity (Switches)	5-43	5-109
5.41	Radio Noise	5-44	5-110
5.42	Rain	5-45	5-111
5.43	Release Voltage (Switches)	5-46.	5-113
5.44	Repeatability (Variable Attenuators)	5-47	5-114
5.45	Deleted		
5.46	Salt Spray (Corrosion)	5-48	5-116
5.47	Sand and Dust	5-50.	5-118
5.48	Seal	5-50	5-119
5.49	Sensitivity of Attenuation (Fixed Attenuators)	5-52	5-121
5.50	Deleted		

Supersedes page ix of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS (CONT)

SECTION	TITLE	INSTR PAGE	SRL PAGE
5.51	Shock, Specified Pulse	5-53	5-123
5.52	Switching Time (Switches)	5-55	5-125
5.53	Temperature/Altitude	5-55	5-125
5.54	Temperature Coefficient	5-56	5-127
5.55	Thermal Shock	5-56	5-128
5.56	Vibration; High Frequency	5-58	5-130
5.57	Vibration, Low Frequency	5-60	5-132
5.58	Vibration, Random	5-62	5-135
5.59	Voltage Standing Wave Ratio	5-63	5-137
SECTION 6	USE OF AEDPS	6-1	
SECTION 7	FIGURES	7-1	
7.1	Adapters	7-3	
7.2	Fixed Attenuators	7-7	
7.3	Variable Attenuators	7-15	
7.4	Directional Couplers	7-21	
7.5	Switches	7-29	
7.5.1	Switch Mounting Patterns	7-37	
SECTION 8	TABLES	8-1	
	Specification Requirements Sheet	8-5	

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SECTION 1

INTRODUCTION

1.1 Scope

This dash numbered part of the Automated Engineering Document Preparation System, MIL-STD-35, covers detailed requirements of Microwave/ Waveguide Components (Fixed and Variable Attenuators, Waveguide to Coaxial Adapters, Directional Couplers, Waveguide and Coaxial Switches).

1.2 Purpose

The purpose of this dash numbered part of MIL-STD-35 is to provide a requester necessary information to properly prepare a request for a Microwave/Waveguide Components Military Specification, Exception (MSE).

1.3 Format

The requester will find it impossible to complete an SRS using only this dash-numbered part of MIL-STD-35. Specification requirements which are standard for all generic families have been included in the master document at the issuance of MIL-STD-35C. These specification requirements are not repeated in each dash-numbered part. The following list contains subjects which are pertinent to every family unless otherwise excepted.

General Description of AEDPS
Part Numbering
Specification Requirements Sheet
Writing Methodology
Mandatory Specification Requirements
General Specification Requirements
Dimensions and Drawings
Applicable Documents
Materials
Finishes
Inspections
Single and Multi- item Specifications (Tabulation)
Sources
Search
General Instructions for SRL
Tables

Supersedes page 1-1 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

1.4 Military Specification, Exception Title Index

It is recommended that the following documents be reviewed prior to using MIL-STD-35-75:

MIL-STD-1328	Coupler, Directional (Coaxial and Waveguide), . Selection of
MIL-STD-1329	Switch, RF Coaxial, Selection of
MIL-STD-1352	Attenuator, Fixed, Selection of
.MIL-STD-1358	Waveguides, Rectangular, Ridged and Circular Selection of

1.4.1 Title

The title of the generated MSE must be selected from one of the titles listed in the Military Specification Exception Title Index (see 1.4.2). If a suitable title is not found in the Military Specification Exception Title Index, a request should be forwarded to USAMICOM, ATTN: DRSMI-RCS, along with the desired title, and the related document. A code will be assigned and the code, title, and related document will be made a part of the Military Specification Exception Title Index. The requester will be notified of the code assigned.

One of the six-digit characteristic value codes listed in the CODE column of the Military Specification Exception Title Index, entered on a Specification Requirements Sheet (SRS) will specify that the title of the MSE will be the title shown with that code in the index. Each MSE title listed in the index is compatible with the document(s) listed with that title in the RELATED DOCUMENT column. The list may or may not be a complete listing.

The information contained in the RELATED DOCUMENT COVERAGE column is intended for the requester's reference; when more than one document is listed for a title, this information will be found useful in determinating which of the documents is most suitable for use as the applicable General Specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

The MSE title uses the basic federal item name listed in Cataloging Handbook H6. Titles with additional modifying and identifying words are provided to assist a designer in defining the scope of the MSE. To allow the designer flexibility, the title is generally not as restrictive as the basic specification to which the exception is taken. The reverse AEDPS title comprises the words that will appear in the Scope paragraph (1.1) of the MSE.

If the item selected from the AEDPS document becomes an item of supply, then the Cataloging Handbook H6 nomenclature must be used.

-The MSE title may or may not be the same as the title used in DODISS, FIIG or the document to which the MSE document was written. Documents . referenced in the MSE that will be listed in the Applicable Documents paragraph (2.1) of the MSE will be identified by the exact title that - appears on the referenced document. The title written on the MSE or in " DODISS or FIIG will not be entered in paragraph 2.1.

1.4.2 Index

The Military Specification Exception Title Index is as follows:

CODE	TITLE	RELATED DOCUMENT	DOCUMENT COVERAGE
Ø91ØØ1	Attenuators, Fixed	MIL-A-3933	Coaxial and Waveguide
Ø91ØØ2	Attenuators,	MIL-A-24215	Coaxial and Waveguide
Ø91ØØ4	Switches, Waveguide	MIL-S-55041	Manual, Electromechanical, and Electromagnetic
Ø91ØØ5	Couplers, Directional	MIL-C-15370	Coaxial Line or Waveguide
Ø91ØØ6	Adapters, Coaxial to Waveguide	MIL-A-22641	Coaxial Connectors, Coaxial Lines, and Waveguides

Supersedes pages 1-3 and 1-4 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SECTION 2

APPLICABLE DOCUMENTS

The following documents form a part of this standard to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-3933	Attenuators, Fixed (Coaxial Line and Waveguide), General Specification for
MIL-T-5422	Testing, Environmental, Aircraft Electronic Equipment .
MIL-C-15370	Couplers, Directional (Coaxial Line or Waveguide), General Specification for
MIL-A-22641	Adapters, Coaxial to Waveguide, General Specification for
MIL-A-24215	Attenuators, Variable (Coaxial and Waveguide), General Specification for
MIL-S-55041	Switches, Waveguide

STANDARDS

MILITARY

MIL-STD-202	Test Methods for Electronic and Electrical Component Parts
MIL-STD-461	Electromagnetic Interference Characteristics Requirements for Equipment

Supersedes page 2-1 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

MILITARY (Cent)

MIL-STD-1328	Coupler, Directional (Coaxial and Waveguide), Selection or
MIL-STD-1329	Switch, RF Coaxial, Selection of
MIL-STD-1352	Attenuator, Fixed, Selection of
MIL-STD-1358	Waveguides, Rectangular, Ridged and Circular, Selection of
MIL-STD-462	Electromagnetic Interference Characteristics, Measurement of
MIL-STD-810	Environmental Test Methods

OTHER PUBLICATIONS

H6	Federal Item Name Directory for Supply Cataloging

(Copies of Standards and Handbooks required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Supersedes page 2-2 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

"GROUP A INSPECTION. GROUP A INSPECTION SHALL BE PERFORMED AS SPECIFIED IN THE SPECIFICATION REFERENCED IN 3.1 EXCEPT THERMAL SHOCK SHALL BE 175 DEG C HIGH TEMPERATURE."

The test method per 1006 code and requirements per 1006 code from the same test shall not be used together. This condition would indicate no exception is being specified. If a test method code(s) has been selected, it is mandatory that a requirement code be selected; and if a requirement code has been selected, it is mandatory that a test method code(s) be selected.

5.4.2 Approved Item Name Code

The approved item name code to be entered on the SRS with Code 1007 for a Microwave/Waveguide Component is selected from the following list:

APPROVED ITEM NAME	ITEM NAME CODE
Adapter -	00186
Fixed Attenuator	14224
Variable Attenuator	00838
Attenuator Assembly	00350
Directional Coupler	00384
Switch	05118

Only the Item Name Code number is entered on the SRS with Code 1007.

5.5 Organization of Design and Test Data

Design data and operating parameters for the four Microwave/Waveguide Component types are arranged such that design data and operating parameters common to all four components are covered first followed by design data and operating parameters specific to each in the order of Adapters, Attenuators, Couplers, and Switches.

All tests are arranged in alphabetical order.

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

5.6 Dimensions and Figures

All specification requirements for dimensions and figures described in MIL-STD-35 are applicable.

The figures applicable to Microwave/Waveguide Components are contained in Section 7. It is mandatory to enter on the SRS Code 1009 and a figure number.

5.7 Applicable Documents

The documents listed in the Applicable Document List of Section 5 of MIL-STD-35 and appropriate codes from Table B of MIL-STD-35 shall be entered on the SRS. In addition, selected documents shown in the DOCUMENTS column below and applicable-codes from Table B of MIL-STD-35 shall be entered on the SRS when the document related codes listed in the CODES column are used to specify tests or requirements. Shown parenthetically in the CODES column is a reference to the applicable test or requirement.

DOCUMENT	CODES
MIL-A-3933	1700 (Attenuation) 1728 (Attenuation Stability) 1738 (Connector Wear Resistance) 1893 (Peak Power) 1995 (Sensitivity of Attenuation) 2020 (Voltage Standing Wave Ratio) (VSWR)
MIL-T-5422	3111 (Temperature/Altitude)
MIL-C-15370	1747 (Coupling Factor) 1759 (Coupling Variation) 1782 (Effective Directivity) 1858 (Insertion Loss) 1913 (Power Dissipation) 2020 (VSWR)
MIL-A-22641	1815 (Gage) 1858 (Insertion Loss) 2020 (VSWR)
MIL-A-24215	1701 (Attenuation) 1769 (Dial Calibration) 1806 (Frequency Sensitivity) 1858 (Insertion Loss) 1894 (Peak Power) 1957 (Repeatabi1ity) 2020 (VSWR)

Supersedes page 5-4 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

DOCUMENTS (CONT)	CODES (CONT)
MIL-S-55041	1793 (Endurance) 1844 (Heat Aging) 1858 (Insertion Loss) 1872 (Isolation) 1884 (Operating Voltage) 1927 (Power Handling Capacity) 1948 (Release Voltage) 1987 (Switching Time) 2020 (VSWR)
MIL-STD-202	1397 (Moisture Resistance) 1427 (Random Vibration) 1447 (High Frequency Vibration) 1467 (Low Frequency Vibration) 1500 (Specified Pulse Shock) 1511 (Insulation Resistance) 2009 (Temperature Coefficient) 4714 (Thermal Shock) 4771 (Salt Spray) 4853 (Humidity) 4862 (DWV/Sea Level) 4960 (Sand and Dust) 6300 (DWV/Reduced)
MIL-STD-461 and 462	1938 (Radio Noise)
MIL-STD-810	3042 (High Temperature) 3065 (Low Temperature) 3088 (Rain) 4755 (Fungus)

Supersedes page 5-5 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

DOCUMENTS (CONT)	CODES (CONT)
H6	Mandatory 1007
Documents to which exception is taken	1006

In addition, when the codes listed below are used-to specify mounting or special preparations in accordance with a document, the document number must be entered again with the appropriate code from Table B of MIL-STD-35.

1520 Insulation resistance, preparation
6280 Dielectric withstanding voltage, reduced pressure, mounting
4684 Shock, specified pulse, mounting
4707 Vibration, high frequency, mounting
4719 Thermal shock, mounting
4729 Vibration, low frequency, mounting
4975 Vibration, random, mounting

For these codes any document from the Index, 1.4.2, may be used. To specify which test in the document contains applicable mounting or preparation requirements, enter on the SRS the test name and the document number (Example 2).

CHAR CODE 13 14 15 16	CHARACTERISTIC VALUE 20 25 30 35 40 45 50
1520	MIL-STD-202, INSULATION RESISTANCE#

EXAMPLE 2

Code 1520 in the above example specifies the special preparations for the Insulation Resistance test, which is not in MIL-A-22641, shall be in accordance with the special preparation for the Insulation Resistance test in MIL-STD-202.

5.8 Tabulation

All specification requirements for tabulation described in MIL-STD-35 are applicable.

Characteristics in this dash numbered part that are candidates for tabulation are contained in the following list. Only characteristic codes from this list shall be entered on the SRS with codes from the Specification Requirement Sheet Tabulation Table of MIL-STD-35.

Supersedes page 5-6 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 1564 and a value, entered on the SRS, will specify the height of the waveguide in inches.

Code 1565 and a value, entered on the SRS, will specify the width of the waveguide in inches.

Code 1591 “and an “X”, entered on the SRS, will specify that the dimensions are inside the cross section.

Code 1592 and an “X”, entered on the SRS, will specify that the dimensions are outside the cross section. It is mandatory that either Code 1591 or Code 1592 be entered on the SRS.

Code 1566 provides for specifying the equivalent type RG-Number of the waveguide. Code 1566 shall not be used” with Code 1567.

Code 1567 provides for specifying the equivalent type WR-Number of the waveguide. Code 1567 shall not be used with Code 1566.

5.9.8 Flanges

The type of flanges that are integral with the component waveguide may be specified by ten codes. None of these codes are mandatory. These codes and information concerning them are as follows:

Code 1569 provides for specifying the input flange UG-type number. Code 1569 shall not be used with Code 1570.

Code 1570 provides for specifying the output flange UG-type number.

Code 1568 and a document designation; entered on the SRS, will specify the flange mating characteristics specification.

There are three additional codes that provide for specifying the type of flange. None of these codes are mandatory. Only one code may be selected. These codes and information concerning them are as follows:

Code 1571 and an “X”, entered on the SRS, will specify that the flange is a choke type.

Code 1572 and an “X”, entered on the SRS, will specify that the flange is a cover type.

Code 1573 and an “X”, entered on the SRS, will specify that the flange is a contact type.

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

The flange connection methods are specified by three codes which are not mandatory. Only one code may be selected. These codes and information concerning them are as follows:

Code 1574 and an "X", entered on the SRS, will specify that the flange shall be connected by clamp rings.

Code 1575 and an "X", entered on the SRS, will specify that the flanges shall be connected by studs.

Code 1576 and an "X", entered on the SRS, will specify that the flanges shall be connected with threaded holes.

Code 1577 and a n-umber, entered on the SRS, will specify the quantity of flange connection devices.

5.9.9 Connectors

There are four codes applicable to the coaxial connector type and specification numbers. None of these codes are mandatory. These codes and information concerning them are as follows:

Code 1578 provides for specifying the input connector type number.

Code 1579 and a document designation, entered on the SRS, will specify that the design and construction requirements for the connectors shall be in accordance with the document.

Code 1580 provides for specifying the output connector type number.

Code 1581 and a document designation, entered on the SRS, will specify that the design and construction requirements for the connectors shall be in accordance with the document.

5.9.10 Weight

There are four codes applicable to the weight of the components. None of these codes are mandatory. Only one code per system of measurement shall be used. These codes and information concerning them are as follows:

Code 7022 and a value, entered on the SRS, will specify the maximum weight of the component in ounces.

Code 7023 and a value, entered on the SRS, will specify the maximum weight of the component in pounds.

Supersedes page 5-12 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 7021 and a value, entered on the SRS, will specify the maximum weight of the component in grams.

Code 7024 and a value, entered on the SRS, will specify the maximum weight of the component in kilograms.

5.10 Design Characteristics (Adapters)

5.10.1 Coaxial End Coupling

There are two codes applicable to the coaxial end couplings of the adapter which are equivalent to standard couplings with a UG-part designation. These codes are mandatory. Information concerning them is as follows:

Code 1606 will specify that the coupling equivalent UG-part designation shall be the number entered with it on the SRS.

Code 1607 will specify that the UG-part designation of the mating coupling shall be the number entered with it on the SRS.

5.11 Design Characteristics (Attenuators)

5.11.1 Eliminate Backlash

Code 1631 and an "X", entered on the SRS, will specify that the variable control mechanism shall have provisions to eliminate backlash: Code 1631 is not mandatory.

5.11.2 Dial Readout

The codes in Table I (Section B) are to be used to specify the direct reading scale calibrated in db increments for various db ranges. None of the codes in Table I are mandatory. Codes selected from the table and entered on the SRS along with the desired data will cause the computer to generate the table and enter the data in the respective table cells. Only lines from which codes have been selected will appear in the MSE.

The two codes on each line of Table I are to be used to specify the scale increment (maximum db) in the first column for a particular db range in the second column (Example 5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC NAME	CHAR CODE 13 14 15 16	CHARACTERISTIC VALUE 20 25 30 35
	1614	Ø.Ø5#
	1615	Ø TO 1#
	1616	Ø.1#
	1617	1 TO 10#
	1618	Ø.2#
	1619	10 TO 20#
	1620	Ø.5#
	1621	20 TO 30#

EXAMPLE 5

The codes and values entered on the SRS in Example 5 specify the following:

Code 1614 specifies that the scal e increment shall be 0.05 db maximum.

Code 1615 specifies that the cali bration range shall be zero to one db for the 0.05 db increment.

Code 1616 specifies that the scal e increment shall be 0.1 db maximum,

Code 1617 specifies that the calibration range shall be one to ten db for-the 0.1 db increment.

Code 1618 specifies that the scale increment shall be 0.2 db maximum.

Code 1619 specifies that the calibration range shall be ten to twenty db for the 0.2 db increment.

Code 1620 specifies that the scale increment shall be 0.5 db maximum.

Code 1621 specifies that the calibration range shall be twenty to thirty db for the 0.5 db increment.

5.11.3 Attenuation

The codes in Table II (Section 8) are to be used to specify attenuation accuracy for various attenuation ranges, tested according to certain specified methods, for various rated attenuation values of fixed attenuators. None of the codes in Table II are mandatory. Codes selected from the table and entered on the SRS along with the desired data will cause the computer to generate the table and enter the data in the respective table cell(s).

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

5.12.7 Frequency Sensitivity

Code 1659 and a value, entered on the SRS, will specify frequency sensitivity in plus or minus db minimum.

5.12.8 Tracking

Code 1660 and a value, entered on the SRS, will specify in db the - maximum change in the difference between forward and reverse coupling over the frequency band.

5.12.9 Amplitude Equality

Code 1661 and a value, entered on the SRS, will specify the output to output amplitude equality in plus or minus db between the two Coupler outputs.

5.12.10 Phase Eqaualitv

Code 1662 and a value, entered on the SRS, will specify the output to output phase equality between the two. Coupler outputs in plus or minus db . This code is not mandatory.

Code 1663 and a value, entered on the SRS, will specify the output to output phase equality between the two Coupler outputs in plus or minus radians. This code is not mandatory.

5.12.11 Mountinq Method

There are eight codes applicable to the method of mounting the Couplers. None of these codes are mandatory. Only one code may be selected. These codes and information concerning them are as follows:

Code 1664 and an “X”, entered on the SRS, will specify that the Coupler shall be mounted with any acceptable method.

Any one of the remaining seven codes entered on the SRS with an “X” will specify the following methods of mounting:

Code 1665	Bolts
Code 1666	Brackets
Code 1667	Clamps
Code 1668	Clips

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 1669”	Connectors
Code 1670	Screws
Code 1671	Studs

5.13 Design Characteristics (Switches)

5.13.1 Actuation

There are three codes applicable to the method of actuating the switch. It is mandatory that one and only one of these codes be selected. These codes and information concerning them are as follows:

Code 1675 and an “X”, entered on the SRS, will specify that the switch shall be manually actuated.

Code 1676 and an “X”, entered on the SRS, will specify that the switch shall be actuated by a solenoid.

Code 1677 and an “X”, entered on the SRS, will specify that the switch shall be actuated by a solenoid.

5.13.2 Coupling

Code 1682 and a value, entered on the SRS, will specify the number of switch positions. This code is mandatory.

5.13.3 Switch Type

There are four codes applicable-to the type of switch. These codes are mandatory if a transfer type or a nontransfer type is selected. Information concerning these codes is as follows:

Code 1678 and a value, entered on the SRS, will speci fy the number of poles of a transfer type switch.

Code 1679 and a value, entered on the SRS, will speci fy the number of throws of the transfer type switch.

Code 1680 and a value, entered on the SRS, will specify the number of poles of a nontransfer type switch.

Supersedes page 5-20 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 1681 and a value, entered on the SRS, will specify the number of throws of the nontransfer type switch.

Codes 1678 and 1679 shall not be used with Codes 1680 and 1681.

5.13.4 Mounting Patterns

Code 1684 and a number selected from figure number Ø91-Ø5-13 through Ø91-Ø5-2Ø, entered on the SRS, will specify the Pattern for mounting the switch. If Code 1684 is entered, the figure number for the mounting pattern must also be entered with Code 1009 after the switch body style figure number.

Code 1685 and an "X", entered on the SRS, will specify that inserts shall be required for tapped hole mounting of switches.

5.13.5 Return Mechanism Type

There are two codes applicable to the type of return mechanism in the switch. These two codes are not mandatory. Only one code may be selected. Information concerning these codes is as follows:

Code 1687 and an "X", entered on the SRS, will specify that the type' of switch return mechanism shall be fail-safe.

Code 1688 and an "X", entered on the SRS, will specify that the switch return mechanism shall be the latching type.

5.1.3.6 Interlock Circuitry

Code 1689 and an "X", entered on the SRS, will specify that the switch design shall include interlock circuitry. This code is not mandatory.

5.13.7 Receptacle Pressure

Code 1690 and an "X", entered on the SRS, will specify that the switch receptacle shall be pressurized. This code is not mandatory.

5.13.8 Holding Current

Code 1691 and a value, entered on the SRS, will specify the maximum holding current in amperes. This code is not mandatory.

5.14 Altitude

Code 3020 is the 1006 test code (5.4).

Code 3021 is the 1006 except test code (5.4).

Supersedes page 5-21 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 3022 and an "X", entered on the SRS, will specify to test in accordance with MIL-STD-810, Method 500.

Code 3023 and a value, entered on the SRS, will specify the duration of specimen operation and measurements in hours.

Code 3027 is the 1006 requirements code (5.4).

Code 3028 is the 1006 except requirements code (5.4).

Code 3029 and an "X", entered on the SRS, will specify that the component shall be capable of operating with no degradation of performance at the reduced barometric pressures and upon return to ambient conditions.

Code 3031 and a value, entered on the SRS, will specify the maximum attenuation in db.

Code 3032 and a value, entered on the SRS, will specify the maximum insertion loss in db.

Code 3033 and a number, entered on the SRS, will specify the maximum VSWR.

5.15 Attenuation (Fixed and Variable Attenuators)

Code 1698 is the 1006 test code (5.4).

Code 1699 is the 1006 except test code (5.4).

Code 1700 and an "X", entered on the SRS, will specify to test in accordance with MIL-A-3933.

The use of Table II codes is explained in paragraph 5.11.3.

Code 1701 and an "X", entered. on the SRS, will specify to test in accordance with MIL-A-24215.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 1703 and an "X", entered on the SRS, will specify that the attenuation shall be measured at minimum, 50 percent, and maximum attenuation.

Code 1707 is the 1006 requirement code (5.4).

Code 1708 is the 1006 except requirement code (5.4).

Code 1697 and a value, entered on the SRS, will specify the nominal measured attenuation in db.

Code 1709 and a value, entered on the SRS, will specify the maximum measured attenuation in db.

Code 1710 and a value, entered on the SRS, will specify the minimum measured attenuation in db.

Code 1716 and an "X", entered on the SRS, will specify the minimum test band frequency as direct current.

Code 1711 and a value, entered on the SRS, will specify the minimum test band frequency in gigahertz. If Code 1711 is used, it is mandatory that Code 1712 be used.

Code 1712 and a value, entered on the SRS, will specify the maximum test band frequency in gigahertz.

Code 1713 and a value, entered on the SRS, will specify the accuracy of attenuation as plus or minus db/db over the reference db level plus insertion loss. If Code 1713 is used, it is mandatory that Code 1714 be used.

Code 1714 and a value, entered on the SRS, will specify the db level used as reference during measurement of the attenuation accuracy.

Code 1715 and a value, entered on the SRS, will specify the accuracy of attenuation as plus or minus db. Code 1715 shall not be used with Codes 1713 and 1714.

Note: Paragraph 5-16 has been deleted.

Supersedes page 5-23 of 23 May 1975.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

5.17 Attenuation Stability (Fixed Attenuators)

Code 1726 is the 1006 test code (5.4).

Code 1727 is the 1006 except test code (5.4).

Code 1728 and an "X", entered on the SRS, will specify to test in accordance with MIL-A-3933.

There are six codes applicable to the type of tests that may be performed in order to determine the stability of attenuation. These codes and information concerning them are as follows:

Code 3140 and an "X", entered on the SRS, will specify that the Moisture Resistance test shall be performed.

Any of the remaining five codes entered on the SRS with an "X" will specify the following tests:

Code 3141	Peak Power
Code 3142	Shock, Specified Impulse
Code 3143	Temperature Change
Code 3144	Thermal Shock
Code 3145	Vibration, Low Frequency

Code 1730 is the 1006 requirements code (5.4).

Code 1731 is the 1006 except requirements code (5.4).

Code 1732 and an "X", entered on the SRS, will specify that there shall be no evidence of mechanical damage.

Code 1733 and a value, entered on the SRS, will specify the maximum db change in attenuation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 1873 and a value, entered on the SRS, will specify the step attenuator minimum isolation setting in db.

Codes 1874 and 1875 and values, entered on the SRS, will specify the swept frequency band in gigahertz.

Code 1876 and a value, entered on the SRS, will specify the crosstalk reference frequency in gigahertz.

Code 1877 is the 1006 requirements code (5.4).

Code 1878 is the 1006 except requirements code (5.4).

Code 1879 and a value, entered on the SRS, will specify the minimum power loss in db.

5.35 Low Temperature

Code 3063 is the 1006 test code (5.4).

Code 3064 is the 1006 except test code (5.4).

Code 3065 and a number, entered on the SRS, will specify the applicable test procedure number from Method 502 of MIL-STD-81O.

Code 3066 and a value, entered on the SRS, will specify the lowered storage temperature in minus degrees Celsius.

Code 3067 and a value, entered on the SRS, will specify the duration in hours of lowered test temperature maintenance. If Code ’3066 is used, it is mandatory that Code 3067 be used.

Code 3068 and a value, entered on the SRS, will specify the duration of component operation in hours while the chamber is maintained at the lowest operating temperature.

Code 3069 and a value, entered on the SRS, will specify the lowest operating temperature in degrees Celsius. If Code 3069 is used, it is mandatory that Code 3068 be used.

Code 3070 is the 1006 requirements code.

Code 3071 is the 1006 except requirements code.

Code 3072 and an. ’’X”, entered on the SRS, will specify that the component shall not be damaged and shall be capable of continuous and intermittent operation.

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 3074 and a value, entered on the SRS, will specify the maximum . attenuation in db.

Codes 3075 and 3076 and values, entered on the SRS, will specify the attenuation range in db.

Code 3077 and a value, entered on the SRS, will specify the maximum insertion loss in db.

Code 3078 and a value, entered on the SRS, will specify the maximum resetability error in db.

Code 3079 and a number, entered on the SRS, will specify the maximum VSWR.

Code 3080 and an “X”, entered on the SRS, will specify that the part shall be within tolerance and shall meet design or performance characteristics. “

5.36 Moisture Resistance

Code 1390 is the 1006 test code (5.4).

Code 1391 is the 1006 except test code (5.4).

Code 1397 and an “X”, entered on the SRS, will specify to test in accordance with Method 106 of MIL-STD-202. .

Code 4981 and a value, entered on the SRS, will specify the loading voltage in volts dc. Do not use code 4981 and code 4980.

Code 4980 and a value, entered on the SRS, will specify the loading voltage in volts ac.

Code 1395 and a value, entered on the SRS, will specify the polarization voltage in volts dc if other than 100 volts dc.

Code 4985 and an “X”, entered on the SRS, will specify that Step 7A of Method 106, MIL-STD-202, shall not be applicable.

Code 4986 and an “X”, entered on the SRS, will specify that Step 7B of Method 106, MIL-STD-202, shall not be applicable.

Code 1399 is the 1006 requirements code (5.4).

Code 1400 is the 1006 except requirements code (5.4).

Supersedes page 5-40 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 1396 and an "X", entered on the SRS, will specify there shall be no evidence of corrosion or change in electrical performance.

Code 3170 and a value, entered on the SRS, will specify the maximum attenuation in db.

Code 3171 and 3172 and values, entered on the SRS, will specify the attenuation range in db.

Code 3173 and a value, entered on the SRS, will specify that the stability of attenuation shall not vary more than plus or minus db.

Code 3174 and a value, entered on the SRS, will specify the maximum insertion loss in db.

Code 3175 and a value, entered on the SRS, will specify the minimum insulation resistance in megohms.

Code 3176 and a number, entered on the SRS, will specify the maximum VSWR.

Code 1398 and an "X", entered on the SRS, will specify that the component shall remain within tolerance.

Code 1392 and an "X", entered on the SRS, will specify that there shall be no degradation of performance of the component.

5.37 Operating Voltage (Switches)

Code 1882 is the 1006 test code (5.4).

Code 1883 is the 1006 except test code (5.4).

Code 1884 and an "X", entered on the SRS, will specify to test in accordance with MIL-S-55041.

Code 1885 is the 1006 requirement code (5.4).

Code 1886 is the 1006 except requirements code (5.4).

Code 1887 and a value, entered on the SRS, will specify the voltage application in volts that shall cause the switch to rotate, slide or move axially from the nonenergized position.

Code 1888 and an "X", entered on the SRS, will specify the nature of the applied voltage shall be alternating current.

Supersedes page 5-41 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 1889 and an “X”, entered on the SRS, will specify the nature of the applied voltage shall be dc. Code 1889 shall not be used with Code 1888.

5.38 Peak Power (Fixed and Variable Attenuators)

Code 1891 is the 1006 test code (5.4).

Code 1892 is the 1006 except test code (5.4).

Code 1893 and an “X”, entered on the SRS, will specify to test in accordance with MIL-A-3933.

Code 1894 and an “X”, entered on the SRS, will specify to test in accordance with MIL-A-24215.

Code 1895 and a value, entered on the SRS, will specify the test power in kilowatts.

Code 1896 and a value, entered on the SRS, will specify the duration of power application in hours. If Code 1895 is used, it is mandatory that Code 1896 be used.

Code 1897 and a value, entered on the SRS, will specify the maximum power in kilowatts applied during attenuation measurements.

Code 1898 and a value, entered on the SRS, will specify the adjusted maximum operating frequency in gigahertz when the maximum power is applied. If Code 1897 is used, it is mandatory that Code 1898 be used.

Code 1899 and an “X”, entered on the SRS, will specify that attenuation shall be measured after the test.

Code 1900 and an “X”, entered on the SRS, will specify that attenuation change shall be measured after the test.

Code 1901 and an “X”, entered on the SRS, will specify that dial calibration shall be measured during the test.

Code 1902 and an “X”, entered on the SRS, will specify that VSWR shall be measured during the test.

Code 1903 is the 1006 requirements code (5.4).

Code 1904 is the 1006 except requirements code (5.4).

Code 1905 and a number, entered on the SRS, will specify the maximum VSWR.

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

5.44 Repeatability (Variable Attenuators)

Code 1955 is the 1006 test code (5.4).

Code 1956 is the 1006 except test code (5.4).

Code 1957 and an "X", entered on the SRS, will specify to test in accordance with MIL-A-24215.

Code 1958 and a value, entered on the SRS, will specify the number of cycles the attenuator shall be operated from minimum through maximum attenuation.

Code 1959 is the 1006 requirements code (5.4).

Code 1960 is the 1006 except requirements code (5.4).

After cycling, various electrical tests are to be performed. Requirements for these tests and applicable code numbers are described below.

Code 1961 and a value, entered on the SRS, will specify the maximum attenuation in db.

Codes 1962 and 1963 and values, entered on the SRS, will specify the attenuation range in db.

Code 1964 and a value, entered on the SRS, will specify the dial accuracy in plus or minus db. Code 1964 is not to be used with Code 1965.

Code 1965 and a value, entered on the SRS, will specify the dial accuracy in plus or minus percent.

Code 1966 and a value, entered on the SRS, will specify the dial accuracy measurement frequency in gigahertz. If Codes 1964 or 1965 are used, it is mandatory that Code 1966 be used.

Code 1967 and a value, entered on the SRS, will specify the total variation in attenuation in maximum db across the operating frequency range.

Code 1968 and a value, entered on the SRS, will specify the maximum insertion loss in db.

If Power Capability is selected as a post-test performance requirement, the following codes (1969, 1970, 1971) would be considered mandatory:

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 1969 and a value, entered on the SRS, will specify the maximum test power in watts.

Code 1670 and a number, entered on the SRS, will specify the maximum VSWR at maximum test power.

Code 1971 and a value, entered on the SRS, will specify the dial accuracy in plus or minus db at maximum test power.

Code 1972 and a value, entered on the SRS, will specify the temperature coefficient in db/db/degrees Celsius.

Code 1973 and a number, entered on the SRS, will specify the maximum VSWR.

NOTE : Paragraph 5.45 has been deleted. .

5.46 Salt Spray (Corrosion)

Code 4769 is the 1006 test code (5.4).

Code 4770 is the 1006 except test code (5.4).

Code 4771 and an “X”, entered on the SRS, will specify to test in accordance with Method 101 of MIL-STD-202.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 4772 and a letter, entered on the SRS, will specify the applicable test condition letter from Method 101 of MIL-STD-202. Code 4772 is mandatory.

Code 4765 and an "X", entered on the SRS, will specify that the component shall be mounted by the normal method.

Code 4766 and an "X", entered on the SRS, will specify that the component shall be mounted by any suitable method.

Code 4773 and a document designation, entered on the SRS, will specify the salt spray mounting method in accordance with the document.

Code. 4877 is the 1006 requirements code (5.4),

Code 4878 is the 1006 except requirements code (5.4).

Code 4782 and an "X", entered on the SRS, will Specify that there shall be no evidence of corrosion, physical damage-or degradation of performance. The use of Code 4782 is mandatory.

Code 3180 and a value, entered on the SRS, will specify the maximum attenuation in db.

Code 3181 and a value, entered on the SRS, will specify the maximum attenuation change in db that exhibits the stability of attenuation.

Code 3182 and a value, entered on the SRS, will specify the maximum insertion loss in db.

Code 3183 and a value, entered on the SRS, will specify the minimum insulation resistance in megohms.

Code 3184 and a value, entered on the SRS, will specify the operating voltage in dc that will cause the switch to rotate, slide or move axially.

Code 3185 and an "X", entered on the SRS, will specify that the component shall be subjected to a power handling capacity test.

Code 3186 and a value, entered on the SRS, will specify the maximum switching time in milliseconds between positions of the switch.

Code 3187 and a number, entered on the SRS, will specify the maximum VSWR.

Supersedes page 5-49 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

5.47 Sand and Dust

Code 4951 is the 1006 test code (5.4).

Code 4952 is the 1006 except test code (5.4).

Code 4960 and an "X", entered on the SRS, will specify to test in accordance with Method 110 of MIL-STD-202.

Code 1539 and an "X", entered on the SRS, will specify that the component shall be reoriented during the test.

Code 6299 and a value, entered on the SRS, will specify the duration of component operation in hours while under exposure.

Code 4956 and an "X", entered on the SRS, will specify that the second 6-hour test shall be performed immediately after temperature stabilization.

Code 4957 is the 1006 requirements code (5.4).

Code 4958 is the 1006 except requirements code (5.4).

Code 4959 and an "X", entered on the SRS, will specify that the component shall show no-evidence of dust penetration.

Code 3191 and a value, entered on the SRS, will specify the maximum attenuation in db.

Code 3192 and a value, entered on the SRS, will specify the maximum insertion loss in db.

Code 3193 and a number, entered on the SRS, will specify the maximum VSWR.

Code 3194 and an "X", entered on the SRS, will specify that the part shall be within tolerance and shall meet design or performance characteristics.

5.48 Seal

---Code_4733 is the 1006 test code (5.4).

Code 4734 is the 1006 except test code (5.4).

Code 4732 and an "X", entered on the SRS, will specify to test in accordance with Method 112 of MIL-STD-202.

Supersedes page 5-50 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 2001 and a value, entered on the SRS, will specify the maximum temperature in degrees Celsius during attenuation measurement.

Code 2002 is the 1006 requirement code (5.4).

Code 2003 is the 1006 except requirement code (5.4).

Code 2004 and a value, entered on the SRS, will specify the maximum change in attenuation at either extreme of the operating frequency, at full input power, or at either extreme of the operating temperature.

NOTE : Paragraph 5.50 has been deleted.

5.51 Shock, Specified Pulse

Code 1501 is the 1006 test code (5.4).

Code 1502 is the 1006 except test code (5.4).

Code 1500 and an “X", entered on the SRS, will specify to test in accordance with Method 213 of MIL-STD-202.

Code 1504 and a letter, entered on the SRS, will specify the applicable test condition letter from Method 213 of MIL-STD-202. Code 1504 is mandatory.

Supersedes page 5-53 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

There are three codes to specify mounting. Only one of these codes may be used. These codes and information concerning them are as follows:

Code 4864 and a document designation, entered on the SRS, will specify that mounting shall be in accordance" with the document. The applicable test name from the reference document should be entered on the SRS in addition to the document designation (5.7).

Code 4685 and an "X", entered on the SRS, will specify that mounting shall be by normal mounting means.

Code 4686 and an "X", entered on the SRS, will specify that mounting shall be by any suitable method.

" Code 1507 is the 1006 requirements code (5.4).

Code 1508 is the 1006 except requirements code (5.4).

Code 1509 and an "X", entered on the SRS, will specify no evidence of physical damage.

Code 3210 and a value, entered on the SRS, will specify the maximum attenuation in db.

Codes 3211 and 3212 and values, entered on the SRS, will specify the attenuation range in db.

Code 3213 and a value, entered on the SRS, will specify the maximum attenuation change that exhibits the stability of attenuation.

Code 3214 and a value, entered on the SRS, will specify the maximum insertion loss in db.

Code 3215 and a value, entered on the SRS, will specify the minimum insulation resistance in megohms.

Code 3216 and a value, entered on the SRS, will specify the maximum resetability error in plus or minus db.

Code 3217 and a number, entered on the SRS, will specify the maximum VSWR.

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

There are two codes available to specify the method of determining mechanical resonance. Only one of the codes may be entered. These codes and information concerning them are as follows:

Code 1533 and an "X", entered on the SRS, will specify that mechanical resonance shall be monitored visually by means of a strobotac.

Code 1534 and an "X", entered on the SRS, will specify that mechanical resonance shall be monitored by electrical output indicators.

Code 1442 and a letter, entered on the SRS, will specify the applicable test circuit letter from Method 310 of MIL-STD-202. The use of Codes 1442 and 1444 is mandatory to specify contact chatter monitoring.

Code 1444 and a letter, entered on the SRS, will specify the applicable test condition letter from Method 310 of MIL-STD-202 that defines the maximum allowable time-duration of contact opening or closing during monitoring.

Code 3243 and an "X", entered on the SRS, will specify the seal test shall be performed after vibration.

Code 1454 is the 1006 requirements code (5.4).

Code 1455 is the 1006 except requirements code (5.4).

Code 1456 and an "X", entered on the SRS, will specify no evidence of physical damage. This code is mandatory when requirements after the high frequency vibration test are to be detailed.

Code 3244 and an "X", entered on the SRS, will specify there shall be no leakage as detected by the continuous escaping of bubbles.

Code 3235 and a value, entered on the SRS, will specify the maximum attenuation in db.

Codes 3236 and 3237 and values, entered on the SRS, will specify the attenuation range in db.

Code 3238 and a value, entered on the SRS, will specify the maximum attenuation change in db that exhibits the stability of attenuation.

Code 3239 and a value, entered on the SRS, will specify the maximum insertion loss in db.

Code 3240 and a value, entered on the SRS, will specify the minimum insulation resistance in megohms.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 3241 and a value, entered on the SRS, will specify the maximum resetability error in plus or minus db.

Code 3242 and a number, entered on the SRS, will specify the maximum VSWR.

"Code 1469 and an "X", entered on the SRS, will specify that the part shall remain within tolerance.

5.57 Vibration, Low Frequency

Code 1465 is the 1006 test code (5.4).

Code 1466 ii the 1006 except test code (5.4).

Code 1467 and an "X", entered on the SRS, will specify to test in accordance with Method 201 of MIL-STD-202. To detail the low frequency vibration test, Code 1467 is mandatory.

Code 4973 and a value, entered on the SRS, will specify the vibration time in minutes in each of three axes. Codes 4973 and 1470 are not to be used together.

Code 1470 and a value, entered on the SRS, will specify the duration in hours of vibration per axis. This code should only be used when the required vibration per axis is other than two hours as specified in Method 201 of MIL-STD-202.

Code 1491 and a letter, entered on the SRS, will specify the applicable test circuit letter from Method 310 of MIL-STD-202. Codes 1491 and , 1492 are mandatory to specify contact chatter monitoring.

Code 1492 and a letter, entered on the SRS, will specify the applicable test condition letter from Method 310 of MIL-STD-202 that defines the maximum allowable time-duration of contact opening or closing during monitoring.

There arethree codes available to specify the method of mounting. Only one may be used. These codes and information concerning them are as follows:

Code 4731 and an "X", entered on the SRS, will specify any suitable mounting method may be used.

Supersedes page 5-60 of 23 May 1975.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.9.8	Flanges	
	UG - type number	
	Input flange	1569
	Ouput flange	1570
	Mating characteristics per specification _____	1568
	Type (Select one)	
	Choke	1571
	Cover	1572
	Contact	1573
	Connection method (Select one)	
	Clamp ring	1574
	Studs	1575
	Threaded holes	1576
	Connection facilities	
	Quantity of devices	1577

Supersedes page 5-69 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.9.9	Connectors	
	Input	
	Type number	1578
	Specification	1579
	output	
	Type number	1580
	Specification	1581
5.9.10	Weight, Maximum	
	Ounces	7022
	Pounds	7023
	Grams	7021
	Kilograms	7024
5.10	ADAPTERS	
5.10.1	Coaxial End Coupling	
	*Equivalent to UG - ____	1606
	*Mates with UG - ____	1607
5.11	ATTENUATORS	
5.11.1	Eliminate Backlash	1631

Supersedes page 5-70 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
5.13.2	*Coupling	
	(Indicate number of positions provided)	1682
5.13.3	Switch Type	
	(Select transfer or nontransfer type)	
	Transfer	
	* ____ pole	1678
	* ____ throw	1679
	Nontransfer	
	* ____ pole	1680
	* ____ throw	1681
5.13.4	Mounting Patterns	
	Pattern number	1684
	Inserts required for tapped hole switches	1685
5.13.5	Return Mechanism Type (Select one)	
	Fail-safe	1687
	Latching	1688
5.13.6	Interlock Circuitry Required	1689

Supersedes page 5-75 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.13.7	Receptacle Pressure	
	(Pressurization required)	1690
5.13.8	Holding Current	
	(Amperes maximum)	1691
5.14	Altitude	
	(Select one test method)	
	Test per 1006 document	3020
	Test per 1006 document except .	3021
	Test per MIL-STD-81O, Method 500	3022
	Duration of operation and measurements (hr)	3023

Supersedes page 5-76 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
5.14 (Cont)	Altitude (Cont)	
	(Select one requirement)	
	Requirement(s) per 1006 document	3027
	Requirement(s) per 1006 document except . .	3028
	Requirement(s) as follows:	
	No degradation of performance	3029
	Test performance requirements	
	Attenuation maximum (db)	3031
	Insertion loss maximum (db)	3032
	VSWR (maximum)	3033
5.15	Attenuation (Fixed and Variable Attenuators)	
	(Select one test method)	
	Test per 1006 document	1698
	Test per 1006 document except .	1699
	Test per MIL-A-3933	1700
	Attenuation Accuracy	Table II

Supersedes page 5-77 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.15 (Cont)	Attenuation (Fixed and Variable Attenuators (Cont	
	Test per MIL-A-24215	1701
	Attenuation shall be measured at minimum, 50 percent, and maximum attenuation.	1703
	(Select one requirement)	
	Requirement(s) per 1006 document	1707
	Requirement(s) per 1006 document except ___.	1708
	Requirements as follows:	
	The measured attenuation shall be	
	____ nominal db	1697
	____ maximum db	1709
	____ minimum db	1710
	Frequency band of	
	DC	1716
	____ minimum GHz	1711
	*____ maximum GHz	1712
	(dB)	

Supersedes page 5-78 of 23 May 1975.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.15 (Cont)	Attenuation (Fixed and Variable Attenuators) (Cont)	
	Accuracy of attenuation (Select one)	
	(± _____ db/db)	1713
	*Over _____ db level plus insertion loss	1714
	(± _____ db)	1715

Supersedes page 5-79 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.17	Attenuation Stability (Fixed Attenuators)	
	(Select one test method)	
	Test per 1006 document	1726
	Test per 1006 document except .	1727
	Test per MIL-A-3933	1728
	Test to be performed	
	Moisture resistance	3140
	Peak power	3141
	Shock, specified impulse	3142
	Temperature change	3143
	Thermal shock	3144
	Vibration, low frequency	3145
	(Select one requirement)	
	Requirement(s) per 1006 document	1730
	Requirement(s)- per 1006 document except .	1731
	Requirement(s) as follows:	
	No evidence of mechanical damage	1732
	Maximum attenuation change ± (dB)	1733

Supersedes page 5-80 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.20 (Cont)	Coupling Variation (Couplers) (Cont)	
	Test per MIL-C-15370.(Cont)	
	Test frequency range	
	*_____ minimum GHz	1760
	*_____ maximum GHz	1761
	(Select one requirement)	
	Requirement(s) per 1006 document	1762
	Requirement(s) per 1006 document except .	1763
	Requirement(s) as follows:	
	Coupling variation	
	_____ db maximum	1764
	*+- db	1765
5.21	Dial Calibration (Variable Attenuators)	
	(Select one test method)	
	Test per 1006 document	1767
	Test per 1006 document except .	1768
	Test per MIL-A-24215	1769
	Check dial calibration at	
	*____ GHz and at	1770
	*____ maximum db attenuation	1771

Supersedes page 5-83 of 23 May 1975.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.21 (Cont)	Dial Calibration (Variable Attenuators) (Cont)	
	(Select one requirement)	
	Requirement(s) per 1006 document	1772
	Requirement(s) per 1006 document except .	1773
	Requirement(s) as follows:	
	(Select one)	
	Dial accuracy	
	+ _____ db	1774
	Dial accuracy	
	± _____ percent	1775
5.22	Dielectric Withstanding Voltage (Reduced Barometric Pressure)	
	(Select one test method)	
	Test per 1006 document	4883
	Test per 1006 document except .	4884
	Test per MIL-STD-202, Method 301.	6300
	MIL-STD-202, Method 105 *Test condition letter	4886

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.22 (Cont)	Dielectric Withstanding Voltage (Reduced Barometric Pressure) (Cont)	
	Test per MIL-STD-202, Method 301.	
	Mounting method (Select one)	
	Any suitable method	3277
	The normal method	3278
	In accordance with (5.7)	6280
	Rate of test voltage application	
	(Select one)	
	Instantaneous	3280
	_____ maximum volts per second	3281
	Test voltage (Select one)	
	_____ (volts dc)	4885
	_____ (volts ac)	4849
	Duration of test voltage (seconds)	4891
	Points of test voltage application	
	Between mutually insulated parts	6292
	Between all insulated parts and ground	6293
	Between current carrying parts and case	6294

Supersedes page 5-85 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.22 (Cont)	Dielectric Withstanding Voltage (Reduced Barometric Pressure) (Cont)	
	Method of connection of test voltage in accordance with (5.7)	4827
	Maximum surge current (milliamps)	6310
	(Select one requirement) .	
	Requirement(s) per 1006 document	4907
	Requirement(s) per 1006 document except .	4908
	Requirement(s) as follows:	
	-No arcing, flashover, breakdown of insulation, or evidence of damage.	4906
	Leakage current (Select one)	
	_____ maximum milliamperes	4894
	_____ maximum microampere	4896
	The part shall remain within tolerance	4901
	No degradation of performance	4902
5.23	Dielectric Withstanding Voltage (Sea Level)	
	(Select one test method)	
	Test per 1006 document	4860
	Test per 1006 document .	4861
	Test per MIL-STD-202 Method 301	4862

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.23 (Cont)	Dielectric Withstanding Voltage (Sea Level) (Cont)	
	Test per MIL-STD-202, Method 301.	
	Test voltage (Select one)	
	(Volts dc)	4854
	(volts ac)	4855
	Duration of test voltage (seconds)	4867
	Rate of test voltage application (Select one)	
	Instantaneous	3275
	_____ maximum volts per second	3276
	Points of test voltage application	
	Between mutually insulated parts	4844
	Between all insulated parts and ground	4845
	Between current carrying parts and case	4846
	Method of connections of test voltage in accordance with (5.7)	6267
	Maximum surge current (milliamps)	4897

Supersedes page 5-87 of 31 December 1974. .

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.23 (Cont)	Dielectric Withstanding Voltage (Sea Level) (Cont)	
	(Select one requirement)	
	Requirement(s) per 1006 document	4873
	Requirement(s) per 1006 document except .	4874
	Requirement(s) as follows:	
	No arcing, lashover, breakdown of insulation, or evidence of damage.	4856
	Leakage current (Select one)	
	_____ maximum milliamps	4875
	_____ maximum milliamps	4817
	The part shall remain within tolerance	4847
	No degradation of performance	4826
5.24	Effective Directivity (Couplers)	
	(Select one test method)	
	Test per 1006 document	1780
	Test per 1006 document except .	1781
	Test per MIL-C-15370	1782

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.24 (Cont)	Effective Directivity (Couplers) (Cont)	
	Test frequency range	
	_____ GHz to	1783
	_____ GHz	1784
	An alternate test shall be conducted.	1785
	(Select one requirement)	
	Requirement(s) per 1006 document	1786
	Requirement(s) per 1006 document except .	1787
	Requirement(s) as follows:	
	Effective directivity shall be _____ minimum db	1788
5.25	Endurance (Switches)	
	(Select one test method)	
	Test per 1006 document	1791
	Test per 1006 document except .	1792
	Test per MIL-S-55041	1793

supersedes page 5-89 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.25 (Cont)	Endurance (Switches) (Cont)	
	*Coupling cycles (indicate number)	1794
	*Coupling cycles per minute.	1795
	VSWR shall be measured after cycling..	1796
	Insertion loss shall be measured after cycling.	1797
	(Select one requirement)	
	Requirement(s) per 1006 document	1798
	Requirement(s) per 1006 document except .	1799
	Requirement(s) as follows:	
	VSWR (maximum)	1800
	Insertion loss (maximum db)	1801
5.26	Frequency Sensitivity (Variable Attenuators)	
	(Select one test method)	
	Test per 1006 document	1804
	Test per 1006 document except .	1805
	Test per MIL-A-24215	1806

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.26 (Cont)	Frequency Sensitivity (Variable Attenuators) (Cont)	
	(Select one requirement)	
	Requirement(s) per 1006 document	1807
	Requirement(s) per 1006 document except .	1808
	Requirement(s) as follows:	
	Maximum variation in attenuation (± db)	1809
5.27	Fungus	
	(Select one test method)	
	Test per 1006 document	4753
	Test per 1006 document except .	4754
	Test per MIL-STD-810 Method 508	4755
	Specimen operation (Select one if required)	
	During exposure	4763
	After exposure	4757
	Duration of test (days) (if other than 28 days)	4756

supersedes page 5-91 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.27 (Cont)	Fungus (Cont)	
	(Select one requirement)	
	Requirement(s) per 1006 document	4759
	Requirement(s) per 1006 document except .	4760
	Requirement(s) as follows:	
	Supplier's certification of compliance may be accepted -in lieu of testing.	4761
	The specimen shall show no evidence of fungus by testing.	4762
5.28	Gage (Adapters)	
	(Select one test method)	
	Test per 1006 document	1813
	Test per 1006 document except .	1814
	Test per MIL-A-22641	1815
	*Complete _____ mating cycles (Class 2 or Class 3 adapter)	1816
	Mating characteristics (Class 1, 4, and 5 adapters)	1817
	Oversize test pin diameter (thousandths of an inch)	1818
	*Plus (ten thousandths of an inch)	1819

Supersedes page 5-92 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.30	High Temperature	
	(Select one test method)	
	Test per 1006 document	3040
	'Test per 1006 document except .	3041
	Test per MIL-STD-810 Method 501	
	*Procedure number .	3042
	Highest operating temperature (deg C)	3044
	*Duration of specimen operation (hour)	3043
	Measurements during and after the test shall be in accordance with the requirements selected.	
	(Select one requirement)	
	Requirement(s) per 1006 document	3047
	Requirement(s) per 1006 document except .	3048
	Requirement(s) as follows:	
	No evidence of damage	3049
	Test performance requirements (Select one or more requirements)	

Supersedes page 5-95 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.30 (Cont)	High Temperature (Cont)	
	Maximum attenuation (db)	3051
	Attenuation range (db to db)	
	*_____ minimum db	3052
	*to _____ maximum db	3053
	Maximum insertion loss (db)	3054
	Resetability error (± maximum db)	3055
	Maximum VSWR	3056
	The part shall be within tolerance and shall meet design or performance characteristics.	3057
5.31	Humidity	
	(Select one test method)	
	Test per 1006 document	4787
	Test per 1006 document except .	4788
	Test per MIL-STD-202 Method 103	4853
	*Test condition letter .	4890
	Polarizing voltage (de)	4793

Supersedes page 5-96 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.35 (Cont)	Low Temperature (Cont)	
	Test per 1006 document except .	3064
	Test per MIL-STD-810 Method 502	3065
	Storage temperature (minus deg C)	3066
	*Duration of maintained temperature [hour(s)]	3067
	Lowest operating temperature (deg C)	3069
	*Duration of specimen operation [hour(s)]	3068
	Measurements during and after the test shall be in accordance with the requirements selected.	
	(Select one requirement)	
	Requirement(s) per 1006 document	3070
	Requirement(s) per 1006 document except .	3071
	Requirement(s) as follows:	
	No damage and capable of continuous and intermittent operation.	3072

Supersedes page 5-103 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
5.35 (Cont)	Low Temperature (Cont)	
	Test performance requirements (Select one or more requirements)	
	Maximum attenuation (db) -	3074
	Attenuation range (db to db)	
	*_____ db	3075
	*to - db	3076
	Maximum insertion loss (db)	3077
	Maximum resetability error (± db)	3078
	Maximum VSWR	3079
	The part shall be within tolerance and shall meet design or performance characteristics.	3080
5.36	Moisture Resistance	
	(Select one test method)	
	Test per 1006 document .	1390
	Test per 1006 document except .	1391
	Test per MIL-STD-202 Method 106	1397

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.36 (Cont)	Moisture Resistance (Cont)	
	Test per MIL-STD-202, Method 106 (Cent)	
	Loading voltage (Select one)	
	dc	4981
	ac	4980
	Polarization voltage (volts dc) (if other than 100 volts dc)	1395
	Step 7A not applicable	4985
	Step 7B not applicable	4986
	(Select one requirement)	
	Requirement(s) per 1006 document	1399
	Requirement(s) per 1006 document except .	1400
	Requirement(s) as follows:	
	*No evidence of corrosion or physical damage	1396
	Test performance requirements (Select one or more requirements)	
	Maximum attenuation (db)	3170
	Attenuation range	
	* _____ db to .	3171
	* _____ db	3172

Supersedes page 5-105 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
5.36 (Cont)	Moisture Resistance (Cont)	
	Attenuation stability	3173
	Maximum insertion loss (db)	3174
	Minimum insulation resistance (megohms)	3175
	Maximum VSWR	3176
	The part shall remain within tolerance	1398
	No degradation of performance	1392
5.37	Operating Voltage (Switches)	
	(Select one test method) .	
	Test per 1006 document	1882
	Test per 1006 document except .	1883
	Test per MIL-S-55041	1884
	(Select one requirement)	
	Requirement(s) per 1006 document	1885
	Requirement(s) per 1006 document except .	1886
	Requirement(s) as follows:	
	The switch shall rotate, slide or move axially from the nonenergized position upon the application of _____ volts.	1887

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTER I ST I C NAME	CODE
5.37 (Cont)	Operating Voltage (Switches) (Cont)	
	*Nature of the voltage (Select one)"	
	ac	1888
	dc	1889
5.38	Peak Power (Fixed and Variable Attenuators)	
	(Select one test method)	
	Test per 1006 document	1891
	Test per 1006 document except .	1892
	Test per MIL-A-3933	1893
	Test per MIL-A-24215	1894
	Applied power (kilowatts)	1895
	"*Duration of application [hour(s)]	1896
	Applied power (kilowatts)	1897
	*Adjusted maximum frequency (GHz)	1898
	Measurements after test	
	Attenuation	1899
	Attenuation change	1900
	Measurements during test	
	Dial calibration	1901
	VSWR	1902

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.38 (Cont)	Peak Power (Fixed and Variable Attenuators) (Cont)	
	(Select one requirement)	
	Requirement(s) per 1006 document	1903
	Requirement(s) per 1006 document except .	1904
	Requirement(s) as follows:	
	VSWR _____ maxi mum	1905
	Change in attenuation maximum (db)	1906
	Dial calibration requirements shall be met. .	1907
	No evidence of mechanical damage	1908
5.39	Power Dissipation (Couplers)	
	(Select one test method)	
	Test per 1006 document	1911
	Test per 1006 document except .	1912
	Test per MIL-C-15370	1913
	Secondary line power dissipation determined between	
	* _____ GHz and	1914
	* _____ GHz	1915

Supersedes page 5-108 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (ML)

REF PARA	CHARACTERISTIC NAME	CODE
5.39 (Cont)	Power Dissipation (Couplers) (Cont)	
	Primary line CW power rating (watts)	1916
	Secondary line VSWR measurement at mid frequency of the "range	
	* _____ GHz (mid frequency)	1917
	The alternate test shall be conducted	1918
	(Select one requirement)	
	Requirement(s) per 1006 document	1919
	Requirement(s) per 1006 document except .	1920
	Requirement(s) as follows:	
	Secondary line VSWR shall not exceed ____	1921
5.40	Power Handling Capacity (Switches)	
	(Select one test method)	
	Test per 1006 document	1925
	Test per 1006 document except .	1926
	Test per MIL-S-55041	1927
	Test shall be conducted with	
	* _____ KW peak power	1928
	* _____ watts average power	1929
	* _____ psig line pressure	1930

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (ML)

REF PARA	CHARACTERISTIC NAME	CODE
5.40 (Cont)	Power Handling Capacity (Switches) (Cont)	
	(Select one requirement)	
	Requirement(s) per 1006 document	1931
	Requirement(s) per 1006 document except ___	1932
	Requirement(s) as follows:	
	There shall be no voltage breakdown no-r evidence of deterioration such as arcing, high current surges, and excessive release of moisture.	1933
	Temperature of the switch shall not exceed _____ degrees C.	1934
5.41	Radio Noise	
	(Select one test method)	
	Test per 1006 document	1936
	Test per 1006 document except .	1937
	Test per MIL-STD-461 and 462	1938
	*Test method number .	1939
	*Equipment class number .	1940
	Appendix Table A -	1941

Supersedes page 5-110 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.41 (Cont)	Radio Noise (Cont)	
	(Select one requirement)	
	Requirement(s) per 1006 document	1942
	Requirement(s) per 1006 document except .	1943
	Requirement(s) as follows:	
	Narrow band radiated emission field	
	db above 1 microvolt per metre maximum radiation	1944
	Broadband and pulsed CW radiated emission field	
	_____ db above 1 microvolt per metre per megacycle maximum radiation	1945
5.42 -	Rain	
	(Select one test method)	
	Test per 1006 document	3086
	Test per 1006 document except .	3087
	Test per MIL-STD-810 Method 506	3088
	Simulated rainfall (Select one)	
	_____ inches/hr	3089
	*+ _____ inches/hr	3090

Supersedes page 5-111 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.42 (Cont)	Rain (Cont)	
	Duration of exposure	
	_____ minutes	3091
	_____ hours	3093
	*Chamber temperature (deg C)	3092
	Measurements after the test shall be in accordance with the requirements selected.	
	(Select one requirement)	
	Requirement(s) per 1006 document	3095
	Requirement(s) per 1006 document except .	3096
	Requirement(s) as follows:	
	No evidence of deterioration of quality	3097
	Test performance requirements (Select one or more requirements)	
	Maximum attenuation (db)	3099
	Attenuation range	
	* db to _____	3100
	* _____ db	3101
	Attenuation stability (db change)	3102

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.42 (Cont)	Rain (Cont)	
	Maximum insertion loss (db)	3103
	Minimum insulation resistance (megohms)	3104
	Maximum VSWR	3105
	The part shall be within tolerance and shall meet design or performance characteristics.	3106
5.43	Release Voltage (Switches)	
	(Select one test method)	
	Test per 1006 document	1946
	Test per 1006 document except .	1947
	Test per MIL-S-55041	1948
	(Select one requirement)	
	Requirement(s) per 1006 document	1949
	Requirement(s) per 1006 document except .	1950
	Requirement(s) as follows:	
	Upon reduction of the operating voltage to volts, the switch shall rotate, slide or move axially from the energized position to the unenergized position.	1951

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.43 (Cont)	Release Voltage (Switches) (Cont)	
	*Nature of the voltage (Select one)	
	dc	1952
	ac	1953
5.44	Repeatability (Variable Attenuators)	
	(Select one test method)	
	Test per 1006 document	1955
	Test per 1006 document except .	1956
	Test per MIL-A-24215 .	1957
	Attenuation cycles	
	Operate _____ cycles from minimum through maximum attenuation.	1958
	Measurements after the test shall be in accordance with the requirements selected.	
	(Select one requirement)	
	Requirement(s) per 1006 document	1959
	Requirement(s) per 1006 document except .	1960

Supersedes page 5-114 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.44 (Cont)	Repeatability (Variable Attenuators) (Cont)	
	Requirement(s) as follows:	
	After the test, the component shall meet the" following performance require-ments (Select one or more)	
	Maximum attenuation (db)	1961
	Attenuation range	
	* _____ db to	1962
	* _____ db	1963
	Dial calibration	
	+ _____ db	1964
	+ _____ percent	1965
	*Frequency (GHz)	1966
	Frequency sensitivity (± db)	1967
	Maximum insertion loss (db)	1968
	Power capability	
	*Maximum power (watts)	1969
	*Maximum VSWR	1970
	*Dial accuracy (± db)	1971
	Temperature coefficient (db/db/deg C)	1972
	Maximum VSWR	1973

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTER I ST I C NAME	CODE
5.46	Salt Spray (Corrosion)	
	(Select one test method)	
	Test per 1006 document	4769
	Test per 1006 document except .	4770
	Test per MIL-STD-202 Method 101	4771
	*Test condition letter .	4772

Supersedes page 5-116 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.46 (Cont)	Salt Spray (Corrosion) (Cont)	
	Test per MIL-STD-202, Method 101 (Cont)	
	Mounting method (Select one)	
	The normal method	4765
	Any suitable method	4766
	In accordance with (5.7)	4773
	Measurements after the test shall be in accordance with the requirements selected.	
	(Select one requirement)	
	Requirement(s) per 1006 document	4877
	Requirement(s) per 1006 document except .	4878
	Requirement(s) as follows:	
	*There shall be no evidence of corrosion, physical damage or degradation of performance.	4782
	Test performance requirements (Select one or more requirements)	
	Maximum attenuation (db)	3180
	Attenuation stability (db change)	3181
	Maximum insertion loss (db)	3182
	Minimum insulation resistance (megohms)	3183

Supersedes page 5-117 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.46 (Cont)	Salt Spray (Corrosion) (Cont)	
	Operating voltage (volts dc)	3184
	Power handling capacity	3185
	Switching time (milliseconds)	3186 "
	Maximum VSWR	3187
5.47	Sand and Dust	
	(Select one test method)	
	Test per 1006 document	4951
	Test per 1006 document except .	4952
	Test per MIL-STD-202 Method 110	4960
	Reorient component during exposure	*1539*
	Operate component during test	
	*Duration of operation and measurement (hours-)	6299
	Perform second 6-hour test immediately after temperature stabilization	4956
	Measurements after the test shall be in accordance with the requirements selected.	

Supersedes page 5-118 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.48 (Cont)	Seal (Cont)	
	Measurements after test	
	Insulation resistance	3196
	(Select one requirement)	
	Requirement(s) per 1006 document	4744
	Requirement(s) per 1006 document except .	4745
	Requirement(s) as follows:	
	Evidence of leakage (Select one)	
	A/W test method sensitivity	4746
	No visible bubbles indicative of leakage	4748
	Requirements after test	
	Minimum insulation resistance (megohms)	3197
	The part shall remain within tolerance	4758
5.49	Sensitivity of Attenuation (Fixed Attenuators)	
	(Select one test method)	
	Test per 1006 document	1993
	Test per 1006 document except .	1994

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.49 (Cont)	Sensitivity of Attenuation (Fixed Attenuators) (Cont)	
	Test per MIL-A-3933	1995
	Attenuation measurements	
	*At minimum frequency (de)	2005
	*At minimum frequency (GHz)	1996
	*At maximum frequency (GHz)	1997
	*At full input power (watts)	1998
	*At the reference power (watts)	1999
	*At minimum temperature (deg C)	2000
	*At maximum temperature (deg C)	2001
	(Select one requirement)	
	Requirement(s) per 1006 document	2002
	Requirement(s) per 1006 document except .	2003
	Requirement(s) as follows:	
	Change in attenuation shall not exceed _____ db	2004

Supersedes page 5-122 of 23 May 1975.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.51	Shock, Specified Pulse	
	(Select one test method)	
	Test per 1006 document	1501
	Test per 1006 document except .	1502
	Test per MIL-STD-202 Method 213.	1500
	*Test condition letter .	1504
	Mounting method (Select one)	
	In accordance with (5.7)	4684
	Normal method	4685

Supersedes page 5-123 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (ML)

REF PARA	CHARACTERISTIC NAME	CODE
5.51 (Cont)	Shock, Specified Pulse (Cont)	
	Any suitable method	4686
	Measurements after the test shall be in accordance with the requirements selected.	
	(Select one requirement)	
	Requirement(s) per 1006 document	1507
	Requirement(s) -per 1006 document except .	1508
	Requirement(s) as follows:	
	*No evidence of mechanical damage	1509
	Test performance requirements (Select one or more requirements)	
	Maximum attenuation (db)	3210
	Attenuation range	
	*_____ db	3211
	*to _____ db	3212
	Attenuation stability (db change)	3213
	Maximum insertion loss (db)	3214
	Minimum insulation resistance (megohms)	3215

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
5.51 (Cont)	Shock, Specified Pulse (Cont)	
	Maximum resetability error (± db)	3216
	Maximum VSWR	3217
	The part shall be within tolerance and shall meet design or performance characteristics.	3218
5.52	Switching Time (Switches)	
	(Select one test method)	
	Test per 1006 document	1985
	Test per 1006 document except .	1986
	Test per MIL-S-55041	1987
	(Select one requirement)	
	Requirement(s) per 1006 document	1988
	Requirement(s) per 1006 document except .	1989
	Requirement(s) as follows:	
	Time between energized and unenergized positions shall not exceed _____ milliseconds .	1990
5.53	Temperature/Altitude	
	(Select one test method)	
	Test per 1006 document	3109

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
5.53 (Cont)	Temperature/Altitude (Cont)	
	Test per 1006 document except .	3110
	Test per MIL-T-5422	3111
	(Select one requirement)	
	Requirement(s) per 1006 document	3112
	Requirement(s) per 1006 document except .	3113
	Requirement(s) as follows:	
	No evidence of voltage breakdown	3114
	Performance requirements (Select one or more requirements) .	
	After test	
	Maximum attenuation (db)	3115
	Maximum insertion loss (db)	3116
	Maximum VSWR	3117
	During test	
	Power handling capacity	3118

Supersedes page 5-126 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
5.56 (Cont)	Vibration, High Frequency (Cont)	
	Monitoring during test per MIL-STD-202, Method 310.	
	*Test circuit number	1442
	*Test condition letter	1444
	Measurements after the test shall be in accordance with requirements selected.	
	Perform seal test after vibration	3243
	(Select one requirement)	
	Requirement(s) per 1006 document	1454
	Requirement(s) per 1006 document except ____	1455
	Requirement(s) as follows:	
	*No evidence of physical damage	1456
	No leakage as detected by escaping bubbles	3244
	Test performance requirements (Select one or more requirements)	
	Maximum attenuation (db)	3235
	Attenuation range	
	*_____ db	3236
	*to _____ db	3237

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
5.56 (Cont)	Vibration, High Frequency (Cont)	
	Attenuation stability (db change)	3238
	Maximum insertion loss (db)	3239
	Minimum insulation resistance (megohms)	3240
	Maximum resetability error (± db)	3241
	Maximum VSWR	3242
	The part shall remain within tolerance	*1469*
5.57	Vibration, Low Frequency	
	(Select one test method)	
	Test per 1006 document	1465
	Test per 1006 document except _____.	1466
	Test per MIL-STD-202 Method 201	1467
	Duration of vibration in each axis (Select one)	
	_____ minutes	4973
	_____ hours	1470

Supersedes page 5-132 of 23 May 1975.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (ML)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
5.57 (Cont)	Vibration, Low Frequency (Cont)	
	Monitoring during test per Method 310, MIL-STD-202	
	*Test circuit letter	1491
	*Test condition letter	1492
	Mounting method (Select one)	
	Any suitable method	4731
	Normal method	4730
	In accordance with (5.7)	4729
	Direction of motion	
	On center line of most sensitive axis	4979
	90 degrees from center line of most sensitive axis	4978
	Direction in accordance with (5.7)	4995
	Electrical load (ohms)	1472
	Pressurization test after vibration test	3245
	Total displacement (inches)	3246
	*at _____ Hz and	3247
	*at _____ Hz	3248

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (ML)

REF PARA	CHARACTERISTIC NAME	CODE
5.57 (Cont)	Vibration, Low Frequency (Cont) .	
	Measurements after the test shall be in accordance with the requirements selected.	
	(Select one requirement)	
	Requirement(s) per 1006 document	1474
	Requirement(s) per 1006 document except .	1475
	Requirement(s) as follows:	
	*No evidence of physical damage	1476
	No leakage as detected by escaping bubbles..	3250
	Test performance requirements (Select one or more requirements)	
	Maximum attenuation (db)	3251
	Attenuation range	
	*_____ db	3252
	*to _____ db	3253
	Attenuation stability (db change)	3254
	Maximum insertion loss (db)	3255
	Minimum insulation resistance (megohms)	3256

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENT LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.57 (Cont)	Vibration, Low Frequency (Cont)	
	Maximum resetability error (± db)	3257
	Maximum VSWR	3258
	The part shall remain within tolerance	1480
5.58	Vibration, Random	
	(Select one test method)	
	Test per 1006 document	1425
	Test per 1006 document except .	1426
	Test per MIL-STD-202 Method 214	1427
	*Test condition number and letter	1428
	*Duration of application (Select one)	
	Hours	1431
	Minutes	1438
	Monitoring instrumentation (Select one)	
	Any suitable instrumentation system	1452
	Calibrated ac to dc converter and strip chart recorder	1453
	Calibrated oscilloscope	1459

Supersedes page 5-135 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.58 (Cont)	Vibration, Random (Cont)	
	Number of test points	1430
	Location of monitoring points (Select one)	
	Any suitable location	1439
	As close as practical to test specimen	1462
	Method of mounting (Select one)	
	Any suitable method	4977
	Normal method	4976
	Mount in accordance with (5.7)	4975
	Pressurization test required	3260
	Measurements during and after test shall be in accordance with the requirements selected.	
	(Select one requirement)	
	Requirement(s) per 1006 document	1434
	Requirement(s) per 1006 document except .	1435
	Requirement(s) as follows:	
	No evidence of physical damage	1436
	No leakage as detected by escaping bubbles	3261

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.58 (Cont)	Vibration, Random (Cont)	
	Test performance requirements (Select one or more requirements)	
	Maximum attenuation (db)	3262
	Attenuation range	
	*_____ db	3263
	*to _____ db	3264
	Attenuation stability (db change)	3265
	Maximum insertion loss (db)	3266
	Minimum insulation resistance (megohms)	1441
	Maximum resetability error (± db)	3268
	Maximum VSWR	3269
	The part shall be within tolerance and shall meet design or performance characteristic CS.	3270
5.59	Voltage Standing Wave Ratio	
	(Select one test method)	
	Test per 1006 document	2018
	Test per 1006 document except .	2019
	Test per (see 5.7)	2020

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
5.59 (Cont)	Voltage Standing Wave Ratio (Cont)	
	Test per VSWR Test Table III	Table III
	(Enter applicable codes and values on SRS from Table III	
	Measure VSWR by reflectometer system	
	Ratio meter indication	
	*Reflection coefficient (P)	2022
	VSWR measurement frequency range	
	DC	2021
	_____ GHz minimum	2023
	* _____ GHz maximum	2024
	(Select one requirement)	
	Requirement(s) per 1006 document	2025
	Requirement(s) per 1006 document except .	2026
	Requirement(s) as follows:	
	Attenuators	
	Maximum VSWR	
	per Table III	*2027*
	at minimum attenuation	*2028*

Supersedes page 5-138 of 23 May 1975.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SECTION 6

USE OF AEDPS

6.1 Procedure

The step by step procedure contained in MIL-STD-35 is applicable to Microwave/Waveguide Components.

Supersedes page 6-1 and 6-2 of 31 December 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Custodians:
Army - MI

Review activities:
Army - AT
Army - AV
Army - EL
Army - ME
Army - MR
Army - SL
Army - WC

User activity:
Army - MU

Preparing activity:
Army - MI

(Project EDS-A101)

New page.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Missile Command
ATTN: DRSMI-RCS
Redstone Arsenal, Al 35809

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.