| INCH-POUND |

MIL-M-48428A (AR)
AMENDMENT 2
24 July 1992

SUPERSEDING
AMENDMENT 1
17 April 1991

MILITARY SPECIFICATION

MICROWAVE CHASSIS ASSEMBLY: 10549047

This amendment forms a part of Military Specification MIL-M-48428A (AR), dated 15 October 1990, and is approved for use by the U.S. Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* 2.1.1: Delete the following:

"MIL-STD-2000 - Standard Requirements for Soldering Electrical and Electronic Equipment"

* 2.1.2: Add the following:

"12950877 - Requirements for Soldering Electrical and Electronic Assemblies"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.

PAGE 4

* 3.301: **Delete in its entirety and substitute the following:**

'3*3.1 vibration. The microwave chassis shall not suffer damage and shall meet the requirements of 3.4 and 3.5 after exposure to the equivalent of 6000 miles of track-laying vehicle operational vibrations as defined by M1L-STD-810 narrowband random-on-random data for equipment installed on the deck of the M113 armored personnel carrier.

*** 3.3.3: Delete in entirety and substitute the following:**

"*3.3.3* Altitude Operating The microwave chassis shall meet the requirements of 3.4 and *3.5* after exposure to barometric pressure encountered at 10,000 feet above sea level (20.6 inches of Hg.)."

PAGE 5 & 6

Table I.: Delete "PRF 19.978 KHz +1 Hz[w] (3 places).sand substitute: 'PRF 19.978 KHz +lHz[n] (3 places).

PAGE 7

*** 3.5.2.1: Delete: '19.978 KHz +** 1 Hz" **and** substitute :19.978 KHz **+ lHz[m]**

PAGE 10

*** 3.7: Delete in its entirety and substitute the following:**

"3.7 Soldering. All soldering shall be **in accordance** with the requirements of Note 2 of Drawing 12950877.[w]

* 4.7.1.1: Delete "514.4[m] and substitute '514".

* 4.7.1.2: Delete '516.4" and substitute "516".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.

PAGE 21

* 4.7.1.3: **Delete** in entirety and substitute the following:

"4.7.1.3 **Altitude Operating. This test shall be performed as specified in Procedure II, Method 500, of MIL-STD-810. The operational checkout shall be as specified In** 4.7.2 and 4.7.3 **for compliance with 3.3.3."**

* 407.1.4.1: **Delete '501.3 and substitute "501".**

* 4.7.1.4.2: Delete "502.3" and substitute "502".

* 4.7.1.5: **Delete '507.3" and substitute "507".**

PAGE 28

*** 4.8: Delete in entirety and substitute:**

"4.8 **Soldering. Soldering processes shall be inspected by certified Inspectors to the requirements and acceptance criteria of Note** 2 **of Drawing 12950877 as specified in paragraph 3.7."**

The margins of this amendment are marked with an asterisk *or* vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

custodian:
Army -AR

Preparing activity:
Army-AR

(Project 1285-A803)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.