MIL-C-14518D
24 September 1985
SUPERSEDING
MIL-C-14518C
20 June 1979

MILITARY SPECIFICATION

CONNECTOR, BRIDLE LINE: SHEAVE TYPE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a sheave-type, bridle-line connector for use in mooring pneumatic floats carrying the superstructure of floating bridges.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

QQ-S-781	- Strapping, Steel, and Seals.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-B-640	- Boxes, Fiberboard, Corrugated, Triple-Wall.

MILITARY

MIL-C-46168	- Coating, Aliphatic Polyurethane, Chemical Agent Resistant.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research and Development Center, ATTN: STRBE-DS, Fort Belvoir, VA 22060-5606 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 5420

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:23Z
Check the source to verify that this is the current version before use.

MIL-G-20241	- Gasket Material, Wool Felt, Impregnated, Adhesive, Pressure-Sensitive.
MIL-S-81733	- Sealant, Corrosion Inhibiting.
MIL-T-704	- Treatment and Painting of Materiel.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-889	- Dissimilar Metals.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWING

ME

D7941	- Connector, Bridle Line: Sheave Type.

(Copies of specifications, standards, and drawings required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951	- Standard Practice for Commercial Packaging.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specifications sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:23Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Description. The bridle-line connector shall be in accordance with drawing D7941 and as specified herein.

3.1.1 Drawing. The drawing forming a part of this specification is an end product drawing. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 4.3 and 6.3).

3.3 Material. Material shall be as specified herein and on the drawing. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification.

3.3.1 Material deterioration and control. The bridle-line connector shall be fabricated from compatible materials, inherently corrosion and deterioration resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable storage and operating environments to which the bridle-line connector may be exposed.

3.3.1.1 Dissimilar metals. Dissimilar metals, as defined in MIL-STD-889, shall be electrically insulated from one another to minimize or prevent galvanic corrosion. Insulation may be provided by an insulating barrier such as a corrosion inhibiting sealant conforming to MIL-S-81733 or chromate tape conforming to MIL-G-20241. Protection against corrosion could also be obtained by exclusion of the electrolyte if feasible.

3.3.1.2 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with components and sub-components, and shall make information available, upon request, to the contracting officer or designated representative.

3.3.2 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the bridle-line connector may be newly fabricated from recovered materials to the maximum extent practicable, provided the bridle-line connector produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the bridle-line connector.

3.4 Performance. The connector shall withstand a load of 5,000 pounds for not less than 10 seconds without failure or permanent deformation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:23Z
Check the source to verify that this is the current version before use.

3.5 Identification marking. The connector shall be metal-die stamped as shown on the drawing. Die stamping shall be legible after painting.

3.6 Treatment and painting. The connector shall be cleaned, treated, and painted as specified in MIL-T-704. Finish coat shall conform to MIL-C-46168, green No. 383. Contact surfaces, regardless of whether such contact is between similar or dissimilar metals, shall be cleaned, treated, and painted prior to assembly.

3.7 Workmanship. The fabricated connector shall be free of sharp edges, slivers, or burrs. Rivets shall fill the holes completely and the rivet heads shall be in full contact with the surface of the member.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials are manufactured, examined, and tested in accordance with referenced specifications, standards, and drawing, as applicable.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.6).

4.3 First article inspection.

4.3.1 Examination. The first article shall be examined for the defects specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Test. The first article shall be tested as specified in 4.5.2. Failure of the test shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination and test shall be in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 202610-18T03:23Z
Check the source to verify that this is the current version before use.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined as specified in 4.5.1. AQL shall be 2.5 percent defective for major defects and 4.0 percent defective for minor defects.

4.4.3 Test. Samples selected in accordance with 4.4.1 shall be tested as specified in 4.5.2. AQL shall be 2.5 percent defective.

4.5 Inspection procedure.

4.5.1 Examination. The connector shall be examined as specified herein for the following defects:

Major

101. Nonconformance to the dimensions shown on the drawings.
102. Material not as specified.
103. Workmanship not as specified.
104. Components missing or not as specified.
105. Materials are not resistant to corrosion and deterioration or treated to be resistant to corrosion and deterioration for the applicable and operating environments.
106. Dissimilar metals as defined in MIL-STD-889 are not effectively insulated from each other.
107. Contractor does not have documentation available for identification of material, material finishes, or treatment.
108. Used, rebuilt, or remanufactured components, pieces or parts incorporated in the generator sets.

Minor

201. Identification marking incorrect, missing, or illegible.
202. Treatment and painting not as specified.

4.5.2 Performance test. Subject the connector to a static load of 5,000 pounds for not less than 10 seconds. Apply the load by pulling on the sheaves in opposite directions with 1/2-inch wire rope. Any evidence of rupture or permanent deformation shall constitute failure of this test.

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a complete pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

Source: https://assist.dla.mil -- Downloaded: 202640-18T03:23Z
Check the source to verify that this is the current version before use.

109. Box closure not as specified for level A or B.
110. Connectors not preserved in accordance with the referenced documents for commercial.
111. Connectors packed together in quantities exceeding the size or weight limitations for level A or B.
112. Strapping not as specified in level A.
113. Packing not in accordance with the referenced document for commercial.
114. Marking missing, illegible, incorrect or incomplete for level A, level B, or commercial.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or commercial as specified (see 6.2).

5.1.1 Level A. Each connector shall be placed in a close-fitting box conforming to PPP-B-636, W6c, style optional. Cushioning shall be provided to prevent movement within the box. Box closure and sealing shall be in accordance with method V, of the appendix to the box specification.

5.1.2 Commercial. Connectors shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, level B, or commercial, as specified (see 6.2).

5.2.1 Level A. The connectors, preserved as specified in 5.1, shall be packed together in close-fitting boxes conforming to PPP-B-621, class 2, style optional, or PPP-B-601, overseas type, style optional; in quantities not to exceed the weight limitation of the box. Closure and strapping shall be in accordance with the appendix to the applicable box specification. Strapping shall conform to QQ-S-781, class 1, type I or IV, finish B, size as applicable.

5.2.2 Level B. The connectors, preserved, as specified in 5.1, shall be packed together in close-fitting boxes conforming to PPP-B-640, class 2, style optional or PPP-B-636, V3c, V11c, V13c, or V15c, style optional, in quantities not to exceed the gross weight or size limitation of the applicable box. Box closure and strapping shall be in accordance with the appendix to the applicable box specification.

5.2.3 Commercial. The connectors, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Marking.

5.3.1 Levels A and B. Marking for levels A and B shall be in accordance with MIL-STD-129.

5.3.2 Commercial. Marking for commercial packaging shall be in accordance with ASTM D 3951. In addition, weight and cube data shall be marked on shipping containers.

Source: https://assist.dla.mil -- Downloaded: 202640-18T03:23Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The bridle-line connector is intended for use in the anchorage of floating bridges for connectiing bridle lines of floating supports of superstructure to main anchorage (shore-to-shore) cables.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. When a first article is required for inspection and approval, and the number of units required (see 3.2).
c. Degree of preservation and packing required (see 5.1 and 5.2).

6.3 First article. When a first article inspection is required, the items should be a preproduction model. The first article should consist of one unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, tests and approval of the first article test results and disposition of the documents' first articles.

Custodian:
Army - ME

Review activity:
Army - SM

User activity:
Navy - MC

Preparing activity:
Army - ME

Project 5420-0157

Source: https://assist.dla.mil -- Downloaded: 202610-18T03:23Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:23Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Belvoir R&D Center
ATTN: STRBE-DS
Fort Belvoir, VA 22060-5606

Source: https://assist.dla.mil -- Downloaded: 202640-18T03:23Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-14518D	Connector, Bridle Line: Sheave Type

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil - Downloaded: 2026-10-18T03:23Z
Check the source to verify that this is the current version before use.