INCH POUND

MIL-C-14518E
06 November 1992
SUPERSEDING
MIL-C-14518D
24 September 1985

MILITARY SPECIFICATION

CONNECTOR, BRIDLE LINE: SHEAVE TYPE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a sheave-type, bridle-line connector for use in mooring pneumatic floats carrying the superstructure of floating bridges.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development, and Engineering Center, ATTN: SATBE-TSE, Fort Belvoir, VA 22060-5606 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5420

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:23Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-B-640	- Boxes, Fiberboard, Corrugated, Triple-Wall.

MILITARY

MIL-T-704	- Treatment and Painting of Materiel.
MIL-C-46168	- Coating, Aliphatic Polyurethane, Chemical Agent Resistant.
MIL-C-53039	- Coating, Aliphatic Polyurethane, Single Component, Chemical Agent Resistant.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-889	- Dissimilar Metals.

(Unless otherwise indicated, copies of federal and military specifications and standards are available form the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government drawings. The following other Government drawings form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those in effect on the date of the solicitation.

DRAWING

ME

D 7941	- Connector, Bridle Line: Sheave Type.

(Copies of drawings required by contractors in connection with specific acquisition functions should be obtained form the USA Belvoir Research, Development, and Engineering Center, ATTN: SATBE-JBS, Fort Belvoir, VA 22060-5606.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of

Source: https://assist.dla.mil -- Downloaded: 202610-18T03:23Z
Check the source to verify that this is the currentversion before use.

the DoDISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3953	- Strapping, Flat Steel and Seals.
D 4675	- Selection and use of Flat Strapping Material.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, (except for related associated detail specifications, specification sheets, or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The bridle-line connector shall be in accordance with drawing D 7941 and as specified herein.

3.1.1 Drawing. The drawing forming a part of this specification is an end product drawing. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 First article. Unless otherwise specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.3 Material. Material shall be as specified herein and on the drawing. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification.

3.3.1 Material deterioration prevention and control. The bridle-line connector shall be fabricated from compatible materials, inherently corrosion resistant, or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operating and storage environments to which the bridle-line connector may be exposed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:23Z
Check the source to verify that this is the current version before use.

3.3.1.1 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion. Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889

3.3.1.2 Identification of materials and finishes. The contractor shall identify the specific material, material finish, or treatment for use with components and subcomponents, and shall make information available, upon request, to the contracting officer or designated representative.

3.3.2 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces, and parts incorporated in the bridle-line connector may be newly fabricated from recovered materials to the maximum extent practicable, provided the bridle-line connector produced meets all other requirements of this specification. Used, rebuilt, or remanufactured components, pieces, and parts shall not be incorporated in the bridle-line connector.

3.4 Performance. The connector shall withstand a load of 5000 pounds for not less than 10 seconds without failure or permanent deformation.

3.5 Identification marking. The connector shall be metal-die stamped as shown on the drawing. Die stamping shall be legible after painting.

3.6 Treatment and painting. The connector shall be cleaned, treated, and painted as specified in MIL-T-704. However, the finish coat shall be green 383, color 34094, conforming to MIL-C-46168 or MIL-C-53039. Contact surfaces, regardless of whether such contact is between similar or dissimilar metals, shall be cleaned, treated, and painted prior to assembly.

3.7 Workmanship. The fabricated connector shall be free of sharp edges, slivers, or burrs. Rivets shall fill the holes completely and the rivet heads shall be in full contact with the surface of the member.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202610-18T03:23Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Component and material inspection. The contractor is responsible for insuring that components and materials are manufactured, examined, and tested in accordance with referenced specifications, standards, and drawing, as applicable.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.6).

4.3 First article inspection.

4.3.1 Examination. The first article shall be examined for the defects specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Test. The first article shall be tested as specified in 4.5.2. Failure of the test shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination shall be in accordance with MIL-STD-105. Sample size shall be determined by using MIL-STD-105, table I and table IIa. A lot shall be accepted when zero defects are found and rejected when one or more defects are found.

4.4.2 Examination. Samples selected as specified in 4.4.1 shall be examined for the defects specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4.3 Test. Samples selected in accordance with 4.4.1 shall be tested as specified in 4.5.2.

4.5 Inspection procedure.

4.5.1 Examination. The connector shall be examined as specified herein for the following defects:

Source: https://assist.dla.mil -- Downloaded: 202610-18T03:23Z
Check the source to verify that this is the current version before use.

Major

101. Components missing or not as specified (see 3.1).
102. Nonconformance to the dimensions shown on the drawings (see 3.1.1).
103. Material not as specified (see 3.3).
104. Materials are not resistant to corrosion and deterioration or treated to be resistant to corrosion and deterioration for the applicable storage and operating environments (see 3.3.1).
105. Dissimilar metals as defined in MIL-STD-889 are not effectively insulated from each other (see 3.3.1.1).
106. Contractor does not have documentation available for identification of material, material finishes, or treatment (see 3.3.1.2)
107. Used, rebuilt, or remanufactured components, pieces or parts incorporated in the bridle-line connector (see 3.2).
108. Workmanship not as specified (see 3.7).

Minor

201. Identification marking incorrect, missing, or illegible (see 3.5).
202. Treatment and painting not as specified (see 3.6).

4.5.2 Performance test. Subject the connector to a static load of 5000 pounds for not less than 10 seconds. Apply the load by pulling on the sheaves in opposite directions with 1/2-inch wire rope. Any evidence of rupture or permanent deformation shall constitute failure of this test.

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a complete pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105. Sample size shall be determined by using MIL-STD-105, table I and table IIa. A lot shall be accepted when zero defects are found and rejected when one or more defects are found.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. Presence of one or more defects shall be cause for rejection.

109. Each connector not preserved as specified for level A or C (see 5.1.1).
110. Connectors not packed together in a shipping box as specified for level A, B, or C (see 5.2.1 and 5.2.2).
111. Connectors packed together in quantities exceeding the size or weight limitations for level A or B (see 5.2.1 and 5.2.2).
112. Strapping not as specified in level A (see 5.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:23Z
Check the source to verify that this is the current version before use.

113. Preservation and packing not in accordance with the referenced document for level C (see 5.2.3).
114. Marking missing, illegible, incorrect, or incomplete for level A, level B, or C (see 5.3).

5. PACKAGING

5.1 Preservation. Preservation shall be level A or level C as specified (see 6.2).

5.1.1 Level A. Each connector shall be placed in a close-fitting box conforming to PPP-B-636, W6c, style optional. Cushioning shall be provided to prevent movement within the box. Box closure and sealing shall be in accordance with method V, of the appendix to the box specification.

5.1.2 Level C. Connectors shall be preserved as specified for level A, except the box shall be domestic class.

5.2 Packing. Packing shall be level A, level B, or level C, as specified (see 6.2).

5.2.1 Level A. The connectors, preserved as specified in 5.1, shall be packed together in close-fitting boxes conforming to PPP-B-621, class 2, style optional, or PPP-B-601, overseas type, style optional; in quantities not to exceed the weight limitation of the box. Closure shall be in accordance with the appendix to the applicable box specification. Strapping shall be in accordance with ASTM D 3953, type 1 or 2, zinc-coated, size as applicable and ASTM D 4675.

5.2.2 Level B. The connectors, preserved as specified in 5.1, shall be packed together in close-fitting boxes conforming to PPP-B-640, class 2, style optional or PPP-B-636, V3c, V11c, V13c, or V15c, style optional, in quantities not to exceed the gross weight or size limitation of the applicable box. Box closure and strapping shall be in accordance with the appendix to the applicable box specification.

5.2.3 Level C. The connectors, preserved as specified in 5.1, shall be packed as specified for level B except the boxes shall be class 1 or domestic class, whichever is applicable and strapping shall not be zinc coated.

5.3 Marking. In addition to any special marking specified in the contract or purchase order, marking shall be in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

Source: https://assist.dla.mil -- Downloaded: 202640-18T03:23Z
Check the source to verify that this is the currentversion before use.

6.1 Intended use. The bridle-line connector is intended for use in the anchorage of floating bridges for connecting bridle-lines of floating supports of superstructure to main anchorage (shore-to-shore) cables.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of the specification.
b. Issue of DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required for inspection and approval, and the number of units required (see 3.2).
d. Levels of preservation and packing required (see 5.1 and 5.2).

6.3 First article. When a first article inspection is required, the item(s) should be a preproduction model. The first article should consist of one or more units. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of the first article test results, and disposition of the first articles. Invitation for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

6.5 Subject term (key word) listing.

Anchorage of floating bridges
Bridle line connector
Mooring pneumatic floats

Custodian:
Army - ME

Preparing activity:
Army - ME

Review activity:
Army - SM
DLA - CS

Project 5420-0209

User activity:
Navy - MC

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:23Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-C-14518E	2. DOCUMENT DATE (YYMMDD) 921106

3. DOCUMENT TITLE
Connector, Bridle Line: Sheave Type

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (if applicable) (2) AUTOVON	7. DATE SUBMITTED

8. PREPARING ACTIVITY

a. NAME Geraldine F. Harlow	b. TELEPHONE (Include Area Code) (1) Commercial (703) 704-3469	(2) AUTOVON 654-3468
c. ADDRESS (Include Zip Code JS Army Belvoir RDE Center ATTN: SATBE-TSE Fort Belvoir, VA 22060-5606	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 202640-18T03:23Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:23Z
Check the source to verify that this is the current version before use.