MIL-C-14583A(MU)
6 October 1967
SUPERSEDING
MIL-C-14583(CmlC)
19 July 1957

MILITARY SPECIFICATION

CANISTER, SMOKE, WP, 5-INCH PROJECTILE, M5

1. SCOPE

1.1 Scope. This specification covers the white phosphorus (WP) filling, and packing of the M5 projectile.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-621	- Boxes, Wood, Nailed and Lock Corner.
PPP-F-320	- Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.
PPP-P-291	- Paperboard, Wrapping, Cushioning.
PPP-T-60	- Tape: Pressure-Sensitive Adhesive, Waterproof, for Packaging.
PPP-T-495	- Tubes, Mailing and Filing.
QQ-S-781	- Steel Strapping, Flat.

FSC 1320

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:28Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-C-215 - Chemical Agent, White Phosphorus (WP).
MIL-S-8660 - Silicon Compound.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

DRAWINGS

US ARMY MUNITIONS COMMAND

DL15-11-3 - Canister, Smoke, WP, 5 Inch Projectile, M5; Loading and Shell Marking Diagram.

DL15-11-97 - Canister, Smoke, WP, 5 Inch Projectile, M5; Filled.

D150-2-1 - Marking Diagram for Shipping Containers.

(All drawings referenced in this specification are included in, or listed on, the above Edgewood Arsenal drawings.)

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:28Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials and components. All materials and components cited on Drawings DL15-11-3 and DL15-11-97 and on the subsidiary drawings shall conform to the specifications listed thereon or to the specific characteristics set forth on the drawings.

3.2 Filling. The canister, Drawing D15-11-97 shall be clean and free of any foreign matter such as oil or chips. The filling, molten white phosphorus conforming to specification MIL-C-215 at a temperature of 130 ± 10°F shall be filled through the pipe plug openings. The process water used in WP filling shall be buffered by a suitable alkaline salt to maintain a pH value between 6.5 and 8.0. The depth of water remaining on the surface of the WP in the filled and closed canister shall not exceed 1/4 inch when tested as specified in 4.3.1. The WP shall be solidified with the canister in a vertical position, pipe plugs down. (See 6.3.)

3.3 Filling height. The filling height shall be determined with the WP at a temperature of 130 ± 5°F, and the canister in a vertical filling position, pipe plugs up. When properly filled, there shall be a void of 3 to 5 percent by volume remaining above the WP and water, when inspected in accordance with 4.3.1. (See 6.4.)

3.4 Assembly. Closing, coating, marking and assembly of the canister shall be as specified on Drawing D15-11-97.

3.5 Cleaning after closing. The exterior surface of the filled and closed canister and the interior of the burster well shall be thoroughly cleaned to remove any grease, oil, white phosphorus or other contamination (see 6.5).

3.6 Leakage. The filled and closed canister shall not leak when tested at 160 ± 5°F and held for a period of 8 hours as specified in 4.3.2.

3.7 Workmanship. The filled canister shall be free from foreign matter (oil, grease etc.) and damage such as dents, cracks, and deformation which could affect its intended use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:28Z
Check the source to verify that this is the current version before use.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Regular production.

4.2.1 Lotting. A lot shall consist of canisters, of one interfix number, filled by the same filling installation under the same conditions. Not more than one manufacturer or interfix number of empty canisters shall be represented in any one lot of filled canisters.

4.2.2 Sampling for examination and nondestructive tests. Sampling shall be conducted in accordance with MIL-STD-105.

4.2.3 Inspection.

4.2.3.1 For examination and nondestructive test. Sample canisters shall be examined and tested in accordance with the classification of defects and MIL-STD-105.

4.2.3.2 For critical defects. Each canister in the lot shall be inspected for the critical characteristics listed in the classification of defects.

4.2.3.3 Classification of defects.

(a) Canister Smoke, WP, 5-inch Projectile, M5 (Dwgs D15-11-3 and D15-11-97).

Categories	Defects	Acceptance standards
Critical:		
1	Leakage	4.3.2
2	WP contamination (3.5)	

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:28Z
Check the source to verify that this is the current version before use.

4.2.3.3 Classification of defects (continued).

(a) Canister Smoke, WP, 5-inch Projectile, M5 (Dwgs D15-11-3 and D15-11-97).

Categories	Defects	Acceptance standards
Major:	AQL 1.0 percent defective	
*101	Filling excessive	4.3.1
*102	Excessive water	4.3.1
103	Maximum diameter incorrect	
104	Burster well adapter thread damaged	
105	Plug above collar incorrect	
106	Marking incorrect	
Minor:	AQL 2.5 percent defective	
201	Coating missing, inadequate or incorrect	
202	Marking missing or illegible	
203	Plug threads not luted	
*204	Filling insufficient	4.3.1
205	Protective finish missing or incorrect	
206	Workmanship (3.7)	

*Note. Sampling for inspection for these characteristics after first acceptable lot, shall be in accordance with MIL-STD-105, Level I.

(b) Preparation for delivery (section 5)

Categories	Defects
Major:	AQL 4.0 percent defective
101	Container incorrect
102	Instruction card missing
103	Strapping loose or missing
104	Marking missing, illegible or incorrect

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:28Z
Check the source to verify that this is the current version before use.

4.3 Tests

4.3.1 Filling height. The filled and closed canister shall be radiographed to insure proper filling, with the canister in a vertical position and the WP molten, as specified.

4.3.2 Leakage. The filled and closed canister shall be placed in an oven in a vertical, plugs-up position, and held at the temperature and time specified, and observed for leaks. The emission of smoke shall constitute leakage.

5. PREPARATION FOR DELIVERY

5.1 Preservation. When the filled and closed canister is not immediately assembled in the projectile, the inside of the burster tube well and the threads of the burster well adapter shall be coated with preservative silicon compound conforming to MIL-S-8660.

5.2 Packing, level A. Six each canisters shall be packed in a class 2, style optional nailed wood box, for type 3 load conforming to PPP-B-621. The internal dimensions shall be 12-3/4 inches long by 8-5/8 inches wide by 13-3/8 inches high. The individual items shall be placed in a fiber tube 3-29/32 inches in diameter by 13 inches long, conforming to type I, class 1 or 2, style A, of PPP-T-495. As an alternate, the individual items may be placed in a full length open end, close fitting tube formed from paperboard conforming to type III, style 1, of PPP-P-291, with firmly taped seam using waterproof pressure-sensitive tape conforming to class 3 of PPP-T-60. Filler pads, fabricated from type CF or SF, weather resistant class fiberboard, conforming to PPP-F-320, shall be placed between sides, ends, top and bottom of the projectile load. Additional filler pads shall be used as required to make a tight pack. The box shall be closed in conformance with applicable requirements of PPP-B-621 using two each flat steel strapping 5/8 inch by 0.010 inch, type I, class B, per QQ-S-781.

5.3 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in conformance with Drawing D150-2-1.

6. NOTES

6.1 This canister is intended for use in the 5 inch 38 caliber projectile as a spotting and anti-personnel weapon.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:28Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) That the Government will furnish radiographic standard R13-21.

6.3 Precautions. Because of the hazardous nature of filling munitions with white phosphorus, filling installations are advised to take all necessary precautions to protect personnel from injury while filling canisters in accordance with this specification.

6.4 Filling aid. Canisters filled with approximately 7 pounds of WP have been found to comply with the requirements of 3.3. This information is furnished as an aid to procurement, and not as a criterion for filling.

6.5 Decontamination. Canisters may be decontaminated by passing through a hot water and detergent spray washer, or by flushing with hot water while vigorously scrubbing with steel wool. Additional cleaning of the burster casing may be effected with a steam lance and a power driven wire brush.

Custodian:
Army - MU

Preparing activity:
Army - MU (EA)

Project No. 1320-A087

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:28Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)*

CITY AND STATE

CONTRACT NO.

QUANTITY OF ITEMS PROCURED

DOLLAR AMOUNT
$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*

DATE

DD, FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE PLATE NO. 15419

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:28Z
Check the source to verify that this is the current version before use.