MILITARY SPECIFICATION

CANISTER, SMOKE, WP, 5-INCH PROJECTILE, M5

This amendment forms a part of Military Specification MIL-C-14583A(MU) dated 6 October 1967.

Page 3

3.6: Delete in its entirety, and substitute the following:

"3.6 Leakage. All joints must be WP wetted prior to oven testing. The closed and cleaned canister shall not leak when maintained at 160 ± 5° F for a minimum period of 8 hours and tested as specified in 4.3.2. Alternate method: The canister shall not leak when maintained at 207 to 212° F for a minimum period of 15 minutes and tested as specified in 4.3.2."

Page 6

4.3.2: Delete in its entirety, and substitute the following:

"4.3.2 Leakage. The filled and closed canister shall be placed in an oven in a vertical filling-port-down position, maintained at the specified temperature (160 ± 5° F), for the required period of time and observed for leakage. For the alternate method the filled and closed canister shall be placed in the oven in a vertical filling-end-up position and maintained at the specified temperature (207 to 212° F) for the required period of time and observed for leakage. When tested at 207 to 212° F, the munition temperature shall be measured by thermocouples/ thermometers inserted in the burster wells of at least two munitions located in each oven batch. Leakage shall be determined by visual examination."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:28Z
Check the source to verify that this is the current version before use.