MIL-R-14561A(AV)
7 June 1971
SUPERSEDING
MIL-R-14561(Ord)
30 June 1957

MILITARY SPECIFICATION

RASP, BUFFING, TIRE TREAD

1. SCOPE

1.1 Scope.--This specification covers a rasp used on flexible shaft-driven, air tool, electric drill, and pedestal-type tire buffing machines.

1.2 Classification.--Rasp shall be of the type, class, and style as specified (see 6.2):

Type I	Rasp used on pedestal-type buffing machines.
Class 1	Hub type.
Class 2	Disc type.
Type II	Rasp used on flexible shaft-driven, air tool, and electric drill tire buffing equipment.
Class 1	Hub type.
Class 2	Bonded abrasive type.
Style A	Arbor mounted.
Style B	Screw thread mounted.
Class 3	Circular blade type.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-B-601	Boxes, Wood, Cleated-Plywood
PPP-B-566	Boxes, Folding, Paperboard
PPP-B-636	Box, Fiberboard
PPP-B-676	Boxes, Setup
PPP-F-320	Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes

FSC 4910

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:26Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116 Preservation, Methods of

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-130	Identification Marking of US Military Property
MIL-STD-143	Specifications and Standards Order of Precedence for the Selection of

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.--The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL BUREAU OF STANDARDS

Handbook H28 Screw-Thread Standards for Federal Services

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington 25, D.C.)

AMERICAN NATIONAL STANDARDS INSTITUTE, INC.

B7.1 Use, Care, and Protection of Abrasive Wheels, Safety Code for the

(Application for copies should be addressed to the American National Standards Institute, Inc. (ANSI), 1430 Broadway, New York, N. Y. 10018)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:26Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Design characteristics.--Type I tire rasp shall be designed for use on pedestal-type buffing machines, for complete or full-circle buffing of tires prior to top treading, full treading, or retreading. Type II tire rasp shall be designed for use on flexible shaft-driven, air tool, and electric drill tire-buffing equipment for sectional or spot buffing, for patch repair or sectional retreading; the class 2 rasp of type II shall have been tested in accordance with the conditions specified in ANSI B7.1. Principal components of the respective types shall be: type I, class 1 and type II, class 1, hub unit and cutting unit; type I, class 2, disc-type housing unit and cutting unit; type II, class 2, styles A and B, single unit; and type II, class 3, one-piece full circular blades and washer separators (see 1.2). All parts subject to wear, breakage, or distortion shall be accessible for adjustment and repair.

3.1.1 First article.--If first article approval is required (see 6.2 (d)), approval and testing shall be in accordance with 4.2.1. Approval of the first article shall not relieve the contractor of his responsibility to furnish a product in accordance with this specification.

3.2 Materials.--Materials shall be capable of withstanding the operations specified herein. Unless otherwise specified, materials shall be selected in accordance with MIL-STD-143.

3.3 Components.--

3.3.1 Type 1, class 1.--

3.3.1.1 Hub unit.--The rasp assembly shall incorporate a detachable round hub unit for mounting the rasp cutting unit. The hub shall be fabricated of aluminum alloy and shall have an arbor hole as specified in the contract or order (see 6.2(e)). The hub unit shall embody the necessary attaching parts to rigidly retain the rasp cutting unit without becoming loose, disassembling, or vibrating during performance (see 3.5). The hub unit shall be of width and diameter as specified in the contract or order (see 6.2(g)), and shall be of such design that the width can be expanded to hold one to three cutting units as specified in 3.3.1.2.

3.3.1.2 Cutting unit.--The cutting unit shall embody a series of cutting blades or segments with adequate means to retain the cutting elements to the hub. The cutting elements shall be of a design to permit removal and replacement on the hub unit in not more than 15 minutes without the use of special tools. The cutting unit shall provide a cutting surface width and diameter as specified in the contract or order

Source: https://assist.dla.mil -- Downloaded: 202610-18T03:26Z
Check the source to verify that this is the current version before use.

(see 6.2(i)). The unit shall be fabricated of metal to adequately comply with 3.5.1.

3.3.2 Type I, class 2.--

3.3.2.1 Disc unit.--The rasp assembly shall incorporate a detachable disc suitable for mounting the cutting units. The disc shall be fabricated of metal to adequately comply with 3.5.1, and shall embody the necessary attaching parts to rigidly retain the rasp cutting units without becoming loose, disassembling, or vibrating during performance (see 3.5.1). The disc shall be of the size and type as specified in the contract or order (see 6.2(h)).

3.3.2.2 Cutting unit.--The cutting unit shall embody a series of cutting blades or segments with adequate means to retain the cutting elements to the disc. The cutting elements shall be of a design to permit removal and replacement on the disc unit in not more than 15 minutes without the use of special tools. The cutting unit shall provide a cutting surface width and diameter as specified in the contract or order (see 6.2(i)). The unit shall be fabricated of metal to adequately comply with 3.5.

3.3.3 Type II, class 1.--This rasp shall be similar to type I, class 1 rasp, except that it shall be a smaller unit designed for use when mounted on an arbor of flexible shaft-driven, air tool, or electric drill tire-buffing equipment. The rasp shall incorporate a hub unit and a cutting unit.

3.3.3.1 Hub unit.--The hub unit shall be suitable for mounting the cutting unit. The hub shall be of aluminum alloy or other metal capable of withstanding the stresses imposed by the operational requirements specified. The rasp shall have an arbor hole as specified in the contract or order (see 6.2(e)). The hub unit shall rigidly retain the cutting unit without becoming disassembled or loosened and without vibration during the buffing operation. The hub unit shall be of the width and diameter specified in the contract or order (see 6.2(g)).

3.3.3.2 Cutting unit.--The cutting unit shall incorporate replaceable blades, segments, or a replaceable composite cutting unit. The unit shall provide adequate means for rigidly retaining the cutting elements without disassembly, looseness, or vibration during operation. The unit shall provide a cutting surface width and diameter as specified in the contract or order (see 6.2(i)).

Source: https://assist.dla.mil -- Downloaded: 202610-18T03:26Z
Check the source to verify that this is the current version before use.

3.3.4 Type II, class 2, style A and style B.--These rasps shall be of the single unit design consisting of a bonded abrasive medium suitable for the purpose intended (see 6.1) and incorporating an appropriate integral means for mounting the rasp as required by the style (see 1.2).

3.3.4.1 Type II, class 2, style A.--Style A rasp shall have the same design characteristics as specified in 3.3.4. The rasp shall be designed for use when mounted on the arbor of flexible shaft-driven air tool or electric drill tire buffing equipment. Dimensions of this rasp shall be as specified in the contract or order (see 6.2(j)).

3.3.4.2 Type II, class 2, style B.--Style B rasp shall have the same design characteristics as specified in 3.3.4. The rasp shall be designed with an integral threaded arbor for use when mounted on the threaded adapter of flexible shaft-driven, air tool or electric drill tire-buffing equipment. The rasp dimensions and the arbor thread size and type shall be as specified in the contract or order (see 6.2(f) and (j)).

3.3.5 Type II, class 3.--Class 3 rasp shall incorporate a series of full circular blades, each separated from the next by washer-type separators. Both blades and separators shall contain an arbor hole for the purpose of mounting on the appropriate adaptor which will serve to lock together the blades and separators forming a complete rasp unit. The blades shall be fabricated of metal suitable for the purpose intended (see 6.1) and to adequately comply with 3.5.2. The rasp design shall permit removal and replacement on the adaptor without the use of special tools. The rasp dimensions, arbor size, and cutting tooth style shall be as specified in the contract or order (see 6.2(e) and (k)).

3.4 Construction.--Tire rasp shall be complete so that when installed it will operate effectively on the equipment for which its type, class or style of rasp was designed, as specified in 3.1.

3.4.1 Castings.--All castings shall be free from blow holes, porosity, hard spots, shrinkage defects, cracks, and other injurious defects that may affect the structural strength or the designed serviceability of the casting involved. Strength and other essential physical and chemical properties of the castings shall be adequate to withstand the stresses imposed by the performance specified in 3.5.

3.4.2 Fastening devices.--All screws, pins, bolts, and similar parts shall be installed with means for preventing loss of tightness and adjustment. All such parts when subject to removal or adjustment shall not be swaged, peened, staked, or otherwise be permanently deformed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:26Z
Check the source to verify that this is the current version before use.

3.4.3 Threads.--All threaded parts shall be in conformance with Handbook H28.

3.4.4 Interchangeability.--All replaceable parts shall be manufactured to definite standards, clearances, and tolerances in order that any such parts of a specific type, class, or style can be replaced or adjusted. All parts having the same manufacturer's part number shall be directly and completely interchangeable with each other with respect to installation and performance.

3.5 Performance.--

3.5.1 Type I.--The rasp shall perform satisfactorily on a tire buffing machine for full circle (complete) buffing of the tire treads. The rasp shall be capable of removing at least 250 pounds of rubber from the tire treads and still maintain the cutting ability to buff the tread of a 9.00 by 20 tire to a depth of at least 5/8-inch (measured at the tire shoulder) in not more than 10 minutes. The cutting time shall be the interval from the beginning of the rasp cutting action on the tire to the completed buffed tire (see 4.3.2.1 and 4.3.3.1).

3.5.2 Type II.--Type II rasps shall perform satisfactorily on flexible shaft-driven, air tool and electric drill tire buffing equipment for sectional and spot buffing (see 4.3.2.2 and 4.3.3.2).

3.6 Identification of product.--Tire rasp shall be identified in accordance with MIL-STD-130.

3.7 Workmanship.--All castings, forgings, molded parts, stampings, and welded parts shall be cleaned and free of sand, dirt, fins, sprues, scale, flux and other harmful or extraneous materials. Processes involving welding, brazing, soldering, peening, or plugging shall not be used on castings or forgings for reclaiming any part of the tire rasp without written authorization of the procuring activity. All components, subassemblies, parts, and final assembly shall be of neat appearance.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.--Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:26Z
Check the source to verify that this is the current version before use.

4.2 Classifications of inspections and tests.--Inspections and tests specified herein shall be classified as (1) first article (see 4.2.1) and quality conformance (see 4.2.2).

4.2.1 First article.--Two samples shall be selected at random from the production line items (see 3.1.1) of the types, classes or styles specified in 6.2. These samples shall be inspected and tested as specified in 4.3. Failure of either of the two samples to pass all inspections and tests shall be cause for rejection.

4.2.2 Quality conformance.--Sampling for acceptance shall be in accordance with level II of MIL-STD-105. Classification of defects and the acceptable quality level (AQL) shall be in accordance with table I, II, or III, as applicable. Rasps selected for sampling shall be inspected and tested as specified in 4.3.

4.3 Tests.--

4.3.1 Conditions.--Tires used in the tests shall be thoroughly inspected prior to the tests, and all foreign matter such as glass, stones, nails, wire, asphalt, and tar shall be removed from the tires.

4.3.2 Performance.--

4.3.2.1 Type I tire rasp.--The tire rasp shall be mounted on a drive spindle of a 15-horsepower precision buffing machine, or equivalent. The buffing machine shall be operated in accordance with the machine manufacturer's instructions, with the rasp buffing a 9.00 X 20 tire. A minimum of 5/8-inch of rubber (measured at the tire shoulder) shall be buffed from the tire tread in not more than a 10-minute period (see 3.5.1).

4.3.2.2 Type II tire rasp.--The tire rasp shall be attached to a flexible shaft-driven, air tool or electric drill tire buffer. The buffer shall then be operated, with the tire rasp performing the appropriate buffing action, in accordance with its intended use (see 6.1), on a 6.70 X 15 tire, in five different locations on the tire. The rasp shall effectively buff the tire with no damage, malfunction, or distortion to the rasp (see 3.5.2).

4.3.3 Operation.--

4.3.3.1 Type I tire rasp.--The tire rasp shall be mounted on the drive spindle of a 15-horsepower precision buffing machine, or equivalent. With the rasp installed, the buffing machine shall be operated in accordance with the machine manufacturer's instructions to remove a total of at least 250 pounds of rubber from a series of tires (the tire

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:26Z
Check the source to verify that this is the current version before use.

sizes and quantity shall be determined by availability and conditions). The tires shall be weighed before and after buffing to determine the amount of rubber removed. If necessary, the rasp may be turned to cut in the opposite direction during the buffing operation. On conclusion of this operational test, the tire rasp shall be tested in accordance with 4.3.2.1 (see 3.5.1).

4.3.3.2 Type II tire rasp.--Type II tire rasps shall be attached to a flexible shaft-driven, air tool or electric drill tire buffer. The buffer shall then be operated with the rasp performing the appropriate buffing action in accordance with its intended use (see 6.1), on a series of tires (the tire sizes and quantity shall be determined by availability and conditions) in 250 different locations on the tires. The rasp shall satisfactorily perform the intended buffing action with no damage, malfunction, or distortion to the rasp.

TABLE I. -- Type I, classes 1 and 2 and type II, class 1 rasp, classification of defects in accordance with MIL-STD-105.

Category	AQL percent defective	Defects	Paragraph reference
MAJOR:	2.5		
101		Defective castings affecting operation.	3.4.1
102		Defective welding, brazing, or soldering affecting operation.	3.7
103		Insecure or defective fastening devices affecting operation.	3.4.2
104		Threads not as specified.	3.4.3, 6.2(f)
105		Omission of a component part.	3.3
106		Unit overall dimensions not as specified.	6.2(g), (h)
107		Unit arbor hole dimension not as specified.	6.2(e)
108		Cutting unit dimensions not as specified.	6.2(i)
MINOR:	4.0		
201		Identification marking not as specified.	3.6
202		Preservation and packaging not as specified.	5.2
203		Packing not as specified.	5.3
204		Marking for shipment not as specified.	5.4

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:26Z
Check the source to verify that this is the current version before use.

TABLE II. -- Type II, class 2, styles A and B rasp, classification of defects in accordance with MIL-STD-105.

Category	AQL percent defective	Defects	Paragraph reference
MAJOR:	2.5		
101		Unit dimensions not as specified.	6.2(j)
102		Abrasive type and bond not suitable for purpose intended.	3.1, 3.3.4, and 6.1
103		Arbor threads not as specified.	3.3.4.2, 6.2(f)
104		Warped or otherwise distorted.	3.7
105		Unit arbor dimensions not as specified.	6.2(e)
106		Imperfections which could cause cracking, chipping, or breaking under operating conditions.	3.7, 4.3.3
107		Insecure or defective fastening devices affecting operation.	3.4.2
108		Type or shape not as specified.	6.1, 6.2(j)
109		Grit not as specified.	6.1, 6.2(j)
MINOR:	4.0		
201		Identification marking not as specified.	3.6
202		Preservation and packaging not as specified.	5.2
203		Packing not as specified.	5.3
204		Marking for shipment not as specified.	5.4

TABLE III. -- Type II, class 3 rasp, classification of defects in accordance with MIL-STD-105.

Category	AQL percent defective	Defects	Paragraph reference
MAJOR:	2.5		
101		Defective materials affecting operation.	3.3.5
102		Defective welding, brazing, or soldering affecting operation.	3.7
103		Insecure or defective fastening devices affecting operation.	3.4.2
104		Omission of a component part.	3.3.5, 3.4, 3.7
105		Unit overall dimensions not as specified.	3.3.5, 6.2(k)
106		Unit arbor hole dimensions not as specified.	3.3.5, 6.2(e)
107		Cutting unit dimensions not as specified.	3.3.5, 6.2(k)
MINOR:	4.0		
201		Identification marking not as specified.	3.6
202		Preservation and packaging not as specified.	5.2
203		Packing not as specified.	5.3
204		Marking for shipment not as specified.	5.4

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:26Z
Check the source to verify that this is the current version before use.

4.4 Inspection of preparation for delivery.--Preparation for delivery shall be inspected to determine conformance with section 5, and defects shall be classified in accordance with table I, II, or III, as applicable.

5. PREPARATION FOR DELIVERY

5.1 Disassembly.--Type I and type II, class 1 tire rasp assemblies shall be disassembled prior to cleaning.

5.2 Preservation and packaging.--Tire rasps shall be preserved and packaged in accordance with level A or level C, as specified (see 6.2(m)).

5.2.1 Level A.--

5.2.1.1 Cleaning and drying.--Tire rasps shall be cleaned in accordance with method C-1 and dried in accordance with any applicable method specified in MIL-P-116.

5.2.1.2 Packaging.--Tire rasps shall be packaged in accordance with method I of MIL-P-116, using type P-1 preservative which shall be allowed to dry before reassembly of components. Disassembled tire rasps shall be reassembled. Cutting areas shall be shielded with two layers of corrugated fiberboard conforming to PPP-F-320. Type I tire rasps shall be placed in individual fiberboard boxes conforming to W6s or W6c of PPP-B-636. Type II tire rasps shall be placed in individual paperboard boxes conforming to PPP-B-566 or PPP-B-676.

5.2.1.3 Intermediate packaging.--Type II tire rasps, packaged as specified in 5.2.1.2, shall be placed in intermediate containers conforming to W6s or W6c of PPP-B-636. The number of units in the intermediate container shall be the number necessary to reach the nearest approximation of 20 pounds gross weight.

5.2.2 Level C.--Tire rasps shall be preserved and packaged in a manner to prevent deterioration and corrosion during shipment to the first receiving activity for immediate use.

5.3 Packing.--Tire rasps, packaged in accordance with 5.2, shall be packed level A, B, or C, as specified (see 6.2(m)).

5.3.1 Level A.--Tire rasps shall be packed in plywood boxes conforming to PPP-B-601, oversea type, surface-treated in accordance with that specification. Gross weight shall not exceed 150 pounds, unless a single shipment on one bill of lading to one destination does not exceed 200 pounds.

Source: https://assist.dla.mil -- Downloaded: 202610-18T03:26Z
Check the source to verify that this is the current version before use.

5.3.2 Level B.--Tire rasps, packaged in accordance with 5.2, shall be packed in containers conforming to Vls of PPP-B-636.

5.3.3 Level C.--Tire rasps, packaged in accordance with 5.2, shall be packed in fiberboard boxes conforming to PPP-B-636.

5.4 Marking.--In addition to any special requirements of the contract or order, shipments shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.--This specification covers two types of rasps intended for buffing tires preparatory to repair: (1) Type I for use on pedestal-type buffing machines for full circle (complete) buffing of tires prior to top treading, full treading, or retreading; and (2) type II for use on flexible shaft-driven, air tool and electric drill tire-buffing equipment for spot or section buffing prior to vulcanizing and sectional treading of the tires. The type II tire rasps entail the following classes and styles:

(a) Class 1: Similar in design to type I, class 1 rasp except it is of smaller dimensions and is for use in tire truing and spot and section buffing of tires prior to retreading.

(b) Class 2, style A: For a variety of applications, including use in place of wire brushes for cleaning the lower shoulder area; removing excess overflow; buffing-off the plug area after tire has been removed from the section mold; innerliner buffing; and preparing the plug area of any sectional tire. Each of these various applications requires a particular shape, grit, and dimensions, as specified in 6.2.

(c) Class 2, style B: For buffing out smaller plug areas, and for small areas of innerliners or hard-to-get-at spots such as under a bead, prior to retreading. The shape, grit, and dimensions should be as specified in 6.2.

(d) Class 3.--For spot and section buffing prior to tire retreading.

6.2 Ordering data.--Procurement documents should specify the following as applicable to the type of tire rasp being procured:

(a) Title, number, and date of this specification.

(b) Type, class, and style required (see 1.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:26Z
Check the source to verify that this is the current version before use.

(c) Quantity required.

(d) Whether first-article approval is required, and quantity to be submitted if different (see 3.1.1 and 4.2.1).

(e) Type I, class 1 and type II, class 1, class 2 style A, class 3 requirements for arbor hole dimensions (see 3.3.1.1 and 3.3.3.1).

(f) Type II, class 2, style B requirements for threaded arbor dimensions, thread size and type (see 3.3.4.2).

(g) Type I, class 1 and type II, class 1 requirements for hub unit dimensions (see 3.3.1.1 and 3.3.3.1).

(h) Type I, class 2 requirements for disc size and type (see 3.3.2.1).

(i) Type I, class 1 and class 2 and type II, class 1 requirements for cutting unit dimensions (see 3.3.1.2, 3.3.2.2 and 3.3.3.2).

(j) Type II, class 2, style A and style B requirements for rasp dimensions, grit, and shapes (see 3.3.4.1 and 3.3.4.2).

(k) Type II, class 3 requirements for blade dimensions and cutting tooth style (see 3.3.5).

(l) Name and model of equipment on which rasp is to be used, if applicable.

(m) Level of preservation and packaging, and packing required (see 5.2 and 5.3).

(n) Whether special marking for shipment is required (see 5.4).

Custodian:

Army -- AV

Preparing Activity:

Army -- AV

Review Activities:

User Activities:

Project No. 4910-A437

Source: https://assist.dla.mil -- Downloaded: 202610-18T03:26Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:26Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding General
US Army Aviation Systems Command
ATTN: AMSAV-R-MN
PO Box 209
St. Louis, Missouri 63166

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:26Z
Check the source to verify that this is the current version before use.