MIL-S-14560E(AL)
26 September 1985
SUPERSEDING
MIL-S-14560D
13 April 1979

MILITARY SPECIFICATION

SPRAY OUTFIT, PAINT; FOR USE WITH STRIPPABLE COMPOUND

This specification is approved for use within the US Army Armament Research and Development Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of spray outfit capable of agitating, force feeding (see 3.2), and spraying strippable compound.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS), and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

PPP-P-704 - Pails, Metal: (Shipping, Steel, 1 through 12 Gallons).

MILITARY

MIL-S-12651 - Sprayers, Packaging of.
MIL-S-12877 - Spray Guns, Paint, Heavy Duty.
MIL-C-16555 - Coating Compound, Strippable, Sprayable.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, ATTN: SMCAR-ETS (R), Rock Island, IL 61299-7300 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 4940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:26Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-H28 - Screw-Thread Standards for Federal Services.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-130 - Identification Marking of US Military Property.
MIL-STD-889 - Dissimilar Metals.

* 2.1.2 Other Government documents. The following other Government documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

US DEPARTMENT OF LABOR

OSHA 2206 - General Industry, OSHA Safety and Health Standards (29 CFR 1910).

(Copies of specifications, standards, and documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

* 2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

ASME - Boiler and Pressure Vessel Codes.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D3951-82 - Standard Practice for Commercial Packaging.
ASTM E380-84 - Standard for Metric Practice.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:26Z
Check the source to verify that this is the current version before use.

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets, or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3 and 6.2.1).

3.2 Design. The spray outfit shall be designed to agitate strippable compound to a homogenized spraying consistency, to either pump or pressure feed (manufacturer's option), to regulate the air pressure, and to spray the strippable compound through an external atomizing-type spray gun. The design shall be such that parts subject to wear, breakage, or distortion shall be accessible for adjustment, repair, or replacement without modification, distortion, or damage to the spray outfit or any component.

* 3.2.1 Measurement system. The US Customary System of Units (US) or the International System of Units (SI) may be used in the design and construction of the spray outfit. In this specification, all measurements, dimensions, sizes and capacities are given in the US system. These measurements may be converted to the SI system by using the conversion factors and methods specified in ASTM E380-84.

* 3.2.2 Interchangeability. All parts shall be manufactured to definite standards, clearances, and tolerances in order that any such parts of a particular type or model may be replaced, interchanged, and adjusted without modification of the replacement parts or any other parts of the unit. When practical, all parts shall be permanently and legibly marked in accordance with MIL-STD-130.

* 3.2.3 Threads. Threads shall conform to FED-STD-H28 and the applicable Detailed Standard section referenced therein.

* 3.2.4 Safety and health requirements. The spray outfit shall comply with the general safety and health requirements promulgated under OSHA 2206 that are applicable to the outfit itself. Exceptions and additional requirements for safety and health shall be as specified in the contract (see 6.2.1 and 6.4).

* 3.3 Material. Materials not specifically designated herein or in the contract shall be of a quality commensurate with commercial practice within the producing industry, shall be suitable for the intended purpose in the design of the end item, and shall meet all requirements specified herein. Materials shall be free from defects which would adversely affect the performance or maintainability of the individual components or the overall assembly. It shall not be permissible to use reclaimed parts as is, or rebuilt from scrap or other used equipment. When dissimilar metals are used in contact with each other, suitable protection against galvanic corrosion shall be applied in accordance with MIL-STD-889.

3.4 Construction. The spray outfit shall be furnished complete so that, when installed, it can be used for the operations specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:26Z
Check the source to verify that this is the current version before use.

3.4.1 Castings and forgings. Castings shall be free from blowholes, porosity, hard spots, shrinkage defects, cracks, or other defects. Forgings shall be free from scale, inclusions, cold shuts, mismatching, sharp edges, or other defects. Castings and forgings shall be free from any properties adversely affecting their strength, durability, or suitability. Reclaiming or repair of major castings and forgings shall be permitted if the repair is not on a critical surface.

3.4.2 Welding, brazing, and soldering. Welding, brazing, and soldering shall be of a quality which shall sustain all requirements of the welded, brazed, or soldered parts. These operations shall not be employed as repair measures for defective parts.

* 3.4.3 Fastening devices. Screws, pins, bolts, and similar parts shall be installed with means for adjustment and for preventing loss of tightness. The methods for adjustment and for preventing loss of tightness shall be in accordance with accepted engineering standards and practices. All such parts when subject to removal or adjustment shall not be swaged, peened, staked, or otherwise deformed.

* 3.4.4 Lubrication. All bearings (except sealed-for-life type), mating gears, and sliding parts shall be provided with standard means for lubrication. Oil holes, grease fittings, and filler caps shall be accessible without requiring disassembly of functional parts. Lubrication reservoirs, if applicable, shall have means for checking levels.

3.4.5 Surfaces. Surfaces of castings, forgings, stampings, and parts shall be clean and free of sand, dirt, fins, sprues, scale, flux, and other harmful or extraneous materials.

* 3.4.6 Protective finishes. Exposed metal (see 6.5.1) and working surfaces, except when the parts involved are inherently corrosion resistant, shall be protected with an electrochemical or chemical conversion finish.

3.5 Performance and product characteristics. The spray outfit, when attached to a filtered air supply from 80 to 120 pounds per square inch gage (psig) pressure at a volume of 30 cubic feet per minute (cfm), shall be capable of pumping or pressure feeding and spraying strippable compound of MIL-C-16555 at room temperature. The spray outfit shall provide continuous agitation of the compound.

3.5.1 Continuous duty. The spray outfit and all components shall be capable of withstanding eight hours of continuous operation each day for ten days, with strippable compound conforming to MIL-C-16555 being agitated, pumped or pressure fed during that entire period of operation. The spray outfit shall be able to withstand the continuous operation without damage, malfunction, leakage, distortion, or impairment of operation.

3.6 Components.

3.6.1 Cover assembly.

3.6.1.1 Pressure feed unit (when provided). The cover assembly shall be a metal stamping or forging, shall be self-centering, and shall have a sealing

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:26Z
Check the source to verify that this is the current version before use.

gasket providing an air and liquid tight seal with the pressure tank specified in 3.6.8. The cover assembly shall not be deformed when the sealing force is applied by the tank fastening devices specified in 3.6.8. The cover assembly shall conform to the ASME Boiler and Pressure Vessel Code (see 2.2) for the pressure specified in 3.6.8.

3.6.1.2 Pump feed unit (when provided). The cover assembly shall be fabricated of sheet steel of not less than Manufacturers' Standard Gage No. 20 (0.036 inch). The cover assembly shall completely shield and fit over the open top of a five gallon container conforming to type II, class 2 or 3, of PPP-P-704 or a container housing, if furnished. If a container housing is furnished, it shall be fabricated of sheet metal of not less than Manufacturers' Standard Gage No. 20 and shall be large enough to completely inclose a five gallon container conforming to type II, class 2 or 3, of PPP-P-704. Provision shall be made for securing the cover assembly to the five gallon container or container housing. The cover assembly or container housing shall incorporate two carrying handles.

3.6.2 Pump assembly (for pump feed unit only). The pump assembly shall be mounted on the cover assembly in 3.6.1.2 and shall be an air motor driven rotary-gear or reciprocating-type unit. The air motor shall operate satisfactorily on the air supply specified in 3.5 to drive the pump for delivering the strippable compound to the spray gun. The pump intake shall be located near the bottom of the container so that no more than 2 1/4 inches of strippable compound shall be left in the emptied container when the container is sitting on a level surface.

3.6.3 Agitator. Each spray outfit shall be provided with an air motor-type agitator capable of operating (in conjunction with other pneumatic components) from the air supply specified in 3.5. The agitator shall be designed to bring the contents of the full container to the consistency and viscosity that shall assure satisfactory application of the strippable compound under the conditions specified in 3.5. A manually operated speed adjusting device shall be provided to shut off any or all air to the motor. The agitator drive may be consolidated with the pump motor drive shaft when pumps are used for liquid feed.

3.6.4 Air pressure control. A regulator, or control valve, shall be provided to control the air pressure to the spray gun. The regulator, or control valve, shall be capable of withstanding pressures up to and including 200 psig. Parts exposed to compressed air shall be constructed of corrosion-resistant materials. The pressure regulator shall be capable of being adjusted to provide a minimum air pressure regulator range of 0 to 100 psig.

3.6.5 Liquid pressure control. Means shall be provided to control the liquid pressure to the spray gun within a minimum range of 0 to 100 psig and be capable of withstanding pressures up to, and including, 200 psig.

3.6.6 Air pressure gage. An air pressure gage shall be provided to indicate the air pressure to the spray gun. The pressure gage shall be a Bourdon tube type. The dial shall be not less than two inches in diameter. Graduations and figures shall be of simple, legible design and on a contrasting background. The gage shall have a minimum pressure scale range of 0 to 100 psig. The scale shall be provided with divisions of not more than five psig, with figure intervals of not more than 20 psig. The error in pressure indication shall not exceed five psig on the middle third of the scale, and ten psig on the upper and lower thirds of the scale.

Source: https://assist.dla.mil -- Downloaded: 202640-18T03:26Z
Check the source to verify that this is the current version before use.

3.6.6.1 Gage dampeners (for pump feed unit only). Gages shall be equipped with pulsation dampeners to reduce wear on the gage movement, and to preclude the possibility of fluid entry into the Bourdon tube. The dampeners shall in no way detract from the accuracy specified in 3.6.6.

3.6.7 Liquid pressure gage. A gage shall be provided to indicate the liquid pressure to the spray gun. Requirements for the liquid pressure gage shall be the same as for the air pressure gage specified in 3.6.6, except that the liquid pressure gage shall have a minimum pressure scale range of 0 to 160 pounds psig.

3.6.8 Pressure tank (for pressure feed unit only). The pressure tank shall be fabricated of steel, shall have a capacity of not less than five gallons, and shall have a galvanized interior and exterior. The tank shall be of seamless or welded construction, cylindrical in shape, having a full open top and concave bottom with welded bottom chime. The pressure tank shall be fitted with fastening devices to seal and lock the cover assembly in position to withstand, without leakage or damage, a test pressure of not less than 165 psig hydrostatic pressure for a period of five minutes. The tank material outlet shall extend near the tank bottom so that not more than 2 1/4 inches of strippable compound shall remain in the emptied tank when the tank is sitting on a level surface. The pressure tank shall incorporate two carrying handles located near the top edge which are diametrically opposite each other. The pressure tank shall be certified for conformance to the ASME Boiler and Pressure Vessel Codes, with a maximum working pressure of 110 psig. The name-plate required by the ASME code shall be permanently attached to the cover or chime. ASME certification shall be acceptable in lieu of an additional pressure (hydrostatic) test (see 4.6.5).

3.6.9 Base. A base shall be provided with means to mount and secure the spray outfit equipped with strippable compound. The base shall be fitted with at least three swivel wheels or swivel casters, not less than two inches in nominal diameter, so that the spray outfit is maneuverable.

3.6.10 Spray gun. A spray gun shall be provided conforming to the requirements of type I of MIL-S-12877, except that the gun shall be fitted with the required air cap and liquid nozzle for spraying strippable compound conforming to MIL-C-16555.

3.6.11 Air and liquid hoses. The following air and liquid hoses shall be provided. Certification of compliance shall be furnished by the manufacturer.

* 3.6.11.1 Air hoses. Two air hoses, each not less than 25 feet in length, shall be provided with each spray outfit. The hoses shall have an oil-resistant tube and cover, shall be fiber or textile reinforced, and shall have a rated working pressure of not less than 200 psig. One hose shall connect the spray gun to the output side of the air pressure regulator or control, and the other hose shall connect the air compressor to the air supply inlet on the cover assembly. The hose from the regulator or control output to the spray gun shall have an inside diameter of not less than 3/8 inch. The hose from the compressor to the cover assembly inlet shall have an inside diameter of not less than 1/2 inch. The air hose couplings shall be swivel, female, straight pipe thread, with a 60° included angle taper seat except that the air hose for connecting the compressor to the cover shall have a quick-disconnect coupling. The air hose to the spray gun shall include the necessary adapters to fit the air connection to the spray gun specified in 3.6.10.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:26Z
Check the source to verify that this is the current version before use.

* 3.6.11.2 Liquid hose. A liquid hose, not less than 1/2 inch inside diameter and not less than 25 feet in length, shall be provided to connect the pump feed or pressure feed unit to the spray gun. The hose shall be compatible with compounds conforming to MIL-C-16555, and shall be rated for a working pressure of not less than 750 psig. Each end shall have a swivel female coupling with standard straight pipe thread, with a 60° included angle taper seat. The liquid hose shall include the necessary adapters to fit the liquid connection of the spray gun specified in 3.6.10.

3.6.12 Valves. Valves shall be constructed to seal and provide positive adjustment and shall be fabricated of noncorrosive materials if exposed to compressed air. Control valves shall be provided at the air operated motors and at the air or liquid system junctions or bypasses on the cover, or at the spray gun. Adjustment ranges shall be provided to insure operation as specified herein.

3.6.12.1 Safety valves. Safety valves shall be provided on pressure tanks to insure that dangerous pressures do not develop. Release pressures for safety valves shall be governed by the ASME Boiler and Pressure Vessel Codes (see 3.6.8).

* 3.7 Painting. Unless otherwise specified (see 6.2.1), painting and finishing shall be in accordance with the best commercial practice in the industry. Before painting, all surfaces shall be clean and be free of all foreign matter detrimental to painting. At least one coat of primer (or a phosphate or chromate base) and one coat of enamel, or equivalent (i.e., epoxy enamel), shall be applied.

3.8 Product identification. The spray outfit shall be marked for product identification in accordance with MIL-STD-130 and, unless otherwise specified (see 6.2.1), shall include the National Stock Number.

3.9 Workmanship. Standards of workmanship shall assure that the spray outfit shall have the stability, strength, durability, safety, and efficient operating characteristics found in the best commercial units and as specified in Section 3.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of Sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:26Z
Check the source to verify that this is the current version before use.

submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 First article inspection. First article inspection shall be applied to a preproduction model or initial production item (see 3.1). Unless otherwise specified (see 6.2.1), first article inspection shall consist of the examination in 4.5 and all tests under 4.6. Failure of the first article to pass the examination or any of the tests shall be cause for rejection.

* 4.4 Quality conformance inspection. Unless otherwise specified (see 6.2.1), quality conformance inspection shall be applied to production items offered for acceptance under the contract. Unless otherwise specified (see 6.2.1), quality conformance inspection shall consist of (a) through (f) below. Failure of any item to pass an examination or test shall be cause for rejection of the item.

(a) Product examination (see 4.5).
(b) Performance test (see 4.6.1).
(c) Functional test (see 4.6.2).
(d) Accuracy of pressure gages test (see 4.6.3).
(e) Pressure test (see 4.6.5).
(f) Packaging inspection (see 4.7).

* 4.4.1 Sampling. Sampling for quality conformance inspection shall be in accordance with MIL-STD-105, using the following Inspection Levels and Acceptable Quality Levels (AQL):

Inspection or test	Inspection Level	AQL
Product examination	II	1.0
Performance test	II	1.0
Functional test	II	1.0
Accuracy of pressure gages test	II	1.0
Pressure test	II	1.0
Packaging inspection	S-4	4.0

NOTE: Lot size shall be no more than 100 spray outfits.

* 4.5 Product examination. Visually and manually examine each spray outfit to determine conformance with the requirements of 3.2 through 3.4.6 and 3.7 through 3.9. Visual examination shall include verification of completeness of manufacture and assembly, conformance to specified standards, adequacy of markings, proper cleaning, and freedom from defects. Manual examination shall include the operation of movable parts by hand to assure proper functioning. The examination provisions may be applied at the earliest practical point in manufacture at which it is feasible to inspect for acceptance without risk of change in the characteristic by subsequent operations. Failure of the contractor to provide objective evidence that the spray outfit and its components have passed the examinations prescribed for it by the contractor's inspection system shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:26Z
Check the source to verify that this is the current version before use.

4.6 Tests.

4.6.1 Performance test. When stabilized at an ambient air temperature of +72° to +78°F, the spray outfit shall be loaded with five gallons of strippable compound conforming to MIL-C-16555, connected to an air source of 30 cfm at 80 to 120 psig, and operated in accordance with the manufacturer's instructions. The spray gun shall be directed into a clean receptacle and the spray outfit shall be operated until the strippable compound container is emptied. During, and upon conclusion of the test, the spray outfit shall be examined to determine compliance with the following:

	REQUIREMENT	REFERENCE
(a)	Functional	3.5
(b)	Cover assembly for pressure feed unit	3.6.1.1
(c)	Cover assembly for pump feed unit	3.6.1.2
(d)	Pump assembly for pump feed unit	3.6.2
(e)	Agitator	3.6.3
(f)	Air pressure control	3.6.4
(g)	Liquid pressure control	3.6.5
(h)	Air pressure gage	3.6.6
(i)	Liquid pressure gage	3.6.7
(j)	Pressure tank for pressure feed unit	3.6.8
(k)	Base	3.6.9
(l)	Spray gun	3.6.10
(m)	Air hoses	3.6.11.1
(n)	Liquid hose	3.6.11.2
(o)	Valves	3.6.12

4.6.2 Functional test. Spray outfit components shall be tested in accordance with the manufacturer's standard procedures to verify compliance with 4.6.1 (b) through (o). Tests may be performed at the individual component level provided compliance with all performance requirements is verified.

4.6.3 Accuracy of pressure gages. Accuracy of the air and liquid pressure gages shall be tested at all major graduations throughout the entire range of the scale by comparison with a standard pressure measuring device having an overall accuracy within one percent of the value being measured (see 3.6.6 and 3.6.7).

* 4.6.4 Continuous duty test. In an ambient air temperature of +72° to +78°F, the spray outfit shall be filled with strippable compound conforming to MIL-C-16555 and connected to an air supply of 30 cfm at 80 to 120 psig. The spray outfit shall be subjected to eight hours of continuous operation each day for ten days (see 3.5.1). When a pump feed unit is furnished, it shall be set up to spray the strippable compound back into the container. Continuous operation shall be considered to be the period of operation, less refill time, with the delay for refilling not to exceed ten minutes. The spray outfit shall agitate, feed, and spray the strippable compound throughout the test with no evidence of damage, malfunction, leakage, or impairment of operation (see 3.5.1). Certification by the contractor that the spray outfit is capable of passing this continuous duty test may be used in lieu of actually conducting the test.

* 4.6.5 Pressure test (for pressure feed unit only). This pressure test shall be conducted only when the manufacturer cannot provide formal ASME certification (see 3.6.8).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:26Z
Check the source to verify that this is the current version before use.

4.6.5.1 Test procedure. The release valve and other parts subject to damage shall be removed. All openings shall be plugged and the pressure tank, with the cover assembly secured in place, shall be subjected to a hydrostatic pressure of 165 psig for a period of five minutes. During, and upon conclusion of, the test period, the pressure tank shall be examined for evidence of leakage, deformation, or other damage (see 3.6.1.1 and 3.6.8).

4.7 Packaging inspection. Packaging inspection shall be conducted before and after packaging to determine compliance with the requirements of Section 5.

5. PACKAGING

* 5.1 Military preservation, packing, and marking. When specified (see 6.2.1), requirements for Level A preservation, Levels A or B packing, and military marking shall be in accordance with MIL-S-12651.

* 5.2 Industrial preservation, packing, and marking. Unless otherwise specified (see 6.2.1), preservation, packing, and marking shall be in accordance with ASTM D3951-82.

6. NOTES.

6.1 Intended use. The spray outfit covered by this specification is intended for use in agitating, pump or pressure feeding, and spraying strippable compound.

6.2 Ordering data.

* 6.2.1 Acquisition requirements. Acquisition documents should specify the following:

(a) Title, number and date of this specification.
(b) First article when required (see 3.1).
(c) Exceptions and additional safety/health requirements when required (see 3.2.4 and 6.4).
(d) Painting and finishing if different (see 3.7).
(e) Product identification if different (see 3.8).
(f) First article inspection if different (see 4.3).
(g) Quality conformance inspection if different (see 4.4).
(h) Level of preservation, packing, and marking if different (see 5.1 and 5.2).

6.3 Contract data requirements. Required technical data such as operator's manuals, parts lists, and other instructions for operation and maintenance, as identified on a numbered DD Form 1664, should be specified on a DD Form 1423 incorporated in the contract.

6.4 Safety and health requirements. In order that equipment integrated into the user's operational environment will comply with OSHA limitations and control of noise levels, radiation, electromagnetic emission, noxious vapors, heat, etc., as applicable, specific requirements concerning such points of operation, and other health and safety requirements, should be specified by the user.

Source: https://assist.dla.mil -- Downloaded: 202610-18T03:26Z
Check the source to verify that this is the currentversion before use.

* 6.5 Definitions.

6.5.1 Exposed metal. Exposed metal is defined as metal exposed to atmospheric conditions, compressed air, solvents, and the material being sprayed (see 3.4.6).

6.6 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodian:

Army - AL

Preparing activity:

Army - AL

Project No. 4940-A485

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:26Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:26Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Research
and Development Center
ATTN: SMCAR-ETS (R)
Rock Island, IL 61299-7300

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:26Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-14560E(AL)	Spray Outfit, Paint; For Use With Strippable Compound

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 202640-18T03:26Z
Check the source to verify that this is the current version before use.