INCH-POUND

A-A-60036

5 July 2022

COMMERCIAL ITEM DESCRIPTION

NUTS, CADMIUM AND HEXAVALENT-CHROMIUM FREE

The General Services Administration has authorized the use of this commercial item description by all federal agencies.

1 SCOPE. This commercial item description (CID) covers nuts which shall not contain cadmium or hexavalent-chromium in their finishes.

2 CLASSIFICATION

2.1 Types.

Type I	-	AIA/NAS1033 - Nut, Self-Locking, Plate, Right Angle, Regular Height, CBORE, Floating
Type II	-	AIA/NAS1291 - Nut, Self-Locking, Hexagon, Low Height, Light Weight
Type III	-	AIA/NAS1329 - Nut, Blind Rivet, Flat Head, Internal Thread, Non-Locking (Free-Running) and Self-Locking (Prevailing Torque)
Type IV	-	AIA/NAS1423 - Nut, Plain, Hexagon, Drilled Jam, Thin
Type V	-	AIA/NASM17829 - Nut, Self-Locking, Hexagon, Regular Height, 250 °F, Non-Metallic Insert, Non-Cres Steel
Type VI	-	AIA/NASM21042 - Nut, Self-Locking, 450° F, Reduced Hexagon, Reduced Height, Ring Base, Non-Corrosion Resistant Steel
Type VII	-	AIA/NASM21044 - Nut, Self-Locking, Hexagon, Regular Height, 250 ºF, 125 KSI Ftu and 60 KSI Ftu
Type VIII	-	AIA/NASM21078 - Nut, Self-Locking, Plate, Two Lug, Non-Metallic Insert, Steel, 125 KSI Ftu, 250 °F
Type IX	-	AIA/NASM21083 - Nut, Self-Locking, Hexagon, Non-Metallic Insert, Low Height, 250 °F
Type X	-	AIA/NASM35649 - Nut, Plain, Hexagon, Machine Screw, UNC-2B
Type XI	-	AIA/NASM35650 - Nut, Plain, Hexagon, UNF-2B

3 SALIENT CHARACTERISTICS.

3.1 Materials. Nuts shall be manufactured as specified in the Aerospace Industry Association (AIA) documents listed in 2.1 by type, except the plating/finishes shall not contain cadmium or hexavalent-chromium as specified herein.

3.2 Dimensions. Dimensions for all designated type of nuts apply after plating/finishing.

Comments, suggestions, or questions on this document should be addressed to U.S. Army DEVCOM Ground Vehicle Systems Center, ATTN: Standardization, FCDD-GVS-SAT, MS #268, 6501 E. 11 Mile Road, Warren, MI 48397-5000 or send email to usarmy.detroit.devcom-gvsc.mbx.standardization@army.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

FSC 5310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

3.3 Finish/plating. Finish/plating types for each type of nut shall be designated as in 7.1.1. The finishes/plating options for the nuts are listed below:

a. Aluminum – shall be chemically treated in accordance with: MIL-DTL-5541, Type II, Class 1A, or MIL-DTL-81706, Type II, Class 1A; or Anodized in accordance with MIL-PRF-8625, Type IC or IIB, Class 1. Sealers (clear or any color) containing hexavalent chromium shall be prohibited.
b. Carbon and Alloy steel – shall be Zinc-Nickel plated in accordance with MIL-PRF-32647, Type K16 or Type K20 as specified herein.
c. CRES A286, 302-305, 302HQ, 316, 317, 347, 340 and 430 - shall be cleaned, descaled and passivated in accordance with SAE AMS2700, Method 1, Type 6 or 7, or Method 2; or ASTM A967/A967M, passivation treatments containing dichromate are prohibited. Post-cleaning treatment is prohibited.

4 REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered, recycled, bio based, and environmentally preferable materials to the maximum extent practicable, in accordance with paragraph 23.403, 23.404(b) of the Federal Acquisition Regulation (FAR), or the sustainable acquisition of EO 13834; as applicable.

5 PRODUCT CONFORMANCE PROVISIONS

5.1 Product conformance. The products provided shall meet the salient characteristics of this Commercial Item Description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

5.2 Responsibility for inspection. The contractor is responsible for the performance of all inspections.

5.3 Contractor certification. The contractor shall certify and maintain substantiating evidence the product offered meets the salient characteristics of this commercial item description and conforms to the producer's own drawings, specifications, workmanship standards, and quality assurance practices. Items with known defects shall not be submitted for Government acceptance. The Government reserves the right to perform or witness any of the inspections it deems necessary to ensure supplies and services conform to prescribed requirements.

6 PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order.

7 NOTES

The following part or identification numbering procedure is for government purposes and does not constitute a requirement for the contractor.

7.1 Table. The following Table indicate new finish/plating PIN's which are Cadmium and hexavalent-chromium free for the designated nuts.

7.1.1 Cadmium and hexavalent-chromium free PIN codes. Cadmium and hexavalent-chromium free part numbers shall be as identified by the examples herein and in conjunction with AIA/NAS/NASM dash numbers listed in the respective specifications (see 2.1). The following finish/plating (cadmium and hexavalent-chromium free) codes are given:

QX - Steel – Zinc-Nickel plate per section 3.3b, Type K16.
QW - Steel – Zinc-nickel plate per section 3.3b, Type K20.
P5 - CRES – Passivate per section 3.3c.
J - Aluminum - Chemically treated per MIL-DTL-5541, Type II, Class 1A or MIL-DTL-81706, Type II, Class 1A
K - Aluminum – Anodize per section 3.3a.
H - No finish/plating
M - Dry film lubricant in accordance with NASM25027

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

TABLE I – Type I (-1) - Nut, Self-Locking, Plate, Right Angle, Regular Height, CBORE, Floating.

New A-A-60036 Part Number	Reference Dash Number (NAS1033)
AA60036-1-*06**	NAS1033*06
AA60036-1-*08**	NAS1033*08
AA60036-1-*3**	NAS1033*3
AA60036-1-*4**	NAS1033*4
AA60036-1-*5**	NAS1033*5

* Indicates material(s):

N = 250 °F Steel nut with nylon insert.
P = 250 °F Steel nut without nylon insert.
A = 450 °F Steel assembly.
C = 800 °F CRES assembly.

** Indicates plating/finish:

QX = Zinc-Nickel Type K16 plate per 3.3b.
QW = Zinc-Nickel Type K20 plate per 3.3b.
P5 = 450 °F Passivated per 3.3c.

Example of NEW part numbers:

AA60036-1-N06QW = a NAS1033 - 0.1380-32 UNJC-3B, 250 °F steel nut with nylon insert, Zinc-Nickel Type K20 plating.
AA60036-1-P06QW = a NAS1033 - 0.1380-32 UNJC-3B, 250 °F steel nut without nylon insert, Zinc-Nickel Type K20 plating.
AA60036-1-A03QX = a NAS1033 - 0.1900-32 UNJF-3B, 450 °F steel assembly, Zinc-Nickel Type K16 plating.
AA60036-1-C06P5 = a NAS1033 - 0.1380-32 UNJC-3B, 800 °F CRES assembly, Passivated.

TABLE II – Type II (-2) - Nut, self-locking, hexagon, low height, light weight.

New A-A-60036 Part Number With dry film lubricant IAW NASM25027 (A286 CRES 450°F)	Reference Dash Number (NAS1291) Nut (A286 CRES 450°F)
AA60036-2-C02P5M	NAS1291C02M
AA60036-2-C04P5M	NAS1291C04M
AA60036-2-C06P5M	NAS1291C06M
AA60036-2-C08P5M	NAS1291C08M
AA60036-2-C3P5M	NAS1291C3M
AA60036-2-C4P5M	NAS1291C4M
AA60036-2-C5P5M	NAS1291C5M
AA60036-2-C6P5M	NAS1291C6M
AA60036-2-C7P5M	NAS1291C7M
AA60036-2-C8P5M	NAS1291C8M
AA60036-2-C9P5M	NAS1291C9M
AA60036-2-C10P5M	NAS1291C10M

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

Example of NEW part numbers:

AA60036-2-C7P5M = a NAS1291 - 0.4375-20 Nut, all metal construction of CRES (A286), passivated, dry film lubricant in accordance with NASM25027.

TABLE III – Type III (-3) - Nut, blind rivet, flat head, internal thread, non-locking (free-running) and self-locking (prevailing torque).

New A-A-60036 Part Number (A= Aluminum Anodized)	New A-A-60036 Part Number (Carbon Steel) Zinc-nickel Plated Type K16	New A-A-60036 Part Number (Alloy Steel) Zinc-nickel Plated Type K16	New A-A-60036 Part Number (CRES 430) Passivated	New A-A-60036 Part Number (CRES 316) Passivated	Reference Dash Number (NAS1329) Nut
AA60036-3-A04K*	AA60036-3-S04QX*	AA60036-3-H04QX*	AA60036-3-C04P5*	AA60036-3-N04P5*	NAS1329**-04
AA60036-3-A06K*	AA60036-3-S06QX*	AA60036-3-H06QX*	AA60036-3-C06P5*	AA60036-3-N06P5*	NAS1329**-06
AA60036-3-A08K*	AA60036-3-S08QX*	AA60036-3-H08QX*	AA60036-3-C08P5*	AA60036-3-N08P5*	NAS1329**-08
AA60036-3-A3EK*	AA60036-3-S3EQX*	AA60036-3-H3EQX*	AA60036-3-C3EP5*	AA60036-3-N3EP5*	NAS1329**-3E
AA60036-3-A3K*	AA60036-3-S3QX*	AA60036-3-H3QX*	AA60036-3-C3P5*	AA60036-3-N3P5*	NAS1329**-3
AA60036-3-A4EK*	AA60036-3-S4EQX*	AA60036-3-H4EQX*	AA60036-3-C4EP5*	AA60036-3-N4EP5*	NAS1329**-4E
AA60036-3-A4K*	AA60036-3-S4QX*	AA60036-3-H4QX*	AA60036-3-C4P5*	AA60036-3-N4P5*	NAS1329**-4
AA60036-3-A5EK*	AA60036-3-S5EQX*	AA60036-3-H5EQX*	AA60036-3-C5EP5*	AA60036-3-N5EP5*	NAS1329**-5E
AA60036-3-A5K*	AA60036-3-S5QX*	AA60036-3-H5QX*	AA60036-3-C5P5*	AA60036-3-N5P5*	NAS1329**-5
AA60036-3-A6EK*	AA60036-3-S6EQX*	AA60036-3-H6EQX*	AA60036-3-C6EP5*	AA60036-3-N6EP5*	NAS1329**-6E
AA60036-3-A6K*	AA60036-3-S6QX*	AA60036-3-H6QX*	AA60036-3-C6P5*	AA60036-3-N6P5*	NAS1329**-6
AA60036-3-A8EK*	AA60036-3-S8EQX*	AA60036-3-H8EQX*	AA60036-3-C8EP5*	AA60036-3-N8EP5*	NAS1329**-8E
AA60036-3-A8K*	AA60036-3-S8QX*	AA60036-3-H8QX*	AA60036-3-C8P5*	AA60036-3-N8P5*	NAS1329**-8

* Denotes placeholder for grip range code in thousands of an inch. The addition of the letter L indicates a thread locking feature.

** Placeholder for material code from NAS1329.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

PIN breakdown	AA60036	= CID Number	
	-2	= Type (by Table)	
	-A	= Material + Finish Code:	A = Aluminum Alloy, Anodized (per 3.3a) SQX = Carbon Steel, Zinc-nickel plated HQX = Alloy Steel, Zinc-nickel plated CP5 = CRES Type 430, Passivated NP5 = CRES Type 316, Passivated
	3 (or 3E)	= Dash Number	
	-	= Keyless Open End	K = Keyed Open End B = Keyless Closed End KB = Keyed Closed End
	130	= Grip Range	
	L	= Locking	Blank = Non-locking

Example of NEW part numbers:

AA60036-3-K3K130L = a NAS1329 nut - Aluminum alloy, chemically treated, keyed open end, 0.1900-32 internal thread, 0.080 to 0.130 grip range, with thread locking feature.

AA60036-3-CP56EKB200 = a NAS1329 nut – CRES 430, passivated, keyed closed end, 0.375-16 internal thread, 0.115 to 0.200 grip range.

AA60036-3-NP54EB140 = a NAS1329 nut – CRES 316, passivated, keyless closed end, 0.250-20 internal thread, 0.080 to 0.140 grip range.

AA60036-3-HQX3K130L = a NAS1329 nut - Alloy steel, Zinc-nickel plated, keyed open end, 0.1900-32 internal thread, 0.080 to 0.130 grip range, with thread locking feature.

AA60036-3-SQX5E-125 = a NAS1329 nut - Carbon steel, Zinc-nickel plated, keyless open end, 0.3125-18 internal thread, 0.030 to 0.125 grip range.

TABLE IV – Type IV (-4) - Nut, plain, hexagon, drilled jam, thin.

New A-A-60036 Part Number (CRES A286) 1/ 2/	Reference Dash Number (NAS1423) (Cadmium Plated Alloy Steel)	Reference Dash Number (NAS1423) (CRES A286)
AA60036-4-C06P5	NAS1423-06	NAS1423C06
AA60036-4-C08P5	NAS1423-08	NAS1423C08
AA60036-4-C3P5	NAS1423-3	NAS1423C3
AA60036-4-C4P5	NAS1423-4	NAS1423C4
AA60036-4-C5P5	NAS1423-5	NAS1423C5
AA60036-4-C6P5	NAS1423-6	NAS1423C6
AA60036-4-C7P5	NAS1423-7	NAS1423C7
AA60036-4-C8P5	NAS1423-8	NAS1423C8
AA60036-4-C9P5	NAS1423-9	NAS1423C9
AA60036-4-C10P5	NAS1423-10	NAS1423C10
AA60036-4-C12P5	NAS1423-12	NAS1423C12
AA60036-4-C14P5	NAS1423-14	NAS1423C14
AA60036-4-C16P5	NAS1423-16	NAS1423C16
AA60036-4-C18P5	NAS1423-18	NAS1423C18
AA60036-4-C20P5	NAS1423-20	NAS1423C20
AA60036-4-C22P5	NAS1423-22	NAS1423C22
AA60036-4-C24P5	NAS1423-24	NAS1423C24
AA60036-4-C26P5	NAS1423-26	NAS1423C26
AA60036-4-C28P5	NAS1423-28	NAS1423C28
AA60036-4-C30P5	NAS1423-30	NAS1423C30
AA60036-4-C32P5	NAS1423-32	NAS1423C32
AA60036-4-C34P5	NAS1423-34	NAS1423C34
AA60036-4-C36P5	NAS1423-36	NAS1423C36
AA60036-4-C40P5	NAS1423-40	NAS1423C40

1/ Suffix "LH" to dash number for left hand thread.

2/ CRES alternative to cadmium plated steel nuts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

Example of part number:

AA60036-3-C8P5 = a NAS1423 CRES (A286) nut, 0.5000-20 UNJF-3B, passivated

TABLE V – Type V (-5) - Nut, self-locking, hexagon, regular height, 250 °F, non-metallic insert, non-CRES steel.

New A-A-60036 Part Number (Steel) Zinc-Nickel Plated, Type K16 replacing cadmium plating	Reference Dash Number, Cadmium Plating (NASM17829)	New A-A-60036 Part Number (Steel) Zinc-Nickel Plated, Type K20 replacing zinc plating	Reference Dash Number, Zinc Plating (NASM17829)
AA60036-5-QX3C	MS17829-3C	AA60036-5-QW3C	MS17829Z3C
AA60036-5-QX4C	MS17829-4C	AA60036-5-QW4C	MS17829Z4C
AA60036-5-QX4F	MS17829-4F	AA60036-5-QW4F	MS17829Z4F
AA60036-5-QX5C	MS17829-5C	AA60036-5-QW5C	MS17829Z5C
AA60036-5-QX5F	MS17829-5F	AA60036-5-QW5F	MS17829Z5F
AA60036-5-QX6C	MS17829-6C	AA60036-5-QW6C	MS17829Z6C
AA60036-5-QX6F	MS17829-6F	AA60036-5-QW6F	MS17829Z6F
AA60036-5-QX7C	MS17829-7C	AA60036-5-QW7C	MS17829Z7C
AA60036-5-QX7F	MS17829-7F	AA60036-5-QW7F	MS17829Z7F
AA60036-5-QX8C	MS17829-8C	AA60036-5-QW8C	MS17829Z8C
AA60036-5-QX8F	MS17829-8F	AA60036-5-QW8F	MS17829Z8F
AA60036-5-QX9C	MS17829-9C	AA60036-5-QW9C	MS17829Z9C
AA60036-5-QX9F	MS17829-9F	AA60036-5-QW9F	MS17829Z9F
AA60036-5-QX10C	MS17829-10C	AA60036-5-QW10C	MS17829Z10C
AA60036-5-QX10F	MS17829-10F	AA60036-5-QW10F	MS17829Z10F
AA60036-5-QX12C	MS17829-12C	AA60036-5-QW12C	MS17829Z12C
AA60036-5-QX12F	MS17829-12F	AA60036-5-QW12F	MS17829Z12F
AA60036-5-QX14C	MS17829-14C	AA60036-5-QW14C	MS17829Z14C
AA60036-5-QX14F	MS17829-14F	AA60036-5-QW14F	MS17829Z14F
AA60036-5-QX16C	MS17829-16C	AA60036-5-QW16C	MS17829Z16C
AA60036-5-QX16F	MS17829-16F	AA60036-5-QW16F	MS17829Z16F
AA60036-5-QX18C	MS17829-18C	AA60036-5-QW18C	MS17829Z18C
AA60036-5-QX18F	MS17829-18F	AA60036-5-QW18F	MS17829Z18F
AA60036-5-QX20C	MS17829-20C	AA60036-5-QW20C	MS17829Z20C
AA60036-5-QX20F	MS17829-20F	AA60036-5-QW20F	MS17829Z20F
AA60036-5-QX22C	MS17829-22C	AA60036-5-QW22C	MS17829Z22C
AA60036-5-QX22F	MS17829-22F	AA60036-5-QW22F	MS17829Z22F
AA60036-5-QX24C	MS17829-24C	AA60036-5-QW24C	MS17829Z24C
AA60036-5-QX24F	MS17829-24F	AA60036-5-QW24F	MS17829Z24F
AA60036-5-QX28C	MS17829-28C	AA60036-5-QW28C	MS17829Z28C
AA60036-5-QX32C	MS17829-32C	AA60036-5-QW32C	MS17829Z32C
AA60036-5-QX36C	MS17829-36C	AA60036-5-QW36C	MS17829Z36C
AA60036-5-QX40C	MS17829-40C	AA60036-5-QW40C	MS17829Z40C

Examples of part number:

AA60036-5-QX3C = a NASM17829 - Steel nut, Zinc-Nickel plated, Type K16, 10-24 UNC-3B with a non-metallic insert.

AA60036-5-QW14F = a NASM17829 - Steel nut, Zinc-Nickel plated, Type K20, 7/8-14 UNF-3B with a non-metallic insert.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

TABLE VI – Type VI (-6) - Nut, Self-Locking, 450° F, Reduced Hexagon, Reduced Height, Ring Base, Non-Corrosion Resistant Steel.

New A-A-60036 Part Number (Steel) Zinc-Nickel Plated, Type K16 Non-Lubricated	Reference Dash Number (NASM21042) Cadmium Plated, Non-Lubricated
AA60036-6-QX02	MS21042-02
AA60036-6-QX04	MS21042-04
AA60036-6-QX06	MS21042-06
AA60036-6-QX08	MS21042-08

New A-A-60036 Part Number (Steel) Zinc-Nickel Plated, Type K16 Dry Film Lubricated IAW NASM25027	Reference Dash Number (NASM21042) Cadmium Plated, Dry Film Lubricated IAW NASM25027
AA60036-6-QXL02	MS21042L02
AA60036-6-QXL04	MS21042L04
AA60036-6-QXL06	MS21042L06
AA60036-6-QXL08	MS21042L08

Example of part number:

AA60036-6-QX04 = a NASM21042 – A self-locking reduced height steel nut, Zinc-Nickel plated, non-lubricated, 0.1120-40 UNJC-3B.
AA60036-6-QXL04 = a NASM21042 – A self-locking reduced height steel nut, Zinc-Nickel plated, dry film lubricated, 0.1120-40 UNJC-3B.

TABLE VII – Type VII (-7) - Nut, self-locking, hexagon, regular height, 250 ºF, 125 KSI Ftu and 60 KSI Ftu.

New A-A-60036 Part Number Zinc-Nickel Plated, Type K16 Lubricated IAW NASM25027	Reference Dash Number (NASM21044) Cadmium Plated Lubricated IAW NASM25027
Steel	Steel
AA60036-7-N02QX	MS21044N02
AA60036-7-N04QX	MS21044N04
AA60036-7-N06QX	MS21044N06
AA60036-7-N08QX	MS21044N08
AA60036-7-N3QX	MS21044N3
AA60036-7-N4QX	MS21044N4
AA60036-7-N5QX	MS21044N5
AA60036-7-N6QX	MS21044N6
AA60036-7-N7QX	MS21044N7
AA60036-7-N8QX	MS21044N8
AA60036-7-N9QX	MS21044N9
AA60036-7-N10QX	MS21044N10
AA60036-7-N12QX	MS21044N12
AA60036-7-N14QX	MS21044N14
AA60036-7-N16QX	MS21044N16
AA60036-7-N18QX	MS21044N18
AA60036-7-N20QX	MS21044N20

New A-A-60036 Part Number Passivated Lubricated IAW NASM25027	Reference Dash Number (NASM21044) Passivated Lubricated IAW NASM25027
CRES	CRES
AA60036-7-C02P5	MS21044C02
AA60036-7-C04P5	MS21044C04
AA60036-7-C06P5	MS21044C06
AA60036-7-C08P5	MS21044C08
AA60036-7-C3P5	MS21044C3
AA60036-7-C4P5	MS21044C4
AA60036-7-C5P5	MS21044C5
AA60036-7-C6P5	MS21044C6
AA60036-7-C7P5	MS21044C7
AA60036-7-C8P5	MS21044C8
AA60036-7-C9P5	MS21044C9
AA60036-7-C10P5	MS21044C10
AA60036-7-C12P5	MS21044C12
AA60036-7-C14P5	MS21044C14
AA60036-7-C16P5	MS21044C16
AA60036-7-C18P5	MS21044C18
AA60036-7-C20P5	MS21044C20

Examples of part number:

AA60036-7-N8QX = a NASM21044 – self-locking, non-metallic insert, regular height steel nut, 0.5000-20 UNJF-3B, Zinc-Nickel plated, lubricated IAW NASM25027.
AA60036-7-C10P5 = a NASM21044 – self-locking, non-metallic insert, regular height CRES nut, 0.6250-18 UNJF-3B, passivated, lubricated IAW NASM25027.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

TABLE VIII – Type VIII (-8) - Nut, self-locking, plate, two lug, non-metallic insert, steel, 125 KSI Ftu, 250 °F

New A-A-60036 Part Number Zinc-Nickel Plated, Type K16 (Steel)	Reference Dash Number (NASM21078) Cadmium Plated (Steel)
Plain Holes	Plain Holes
AA60036-8-04QX	MS21078-04
AA60036-8-06QX	MS21078-06
AA60036-8-08QX	MS21078-08
AA60036-8-3QX	MS21078-3
AA60036-8-4QX	MS21078-4
AA60036-8-5QX	MS21078-5
AA60036-8-6QX	MS21078-6
AA60036-8-7QX	MS21078-7
AA60036-8-8QX	MS21078-8
AA60036-8-9QX	MS21078-9
AA60036-8-10QX	MS21078-10

New A-A-60036 Part Number Zinc-Nickel Plated, Type K16 (Steel)	Reference Dash Number (NASM21078) Cadmium Plated (Steel)
CSK or Dimpled holes	CSK or Dimpled holes
AA60036-8-04KQX	MS21078-04K
AA60036-8-06KQX	MS21078-06K
AA60036-8-08KQX	MS21078-08K
AA60036-8-3KQX	MS21078-3K
AA60036-8-4KQX	MS21078-4K
AA60036-8-5KQX	MS21078-5K
AA60036-8-6KQX	MS21078-6K
---	---
---	---
---	---
---	---

NOTE: --- in table = not applicable.

Examples of part number:

AA60036-8-4QX = a NASM21078 – Nut, self-locking, plate, two lug, non-metallic insert, steel, Zinc-Nickel plated: 125 KSI Ftu, 250 °F; 0.2500-28 UNJF-3B; plain holes.

AA60036-8-6KQX = a NASM21078 – Nut, self-locking, CSK (or dimpled) hole, two lug plate, steel, non-metallic insert, Zinc-Nickel plated, 0.3750-24 UNJF-3B.

TABLE IX – Type IX (-9) - Nut, self-locking, hexagon, non-metallic insert, low height, 250 °F

New A-A-60036 Part Number Chemically treated	New A-A-60036 Part Number Anodized	New A-A-60036 Part Number Passivated	Reference Dash Number (NASM21083)		
Aluminum	Aluminum	CRES	Aluminum	Steel	CRES
AA60036-9-D02J	AA60036-9-D02K	AA60036-9-C02P5	MS21083-D02	MS21083-N02	MS21083-C02
AA60036-9-D04J	AA60036-9-D04K	AA60036-9-C04P5	MS21083-D04	MS21083-N04	MS21083-C04
AA60036-9-D06J	AA60036-9-D06K	AA60036-9-C06P5	MS21083-D06	MS21083-N06	MS21083-C06
AA60036-9-D08J	AA60036-9-D08K	AA60036-9-C08P5	MS21083-D08	MS21083-N08	MS21083-C08
AA60036-9-D3J	AA60036-9-D3K	AA60036-9-C3P5	MS21083-D3	MS21083-N3	MS21083-C3
AA60036-9-D4J	AA60036-9-D4K	AA60036-9-C4P5	MS21083-D4	MS21083-N4	MS21083-C4
AA60036-9-D5J	AA60036-9-D5K	AA60036-9-C5P5	MS21083-D5	MS21083-N5	MS21083-C5
AA60036-9-D6J	AA60036-9-D6K	AA60036-9-C6P5	MS21083-D6	MS21083-N6	MS21083-C6
AA60036-9-D7J	AA60036-9-D7K	AA60036-9-C7P5	MS21083-D7	MS21083-N7	MS21083-C7
AA60036-9-D8J	AA60036-9-D8K	AA60036-9-C8P5	MS21083-D8	MS21083-N8	MS21083-C8
AA60036-9-D9J	AA60036-9-D9K	AA60036-9-C9P5	MS21083-D9	MS21083-N9	MS21083-C9
AA60036-9-D10J	AA60036-9-D10K	AA60036-9-C10P5	MS21083-D10	MS21083-N10	MS21083-C10
AA60036-9-D12J	AA60036-9-D12K	AA60036-9-C12P5	MS21083-D12	MS21083-N12	MS21083-C12
AA60036-9-D14J	AA60036-9-D14K	AA60036-9-C14P5	MS21083-D14	MS21083-N14	MS21083-C14
AA60036-9-D16J	AA60036-9-D16K	AA60036-9-C16P5	MS21083-D16	MS21083-N16	MS21083-C16
AA60036-9-D18J	AA60036-9-D18K	AA60036-9-C18P5	MS21083-D18	MS21083-N18	MS21083-C18
AA60036-9-D20J	AA60036-9-D20K	AA60036-9-C20P5	MS21083-D20	MS21083-N20	MS21083-C20
AA60036-9-D22J	AA60036-9-D22K	AA60036-9-C22P5	MS21083-D22	MS21083-N22	MS21083-C22
AA60036-9-D24J	AA60036-9-D24K	AA60036-9-C24P5	MS21083-D24	MS21083-N24	MS21083-C24

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

Examples of part number:

AA60036-9-KD4 = a NASM21083 – 0.2500-28 aluminum nut, non-metallic insert, anodized or chemically treated.
AA60036-9-C4P5 = a NASM21083 – 0.2500-28 CRES nut, non-metallic insert, passivated.

TABLE X – Type X (-10) - Nut, Plain, Hexagon, Machine Screw, UNC-2B

New A-A-60036 Part Number Zinc-Nickel Plated	Reference Dash Number (NASM35649)
Carbon Steel	Carbon Steel
AA60036-10-222QX	MS35649-222
AA60036-10-242QX	MS35649-242
AA60036-10-262QX	MS35649-262
AA60036-10-282QX	MS35649-282
AA60036-10-202QX	MS35649-202
AA60036-10-2252QX	MS35649-2252
AA60036-10-2312QX	MS35649-2312
AA60036-10-2382QX	MS35649-2382

New A-A-60036 Part Number Passivated	Reference Dash Number (NASM35649)
CRES	CRES
AA60036-10-224P5	MS35649-224
AA60036-10-244P5	MS35649-244
AA60036-10-264P5	MS35649-264
AA60036-10-284P5	MS35649-284
AA60036-10-204P5	MS35649-204
AA60036-10-2254P5	MS35649-2254
AA60036-10-2314P5	MS35649-2314
AA60036-10-2384P5	MS35649-2384

Examples of part number:

AA60036-10-222QX = a NASM35649 – Nut, plain, hexagon, machine screw, thread size 0.0860-56 UNC-2B; steel, Zinc-Nickel Type K16 plated.
AA60036-10-264P5 = a NASM35649 – Nut, plain, hexagon, machine screw, thread size 0.1380-32 UNC-2B; CRES, passivated.

TABLE XI – Type XI (-11) - Nut, Plain, Hexagon, UNF-2B

New A-A-60036 Part Number Zinc-Nickel Plated	Reference Dash Number (NASM35650)
Carbon Steel	Carbon Steel
AA60036-11-312QX	MS35650-312
AA60036-11-322QX	MS35650-322
AA60036-11-342QX	MS35650-342
AA60036-11-362QX	MS35650-362
AA60036-11-382QX	MS35650-382
AA60036-11-302QX	MS35650-302
AA60036-11-3252QX	MS35650-3252
AA60036-11-3312QX	MS35650-3312
AA60036-11-3382QX	MS35650-3382
AA60036-11-3392QX	MS35650-3392
AA60036-11-34022QX	MS35650-3402

New A-A-60036 Part Number Passivated	Reference Dash Number (NASM35650)
CRES	CRES
AA60036-11-314P5	MS35650-314
AA60036-11-324P5	MS35650-324
AA60036-11-344P5	MS35650-344
AA60036-11-364P5	MS35650-364
AA60036-11-384P5	MS35650-384
AA60036-11-304P5	MS35650-304
AA60036-11-3254P5	MS35650-3254
AA60036-11-3314P5	MS35650-3314
AA60036-11-3384P5	MS35650-3384
AA60036-11-3394P5	MS35650-3394
AA60036-11-3404P5	MS35650-3404

Examples of part number:

AA60036-11-322QX = a NASM35650 – Nut, plain, hexagon, thread size 0.0860-64 UNF-2B; carbon steel, Zinc-Nickel Type K16 plated.
AA60036-11-384P5 = a NASM35650 – Nut, plain, hexagon, thread size 0.1640-36 UNF-2B; CRES, passivated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

7.2 Source of government documents.

7.2.1 FAR: Copies of the Federal Acquisition Regulations are available online from https://www.acquisition.gov/browse/index/far.

7.2.2 Executive order (EO). Copies of the EO documents are available online from https://www.epa.gov/greeningepa/executive-order-13693.

7.2.3 Military specifications: Copies of military specifications are available online from https://quicksearch.dla.mil.

7.3 Sources for Non-Government documents.

7.3.1 AIA documents. Copies of Aerospace Industry Association are available online from https://www.aia-aerospace.org/standards/.

7.3.2 ASTM documents. Copies of American Society for Testing and Materials documents are available online from https://www.astm.org/.

7.3.3 SAE documents. Copies of Society of Automotive Engineers documents are available online from https://www.sae.org.

7.4 Ordering data. The contract or order should specify the following:

a. Title, number and date of this CID.
b. National stock number, (if available).
c. Material (steel alloy, steel, or aluminum).
d. Part number.
e. Quantity.

Key words:

a. Steel
b. Plating
c. Finish
d. Passivate

MILITARY INTERESTS:

Custodian:
Army – AT
Navy – AS
Air Force – 71
DLA – CC

Review activities:
Army – AR, AV, CR, MI
Navy – AS, CG, MC, YD
Air Force – 03, 11, 70
DLA – GS4, GS7

CIVIL AGENCY COORDINATING ACTIVITY:
GSA-FAS

Preparing Activity:
Army – AT

(Project 5310-2022-025)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

NOTE: The activities listed above were interested in this document as of the date of this document. Since organization and responsibilities can change, you should verify the currency of the information above using the ASSIST database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.