INCH-POUND

A-A-60048

28 November 2022

COMMERCIAL ITEM DESCRIPTION

CLAMPS, LOOP, CADMIUM AND HEXAVALENT-CHROMIUM FREE

The General Services Administration has authorized the use of this commercial item description by all federal agencies.

1 SCOPE. This commercial item description (CID) covers clamps which shall not contain cadmium or hexavalent-chromium in their finishes.

2 CLASSIFICATION

2.1 Types.

Type I - SAE AS21919 - Clamp, Loop Type, Cushioned Support

3 SALIENT CHARACTERISTICS.

3.1 Materials. Clamps shall be manufactured as specified in the Society of Automotive Engineers (SAE) International documents listed in 2.1 by type, except the plating/finishes shall not contain cadmium or hexavalent-chromium as specified herein (see 3.3).

3.2 Dimensions. Dimensions for all designated type of clamps apply after plating/finishing.

3.3 Hexavalent-chromium free codes and finish/plating options. Finish/plating codes for all designated types of clamps:

J - Aluminum alloy shall be chemically treated in accordance with MIL-DTL-5541, Type II, Class 1A; or anodized in accordance with MIL-PRF-8625, Type IC, II or IIB, Class 1 or 2, Sealers (clear or any color) containing hexavalent chromium shall be prohibited.

P5 - CRES shall be cleaned, descaled and passivated in accordance with SAE AMS 2700 Method 1, Type 6, 7, or 8 or Method 2. Post treatment is prohibited.

Comments, suggestions, or questions on this document should be addressed to U.S. Army DEVCOM Ground Vehicle Systems Center, ATTN: Standardization, FCDD-GVS-SAT, MS #268, 6501 E. 11 Mile Road, Warren, MI 48397-5000 or emailed to usarmy.detroit.devcom-gvsc.mbx.standardization@army.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

FSC 5340

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

3.4 Interchangeability. When SAE specifications list interchangeability parts, do not interchange parts containing cadmium or hexavalent-chromium with the cadmium and hexavalent-chromium free parts listed herein without design authority approval.

4 REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered, recycled, bio based, and environmentally preferable materials to the maximum extent practicable, in accordance with paragraph 23.403, 23.404(b) of the Federal Acquisition Regulation (FAR), or Federal Sustainability contained in EO 14057; as applicable.

5 PRODUCT CONFORMANCE PROVISIONS

5.1 Product conformance. The products provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

5.2 Responsibility for inspection. The contractor is responsible for the performance of all inspections.

5.3 Contractor certification. The contractor shall certify and maintain substantiating evidence the product offered meets the salient characteristics of this commercial item description and conforms to the producer's own drawings, specifications, workmanship standards, and quality assurance practices. Items with known defects shall not be submitted for Government acceptance. The Government reserves the right to perform or witness any of the inspections it deems necessary to ensure supplies and services conform to prescribed requirements.

6 PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order.

7 NOTES

The following part or identification number (PIN) procedure is for Government purposes and does not constitute a requirement for the contractor.

7.1 Table. The following table indicates new finish/plating PIN's which are cadmium and hexavalent-chromium free for the designated clamps.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

TABLE I – Type I (-1) - Clamp, loop type, cushioned support.

A-A-60048 Part Number	Reference Part/Dash Number (from SAE AS21919)
AA60048-1-W*01	AS21919W*01
AA60048-1-W*02	AS21919W*02
AA60048-1-W*03	AS21919W*03
AA60048-1-W*04	AS21919W*04
AA60048-1-W*05	AS21919W*05
AA60048-1-W*06	AS21919W*06
AA60048-1-W*07	AS21919W*07
AA60048-1-W*08	AS21919W*08
AA60048-1-W*09	AS21919W*09
AA60048-1-W*10	AS21919W*10
AA60048-1-W*11	AS21919W*11
AA60048-1-W*12	AS21919W*12
AA60048-1-W*13	AS21919W*13
AA60048-1-W*14	AS21919W*14
AA60048-1-W*15	AS21919W*15
AA60048-1-W*16	AS21919W*16
AA60048-1-W*17	AS21919W*17
AA60048-1-W*18	AS21919W*18
AA60048-1-W*19	AS21919W*19

A-A-60048 Part Number	Reference Part/Dash Number (from SAE AS21919)
AA60048-1-W*20	AS21919W*20
AA60048-1-W*21	AS21919W*21
AA60048-1-W*22	AS21919W*22
AA60048-1-W*23	AS21919W*23
AA60048-1-W*24	AS21919W*24
AA60048-1-W*25	AS21919W*25
AA60048-1-W*26	AS21919W*26
AA60048-1-W*27	AS21919W*27
AA60048-1-W*28	AS21919W*28
AA60048-1-W*29	AS21919W*29
AA60048-1-W*30	AS21919W*30
AA60048-1-W*31	AS21919W*31
AA60048-1-W*32	AS21919W*32
AA60048-1-W*33	AS21919W*33
AA60048-1-W*34	AS21919W*34
AA60048-1-W*35	AS21919W*35
AA60048-1-W*36	AS21919W*36
AA60048-1-W*37	AS21919W*37
AA60048-1-W*38	AS21919W*38

A-A-60048 Part Number	Reference Part/Dash Number (from SAE AS21919)
AA60048-1-W*40	AS21919W*40
AA60048-1-W*42	AS21919W*42
AA60048-1-W*43	AS21919W*43
AA60048-1-W*44	AS21919W*44
AA60048-1-W*45	AS21919W*45
AA60048-1-W*46	AS21919W*46
AA60048-1-W*48	AS21919W*48
AA60048-1-W*50	AS21919W*50
AA60048-1-W*52	AS21919W*52
AA60048-1-W*54	AS21919W*54
AA60048-1-W*56	AS21919W*56
AA60048-1-W*58	AS21919W*58
AA60048-1-W*64	AS21919W*64
AA60048-1-W*66	AS21919W*66

NOTE: Part numbers shown for parts which includes a wedge clamp (see PIN construction on next page)

* Material and cushioning code (see PIN construction)

PIN construction details: (continued on next page)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

PIN construction

AA60048 -1 -W DG 08 Y

- Reduced mounting hole diameter (see SAE AS21919)
- Size code (see SAE AS21919)
- Material and cushion code (see SAE AS21919 for any additional information)
  - Material / finish (first letter):
    - C = Type 321 CRES per SAE AMS5510 finish per code P5 (see 3.3).
    - D = 2024-T42 Aluminum alloy per SAE AMS-QQ-A-250/5 finish per code J (see 3.3).
  - Cushion (second letter):
    - E = Ethylene propylene per MIL-DTL-85052/2 or SAE AMS3253
    - F = Nitrile per MIL-DTL-85052/1 or SAE AMS3224
    - G = Chloroprene per SAE AMS3209 And Ozone Resistance Requirements
    - H = Silicone per SAE AMS3310
    - J = Fluorosilicone per MIL-DTL-25988, Type II, Class 1, Grade 60
- Wedge (Omit for non-wedge clamp)
- Table number in this CID (-1 = Table I)
- CID identifier (part of basic part number)

Examples of clean finish PIN's:

AA60048-1-WDG08Y	=	an SAE AS21919 - wedge type clamp, aluminum, chloroprene cushioning material, tube OD Ø (Ref.) of 0.500 inch, chemically or Alodine treated.
AA60048-1-DG08Y	=	an SAE AS21919 - clamp, aluminum, chloroprene cushioning material, tube OD Ø (Ref.) of 0.500 inch, chemically or Alodine treated.
AA60048-1-WCF08Y	=	an SAE AS21919 - wedge type clamp, CRES, nitrile cushioning material, tube OD Ø (Ref.) of 0.500 inch, passivated.
AA60048-1-CF08Y	=	an SAE AS21919 - clamp, CRES, nitrile cushioning material, tube OD Ø (Ref.) of 0.500 inch, passivated.

7.2 Source of Government documents.

7.2.1 FAR: Copies of the Federal Acquisition Regulations are available online from https://www.acquisition.gov/browse/index/far.

7.2.2 Executive order (EO). Copies of EO 14057 are available online from https://www.fedcenter.gov/_kd/go.cfm?destination=ShowItem&Item_ID=38808.

7.2.3 Military specifications: Copies of military specifications are available online from https://quicksearch.dla.mil.

7.3 Sources for non-Government documents.

7.3.1 SAE documents: Copies of SAE International are available online from https://www.sae.org.

7.4 Ordering data. The contract or order should specify the following:

a. Title, number and date of this CID.
b. National stock number, (if available).
c. Material (base metal and cushioning material).
d. Part number.
e. Quantity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

7.5 Key words:

a. Chemically treated
b. CRES
c. Finish
d. Plating
e. Passivate

MILITARY INTERESTS:

Custodian:
Army – AT
Navy – AS
Air Force – 71
DLA – CC

Review activities:
Army – AR, AV, CR, MI
Navy – CG, MC, YD
Air Force – 03, 11, 70
DLA – GS4, GS7

CIVIL AGENCY COORDINATING ACTIVITY:
GSA-FAS

Preparing Activity:
Army – AT

(Project 5340-2023-002)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.