INCH-POUND
A-A-60061
6 MAY 2024

COMMERCIAL ITEM DESCRIPTION

AIR COMPRESSOR FOR T-10/11 NOISE SUPPRESSOR

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE. This CID is for a reciprocating air compressor assembly including tank.

2. SALIENT CHARACTERISTICS.
The compressor shall meet the following requirements:

Air storage capacity	**80 gallons**
Air production capacity	17 cubic feet per minute (CFM) at 90 pounds per square inch (PSI)
Maximum pressure	At least 175 PSI
Power (US)	200 VAC, 3 phase/60Hz
Power (EU)	400 VAC, 3 phase/50Hz

2.1 Air compressor description. This is an air compressor assembly that, upon installation and activation, can provide 17 CFM of air at 90 PSI, and storage of 80 gallons of air at 175 PSI.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data that may improve this document should be addressed to AFLCMC/EZSS, Bldg. 28, 2145 Monahan Way, Wright-Patterson AFB, OH 45433-7017 or emailed to ENGINEERING.STANDARDS@US.AF.MIL. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 4310

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.2 Design and construction. The design shall promote cost effective, life-cycle sustainability by addressing considerations such as incorporating open standards and reducing pollutant emissions and wastes, while satisfying system performance requirements. It shall be designed and constructed so that no parts will work loose in service, and to withstand the strains, jars, vibrations, and other conditions incident to shipping, storage, installation, and service. It shall be weatherproof and designed to prevent the intrusion of water, sand, and dust into critical operating components. The Air Compressor shall be designed and constructed in accordance with all applicable European Union (EU) requirements in order to have the "CE" marking affixed (see 2.2.3).

2.2.1 Protective coatings. This item will be used indoors in areas that are not climate controlled throughout CONUS and OCONUS USAF installations. Materials that deteriorate when exposed to temperature cycling typical to tropical and semi-arctic environments, humidity cycling, or operational conditions normally encountered during the service life of the item shall not be used or shall have means of protection against such deterioration that does not prevent compliance with the performance requirements specified herein. Protective coatings that chip, crack, or scale with age or extremes of climatic conditions or when exposed to heat shall not be used. See 2.2.4.1 for prohibited hazardous materials.

2.2.2 Markings. All external devices which require an operational or maintenance interface shall be marked in accordance with MIL-STD-130. Markings shall be applied with decals and shall be 1-inch-high block letters unless prohibited by the available space. In such cases, the markings shall be the largest size possible. Markings, Information/Caution shall be Lusterless Black, Color Number 37038 in accordance with SAE-AMS-STD-595, and Markings, Warning/Danger shall be Lusterless Red, Color Number 31136 in accordance with SAE-AMS-STD-595.

2.2.3 Identification plate. An identification plate in accordance with MIL-STD-130 shall be securely attached to the Air Compressor in a readily accessible location. The identification plate shall contain the following information: nomenclature, part number, serial number, date of manufacture, manufacturer's name, Commercial and Government Entity (CAGE) code, date of warranty expiration, and National Stock Number (NSN). The Air Compressor and any of its components for which the Government's unit cost is more than $5,000, is serially managed, or the procuring agency determines is mission essential, shall have Unique Identification (UID) (also known as Item Unique Identification (IUID)) information permanently affixed on or near the respective identification plate(s), marked in accordance with MIL-STD-130. UID information shall be included as both a 2D Data Matrix and human readable markings. The "CE" marking shall be affixed in accordance with EU requirements on or adjacent to the identification plate.

2.2.4 Environment, Safety, and Occupational Health (ESOH).

2.2.4.1 Hazardous material. The design shall minimize, and control hazards associated with the inclusion or use of hazardous or toxic materials and the generation of toxic or noxious gases. The Air Compressor shall not generate or use Class I or Class II Ozone Depleting Substances (ODS) during operation, maintenance, or disposal. Class I ODS and hazardous materials shall not be used in any system, component, or process. The Air Compressor shall not contain or use either

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

hexavalent chromium or cadmium without written approval by the procuring activity. Hazardous materials are defined in AFI 32-7086; Class I and Class II ODS are defined in 40CFR82.

2.2.4.2 Component protection. All rotating and reciprocating parts and all parts subject to high operational temperatures or subject to being electrically energized, that are of such nature or so located as to be hazardous to personnel, shall be guarded or insulated to eliminate the hazard. All wires, cables, tubes, and hoses shall be supported and protected to minimize chafing and abrasion and shall be located so as to provide adequate clearance from moving parts and high operational temperatures. Grommets shall be provided wherever wires, cables, tubes, or hoses pass through bulkheads, partitions, or structural members.

2.2.4.3 Foreign object damage (FOD). All loose metal parts, such as pins or connector covers, shall be securely attached to the Air Compressor with wire ropes or chains. "Dog tag" style beaded chains shall not be provided. Removable panels, if provided, shall be attached with captive fasteners.

2.2.5 Noise. Noise level shall not exceed 80 decibels adjusted (dB(A)). If the sound level is above 80 dB(A), the contractor shall provide a hazardous noise warning plate stating that operator's hearing protection is required when operating the air compressor.

2.2.5 Fastening devices. All screws, bolts, nuts, pins, and other fastening devices shall be properly designed, manufactured, and installed with adequate means of preventing loss of torque or adjustment. Cotter pins, lock washers, or nylon patches shall not be used for this purpose, except for the attachment of trim items or as provided in commercial (see 6.3.1) components. Tapped threads shall have a minimum thread engagement in accordance with Table I.

TABLE I. Minimum thread engagement.

Material	Minimum Thread Engagement
Steel	1.0 times the nominal fastener diameter
Cast iron, brass, or bronze	1.5 times the nominal fastener diameter
Aluminum, zinc, or plastic	2.0 times the nominal fastener diameter

2.2.6 Welders and welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface parts to be welded shall be free from rust, scale, paint, grease, and other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the welded parts. Welds shall transmit stress without cracking or permanent distortion when the parts connected by the welds are subjected to test, proof, and service loadings.

2.3 Environmental conditions.

2.3.1 Operating temperature range. The Air Compressor shall be capable of operating in ambient temperatures ranging from 32 °F to 125 °F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.3.2 Storage temperature range. The Air Compressor shall be capable of being stored in ambient temperatures ranging from -65 °F to 160 °F.

2.4 Weight and dimensions. Overall weight and dimensions in transport configuration shall not exceed:

Weight	700 pounds
Length	36 inches
Width	48 inches
Height	80 inches

2.5 Surface transportability. The Air Compressor shall be transportable via all modes of surface shipment (highway, rail, and water) in accordance with MIL-STD-1366 and shall be capable of withstanding the mechanical shock and vibration characteristics of highway, rail, and water transport, except that design for rail impact testing (see MIL-STD-1366) is not required.

2.6 Maintainability. The Air Compressor shall be designed for maintainability in accordance with MIL-STD-1472; forces shall not exceed those specified for both males and females.

2.6.1 Inspection and servicing provisions.

a. Pre-use inspections and servicing tasks shall not require tools.

b. Routine service and preventive maintenance shall not require special tools (see 6.3.3).

c. Drain plugs and filters shall be directly accessible from the ground.

d. The Air Compressor shall be designed with maximum usage of sealed lifetime lubrication bearings.

2.6.2 Special tools. The design of the item shall minimize the requirement for special tools (see 6.3.3). All special tools shall be provided with, and stored on, the Air Compressor.

2.7 Performance.

2.7.1 Capacity. The Air Compressor shall be able to provide at least 17 CFM of air compressed to 90 PSI.

2.7.2 Maximum pressure. The Air Compressor shall have a maximum tank storage pressure of 175 PSI.

2.7.3. Nominal power. The Air Compressor shall have an electric motor rated at or above 5 horsepower.

2.7.4. Outlet. The Air Compressor shall use National Pipe Thread (NPT) standard 0.75-inch outlet for use of compressed air.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.7.5. Tank. The Air Compressor storage tank shall be 80 gallons in a vertical configuration.

2.7.6. Electrical. The Air Compressor shall use either 200V/3P/60Hz ±10%, or 400V/3P/50Hz ± 10% mains power.

2.8 Workmanship. The Air Compressor, including all parts and accessories, shall be constructed, and finished in a thoroughly workmanlike manner. Workmanship objectives shall include freedom from blemishes, defects, burrs and sharp corners and edges; accuracy of dimensions, surface finish, and radii of fillets; thoroughness of welding, painting, and riveting; marking of parts and assemblies; and proper alignment of parts and tightness of assembly fasteners.

2.8.1 Bolted connections. Bolt holes shall be accurately punched or drilled and shall be deburred. Threaded fasteners shall be tight and shall not work loose during testing or service usage.

2.8.2 Riveted connections. Rivet holes shall be accurately punched or drilled and shall be deburred. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the component.

2.8.3 Gear and lever assemblies. Gear and lever assemblies shall be properly aligned and meshed and shall be operable without interference, tight spots, loose spots, or other irregularities. Where required for accurate adjustment, gear assemblies shall be free of excessive backlash.

2.8.4 Cleaning. The Air Compressor shall be thoroughly cleaned. Loose, spattered, or excess solder; welding slag; stray bolts, nuts, and washers; rust; metal particles; pipe compound; and other foreign matter shall be removed during and after final assembly.

3. REGULATORY REQUIREMENTS.

3.1 Recycled, recovered, environmentally preferable, or biobased materials. Recycled, recovered, environmentally preferable, or biobased materials should be used to the maximum extent possible, provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with 23.403 of the Federal Acquisition Regulation (FAR). However, used, rebuilt, or refurbished items shall not be provided.

3.2 Green procurement program. Green Procurement Program (GPP) is a mandatory federal acquisition program that focuses on the purchase and use of environmentally preferable products and services. GPP requirements apply to all acquisitions using appropriated funds, including services and new requirements. FAR 23.404(b) applies and states the GPP requires 100% of EPA designated product purchase that are included in the Comprehensive Procurement Guidelines list that contains recovered materials, unless the item cannot be acquired: a) competitively within a reasonable timeframe; b) meet appropriate performance standards, or c) at a reasonable price. The prime contractor is responsible for ensuring that all subcontractors comply with this requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

4. PRODUCT CONFORMANCE PROVISIONS.

The products provided shall meet the salient characteristics of this Commercial Item Description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace, modified as necessary to comply with the requirements herein. The Government reserves the right to require proof of such conformance.

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First production inspection (see 4.2).

b. Conformance inspection (see 4.3).

4.2 First production inspection. The first production Air Compressor shall be subjected to the analyses, demonstrations, examinations, and tests described in 4.5.1 through 4.5.6. The contractor shall provide or arrange for all test equipment and facilities. The compatibility test shall be performed after successful completion of all other portions of the first production inspection.

4.3 Conformance inspection. Each production Air Compressor shall be subjected to the examination described in 4.5.1.

4.4 Inspection requirements.

4.4.1 General inspection requirements. Apparatus used in conjunction with the inspections specified herein shall be laboratory precision type, calibrated at proper intervals to ensure laboratory accuracy.

The Air Compressor shall be tested to ensure it is correctly installed, connected to electrical power, and operable. The physical dimensions, weight, tank storage volume, CFM capacity, and pressure capacity shall be either tested or certified by the manufacturer.

4.4.2 Data. During all testing specified herein, at least the following data, unless not applicable, shall be recorded at intervals not to exceed 30 minutes. Additional data or shorter intervals shall be provided as appropriate for any specific test.

a. Date.

b. Time started.

c. Time finished.

d. Ambient temperature.

4.4.3 Test rejection criteria. Throughout all tests specified herein, the Air Compressor shall be closely observed for the following conditions, which shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

a. Failure to conform to design or performance requirements specified herein or in the contractor's technical proposal.

b. Any spillage or leakage of any liquid, including fuel, coolant, lubricant, or hydraulic fluid, under any condition, except as allowed herein.

c. Thermal or structural failure of any component, including permanent deformation, or evidence of impending failure.

d. Evidence of excessive wear. If excessive wear is suspected, the original equipment manufacturer's (OEM's) specifications or tolerances shall be utilized for making a determination.

e. Evidence of corrosion or deterioration.

f. Misalignment of components.

g. Conditions that present a safety hazard to personnel during operation, servicing, or maintenance.

4.5 Test methods.

4.5.1 Examination of product. Each Air Compressor shall be examined to verify compliance with the requirements herein prior to accomplishing any other demonstrations or tests listed in 4.5. A contractor-generated, Government-approved checklist (part of the test procedure) shall be used to identify each requirement not verified by an analysis, certification, demonstration, or test, and shall be used to document the examination results. Particular attention shall be given to materials, workmanship, dimensions, protective coatings and sealants and their application, welding, fastening, and markings. Proper operation of each Air Compressor function shall be verified. Certifications and analyses shall be provided in accordance with Table II. Each production Air Compressor shall be inspected to a Government-approved reduced version of the checklist.

TABLE II. Certifications and analyses.

Paragraph	Required Certifications and Analyses
2. SALIENT CHARACTERISTICS.	Contractor certification that the Air Compressor develops 17 CFM of air at 90 PSI when connected to either 200VAC/60Hz or 400VAC/50Hz electrical sources.
2.2 Design and construction.	Contractor documentation that the Air Compressor is in accordance with all applicable EU requirements in order to have the "CE" marking affixed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

TABLE II. Certifications and analyses - Continued.

Paragraph	Required Certifications and Analyses
2.2.5 Noise.	Contractor certification that operating noise level is at or below 80 dB.
2.3.1 Operating temperature range.	Contractor certification that the Air Compressor is capable of operating in ambient temperatures ranging from 32 °F to 125 °F.
2.3.2 Storage temperature range.	Contractor certification that the Air Compressor is capable of storage in ambient temperatures ranging from -65 °F to 160 °F.
2.4 Weight and dimensions.	Contractor certification that the Air Compressor complies with the following maximum weight and dimensions: Weight 700 pounds. Length 36 inches. Width 48 inches. Height 80 inches.

4.5.2 Weight and dimension tests.

4.5.2.1 Weight test. The weight of a first production Air Compressor shall be measured to demonstrate compliance with the weight requirement of 2.4.

4.5.2.2 Dimension measurement. A first production Air Compressor shall be measured to demonstrate compliance with the dimensional requirements of 2.4.

4.5.3 Maintainability demonstration. All recommended preventive maintenance tasks shall be performed, and the task times shall be recorded. The recommended frequencies of the preventive maintenance tasks and the times recorded to accomplish the tasks shall be used to develop an expected value of preventive maintenance time per measure of use, such as calendar time or hours of operation. It shall be demonstrated that the forces required do not exceed those allowed in MIL-STD-1472. All preventive maintenance tasks recommended to be performed daily and at the routine PMI shall also be performed by personnel wearing arctic mittens.

5. PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

6. NOTES.

6.1 Source of documents.

6.1.1 Department of Defense and Federal documents. Department of Defense and Federal documents are available online at https://quicksearch.dla.mil/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia PA 19111-5094.

6.1.2 AFI. Copies of AFIs are available online at https://www.e-publishing.af.mil/.

6.1.3 CFR. Copies of the CFR are available online at https://www.ecfr.gov/.

6.1.3 FAR. The FAR may be obtained from the Superintendent of Documents, P.O. Box 371954, Pittsburgh PA 15250-7954. Electronic copies of the FAR may be obtained from https://farsite.hill.af.mil/.

6.1.4 ASTM documents. Application for copies should be addressed to ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken PA 19428-2959, https://www.astm.org/.

6.1.5 AWS documents. Application for copies should be addressed to American Welding Society, 550 N.W. LeJeune Road, Miami FL 33126, https://www.aws.org/.

6.1.6 NEMA documents. Application for copies should be addressed to NEMA, 1300 North 17th Street, Suite 1847, Rosslyn VA 22209, https://www.nema.org/.

6.1.7 SAE documents. Application for copies should be addressed to SAE International, 400 Commonwealth Drive, Warrendale PA 15096, https://www.sae.org/.

6.1.8 TMC documents. Application for copies should be addressed to Technology and Maintenance Council, American Trucking Associations, 2200 Mill Road, Alexandria VA 22314-5388, https://www.trucking.org/Technology_Council.aspx.

6.1.9 Tire and Rim Association documents. Application for copies should be addressed to The Tire and Rim Association, Inc., 175 Montrose West Ave., Suite 150, Copley OH 44321, https://www.us-tra.org/.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this CID.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

6.3 Definitions.

6.3.1 Commercial item.

(1) Any item, other than real property, that is of a type customarily used by the general public or by non-Governmental entities for purposes other than Governmental purposes, and—

(i) Has been sold, leased, or licensed to the general public; or

(ii) Has been offered for sale, lease, or license to the general public;

(2) Any item that evolved from an item described in paragraph (1) of this definition through advances in technology or performance and that is not yet available in the commercial marketplace, but will be available in the commercial marketplace in time to satisfy the delivery requirements under a Government solicitation;

(3) Any item that would satisfy a criterion expressed in paragraphs (1) or (2) of this definition, but for—

(i) Modifications of a type customarily available in the commercial marketplace; or

(ii) Minor modifications of a type not customarily available in the commercial marketplace made to meet Federal Government requirements. Minor modifications means modifications that do not significantly alter the non-Governmental function or essential physical characteristics of an item or component, or change the purpose of a process. Factors to be considered in determining whether a modification is minor include the value and size of the modification and the comparative value and size of the final product. Dollar values and percentages may be used as guideposts, but are not conclusive evidence that a modification is minor;

(4) Any combination of items meeting the requirements of paragraphs (1), (2), (3), or (5) of this definition that are of a type customarily combined and sold in combination to the general public;

(5) Installation services, maintenance services, repair services, training services, and other services if—

(i) Such services are procured for support of an item referred to in paragraph (1), (2), (3), or (4) of this definition, regardless of whether such services are provided by the same source or at the same time as the item; and

(ii) The source of such services provides similar services contemporaneously to the general public under terms and conditions similar to those offered to the Federal Government;

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

(6) Services of a type offered and sold competitively in substantial quantities in the commercial marketplace based on established catalog or market prices for specific tasks performed or specific outcomes to be achieved and under standard commercial terms and conditions. For purposes of these services—

(i) "Catalog price" means a price included in a catalog, price list, schedule, or other form that is regularly maintained by the manufacturer or vendor, is either published or otherwise available for inspection by customers, and states prices at which sales are currently, or were last, made to a significant number of buyers constituting the general public; and

(ii) "Market prices" means current prices that are established in the course of ordinary trade between buyers and sellers free to bargain and that can be substantiated through competition or from sources independent of the offerors.

(7) Any item, combination of items, or service referred to in paragraphs (1) through (6) of this definition, notwithstanding the fact that the item, combination of items, or service is transferred between or among separate divisions, subsidiaries, or affiliates of a contractor; or

(8) A nondevelopmental item, if the procuring agency determines the item was developed exclusively at private expense and sold in substantial quantities, on a competitive basis, to multiple State and local Government. (Reference the Federal Acquisition Regulation (FAR) 2.101)

6.3.2 Common hand tool. A non-powered tool that is likely to be found in a typical mechanic's toolbox. Common hand tools include open end, boxed end, combination, socket (both 6- and 12-point in both standard and deep-well), and hex key wrenches, in SAE sizes up to and including 1-inch and metric sizes up to and including 25-mm; ratchet handles, extensions, and swivels; slotted and Phillips-head screwdrivers; regular and snap-ring pliers; and a ball-peen hammer.

6.3.3 Special tool. A tool that is not commercially and readily available from a source other than the Air Compressor contractor.

6.4 Key words.

17 CFM
175 PSI
80 gallons
Reciprocating air compressor
shop air compressor

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

MILITARY INTERESTS:

Custodians:
Army - AT
Navy - AS
Air Force - 184

Preparing activity:
Air Force - 184

Project 4310-2024-001

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.